

Application

- Working pressure: 0.5-3.5Bar.
- Filtration Required: Above 120mesh.
- Lay in line and levelly, all the holes of emitter must be upward.
- Suitable for the planing on hills and mountains, or Sub-surface multi seasonal row crop.

Technical Data:

16mm / Maximum Length (m) of Run		10% Flow Variation / Inlet Pressure 3.0Bar / Slope 0%				
Flow	Spacing	20cm	30cm	40cm	50cm	100cm
1.0 L/h		150	210	270	320	540
1.6 L/h		110	150	190	230	410
2.0 L/h		90	130	165	200	345

20mm / Maximum Length (m) of Run		10% Flow Variation / Inlet Pressure 3.0Bar / Slope 0%				
Flow	Spacing	20cm	30cm	40cm	50cm	100cm
1.0 L/h		250	340	430	510	850
1.6 L/h		190	270	310	380	620
2.0 L/h		160	220	270	320	540

22mm / Maximum Length (m) of Run		10% Flow Variation / Inlet Pressure 3.0Bar / Slope 0%				
Flow	Spacing	20cm	30cm	40cm	50cm	100cm
1.0 L/h		325	440	540	645	1060
1.6 L/h		225	330	410	490	795
2.0 L/h		210	285	360	430	700

