

CONTENTS

Which pump for which job?


Every pump is quoted complete with its electric motor. To size one, we need the flow you need (m³/h), the total head (the height you lift the water plus the pressure your emitters need and the friction in the pipes) and your power supply. Send us those and we will pick the model.




SLS



SLW



SLNC



SLD

Range	Type	Flow	Head	Typical irrigation use
SLS	Vertical single-stage centrifugal pump	1.8–1 400 m³/h	9.2–156 m	Booster pump on an irrigation main or in a pump room, lifting pressure for drip and micro-sprinkler blocks, and circulating clean water for fertigation and packhouses.
SLW	Horizontal single-stage centrifugal pump	2.8–1 400 m³/h	9.2–156 m	Booster and transfer pump for irrigation mains, filter stations and fertigation lines where there is little headroom, or where a low, stable pump on a plinth is preferred.
SLNC	Single-stage end-suction pump with back pull-out	15–2 000 m³/h	10–140 m	Main irrigation pump drawing from dams, rivers and canals to feed centre pivots, sprinklers and drip systems.
SLD	Horizontal multistage centrifugal pump	6.3–1 100 m³/h	22–1 153 m	Pumping to lands on high ground or a long way from the water source, feeding pivots and sprinklers at the end of long mainlines, and filling reservoirs uphill.

SLS vertical in-line pump

SLW horizontal in-line pump

SLNC end-suction centrifugal pump

SLD horizontal multistage pump

04

05

06

07