

HARVESTING

Potato harvesters

Trailed, mounted and self-propelled harvesters for every farm size, with combined digging shares, sieving webs and haulm separation for a low bruising rate and clean, well-exposed tubers.

4UL-170Z/4UL-170C

Potato Combine Harvester



Specification	Unit	4UL-170Z	4UL-170C
Hitch type		Trailed	Trailed
Dimensions (L x W x H)	mm	9700×3200×3400	6670×2680×2890
Weight	kg	5960	3270
Tractor power required	hp	140–210	120–180
Row spacing	mm	900	900
Rows		2+2	2
Working width	mm	1700	1700
Digging depth	mm	150–300	150–300
Digging share		Fixed combined shovel	Fixed combined shovel
Web width	mm	1660	1660
Max. loading height	mm	4000	2940
Work rate	ha/h	≥0.53	≥0.4

4UL-170F/4UL-170G

Potato Combine Harvester



Specification	Unit	4UL-170F	4UL-170G
Hitch type		Trailed	Trailed
Dimensions (L x W x H)	mm	10500×3300×3900	11650×3100×3950
Weight	kg	12180	12650
Tractor power required	hp	120–200	140–200
Row spacing	mm	750–900	750–900
Rows		2	2
PTO speed	rpm	540	540
Hopper capacity	kg	6000	6000
Discharge height	mm	4500	4500
Sorting platform crew		2+2	2+2
Cleaning system		Haulm pulling rollers + spiral roller cleaner	+ Haulm separation web + spiked roller sieve + finger-bar stone separator