

4UX-160/160G/170G

Potato Harvester



▲ 4UX-170G

Specification	Unit	4UX-160	4UX-160G	4UX-170G
Hitch type		Mounted	Mounted	Mounted
Dimensions (L x W x H)	mm	3880×1982×1260	4450×2800×1400	4450×2900×1400
Weight	kg	1415	1570	1640
Tractor power required	hp	120-160	≥92	≥92
Row spacing	mm	750-800	750-800	750-900
Rows		2	2 (22/24 web)	2 (22/24 web)
Working width	mm	1600	1600	1700
Digging depth	mm	150-300	150-300	150-300
Lifting rate (potatoes exposed)		≥96%	≥96%	≥96%
Potato damage rate		≤1.5%	≤1.5%	≤1.5%
Skin damage rate		≤2%	≤2%	≤2%
Work rate	ha/h	≥0.33	≥0.33	≥0.46

4UQ-160/170A

Potato Harvester



Specification	Unit	4UQ-160	4UQ-170A
Hitch type		Trailed	Trailed
Dimensions (L x W x H)	mm	5100×1942×1467	5595×2610×1625
Weight	kg	1483	2447
Tractor power required	hp	≥85	125-160
Row spacing	mm	≤800	800-900
Rows		2	2
Working width	mm	1400	1700
Digging depth	mm	150-300	150-300
Lifting rate (potatoes exposed)		≥96%	≥96%
Potato damage rate		≤1.5%	≤1.5%
Skin damage rate		≤2%	≤2%
Work rate	ha/h	≥0.4	≥0.4