

5XF-60X/60X.1/60X.6
Potato Receiving Hopper


Specification	Unit	5XF-60X	5XF-60X.1	5XF-60X.6
Dimensions (L x W x H)	mm	6795×3400×3300	7391×3400×3300	12149×3400×3426
Weight	kg	4790	5600	6470
Sorting table width	mm	2000	2000	2000
Capacity	t/h	60	60	60
Conveyor type		PVC rod web + PVC belt	PVC rod web + PVC belt	PVC rod web + PVC belt
Drive		Hydraulic power pack + drum motor	Hydraulic power pack + drum motor	Hydraulic power pack + drum motor
Total power	kW	17.2	18.3	18.4
Power supply		380 V AC, 50 Hz	380 V AC, 50 Hz	380 V AC, 50 Hz
Controls		Lever + buttons	Lever + buttons	Lever + buttons
Hopper volume	m³	12.6 m³ (≈8.2 t potatoes)	12.6 m³ (≈8.2 t potatoes)	12.6
Cleaning roller type		Polyurethane rollers	Polyurethane rollers	Polyurethane rollers
Cleaning rollers		7	13	7
Sorting stages		Two-stage sorting	Three-stage sorting	Two-stage sorting

5XF-80
Potato Receiving Hopper


Specification	Unit	5XF-80
Dimensions (L x W x H)	mm	8650×3400×3300
Weight	kg	6100
Sorting table width	mm	2400
Capacity	t/h	80
Conveyor type		PVC rod web + PVC belt
Drive		Hydraulic power pack + drum motor
Total power	kW	17.2
Power supply		380 V AC, 50 Hz
Controls		Lever + buttons
Hopper volume	m³	18.4 m³ (≈11.9 t potatoes)
Cleaning roller type		Polyurethane rollers
Cleaning rollers		9
Sorting stages		Two-stage sorting