

5S1-60 Belt Conveyor/5S2-60 Telescopic Conveyor



Specification	Unit	5S1-60-4	5S1-60-6	5S1-60-8	5S2-60-8
Dimensions (L × W × H)	mm	4200×1180×1100	6200×1180×1100	8060×1180×1100	9900×1360×2000
Weight	kg	475	630	703	1680
Max. incline		3	3	4	3
Capacity	t/h	60	60	60	60
Potato damage rate		≤1	≤1	≤1	≤1
Motor power	kW	1.5	2.2	2.2	2.2
Belt speed	m/s	0.55/0.85/1.1	0.55/0.85/1.1	0.55/0.85/1.1	0.55/0.85/1.1
Motors		1	1	1	2
Power supply		380 V AC	380 V AC	380 V AC	380 V AC
Conveyor belt		Multi-ply rubber belt	Multi-ply rubber belt	Multi-ply rubber belt	Multi-ply rubber belt
Belt width	mm	685	685	685	685
Height adjustment		Support legs	Support legs	Support legs	Support legs / lifting jack

5S1-80 Belt Conveyor/5S2-80 Telescopic Conveyor



Specification	Unit	5S1-80-6.5	5S1-80-8.5	5S1-80-9.0	5S2-80-8.5
Dimensions (L × W × H)	mm	7000×1190×1060	8750×1190×1060	9500×1190×1060	10031×1558×2055
Weight	kg	550	660	700	1800
Max. incline		4.7	4.7	4.1	7.1
Capacity	t/h	80	80	80	80
Potato damage rate		≤1	≤1	≤1	≤1
Motor power	kW	2.2	2.2	2.2	2.2
Belt speed	m/s	0.55/0.85/1.06	0.55/0.85/1.06	0.55/0.85/1.06	0.55/0.85/1.06
Motors		1	1	1	2
Power supply		380 V AC	380 V AC	380 V AC	380 V AC
Conveyor belt		Multi-ply rubber belt, 13495 mm	Multi-ply rubber belt, 17020 mm	Multi-ply rubber belt, 18495 mm	Multi-ply rubber belt, 17020×2 mm
Belt width	mm	780	780	780	780
Height adjustment		Support legs	Support legs	Support legs	Support legs / lifting jack
Telescopic extension	mm	—	—	—	6229
Total power	kW	2.2	2.2	2.2	5.15