

15.15 Příloha č.15: Konfigurační soubor zařízení VoiceRouter z prostředí Cisco Packet Tracer

```
!  
version 12.4  
no service timestamps log datetime msec  
no service timestamps debug datetime msec  
service password-encryption  
!  
hostname VoiceRouter  
!  
!  
!  
enable secret 5 $1$mERr$40YJivYfOiXO5rtq4zVx9/  
!  
!  
!  
!  
!  
aaa new-model  
!  
aaa authentication login SSH_AUTH group radius local  
!  
!  
!  
!  
!  
!  
!
```

```
no ip cef
no ipv6 cef
!
!
!
!
!
!
!
!
!
!
ip domain-name example.com
!
!
spanning-tree mode pvst
!
class-map match-any VOICE
  match ip dscp ef
!
policy-map QOS-POLICY
  class VOICE
    priority 1500
  class class-default
    fair-queue
!
!
!
!
```

```
!  
interface Loopback0  
  description "pro spravu zarizeni"  
  ip address 172.20.75.10 255.255.255.255  
!  
interface FastEthernet0/0  
  description "linka do R2"  
  ip address 172.20.0.78 255.255.255.252  
  service-policy output QOS-POLICY  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  duplex auto  
  speed auto  
  shutdown  
!  
interface Vlan1  
  no ip address  
  shutdown  
!  
router ospf 1  
  router-id 9.9.9.9  
  log-adjacency-changes  
  network 172.20.0.76 0.0.0.3 area 0  
  network 172.20.75.10 0.0.0.0 area 0  
!  
ip classless
```

```
!  
ip flow-export version 9  
!  
!  
!  
banner motd $Prakticka cast bakalarske prace v prostredi Cisco Packet Tracer$  
!  
radius-server host 172.20.50.10 auth-port 1645 key HuXGa6  
!  
!  
!  
!  
telephony-service  
  max-ephones 15  
  max-dn 15  
  ip source-address 172.20.0.78 port 2000  
!  
ephone-dn 1  
  number 1501  
!  
ephone-dn 2  
  number 1502  
!  
ephone-dn 3  
  number 1503  
!  
ephone-dn 4  
  number 1504  
!
```

ephone-dn 5
number 1505
!
ephone-dn 6
number 1581
!
ephone-dn 7
number 1582
!
ephone-dn 8
number 1583
!
ephone-dn 9
number 1584
!
ephone-dn 10
number 1585
!
ephone-dn 11
number 1551
!
ephone-dn 12
number 1552
!
ephone-dn 13
number 1553
!
ephone-dn 14
number 1554

!

ephone-dn 15

number 1555

!

ephone 1

device-security-mode none

mac-address 0060.5C3B.E46C

type 7960

button 1:1

!

ephone 2

device-security-mode none

mac-address 00E0.B07C.1EC8

type 7960

button 1:2

!

ephone 3

device-security-mode none

mac-address 00E0.A31E.1D5B

type 7960

button 1:3

!

ephone 4

device-security-mode none

mac-address 0060.47AC.3B09

type 7960

button 1:4

!

ephone 5

device-security-mode none
mac-address 00D0.FFC5.0BCE
type 7960
button 1:5

!

ephone 6
device-security-mode none
mac-address 0001.9758.BED3
type 7960
button 1:6

!

ephone 7
device-security-mode none
mac-address 0005.5E51.0948
type 7960
button 1:7

!

ephone 8
device-security-mode none
mac-address 000A.41EC.02EA
type 7960
button 1:8

!

ephone 9
device-security-mode none
mac-address 0060.479B.5DA0
type 7960
button 1:9

!

ephone 10

device-security-mode none

mac-address 0001.C724.7012

type 7960

button 1:10

!

ephone 11

device-security-mode none

mac-address 0090.2BBC.670E

type 7960

button 1:11

!

ephone 12

device-security-mode none

mac-address 0006.2ABB.AA45

type 7960

button 1:12

!

ephone 13

device-security-mode none

mac-address 0004.9A56.D59A

type 7960

button 1:13

!

ephone 14

device-security-mode none

mac-address 0010.11A3.B442

type 7960

button 1:14


```
!  
ephone 15  
  device-security-mode none  
  mac-address 0001.4283.7A88  
  type 7960  
  button 1:15  
!  
line con 0  
  password 7 08147E5D3E3B50  
!  
line aux 0  
  password 7 08147E5D3E3B50  
!  
line vty 0 4  
  login authentication SSH_AUTH  
  transport input ssh  
!  
!  
!  
end
```