

Security Standards & Data Protection Report

ACC User Management Application

Prepared by: Digibuild Report Date: 7 August 2026 Application Version: v2.1.0

Classification: Confidential

1. Data Processed

The application processes the following categories of personal and operational data:

Data Category	Examples	Storage Location	Encrypted
User Identity	Name, email address	Google Firestore (cloud)	✓ AES-256-GCM at rest
Authentication Credentials	Hashed passwords, JWT tokens	Firebase Authentication	✓ Firebase managed encryption
Access Tokens	Autodesk API 2-legged tokens	Server memory only (not persisted)	✓ In-memory, never written to disk
Project / Folder Permissions	Role assignments, folder access levels	Autodesk ACC API + Firestore	✓ TLS in transit; Firestore at rest
Audit Logs	Login timestamps, IP addresses, action logs	Server logs (VM)	✓ Access-restricted VM storage

Data Minimisation: The application collects only the personal data strictly necessary to manage project user permissions. No financial data, health data, or special categories of personal data (as defined by GDPR Article 9) are processed.

2. Encryption & Data Protection

Encryption at Rest

- **Algorithm:** AES-256-GCM (authenticated encryption — ciphertext integrity is cryptographically verified on every read, tampered data is rejected rather than silently decrypted)
- **Key derivation:** script, combined with a dedicated server-side encryption secret plus a unique random salt per record
- **IV:** Fresh random Initialisation Vector for every encryption operation
- **Storage:** Encrypted ciphertext, salt, IV and authentication tag stored in Firestore; the encryption secret is never stored alongside the data it protects
- **Key management:** Encryption key stored as environment variable, never hardcoded

Encryption in Transit

- **Protocol:** TLS 1.2 / 1.3 (HTTPS only in production)
- **HSTS:** Strict-Transport-Security max-age=31,536,000; includeSubDomains; preload
- **Upgrade policy:** CSP upgrade-insecure-requests directive enforces HTTPS
- **API traffic:** All calls to Autodesk ACC API over HTTPS
- **Firebase:** WebSocket over WSS (encrypted WebSocket)

Firestore (Google Cloud) Encryption

Google Cloud Firestore automatically encrypts all data at rest using AES-256 and all data in transit using TLS. This is in addition to the application-level AES-256-GCM authenticated encryption applied before data reaches Firestore — providing double-layer encryption, with integrity verification, for sensitive fields.

Secret / Key Storage

No credentials, API keys, or encryption keys are hardcoded in source code. All secrets are injected at runtime via OS environment variables and excluded from version control via `.gitignore`. The application fails with a fatal error on startup if any required secret is missing.

3. Authentication & Access Control

Control	Implementation
✓ Firebase Authentication	Industry-standard identity platform (Google) with email / password authentication
✓ Email Verification	Enforced server-side — non-admin accounts cannot log in until their email address is verified
✓ JWT Token Authentication	All API requests authenticated using short-lived JSON Web Tokens issued by Firebase

Control	Implementation
✓ Firestore App Check (reCAPTCHA v3)	Prevents automated / bot access to Firestore backend resources
✓ Role-Based Access Control (RBAC)	Admin and standard user roles enforced server-side; admin checks performed in Firestore Security Rules
✓ Firestore Security Rules	Server-side rules prevent any authenticated user from accessing another user's data
✓ Per-User Data Isolation	Multi-tenant architecture — each user can only read/write their own data partition
✓ No Client-Side Credential Storage	Session tokens are never written to localStorage or sessionStorage. The Autodesk API client secret is never sent to or held in the browser at all — the OAuth token exchange is performed entirely server-side
✓ OAuth State Parameter Validation	A cryptographically random state value is generated and verified before any authorization code is exchanged, protecting the Autodesk login flow against cross-site request forgery

4. Application Security — OWASP Top 10 Compliance

The following table maps the OWASP Top 10 (2021) vulnerability categories to the controls implemented in the application.

	OWASP Category	Status	Controls in Place
✓	A01 — Broken Access Control	MITIGATED	Firebase Security Rules + server-side admin middleware; per-user data isolation
✓	A02 — Cryptographic Failures	MITIGATED	AES-256-GCM authenticated encryption with script key derivation from a dedicated server-side secret; TLS 1.2/1.3; HSTS enforced; the Autodesk API client secret is never transmitted to or held in the browser
✓	A03 — Injection / XSS	MITIGATED	<code>escapeHtml()</code> function applied throughout; data originating outside the application (Autodesk project, hub, folder, company and role names; user-submitted emails shown in the admin panel) is rendered via safe DOM APIs (<code>textContent</code> / <code>element</code> properties) rather than HTML string concatenation; strict CSP blocks unauthorized script execution. A full audit of every dynamic HTML insertion point in the codebase (~100 locations) confirmed each is either non-dynamic (fixed markup with no interpolated content), interpolates only trusted internal values (counts, timestamps, fixed labels), or is explicitly escaped.
✓	A04 — Insecure Design	MITIGATED	Threat-modelled architecture; secrets management via environment variables; no debug endpoints in production
✓	A05 — Security Misconfiguration	MITIGATED	Comprehensive security headers (7 headers active); CORS restricted to allowed origins; no default credentials; static file serving is scoped exclusively to a dedicated public assets directory — server-side configuration and credential files are never web-accessible
✓	A06 — Vulnerable Components	MITIGATED	Dependencies tracked in <code>package.json</code> ; regular audit cycle
✓	A07 — Auth & Session Failures	MITIGATED	Firebase-managed auth; short-lived JWTs; enforced email verification before login; rate limiting (5 login attempts / 15 min); CSRF-protected OAuth flow via validated state parameter
✓	A08 — Software Integrity Failures	MITIGATED	CSP restricts script sources to explicit whitelist; external resources loaded from HTTPS CDNs only; Subresource Integrity (SRI) hashes verify every externally-loaded script matches its expected content before execution

OWASP Category	Status	Controls in Place
✓ A09 — Logging & Monitoring Failures	MITIGATED	Request logging with IP tracking; authentication event logging; error logging (non-verbose to users)
✓ A10 — Server-Side Request Forgery	MITIGATED	Server only makes outbound requests to whitelisted Autodesk and Google endpoints; no user-controlled URL parameters passed to backend fetch calls

5. HTTP Security Headers

All production responses include the following security headers, providing defence-in-depth against common browser-based attacks:

Header	Value / Description
✓ Strict-Transport-Security	max-age=31536000; includeSubDomains; preload — Forces HTTPS for 1 year across all subdomains
✓ Content-Security-Policy	Strict policy with default-src 'self'; frame-ancestors 'none'; form-action 'self'; object-src 'none'; upgrade-insecure-requests
✓ X-Frame-Options	DENY — Prevents clickjacking by disallowing the application from being embedded in any iframe
✓ X-Content-Type-Options	nosniff — Prevents MIME-type sniffing attacks
✓ X-XSS-Protection	1; mode=block — Activates browser's built-in XSS filter
✓ Referrer-Policy	strict-origin-when-cross-origin — Limits referrer information sent to third parties
✓ Permissions-Policy	geolocation=(), microphone=(), camera=() — Disables access to sensitive browser APIs not required by the application

6. Infrastructure & Hosting Security

Hosting Environment

- **Provider:** Google Cloud Platform (VM)
- **Region:** European data centre

Database — Google Firestore

- **Provider:** Google Firebase / Firestore
- Managed, serverless NoSQL database

- **Domain:** usermgt.digibuild.ch (HTTPS)
- **Process manager:** PM2 (auto-restart, single instance)
- **OS firewall:** Only ports 80, 443, 3000 open

- Automatic replication & backups
- AES-256 encryption at rest (Google-managed)
- TLS 1.3 encryption in transit
- SOC 1, SOC 2, ISO 27001 certified

Rate Limiting & DoS Protection

- **Global API:** 100 requests / 15 minutes per IP
- **Login endpoint:** 5 attempts / 15 minutes per IP
- **Register endpoint:** 5 attempts / 15 minutes per IP
- **Algorithm:** Sliding window with Redis backend
- **Behaviour:** Returns HTTP 429 on breach

Network & CORS Controls

- CORS restricted to explicitly whitelisted origins only
- No wildcard (*) origins in production
- Credentials flag enabled only for allowed origins
- Preflight requests validated server-side
- HTTP→HTTPS redirect active in production

Google Cloud & Firebase Security Certifications: The underlying infrastructure (Google Cloud Platform and Firebase) holds the following certifications: **ISO/IEC 27001, SOC 1 Type II, SOC 2 Type II, SOC 3, PCI DSS, FedRAMP** and more. Full details: cloud.google.com/security/compliance and firebase.google.com/support/privacy.

7. Known Limitations & Roadmap

Item	Status	Risk Level	Mitigation / Plan
Firestore SDK requires unsafe-inline CSP	ACCEPTED	Low (documented Firestore limitation)	All other CSP directives are strict; Google has certified this as the only supported method

8. Security Controls Summary

Control Domain	Status
✓ AES-256-GCM authenticated encryption at rest (application layer)	ACTIVE
✓ AES-256 encryption at rest (Firestore / GCP layer)	ACTIVE
✓ TLS 1.2/1.3 encryption in transit	ACTIVE

Control Domain		Status
✓	HSTS (HTTP Strict Transport Security)	ACTIVE
✓	Firebase Authentication (industry-standard)	ACTIVE
✓	Email verification enforced before login (non-admin accounts)	ACTIVE
✓	JWT token-based session management	ACTIVE
✓	Firebase App Check (reCAPTCHA v3 bot protection)	ACTIVE
✓	Role-Based Access Control (RBAC)	ACTIVE
✓	Firestore server-side Security Rules	ACTIVE
✓	CORS restricted to whitelisted origins	ACTIVE
✓	Rate limiting (API + authentication endpoints)	ACTIVE
✓	7 HTTP security headers (CSP, HSTS, X-Frame-Options, etc.)	ACTIVE
✓	XSS protection (escapeHtml + safe DOM rendering of external data + CSP)	ACTIVE
✓	Clickjacking protection (X-Frame-Options: DENY + CSP frame-ancestors)	ACTIVE
✓	Subresource Integrity (SRI) on all externally-loaded scripts	ACTIVE
✓	Request logging with IP tracking	ACTIVE
✓	Secrets management via environment variables (no hardcoded keys)	ACTIVE
✓	Server-side OAuth token exchange (Autodesk client secret never exposed to the browser)	ACTIVE
✓	OAuth state parameter validation (CSRF protection on login flow)	ACTIVE
✓	Static asset serving scoped to a dedicated public directory	ACTIVE
✓	Per-user data isolation (multi-tenant)	ACTIVE

