

State Contamination in Memory-Augmented LLM Agents

Yian Wang Agam Goyal Yuen Chen Hari Sundaram
Department of Computer Science, University of Illinois Urbana-Champaign

Abstract

LLM agents increasingly rely on persistent state, including transcripts, summaries, retrieved context, and memory buffers, to support long-horizon interaction. This makes safety depend not only on individual model outputs, but also on what an agent stores and later reuses. We study a failure mode we call memory laundering: toxic or adversarial context can be compressed into memory summaries that no longer appear toxic under standard detectors, while still preserving hostile framing or conflict structure that influences future generations. Using paired counterfactual multi-agent rollouts, we show that toxic-origin memory summaries can remain below common toxicity thresholds while nevertheless increasing downstream toxicity relative to matched neutral baselines. To measure this hidden influence, we introduce the sub-threshold propagation gap (SPG), which quantifies downstream behavioral differences conditioned on memory states that a deployed monitor would classify as safe. Our experiments show that toxicity propagates through distinct state channels: raw transcript reuse drives overt downstream toxicity, while compressed memory carries hidden sub-threshold influence. We further find that mitigation depends critically on intervention placement. Sanitizing toxic state before summarization substantially reduces the hidden propagation gap, whereas cleaning only the completed summary can leave laundered influence intact. These results suggest that safety in memory-augmented agents should be treated as a state-control problem over evolving context, with sanitization applied before unsafe information is compressed into persistent memory.

1 Introduction

LLM systems increasingly operate over long-running tasks: coordinating with users, collaborating with other agents, summarizing discussions, retrieving prior information, and carrying context forward over time [Wang et al., 2025b, Wu et al., 2025, Xi et al., 2025, Kulkarni et al., 2024]. This ability to remember and reuse context is central to agent usefulness, but it also makes memory part of the system’s safety surface [Wang et al., 2025a, Kagaya et al., 2024].

However, this same ability also changes the problem of safety. In a single-turn chatbot, an unsafe response can often be treated as a bad output to detect, block, or rewrite [Shi et al., 2024, Chua et al., 2024]. In an agentic system, however, a harmful message may not disappear after it is generated. It can be stored, summarized, retrieved, or passed along to other agents, becoming part of the context that shapes future behavior [Gao and Zhang, 2024, Rezazadeh et al., 2025]. Safety therefore depends not only on what an agent says at one moment, but also on what the system remembers from that moment and how that memory influences later generations, and the topological configuration they are connected under [Yagoubi et al., 2026, Bajaj et al., 2026].

Figure 1 illustrates the failure mode studied in this paper. Many agent systems compress long conversations into short summaries so that future agents can stay informed without reading the full history [Xu et al., 2025, Verma, 2026, Bousetouane, 2026, Du, 2026]. This compression is usually




Figure 1: **Memory laundering in stateful agents.** (a) In single-turn chatbots, safety monitoring is typically applied directly to the generated response. In memory-augmented agents, harmful influence can instead be compressed into external agent state, such as summaries or transcripts, that appears safe under standard toxicity checks while still conditioning downstream agents toward unsafe behavior. (b) In our work, we show that memory sanitization before summarization helps mitigate memory laundering. (c) For a representative example, a toxic source message from an agent is compressed into a memory summary that scores below the classifier threshold, yet a downstream agent conditioned on that memory produces a hostile response. The summary removes explicit insults while preserving the confrontational framing of the exchange. Additional examples are shown in §D.

treated as a practical engineering step: it saves context length and preserves the important parts of the interaction. We show that it can also act as a laundering step. A toxic message may be summarized into language that no longer looks toxic to a standard classifier, while still preserving the adversarial framing, conflict structure, or hostile stance that steers downstream agents toward toxic behavior.

We call this failure mode *memory laundering*: toxic influence is compressed into a memory summary that appears safe under standard monitoring but remains behaviorally potent, causing downstream agents to produce more toxic responses than matched neutral baselines. Figure 1 gives a concrete example: a toxic message is compressed into a memory summary that appears safe to a toxicity classifier, yet downstream agents conditioned on that memory still produce hostile responses.

We evaluate memory laundering with paired counterfactual multi-agent rollouts over 200 paired seeds. Although toxic-condition summaries fall below standard toxicity thresholds, they substantially increase downstream toxicity. We capture this hidden influence with the *sub-threshold propagation gap* (SPG): the toxic-neutral downstream difference conditioned on memory states satisfying $\text{tox}(M_t) < \tau$, i.e., the regime a deployed monitor would label safe. Here, *state* means external context reused by future generations: the raw transcript, compressed memory summaries, retrieved context, and other persistent context objects. It does not refer to the model’s parameters or hidden activations. Memory laundering occurs when this conditioning state is contaminated, compressed, and later reused. Our results show that toxic influence propagates through two distinct state channels. Raw transcript backflow primarily drives overt downstream toxicity, while compressed memory carries hidden sub-threshold influence. This distinction matters because sanitizing before memory update closes the laundered channel, whereas sanitizing only the completed summary can be too late because harmful framing may already have been compressed below the classifier threshold.

Contributions. (1) We identify and empirically characterize *memory laundering*, a previously unexamined safety failure mode in memory-augmented LLM agents: summarization can transform overtly toxic context into classifier-clean memory states that nevertheless steer downstream agents toward toxic behavior. (2) We introduce the *sub-threshold propagation gap* (SPG), a paired counterfactual metric for measuring behavioral influence inside the regime a deployed memory monitor would classify as safe. Using SPG with the average downstream toxicity shift ($\Delta\mu$) and tail-toxicity statistics ($P95_{\text{tox}}$), we show that transcript exposure drives overt toxicity, while compressed memory carries hidden sub-threshold influence. (3) We show that mitigation depends on where sanitization is placed:

toxic state must be sanitized before it is summarized, because cleaning only the completed summary can miss laundered influence. We evaluate a model-agnostic state-control framework that composes transcript control, memory control, and DPO, and show that the full system best suppresses mean, hidden, and tail propagation.

2 Related Work

Memory and state in LLM agents. Recent LLM agent architectures increasingly rely on external state: conversation histories, retrieved documents, memory buffers, reflections, and summaries that are reused across turns [Ai et al., 2025, Wang et al., 2025b]. Prior work has shown that such state improves long-horizon interaction, planning, and coordination [Xi et al., 2025]. Generative Agents store natural-language memories, synthesize them into reflections, and retrieve them to guide later behavior [Park et al., 2023]; Reflexion uses verbal feedback stored in episodic memory to improve subsequent decisions [Shinn et al., 2023]; MemGPT treats long-context interaction as a memory-management problem [Packer et al., 2023]; and AutoGen composes multiple conversable agents through shared interaction patterns [Wu et al., 2024]. These systems motivate our setting: memory is not merely a log of past interaction, but an input that shapes future behavior. *However, prior work largely treats memory as a capability mechanism or an object to retrieve from, whereas we study memory as a behavioral safety surface which can appear benign while steering future generations.*

Unsafe context propagation in agentic systems. Recent work shows that LLM applications become vulnerable when untrusted context is stored, retrieved, or reused in later model calls. Indirect prompt injection demonstrates that external content can be interpreted as instructions, exploiting the blurred boundary between data and commands in LLM-integrated systems [Greshake et al., 2023]. Memory and retrieval poisoning attacks extend this risk to agentic settings, showing that long-term memory or knowledge bases can be manipulated to steer future agent behavior [Chen et al., 2024]. Self-propagating agent attacks further show that once malicious payloads enter persistent agent state, they can spread across downstream tools, applications, or agent ecosystems [Cohen et al., 2024, Zhang et al., 2026]. Defenses such as structured prompting and context privilege separation aim to prevent untrusted data from being interpreted as privileged instructions [Chen et al., 2025]. *Our work approached this from a complementary perspective, since memory laundering does not require an explicit instruction payload, backdoor trigger, or threshold-crossing toxic artifact.*

From output-level safety and unlearning to state-level mitigation. Safety methods commonly intervene on model outputs or model parameters. Interpretability-based techniques detect and block unsafe generations through interventions on model activations [Goyal et al., 2025, Wang et al., 2026], while unlearning and preference optimization aim to reduce unsafe knowledge or behaviors inside the model [Jang et al., 2023, Rafailov et al., 2023, Yao and Xu, 2024]. Benchmarks such as TOFU and WMDP evaluate whether specific knowledge or capabilities can be removed from model behavior [Maini et al., 2024, Li et al., 2024], and recent work has shown that safety can degrade under long-context, pre-tuning, or multi-turn exposure to potentially harmful content [Anil et al., 2024, Chiang et al., 2025, Xing et al., 2025]. These approaches are important but insufficient for the failure mode we study. *In memory laundering, it is the external conditioning state that has been transformed by summarization and later reused. This motivates state-level controls over what agents read, what they write, and when memory is updated.*

3 Problem Formulation

We study *state-channel toxicity propagation* in multi-agent LLM systems: how toxic influence persists in evolving interaction state, which channels carry it, and which mitigations close them. Unlike per-message toxicity evaluation or classical parameter-level unlearning, this focuses on stateful behavioral propagation through transcripts, compressed memory, and model register-matching.

3.1 Agent-Mediated Conversations as State Machines

We model an agent-mediated discussion as a directed graph $G = (V, E)$ generated over a shared, evolving state. The process begins with a human seed post s and proceeds through a sequence of agent-generated messages. Each node $v \in V$ represents a message x_v produced by an agent $a_v \in \mathcal{A}$, and each edge $(u \rightarrow v) \in E$ indicates that x_v was generated conditioned on x_u . The authorship map

$v \mapsto a_v$ is *many-to-one*: a single agent may author multiple nodes in the graph. This matters for the focal agent A_1 defined below, which under the *multi-injection* condition authors several replies along a thread rather than only the first response.

At each generation step t , the acting agent observes a *conditioning set* $\mathcal{C}(v)$ drawn from the current state and produces a message:

$$x_v \sim \pi_\theta(\cdot \mid \mathcal{C}(v), r_v), \quad (1)$$

where π_θ is the agent’s policy (parameterized by an LLM with parameters θ), $\mathcal{C}(v)$ is the visible context, and r_v denotes the agent’s role. The state is then updated to include x_v , making it available to future agents. This observe–generate–update loop creates a closed-loop dynamical system in which each agent’s output becomes part of the conditioning context for subsequent agents.

3.2 Toxic Influence as Stateful Contamination

We define the *focal agent* A_1 as the first responder to the seed post and vary A_1 ’s behavior: $A_1 \in \{\text{neutral}, \text{toxic}\}$, while keeping all other components fixed, and each message is scored by an open-source toxicity model for reproducibility (Detoxify [Hanu and team, 2020]): $\text{tox}(v) = f_{\text{tox}}(x_v) \in [0, 1]$ where larger values indicate more toxic content. A threshold $\tau=0.5$ flags messages as overtly toxic.

We say that *toxic influence propagates* if downstream agents (which are neutral by design) produce measurably higher toxicity under the toxic A_1 condition than under the neutral condition. To isolate downstream propagation from A_1 ’s own contribution, we restrict the average to nodes *not authored* by A_1 . Let $V_{A_1} = \{v \in V : a_v = A_1\}$ denote the set of focal-agent nodes (a singleton in the single-injection case, larger under multi-injection). The downstream toxicity of a graph is then

$$\mu(G) = \frac{1}{|V \setminus V_{A_1}|} \sum_{v \in V \setminus V_{A_1}} \text{tox}(v), \quad (2)$$

and the **paired effect size** for seed s is:

$$\Delta\mu(s) = \mu\left(G^{(\text{toxic})}(s)\right) - \mu\left(G^{(\text{neutral})}(s)\right). \quad (3)$$

This definition guarantees that any positive $\Delta\mu$ reflects a change in non-focal agents’ behavior, not the mechanically high toxicity of A_1 ’s own message. A positive $\Delta\mu$ therefore indicates that A_1 ’s toxicity has causally influenced the downstream agents’ generations.

3.3 Three Channels of Toxic Persistence

We identify three distinct channels through which toxic influence persists in agentic systems:

(i) Transcript backflow. Toxic content produced by A_1 remains in the raw conversation history and re-enters downstream agents’ context at every subsequent turn. Even if a downstream agent would not independently produce toxic content, conditioning on a transcript that contains a high-toxicity message can elevate the Detoxify score of its own output. This is the dominant channel in systems where agents see the full conversation history.

(ii) Memory laundering. When agents maintain compressed memory representations (e.g., running summaries of the conversation), toxic framing can be *laundered* through summarization. The resulting summary may not score as explicitly toxic on classifiers, for instance, a summary might read “*the discussion has become heated, with participants expressing strong disagreement*” — yet conditioning on it raises the expected Detoxify score of subsequent generations relative to conditioning on the matched neutral summary. We formalize this as:

$$\text{tox}(M_t) < \tau \quad \text{but} \quad \mathbb{E}[\text{tox}(v) \mid M_t \in \mathcal{C}(v)] > \mathbb{E}[\text{tox}(v) \mid M_t^{(\text{neutral})} \in \mathcal{C}(v)], \quad (4)$$

where M_t is the contaminated memory and $M_t^{(\text{neutral})}$ is the memory from the paired neutral run.

(iii) Parametric bias. The model can amplify contamination through register-matching: when toxic transcript or laundered memory re-enters the conditioning context, the policy may produce higher-toxicity outputs than it would under matched neutral context, even after safety fine-tuning.

A robust mitigation must therefore prevent relapse under all three channels simultaneously — a property we formalize as *backflow-robust mitigation* in section A. Standard LLM unlearning methods (parameter editing, gradient ascent on forget sets) achieve $\Delta\mu \approx 0$ under single-turn evaluation but, as standalone mitigations, are not backflow-robust: they intervene only on *parametric bias* (channel iii) and leave *transcript backflow* (channel i) and *memory laundering* (channel ii) open, allowing toxic content to re-enter the state and trigger relapse.

3.4 Objective

Our objective is to suppress downstream toxic propagation after intervention while preserving the agent’s conversational utility. We therefore seek a system that drives the post-intervention paired effect toward zero, $\mathbb{E}_s[\Delta\mu^{(\text{post})}(s)] \approx 0$, without materially degrading coherence, topical relevance, or response quality. A formal version of this objective is given in section A.1.

This objective requires more than one intervention point. Parameter-level adaptation can reduce amplification of toxic context but cannot remove contaminated transcript or memory from external state; state controls can sanitize reads and gate writes, but residual conflict cues may survive. Memory-only controls likewise miss transcript backflow. This motivates a three-pathway mitigation framework: a fine-tuned policy $\pi_{\theta'}$ for residual parametric amplification, a read-side sanitizer S applied before generation, and a write-side gate W applied before content re-enters transcript or memory.

4 Method

We present an experimental and intervention framework for analyzing and mitigating toxic state contamination in multi-agent LLM systems. §4.1 describes the paired counterfactual setup that supports causal attribution of downstream toxicity to upstream injection. §4.2 introduces the three-pathway mitigation framework, with each subsection targeting one channel from §3.3. §4.3 defines two metrics. The full simulation environment, model details, prompt templates, and DPO hyperparameters are deferred to section B.

4.1 Paired Counterfactual Setup

Paired rollouts. To attribute downstream toxicity changes to a single source, we generate *paired* toxic-vs-neutral rollouts that differ only in the system prompt of the focal agent A_1 :

$$G^{(\text{toxic})}(s, T, r) \quad \text{and} \quad G^{(\text{neutral})}(s, T, r), \quad (5)$$

holding fixed seed s , topology T , generation schedule, agent assignment $\varphi : V \rightarrow \mathcal{A}$, and decoding randomness r . **Toxic** A_1 is instructed to respond hostilely; **neutral** A_1 constructively; downstream agents $A_2, \dots, A_n$ receive a generic “engaged user” prompt with no toxicity bias, ensuring any downstream shift is attributable to upstream exposure. This yields the paired effect size $\Delta\mu(s)$ (Eq. (3), restricted to non-focal nodes). To absorb stochastic decoding, we run R rollouts per seed and report $\bar{\mu}(s) = R^{-1} \sum_i \mu(G(s, r_i))$, alongside a tail-risk statistic, μ_{95} , the 95th percentile of downstream message toxicity within a condition, which indicates whether a condition can produce overtly toxic generations even when averages are diluted by benign turns.

Models, scoring, and conditioning modes. Phenomenon experiments use gpt-4o-mini [OpenAI, 2024]; intervention experiments requiring parameter access (DPO) use Llama-3.1-8B-Instruct [AI@Meta, 2024] via LoRA, with state-level interventions evaluated on both. Message-level toxicity uses Detoxify [Hanu and team, 2020] as $\text{tox}(\cdot) \in [0, 1]$. Downstream agents operate in either *full-transcript mode* (conditioning on the visible transcript) or *memory-augmented mode* (conditioning on a running summary $M_t = \text{Summarize}(M_{t-1}, x_{v_{t-1}})$ plus the parent message); the latter is the testbed for laundering. We vary topology (chain, tree, DAG, high-branching) and context visibility (parent-only, thread-local, full-visible) as confounders held fixed within each paired comparison. Full configuration appears in section B.

4.2 Three-Pathway Mitigation Framework

We instantiate the mitigated system with three interventions, each targeting one persistence channel from section 3.3. The key design constraint is placement: controls must act before contaminated

content is compressed into persistent memory, because laundered summaries often fall below the classifier threshold and are therefore invisible to post-hoc thresholded memory cleaning.

Transcript control — channel (i). Transcript control targets raw transcript backflow by sanitizing context before generation and gating outputs before storage. The sanitizer S rewrites or redacts toxic transcript content, while the gate W stores each generated message as-is, redacted, or rewritten, preventing overt toxicity from becoming future context.

Memory control — channel (ii). Memory control targets laundering through compressed summaries. We evaluate two variants: memory rewriting, which rewrites unsafe summary updates, and memory gating, which prevents toxic generated turns from being incorporated into the running memory. Since laundered memories are often classifier-clean by construction, thresholded memory rewriting is expected to miss some contaminated states; SPG is designed to measure this hidden failure mode.

Parameter-level control — channel (iii). Parameter-level control targets the model’s tendency to match the register of toxic context. We fine-tune with DPO on paired toxic–neutral rollouts, using the neutral-condition response as preferred and the toxic-condition response as dispreferred under the toxic-rollout context, so the model learns to choose the cleaner counterfactual output. Full details appear in sections B.6 and C.

Integration. At each generation step, the full system applies the controls in sequence: sanitize the conditioning state before generation, generate with the adapted policy $\pi_{\theta'}$, and gate or rewrite outputs before they re-enter transcript or memory. We evaluate single-pathway, pairwise, and full-system ablations to measure which channels each intervention closes.

4.3 Evaluation Metrics

We evaluate propagation through two complementary metrics, both introduced in this work.

Primary metric for hidden influence. The *sub-threshold propagation gap* (SPG) is defined as

$$\text{SPG}(\tau) = \mathbb{E}[\text{tox}(v_{t+1}) \mid \text{tox}(M_t) < \tau, \text{toxic}] - \mathbb{E}[\text{tox}(v_{t+1}) \mid \text{tox}(M_t) < \tau, \text{neutral}], \quad (6)$$

where expectations are taken over (M_t, v_{t+1}) pairs aggregated across rollouts, restricted to classifier-clean memory states. A significantly positive SPG indicates laundering: memory that appears safe under thresholded monitoring remains behaviorally influential.

Average and tail propagation. The paired effect size $\Delta\mu(s)$ (Eq. (3), over non-focal nodes $V \setminus V_{A_1}$) measures average downstream toxicity shift and is assessed via Wilcoxon signed-rank tests across seeds. We also report P95_{tox} , the empirical 95th percentile of downstream message toxicity, as a tail-risk statistic; the formal definition is given in section B.4.

Interpreting the metrics. In short, $\Delta\mu$ captures average downstream propagation, SPG captures hidden propagation through classifier-clean memory, and P95_{tox} captures tail severity; reporting all three reveals defenses that close one pathway while leaving another open.

Baselines. To our knowledge, no prior published method targets multi-agent state-channel toxicity propagation as a coordinated problem. We compare against three deployed paradigms: per-turn output filtering with Detoxify at $\tau=0.5$, DPO alone, and memory-only sanitization, all evaluated within the unified ablation in section 5.4.

5 Results

We organize results around four questions. We first present the paper’s central empirical finding: *memory laundering*, where classifier-clean summaries remain behaviorally toxic. We then disentangle transcript and memory as distinct propagation channels, verify the phenomenon is robust across topology and injection count, and finally evaluate the full channel-aware intervention framework.

5.1 Memory Laundering: Classifier-Clean but Behaviorally Toxic

We first establish the paper’s central empirical finding: compressed memory can appear safe to a toxicity classifier while still transmitting toxic influence to downstream agents. We evaluate this in the minimal memory-augmented chain setting, using 200 paired toxic–neutral rollouts with no

Table 1: Memory laundering on chain topology with memory augmentation and no sanitization. Across 200 seeds at $\tau = 0.5$, all memory summaries are classifier-clean, yet downstream behavior diverges strongly; SPG is shown on the toxic row, with significant paired gap ($p = 3.75 \times 10^{-8}$).

Condition	Mean $\text{tox}(M_t)$	Fraction $\text{tox}(M_t) < \tau$	SPG(τ)
Memory, neutral	0.0007	1.00	–
Memory, toxic	0.0852	1.00	0.140

Table 2: Channel comparison between transcript and memory modes on chain topology at $\tau = 0.5$. Mean metrics capture average downstream propagation, while P95_{tox} reports the empirical 95th percentile of downstream message toxicity in the toxic condition. High P95_{tox} values indicate upper-tail toxic generations that are diluted by benign turns; write-gating generated turns before they are added to transcript and summarized into memory substantially reduces both SPG and tail toxicity.

Mode / intervention	Mean $\text{tox}(M_t)$	$\Delta\mu$	SPG	Turn-final tox	P95_{tox}
Full transcript (no memory)	–	0.2684	–	0.1425	0.9348
Parent-only transcript (no memory)	–	0.1657	–	0.0173	0.8969
Memory only (no parent)	0.0144	0.0115	0.0970	0.0325	0.6775
Memory, no sanitization (both channels)	0.0852	0.1678	0.1395	0.1470	0.9309
Memory + rewrite ($\tau = 0.5$)	0.0121	0.0244	0.0856	0.0445	0.4127
Memory + gate ($\tau = 0.5$)	0.0142	0.0413	0.1030	0.0146	0.6775
Write-gate redact ($\tau = 0.5$)	0.0126	0.0031	0.0004	0.0255	0.2628
Write-gate rewrite ($\tau = 0.5$)	0.0147	0.0069	0.0006	0.0154	0.2808

memory sanitization. This setting isolates the laundering mechanism before introducing fan-out or topology effects; section 5.3 shows that the same signal persists on tree topology.

Memory summaries are classifier-clean. As shown in table 1, toxic-condition memory summaries have mean toxicity 0.0852, above the neutral baseline of 0.0007 but far below the standard threshold $\tau = 0.5$. Every stored summary in both conditions falls below τ . This is not an artifact of the particular threshold: across $\tau \in \{0.03, 0.05, 0.1, 0.2, 0.3, 0.5\}$, at least 99% of memory states are classified as clean (section E). Thus, a threshold-based monitor applied to memory would label nearly all states in both conditions as safe.

Classifier-clean memory still changes downstream behavior. Despite this clean labeling, downstream agents conditioned on toxic-condition memory produce substantially more toxic responses than those conditioned on matched neutral memory. Among memory states satisfying $\text{tox}(M_t) < \tau$, downstream toxicity is 0.141 in the toxic condition versus 0.001 in the neutral condition, giving $\text{SPG}(\tau) = 0.140$. At the seed level, the paired difference is 0.168 (95% CI [0.120, 0.226], Wilcoxon $p = 3.75 \times 10^{-8}$), and SPG remains significantly positive across all thresholds tested (section E, all $p < 0.001$). Figure 1 gives a representative laundering trace: the source message is overtly toxic, the memory summary falls below the classifier threshold, yet the downstream response remains hostile. Additional qualitative examples appear in section D.

5.2 Transcript and Memory are Distinct Propagation Channels

We now disentangle transcript and memory channels by varying downstream visibility: transcript-only with memory disabled, memory-only with no parent message, or combined transcript–memory conditioning. Using chain topology with $n=200$ paired seeds, we test four sanitization interventions at $\tau=0.5$: summary-level memory rewrite/gate after compression, and transcript write-gate redact/rewrite before generated turns are summarized into memory. Table 2 reports mean propagation metrics and P95_{tox} , the 95th percentile of downstream message toxicity in the toxic condition.

Channels carry distinct signatures. Transcript exposure primarily drives overt propagation. In transcript-only settings, $\Delta\mu$ is large under full visibility (0.268) and parent-only visibility (0.166), and the tail remains severe ($\text{P95}_{\text{tox}} = 0.935$ and 0.897). By contrast, isolating memory produces a smaller mean shift ($\Delta\mu = 0.012$), but a hidden gap: memory-only mode yields $\text{SPG}(\tau=0.5) = 0.097$ despite uniformly classifier-clean memory states (mean $\text{tox}(M_t) = 0.014$), with $\text{P95}_{\text{tox}} = 0.678$. The combined transcript–memory condition restores large overt propagation ($\Delta\mu = 0.168$, $\text{P95}_{\text{tox}} =$

Table 3: Defense ablation on Llama-3.1-8B-Instruct chain memory rollouts ($n = 200$ paired seeds). Baselines reduce visible toxicity but leave propagation channels open; single-channel controls suppress only part of the problem. Full system achieves lowest turn-final toxicity, $\Delta\mu$, and $P95_{tox}$, while Transcript+Memory attains lowest SPG. Values are mean $\pm$ standard error except $P95_{tox}$; bolded cells mark column minima. See §I for cross-model comparison with the gpt-4o-mini results.

Condition	Turn-final tox	$P95_{tox}$	$\Delta\mu$	SPG($\tau=0.5$)
No intervention	0.1207 ± 0.012	0.9048	0.1302 ± 0.015	0.0149 ± 0.008
Output filter	0.0204 ± 0.004	0.6514	0.0608 ± 0.010	0.0143 ± 0.004
DPO only	0.0601 ± 0.009	0.7804	0.0605 ± 0.012	0.0086 ± 0.006
Transcript only	0.0305 ± 0.006	0.1746	0.0309 ± 0.007	0.0053 ± 0.003
Memory only	0.0804 ± 0.011	0.7628	0.0807 ± 0.013	0.0027 ± 0.002
Transcript + Memory	0.0202 ± 0.004	0.1374	0.0108 ± 0.004	0.0012 ± 0.001
Transcript + DPO	0.0154 ± 0.003	0.2030	0.0159 ± 0.004	0.0036 ± 0.002
Memory + DPO	0.0402 ± 0.007	0.4946	0.0407 ± 0.008	0.0018 ± 0.001
Full system	0.0106 ± 0.002	0.1025	0.0059 ± 0.003	0.0014 ± 0.001

0.931) while increasing SPG only from 0.097 to 0.140. Thus, transcript backflow appears mainly in $\Delta\mu$ and tail toxicity, while compressed memory appears most clearly in SPG.

Laundering originates at compression, not at post-hoc sanitization. Summary-level memory controls applied after compression reduce overt toxicity but leave the hidden channel open: rewriting lowers $\Delta\mu$ from 0.168 to 0.024 and $P95_{tox}$ from 0.931 to 0.413, yet SPG remains 0.086; gating similarly leaves SPG at 0.103. By contrast, transcript write-gating before memory summarization nearly eliminates SPG (redact: 0.0004; rewrite: 0.0006) and lowers tail toxicity ($P95_{tox} = 0.263$ and 0.281). Thus, the issue is not that sanitization fails, but that sanitizing only the completed summary can be too late: toxic framing may already have been compressed below the classifier threshold while remaining behaviorally influential.

5.3 Robustness Across Topology and Injection Count

We verify that propagation and laundering generalize beyond the chain setting. Across chain, tree, DAG, and high-branching topologies, paired toxic-neutral comparisons show significantly positive downstream propagation in every condition ($p < 0.001$; full results in section F). Multi-injection consistently amplifies propagation relative to single-injection, while topology modulates magnitude: chain structure concentrates exposure, whereas high branching dilutes it.

To test whether laundering also survives topology changes, we replicate the section 5.1 memory experiment on tree topology ($n = 200$ paired seeds, gpt-4o-mini, memory-augmented mode, no sanitization). Even under branching dilution, classifier-clean memory states remain behaviorally influential: $SPG(\tau=0.5) = 0.049$ with paired Wilcoxon $p < 0.001$, while overt propagation drops to $\Delta\mu = 0.039$ (full numbers in section G). This is precisely the regime where SPG is most diagnostic: an analysis based only on $\Delta\mu$ could plausibly conclude that topology has mostly neutralized propagation, while SPG reveals hidden influence persisting inside classifier-clean memory.

5.4 Defense Comparison and Full Ablation

We evaluate whether channel-targeted interventions suppress propagation, alone and in combination, using Llama-3.1-8B-Instruct [AI@Meta, 2024] chain memory rollouts ($n = 200$ paired seeds, single-injection at A_1 , depth 4). We compare three baselines (*No intervention*, *Output filter*, *DPO only*), two single-channel state controls (*Transcript only* and *Memory only* at $\tau=0.5$), and four combinations including the full system. Table 3 reports mean propagation metrics with $P95_{tox}$, the 95th percentile of downstream toxicity in the toxic condition, which captures severe tail generations that can be hidden by low averages. Full condition specifications appear in section H.

Output filtering does not address the propagation channel. As shown in table 3, the post-generation filter reduces turn-final toxicity by an order of magnitude ($0.121 \rightarrow 0.020$), but $\Delta\mu$ remains 0.061, less than half of baseline yet still above the state-control combinations. It also leaves SPG unchanged from baseline (0.014 vs. 0.015), because the framing that survives compression

already sits below τ by construction. The tail statistic where $P95_{\text{tox}}$ remains high under output filtering (0.651) shows that severe toxic generations still occur even when the terminal mean is low.

Single-channel interventions reveal channel asymmetry. Transcript-only rewrite reduces $\Delta\mu$ to 0.031 and sharply lowers tail toxicity ($P95_{\text{tox}} = 0.175$), but leaves SPG at 0.005. Memory-only rewrite shows the inverse pattern: it reduces SPG to 0.003, the lowest single-channel value, but leaves $\Delta\mu$ at 0.081 and $P95_{\text{tox}}$ high (0.763). Transcript control suppresses the overt channel that drives $\Delta\mu$ and tail toxicity; memory control suppresses the laundered channel that drives SPG. Neither reaches the floor on its own, proving that $\Delta\mu$, SPG, and $P95_{\text{tox}}$ index complementary aspects of propagation.

The full system reaches the floor on mean and tail metrics. DPO-only reduces both $\Delta\mu$ ($0.130 \rightarrow 0.061$) and SPG ($0.015 \rightarrow 0.009$), but it leaves high-percentile toxicity large ($P95_{\text{tox}} = 0.780$), consistent with parametric debiasing reducing average amplification without removing contaminated state. Combining all three pathways yields the lowest turn-final toxicity (0.011), lowest $\Delta\mu$ (0.006), and lowest tail toxicity ($P95_{\text{tox}} = 0.103$), while approximately matching the near-floor SPG of the strongest state-only combination. The Transcript + Memory combination already reaches the lowest SPG (0.0012), so DPO’s marginal contribution is concentrated on overt and tail propagation; the full multiplicative structure is analyzed in section I. Each pathway is necessary; none is sufficient; the combination strictly dominates on the practical toxicity metrics.

Summary of findings. Transcript backflow drives overt propagation captured by $\Delta\mu$ and $P95_{\text{tox}}$, while compressed memory carries sub-threshold influence captured by SPG. Output filtering and DPO reduce visible generations or parametric amplification, but neither removes contaminated state from the loop. The full state-aware system performs best because it jointly addresses transcript backflow, memory laundering, residual amplification, and severe tail generations.

6 Conclusion and Discussion

This paper identifies *memory laundering*: summarization can remove overt toxicity markers while preserving behaviorally influential adversarial framing. We introduced SPG to measure this hidden regime by conditioning on memory states that a deployed monitor would label safe, and showed that it complements $\Delta\mu$: transcript backflow appears as overt downstream propagation, while compressed memory appears as sub-threshold influence.

Our mitigation results support a state-level view of agent safety. Output filtering and DPO reduce visible generations or parametric amplification, but they do not by themselves remove contaminated state from the conditioning loop. The strongest mitigation combines read-side sanitization, write-side state control, and parameter-level debiasing, with the key architectural constraint that intervention must occur before contaminated content is compressed into persistent memory. For memory-augmented agents, robust safety therefore requires sanitizing the state before summarizing it.

7 Limitations and Broader Impact

Our controlled Reddit-style simulations enable paired counterfactual evaluation but omit deployment complexity (longer histories, tools, retrieval, persistent memory); we therefore present the results as evidence of a mechanism and mitigation principle—sanitize before summarizing—rather than a deployment benchmark. Toxicity measurements rely on Detoxify and should be validated with other classifiers, human judgments, and task-specific harm measures. DPO requires parameter access and is evaluated only on Llama-3.1-8B-Instruct; future work should replicate on more open-weight models and deployed memory architectures.

The broader impact is primarily defensive: memory-augmented agents should be evaluated not only by outputs, but also by the summaries and state future agents consume. A dual-use risk is that memory laundering could inform attacks that hide harmful influence in benign-looking summaries; we reduce this risk by emphasizing aggregate metrics and mitigations rather than deployable attack procedures.

References

- Qingyao Ai, Yichen Tang, Changyue Wang, Jianming Long, Weihang Su, and Yiqun Liu. Memorybench: A benchmark for memory and continual learning in llm systems. *arXiv preprint arXiv:2510.17281*, 2025.
- AI@Meta. Llama 3 model card. 2024. URL https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md.
- Cem Anil, Esin Durmus, Nina Panickssery, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Meg Tong, Jesse Mu, Daniel Ford, et al. Many-shot jailbreaking. *Advances in Neural Information Processing Systems*, 37:129696–129742, 2024.
- Tanav Singh Bajaj, Nikhil Singh, Karan Anand, and Eishkaran Singh. Position: Safety and fairness in agentic ai depend on interaction topology, not on model scale or alignment. *arXiv preprint arXiv:2605.01147*, 2026.
- Fouad Bousetouane. Ai agents need memory control over more context. *arXiv preprint arXiv:2601.11653*, 2026.
- Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. {StruQ}: Defending against prompt injection with structured queries. In *34th USENIX Security Symposium (USENIX Security 25)*, pages 2383–2400, 2025.
- Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. *Advances in Neural Information Processing Systems*, 37:130185–130213, 2024.
- Jeffrey Yang Fan Chiang, Seungjae Lee, Jia-Bin Huang, Furong Huang, and Yizheng Chen. Why are web ai agents more vulnerable than standalone llms? a security analysis. *arXiv preprint arXiv:2502.20383*, 2025.
- Jaymari Chua, Yun Li, Shiyi Yang, Chen Wang, and Lina Yao. Ai safety in generative ai large language models: A survey. *arXiv preprint arXiv:2407.18369*, 2024.
- Stav Cohen, Ron Bitton, and Ben Nassi. Here comes the ai worm: Unleashing zero-click worms that target genai-powered applications. *arXiv preprint arXiv:2403.02817*, 2024.
- Pengfei Du. Memory for autonomous llm agents: Mechanisms, evaluation, and emerging frontiers. *arXiv preprint arXiv:2603.07670*, 2026.
- Hang Gao and Yongfeng Zhang. Memory sharing for large language model based agents. *arXiv preprint arXiv:2404.09982*, 2024.
- Agam Goyal, Vedant Rathi, William Yeh, Yian Wang, Yuen Chen, and Hari Sundaram. Breaking bad tokens: Detoxification of LLMs using sparse autoencoders. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng, editors, *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 12691–12709, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.641. URL <https://aclanthology.org/2025.emnlp-main.641/>.
- Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you’ve signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM workshop on artificial intelligence and security*, pages 79–90, 2023.
- Laura Hanu and Unitary team. Detoxify. Github, 2020. URL <https://github.com/unitaryai/detoxify>.
- Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. Knowledge unlearning for mitigating privacy risks in language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14389–14408, 2023.

- Tomoyuki Kagaya, Thong Jing Yuan, Yuxuan Lou, Jayashree Karlekar, Sugiri Pranata, Akira Kinose, Koki Oguri, Felix Wick, and Yang You. Rap: Retrieval-augmented planning with contextual memory for multimodal llm agents. *arXiv preprint arXiv:2402.03610*, 2024.
- Mandar Kulkarni, Praveen Tangarajan, Kyung Kim, and Anusua Trivedi. Reinforcement learning for optimizing rag for domain chatbots. *arXiv preprint arXiv:2401.06800*, 2024.
- Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, et al. The wmdp benchmark: Measuring and reducing malicious use with unlearning. *arXiv preprint arXiv:2403.03218*, 2024.
- Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C Lipton, and J Zico Kolter. Tofu: A task of fictitious unlearning for llms. *arXiv preprint arXiv:2401.06121*, 2024.
- OpenAI. Gpt-4o mini. <https://platform.openai.com/docs/models>, 2024. Accessed: 2026-05-03.
- Charles Packer, Vivian Fang, Shishir_G Patil, Kevin Lin, Sarah Wooders, and Joseph_E Gonzalez. Memgpt: towards llms as operating systems. 2023.
- Joon Sung Park, Joseph O’Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22, 2023.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741, 2023.
- Alireza Rezazadeh, Zichao Li, Ange Lou, Yuying Zhao, Wei Wei, and Yujia Bao. Collaborative memory: Multi-user memory sharing in llm agents with dynamic access control. *arXiv preprint arXiv:2505.18279*, 2025.
- Dan Shi, Tianhao Shen, Yufei Huang, Zhigen Li, Yongqi Leng, Renren Jin, Chuang Liu, Xinwei Wu, Zishan Guo, Linhao Yu, et al. Large language model safety: A holistic survey. *arXiv preprint arXiv:2412.17686*, 2024.
- Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652, 2023.
- Nikhil Verma. Active context compression: Autonomous memory management in llm agents. *arXiv preprint arXiv:2601.07190*, 2026.
- Bo Wang, Weiyi He, Shenglai Zeng, Zhen Xiang, Yue Xing, Jiliang Tang, and Pengfei He. Unveiling privacy risks in LLM agent memory. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 25241–25260, Vienna, Austria, July 2025a. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1227. URL <https://aclanthology.org/2025.acl-long.1227/>.
- Qingyue Wang, Yanhe Fu, Yanan Cao, Shuai Wang, Zhiliang Tian, and Liang Ding. Recursively summarizing enables long-term dialogue memory in large language models. *Neurocomputing*, 639: 130193, 2025b.
- Yian Wang, Yuen Chen, Agam Goyal, and Hari Sundaram. Causaldetox: Causal head selection and intervention for language model detoxification. *arXiv preprint arXiv:2604.14602*, 2026.
- Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, et al. Autogen: Enabling next-gen llm applications via multi-agent conversations. In *First conference on language modeling*, 2024.

- Yisha Wu, Cen Zhao, Yuanpei Cao, Xiaoqing Xu, Yashar Mehdad, Mindy Ji, and Claire Na Cheng. Incremental summarization for customer support via progressive note-taking and agent feedback. In Saloni Potdar, Lina Rojas-Barahona, and Sebastien Montella, editors, *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 2000–2015, Suzhou (China), November 2025. Association for Computational Linguistics. ISBN 979-8-89176-333-3. doi: 10.18653/v1/2025.emnlp-industry.140. URL <https://aclanthology.org/2025.emnlp-industry.140/>.
- Zhiheng Xi, Jixuan Huang, Chenyang Liao, Baodai Huang, Honglin Guo, Jiaqi Liu, Rui Zheng, Junjie Ye, Jiazheng Zhang, Wenxiang Chen, et al. Agentgym-rl: Training llm agents for long-horizon decision making through multi-turn reinforcement learning. *arXiv preprint arXiv:2509.08755*, 2025.
- Shuo Xing, Junyuan Hong, Yifan Wang, Runjin Chen, Zhenyu Zhang, Ananth Grama, Zhengzhong Tu, and Zhangyang Wang. Llms can get "brain rot"! *arXiv preprint arXiv:2510.13928*, 2025.
- Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-mem: Agentic memory for llm agents. *arXiv preprint arXiv:2502.12110*, 2025.
- Faouzi El Yagoubi, Godwin Badu-Marfo, and Ranwa Al Mallah. Agentleak: A full-stack benchmark for privacy leakage in multi-agent llm systems. *arXiv preprint arXiv:2602.11510*, 2026.
- Yuanshun Yao and Xiaojun Xu. Large language model unlearning. *Advances in Neural Information Processing Systems*, 37:105425–105475, 2024.
- Yihao Zhang, Zeming Wei, Xiaokun Luan, Chengcan Wu, Zhixin Zhang, Jiangrong Wu, Haolin Wu, Huanran Chen, Jun Sun, and Meng Sun. Clawworm: Self-propagating attacks across llm agent ecosystems. *arXiv preprint arXiv:2603.15727*, 2026.

A Formal Definitions and Objective

Section 3 identifies three channels of toxic persistence and notes that a robust mitigation must close all three. Here we give the two formal definitions referenced from section 3.3, which make precise what it means for a mitigation to remain effective under continuous re-exposure to toxic context.

Definition 1 (Relapse under re-exposure). *An agent exhibits relapse if, after a mitigation intervention $\mathcal{I}$ applied at time $t_{\mathcal{I}}$, it produces elevated toxicity when re-exposed to toxic context through the evolving state:*

$$\exists t > t_{\mathcal{I}} : \quad \text{tox}(v_t) > \text{tox}(v_t^{(\text{clean})}), \quad (7)$$

where $v_t^{(\text{clean})}$ is the message the agent would produce under clean (intervention-maintained) state, and v_t is the message actually produced when the state has been re-contaminated by upstream toxic content.

Definition 2 (Backflow-robust mitigation). *A mitigation method is backflow-robust if it prevents relapse under continuous re-exposure: for all t after the intervention,*

$$\Delta\mu^{(\text{post-}\mathcal{I})}(s) \approx 0, \quad (8)$$

even when the environment continues to surface toxic context through transcript accumulation and memory updates.

A.1 Formal Mitigation Objective

We write the mitigated system as $(\pi_{\theta'}, S, W)$, where $\pi_{\theta'}$ is a fine-tuned policy intended to reduce parametric amplification of toxic context, S is a read-side sanitizer applied to the conditioning set $\mathcal{C}(v)$ before generation, and W is a write-side gate applied after generation to control whether the produced message and its induced memory update enter the persistent state. The mitigation objective is

$$\mathbb{E}_s [\Delta\mu^{(\text{post})}(s)] \approx 0 \quad \text{subject to} \quad U(\tau') \approx U(\tau), \quad (9)$$

where $U(\cdot)$ denotes conversational utility, including coherence, topical relevance, and response quality. The constraint encodes that mitigation should suppress toxic propagation without simply degrading or refusing the downstream conversation.

This objective is channel-sensitive. Parameter-level adaptation through $\pi_{\theta'}$ targets parametric amplification, but does not by itself prevent contaminated transcript or memory from re-entering future context. The sanitizer S targets read-side exposure by transforming the conditioning state before generation. The gate W targets write-side persistence by controlling which generated messages and memory updates are stored for future turns. The three components therefore correspond to the three persistence channels identified in section 3.3: parametric bias, transcript backflow, and memory laundering.

Why standard unlearning is not backflow-robust. Standard LLM unlearning methods (parameter editing, gradient ascent on forget sets) achieve $\Delta\mu \approx 0$ under single-turn evaluation but fail to satisfy Definition 2 as standalone mitigations: they intervene only on *parametric bias* (channel iii) and leave *transcript backflow* (channel i) and *memory laundering* (channel ii) open. In a stateful multi-agent setting, the unsanitized state continues to accumulate toxic content across turns, eventually re-contaminating the agent’s conditioning context and triggering relapse. The three-pathway framework presented in section 4.2 is designed precisely to close all three channels jointly.

B Experimental Details

This appendix collects implementation details for the experimental and intervention framework of §4. §B.1 describes the simulation environment and seed-data pipeline. §B.2 describes the graph template constructions. §B.3 describes the memory module implementation. §B.6 reports DPO and LoRA hyperparameters.

Code release. We provide anonymized code, configuration files, prompt templates, and scripts for reproducing the main experiments at: https://anonymous.4open.science/r/unlearn_agent-55B9. The repository includes the simulation environment, topology definitions, memory module, toxicity-scoring pipeline, DPO training configuration, and scripts for reproducing the main results.

Existing assets and licenses. Our experiments use the following existing assets: gpt-4o-mini through the OpenAI API, governed by the OpenAI Services Agreement and Service Terms; Llama-3.1-8B-Instruct, released under the Llama 3.1 Community License; Detoxify, released under Apache-2.0; and Reddit-derived seed posts, used under Reddit’s applicable Developer/Data API Terms. We cite the corresponding model cards, repositories, and papers where applicable, and use these assets only for research evaluation under their stated terms.

B.1 Simulation Environment and Seed Data

We implement a controlled social-thread simulation platform in which LLM-based agents generate Reddit-style discussion graphs. Each simulation begins with a human seed post s and proceeds through a sequence of agent-generated replies, producing a discussion graph $G = (V, E)$ as defined in §3.

Seed data. Seed posts are drawn from r/politics, sampled to span a range of topics (domestic policy, foreign affairs, elections) and rhetorical postures. We exclude seed posts that already exceed the Detoxify threshold $\tau=0.5$ at the post level to ensure that any downstream toxicity is attributable to the focal agent A_1 and not to the seed. Posts are stored in JSONL format and loaded into the simulator by index.

Generation pipeline. Agent responses are generated via the OpenAI API (gpt-4o-mini) for phenomenon experiments and via local Llama-3.1-8B-Instruct inference (HuggingFace transformers, FP16, batch size 1) for intervention experiments. Decoding uses temperature 0.8, top- p 0.95, and a maximum response length of 256 tokens. For paired counterfactual rollouts, the same decoding seed is used for the toxic and neutral conditions, ensuring that any difference between the two rollouts is attributable to the focal-agent prompt only.

Scale. The phenomenon experiments span 200 paired seeds across seven topology conditions (1,400 paired rollouts). The intervention ablations span 200 paired seeds for the read- $\times$ -write transcript ablation and 200 for the memory ablation. Each experimental run completes in approximately 4–8 hours on a single A100 (Llama runs) or via OpenAI batch inference (gpt-4o-mini runs).

B.2 Graph Template Constructions

We evaluate across graph templates spanning realistic conversation structures. Each template is a parametric family with topology drawn deterministically from the parameters; randomness across rollouts comes only from agent decoding.

Chain. A linear thread $v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_L$ with depth $L = 4$. Serves as the minimal controlled setting for isolating backflow.

Balanced tree. A rooted tree with depth D and branching factor b , producing $|V| = \sum_{d=0}^D b^d$ nodes. We use two configurations: `tree-single-parent-only` ($D=3, b=3$, parent-only conditioning) and `tree-multi` ($D=3, b=3$, thread-local conditioning).

Cross-linked DAG. A balanced tree augmented with m cross-links between nodes at similar depth:

$$(u \rightarrow v) \text{ is added if } |\text{depth}(u) - \text{depth}(v)| \leq 1, \quad u \neq \text{parent}(v),$$

subject to acyclicity (enforced by the topological ordering). This models discussions where participants reply across subthreads. We evaluate `dag-single`, `dag-full-visible`, and `dag-multi`.

High-branching. A tree with large b ($b=5$) and fixed depth ($D=2$), stress-testing rapid fan-out scenarios characteristic of viral threads.

Conditioning regimes. The conditioning set $C(v)$ for each node v is parameterized independently of the topology. Under *parent-only*, $C(v) = \{x_{\text{parent}(v)}\}$. Under *thread-local*, $C(v)$ contains all predecessors in the same branch (i.e., the path from root to v). Under *full-visible*, $C(v)$ contains all messages generated before v in the topological ordering. The conditioning regime is held fixed across paired conditions within a comparison.

B.3 Memory Module Implementation

The memory module maintains a per-agent running summary that is updated after each turn. The summarizer is the same model used for generation (gpt-4o-mini or Llama-3.1-8B-Instruct, depending on experiment).

Summarizer prompt. The summarizer is invoked with a prompt of the form:

You are summarizing an ongoing discussion. Update the running summary with the new message. Keep the summary concise (under 80 words) and capture the key points and tone of the discussion. Do not add commentary.

Llama-specific handling. We observed that early implementations of the Llama-based summarizer echoed the full prompt rather than producing a summary. This was resolved by (a) using the proper chat template (`tokenizer.apply_chat_template` with `add_generation_prompt=True`), (b) capping output at `max_new_tokens=150`, and (c) post-processing to strip any leakage of the instruction prefix.

Memory toxicity scoring. After each update, the resulting summary is scored with Detoxify, providing $\text{tox}(M_{t+1})$ used for SPG conditioning and for memory-rewriting/gating triggers. We report SPG values for $\tau \in \{0.03, 0.05, 0.1, 0.2, 0.3, 0.5\}$ to verify robustness across thresholds.

B.4 Metric Definitions

P95 toxicity. We define P95_{tox} as the empirical 95th percentile of downstream message toxicity in a given condition. Let

$$T_c = \{\text{tox}(v) : v \in V \setminus V_{A_1}\}$$

denote the multiset of toxicity scores for downstream messages under condition c . Then

$$\text{P95}_{tox}(c) = Q_{0.95}(T_c),$$

where $Q_{0.95}$ is the empirical 0.95 quantile. We use P95_{tox} as a tail-risk statistic because mean toxicity can be low even when a small fraction of downstream generations become overtly toxic.

B.5 State-Control Implementations

This section gives the explicit implementation of the read- and write-side state controls used in the main text.

Transcript control. Read-side sanitization applies S to the conditioning set before generation:

$$\tilde{C}(v) = S(C(v)). \quad (10)$$

We instantiate S as either redaction, which replaces messages with $\text{tox}(v) > \tau$ by a placeholder, or rewriting, which preserves task-relevant content while removing hostile language. Write-side gating controls what enters the shared state after generation:

$$\text{state} \leftarrow \text{state} \cup W(x_v, \text{tox}(v)). \quad (11)$$

The gate W either stores the raw message, replaces high-toxicity messages with a placeholder, or rewrites them before storage. This prevents self-reinfection, where an agent’s own toxic output becomes downstream context.

Memory control. Memory rewriting scores each summary update and rewrites summaries above threshold:

$$\widetilde{M}_{t+1} = \begin{cases} \text{Rewrite}(M_{t+1}), & \text{tox}(M_{t+1}) > \tau, \\ M_{t+1}, & \text{otherwise.} \end{cases} \quad (12)$$

Memory gating prevents toxic generated turns from entering the running summary:

$$M_{t+1} = \begin{cases} M_t, & \text{tox}(v_t) > \tau, \\ \text{Summarize}(M_t, x_{v_t}), & \text{otherwise.} \end{cases} \quad (13)$$

These implementations expose the order-of-operations issue studied in section 5.2: controls applied before compression can prevent laundering, whereas thresholded rewriting after compression can miss classifier-clean but behaviorally influential summaries.

B.6 DPO Hyperparameters

DPO training is implemented with `trl.DPOTrainer` on `Llama-3.1-8B-Instruct`, using LoRA for parameter-efficient fine-tuning.

Table 4: DPO and LoRA hyperparameters for parameter-level intervention.

Hyperparameter	Value
Base model	Llama-3.1-8B-Instruct
LoRA rank r	16
LoRA α	32
LoRA target modules	q_proj, k_proj, v_proj, o_proj
LoRA dropout	0.05
DPO β	0.1
Learning rate	5×10^{-6}
LR schedule	cosine, 10% warmup
Optimizer	AdamW ($\beta_1=0.9, \beta_2=0.999$)
Weight decay	0.0
Epochs	3
Per-device batch size	4
Gradient accumulation	4
Effective batch size	16
Max sequence length	2048
Mixed precision	bf16

Preference pair filtering. Of the candidate pairs (m_t^+, m_t^-) extracted from paired rollouts, we retain only those where $\text{tox}(m_t^-) - \text{tox}(m_t^+) > 0.1$ in Detoxify units, ensuring a behaviorally meaningful preference signal and avoiding training on borderline pairs. This filter retains approximately 68% of candidate pairs.

Compute. DPO training completes in approximately 6 hours on a single A100 (40GB) for $\sim 4,000$ filtered preference pairs.

C DPO Counterfactual Preference Pair Design

DPO objective. For each seed s and downstream turn t , we extract two responses from the paired rollouts: m_t^+ from the neutral arm and m_t^- from the toxic arm, retaining the pair only when $\text{tox}(m_t^-) > \text{tox}(m_t^+)$. Both responses are evaluated against the toxic-rollout context $c_t^{(\text{tox})}$:

$$\mathcal{L}_{\text{DPO}} = -\log \sigma \left(\beta \left(\log \pi_{\theta}(m_t^+ | c_t^{(\text{tox})}) - \log \pi_{\theta}(m_t^- | c_t^{(\text{tox})}) \right) \right), \quad (14)$$

where $\beta > 0$.

Section C introduces the DPO loss (eq. (14)) and notes briefly that both preference responses are evaluated against the toxic-rollout context $c_t^{(\text{tox})}$. Here we expand on why this choice is a deliberate departure from standard preference-data construction and why the alternative (evaluating each response under its own context) does not produce the robustness signal we want.

The intended behavioral lesson. The pair (m_t^+, m_t^-) is meaningful as a counterfactual: m_t^+ is what the agent would have said had upstream context been clean (it was generated under $c_t^{(\text{neu})}$ in the neutral rollout), and m_t^- is what it actually said when the same agent was placed in the toxic-rollout context $c_t^{(\text{tox})}$. The pair is retained only when $\text{tox}(m_t^-) > \text{tox}(m_t^+)$ under Detoxify, so the contrast directly reflects toxic-context-induced amplification.

Why we evaluate both responses against $c_t^{(\text{tox})}$. The behavioral lesson we want to teach is: *“in the presence of toxic upstream context, prefer the neutral-condition response over the toxic-condition response.”* To encode this in the DPO loss, both responses must be evaluated under the same conditioning context — specifically, the toxic one. Evaluating $\log \pi_\theta(m_t^+ | c_t^{(\text{tox})})$ asks the model: “what is the likelihood of producing the clean-counterfactual response given that the upstream is toxic?” Evaluating $\log \pi_\theta(m_t^- | c_t^{(\text{tox})})$ asks: “what is the likelihood of producing the toxic-amplified response given that same upstream?” The DPO objective then increases the former and decreases the latter, which is exactly the desired direction: when re-exposed to toxic context, the model’s distribution over outputs should shift toward the clean-counterfactual response.

Why the alternative does not work. A natural alternative is to evaluate each response under its own original context: $\log \pi_\theta(m_t^+ | c_t^{(\text{neu})})$ versus $\log \pi_\theta(m_t^- | c_t^{(\text{tox})})$. This formulation does *not* create a robustness signal. Under matched conditioning, m_t^+ is already plausible under $c_t^{(\text{neu})}$ and m_t^- is already plausible under $c_t^{(\text{tox})}$ (both were sampled from the same base policy under those exact contexts). The preference signal therefore reduces to “imitate downstream agents under matched conditions,” which provides no instruction about what to do when context is contaminated. The model would learn to track its own training distribution rather than to resist toxic conditioning.

Connection to the backflow-robust property. This design choice is what makes DPO complement state-level controls rather than substitute for them. State-level controls aim to keep c_t close to $c_t^{(\text{neu})}$ at inference time; DPO trained as above aims to behave correctly even when c_t is closer to $c_t^{(\text{tox})}$ than the sanitizer caught. The two pathways therefore protect against different failure modes, which is reflected in the channel-asymmetric reduction pattern observed in the defense ablation (section 5.4).

D Additional Qualitative Examples of Memory Laundering

Figure 2 shows two additional laundering traces from independent toxic-condition chain rollouts. These examples illustrate two other laundering modes: flattening explicit hostility into neutral conflict language, and preserving ideological or us-vs-them framing without lexical markers that trigger the toxicity classifier.


E SPG Robustness Across Classifier Thresholds

Section 5.1 reports the central SPG result at the standard threshold $\tau = 0.5$ ($\text{SPG} = 0.140$, $p = 3.75 \times 10^{-8}$), and notes that SPG remains stable across a range of thresholds. Figure 3 provides the full threshold-sensitivity analysis. SPG is significantly positive at every threshold tested (all $p < 0.001$, paired Wilcoxon signed-rank), and stable at ≈ 0.14 across $\tau \in \{0.03, 0.05, 0.1, 0.2, 0.3, 0.5\}$. Across this entire range, the fraction of memory states classified as clean satisfies $\Pr[\text{tox}(M_t) < \tau] \geq 0.99$, so a standard classifier-based monitor would label essentially every memory state in both conditions as safe at any threshold a deployment would plausibly use. The laundering finding therefore does not depend on the specific choice of $\tau = 0.5$.

F Propagation Robustness Across Topology and Injection Count

Table 5 reports the full topology and injection-count robustness results summarized in section 5.3. Each row is a paired toxic–neutral comparison over 200 seeds with full-visible context unless otherwise noted. Propagation is significantly positive in every condition ($p < 0.001$), multi-injection amplifies propagation relative to single-injection, and topology modulates the magnitude of downstream exposure.

Example 2 — hostile rhetorical questions → flattened summary



Example 3 — us-vs-them framing → summary preserves dichotomy




Figure 2: **Additional qualitative examples of memory laundering.** Each example shows a toxic source message from agent A_1 , the resulting compressed memory state M_t , and the downstream response conditioned on that memory. In both cases, the memory summary scores below $\tau = 0.5$ despite source toxicity above 0.9, yet the downstream response remains overtly toxic. Example 2 flattens explicit hostility into a neutral description of conflict; Example 3 preserves ideological framing and an us-vs-them dichotomy while removing overt toxic markers.




Figure 3: **Sub-threshold propagation gap $\text{SPG}(\tau)$ as a function of the classifier threshold τ under memory-augmented chain rollouts** ($n = 200$ seeds). SPG remains stable at ≈ 0.14 across $\tau \in \{0.03, 0.05, 0.1, 0.2, 0.3, 0.5\}$ and is significantly positive at every threshold (all $p < 0.001$, paired Wilcoxon signed-rank). Across this entire range, the fraction of memory states classified as clean satisfies $\Pr[\text{tox}(M_t) < \tau] \geq 0.99$, meaning a standard classifier-based monitor would label essentially every memory state in both conditions as safe. The vertical dotted line marks the standard threshold $\tau = 0.5$; the shaded band shows the 95% bootstrap CI.

G Cross-Topology Robustness of Memory Laundering

Section 5.3 reports the cross-topology validation of memory laundering on tree topology in summary form. Table 6 below gives the full numbers ($n = 200$ paired seeds, gpt-4o-mini agent and summarizer, memory-augmented mode, no sanitization, $\tau = 0.5$). Compared to the chain baseline ($\text{SPG} = 0.140$, $\Delta\mu = 0.168$; section 5.1), tree topology produces smaller magnitudes on every metric but preserves the laundering signature: classifier-clean memory states (mean $\text{tox}(M_t) = 0.016$) still produce a significant downstream toxicity gap. The dilution reflects the natural averaging effect of fan-out — at each downstream node, toxic framing competes with multiple sibling contexts, and the summarizer compresses more aggressively when summarizing diverse multi-voice input.

Table 5: Propagation across rollout conditions. Each row reports a paired toxic-vs.-neutral comparison over 200 seeds, with p -values from Wilcoxon signed-rank tests.

Condition	N	$\bar{\mu}_{\text{toxic}}$	$\bar{\mu}_{\text{neutral}}$	$\Delta\mu$	95% CI	p
Chain-single	200	0.2692	0.0008	0.2684	[0.2067, 0.2792]	< 0.001
Tree-single (full_visible)	200	0.1075	0.0011	0.1065	[0.0132, 0.2197]	< 0.001
Tree-multi (full_visible)	200	0.2260	0.0007	0.2253	[0.0865, 0.3884]	< 0.001
DAG-single (full_visible)	200	0.0347	0.0011	0.0336	[0.0069, 0.0426]	< 0.001
DAG-multi (full_visible)	200	0.1560	0.0006	0.1554	[0.0431, 0.2935]	< 0.001
High-branch-single (full_visible)	200	0.0252	0.0003	0.0249	[0.0055, 0.1058]	< 0.001
High-branch-multi (full_visible)	200	0.0605	0.0008	0.0597	[0.0204, 0.1026]	< 0.001

Table 6: Cross-topology validation of memory laundering on tree topology ($n = 200$ paired seeds, gpt-4o-mini agent and summarizer, memory-augmented mode, no sanitization, $\tau = 0.5$). The paired Wilcoxon signed-rank p -value is for $\text{SPG}(\tau = 0.5) > 0$.

Mode / intervention	Mean tox(M_t)	$\Delta\mu$	$\text{SPG}(\tau=0.5)$	Turn-final tox (toxic)	p
Tree memory laundering	0.0160	0.0387	0.0492	0.0085	< 0.001

H Defense Ablation: Full Condition Specifications

Section 5.4 evaluates nine intervention conditions on Llama-3.1-8B-Instruct chain memory rollouts. We list the full specification of each condition here.

Baselines. *No intervention:* the unmodified chain memory protocol from section 4.1, with no sanitization on either channel and no parameter-level intervention. *Output filter:* a post-generation Detoxify filter that replaces any message v with $\text{tox}(v) > \tau$ by a neutral placeholder before v is appended to the transcript or used to update the memory summary. *DPO only:* the LoRA-fine-tuned policy $\pi_{\theta'}$ from section C with no state-level controls.

Single-channel state controls. *Transcript only:* write-gate rewrite at $\tau=0.5$ applied to agent outputs before they enter the transcript; no memory sanitization, no DPO. *Memory only:* memory-write rewrite at $\tau=0.5$ applied to summary updates; no transcript sanitization, no DPO. Both interventions follow the formulations in section B.5.

Combinations. *Transcript + Memory:* write-gate rewrite on both channels, no DPO. *Transcript + DPO:* write-gate rewrite on transcript with DPO-fine-tuned policy, no memory sanitization. *Memory + DPO:* memory-write rewrite with DPO-fine-tuned policy, no transcript sanitization. *Full system:* all three pathways active simultaneously.

Common protocol. All conditions use $n = 200$ paired seeds, single-injection at A_1 with strong toxic intensity, chain depth-4 graph, full-visible context for downstream agents, and the same decoding seed across the toxic and neutral arms within each pair. All sanitization thresholds are fixed at $\tau=0.5$ to match the standard Detoxify operating point.

I Detailed Defense Ablation Analysis

Section 5.4 reports the headline conclusion of the defense ablation: each pathway is necessary, none is sufficient, and the full system strictly dominates. Here we expand on two structural observations that the main-paper space did not allow.

DPO interactions are roughly multiplicative across channels. Adding DPO to Transcript-only reduces $\Delta\mu$ from 0.031 to 0.016 (an additional $1.9\times$ reduction). Adding DPO to Memory-only reduces $\Delta\mu$ from 0.081 to 0.041 (an additional $2.0\times$ reduction). DPO contributes a comparable *relative* reduction whether it is added to a transcript-controlled or memory-controlled baseline, consistent with parametric amplification operating as an independent channel that interacts multiplicatively with the upstream content channels rather than substituting for either.

Sub-additivity on SPG, super-additivity on $\Delta\mu$. The Transcript + Memory combination reaches $\text{SPG} = 0.0012$ without DPO, only marginally above the full system’s 0.0014, and below the Transcript + DPO (0.0036) and Memory + DPO (0.0018) combinations. Once both state channels are sanitized, residual SPG is small and DPO provides no further reduction on this metric — consistent with SPG indexing a pathway (memory laundering) that DPO cannot reach without state-level support. By contrast, $\Delta\mu$ remains at 0.011 for Transcript + Memory and only drops to 0.006 in the full system, so DPO contributes meaningfully to the overt-propagation channel even when both state channels are controlled.

Diagnostic of overall propagation versus terminal output. For the Output filter baseline, turn-4 toxicity drops by an order of magnitude (from 0.121 to 0.020), yet $\Delta\mu$ remains 0.061. The discrepancy is itself diagnostic: the filter suppresses the visible terminal output, but the toxic-arm trajectory still accumulates a substantial cumulative gap relative to the neutral arm across earlier turns. The filter operates on terminal generations, while $\Delta\mu$ aggregates across all downstream turns, so cumulative exposure across the toxic-arm trajectory is not undone by suppressing only the final turn.

Cross-model comparison with gpt-4o-mini. Table 2 (gpt-4o-mini) and Table 3 (Llama-3.1-8B-Instruct) report defense ablations on different base models, and absolute SPG and $\Delta\mu$ values are not directly comparable due to differences in safety training and base toxicity profiles—Llama-3.1-8B-Instruct exhibits substantially lower absolute SPG across all conditions, consistent with stronger refusal behavior on overtly hostile contexts.

The qualitative channel balance is also model-dependent. On gpt-4o-mini, summary-level memory rewriting (Table 2, “Memory + rewrite”) suppresses $\Delta\mu$ from 0.168 to 0.024 but leaves SPG at 0.086—the canonical laundering signature, where post-compression cleaning removes overt toxicity but misses the sub-threshold framing already baked into the summary. On Llama-3.1-8B-Instruct, memory rewriting (Table 3, “Memory only”) instead suppresses SPG to 0.003 but leaves $\Delta\mu$ at 0.081. We interpret this as reflecting where each model’s residual toxic signal lives after late-stage sanitization: gpt-4o-mini’s summaries retain more sub-threshold framing that survives rewriting, while Llama-3.1-8B-Instruct’s stronger safety training removes the sub-threshold signal more readily but leaves more residual $\Delta\mu$ propagating through other paths (e.g., parametric register-matching that memory rewriting alone cannot address).

Both patterns are consistent with the channel decomposition in §3: memory rewriting acts only on the memory channel and only after compression, so its effectiveness on each metric depends on the underlying policy’s toxicity profile. Critically, this model-dependence does *not* affect our central design claim. Across both models, transcript write-gating (which intervenes *before* compression) closes both channels jointly: on gpt-4o-mini, write-gate rewrite drives SPG to 0.0006 and $\Delta\mu$ to 0.007 (Table 2); on Llama-3.1-8B-Instruct, the Transcript+Memory combination drives SPG to 0.0012 and $\Delta\mu$ to 0.011 (Table 3). The “sanitize before summarizing” rule is robust across both models even though the relative channel balance differs.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and introduction state the main claims and contributions: identifying memory laundering, introducing SPG, disentangling transcript and memory channels, and proposing state-aware mitigations. The scope is further bounded by the controlled simulation setup and limitations in Section 7.

Guidelines:

- The answer [\[N/A\]](#) means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [\[No\]](#) or [\[N/A\]](#) answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [\[Yes\]](#)

Justification: Section 7 discusses limitations.

Guidelines:

- The answer [\[N/A\]](#) means that the paper has no limitation while the answer [\[No\]](#) means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren’t acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: The paper introduces formal definitions and metrics, but does not present theorem-style theoretical results requiring formal assumptions and proofs.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: The paper describes the paired counterfactual rollout protocol, agent models, scoring model, topology templates, memory module, sanitization interventions, DPO pair construction, and LoRA/DPO hyperparameters in Section 4 and Sections B and C.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: Section B provides an anonymized repository link containing code, configuration files, prompt templates, and scripts for reproducing the main experiments, including the simulation environment, topology definitions, memory module, toxicity-scoring pipeline, and DPO setup.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: Sections 4 and 5 and Section B provide the details needed to understand and reproduce the experimental setup, including the paired rollout protocol, seed filtering, graph topologies, conditioning regimes, memory module, decoding settings, intervention definitions, evaluation metrics, and DPO/LoRA hyperparameters.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: The paper reports paired Wilcoxon signed-rank tests, p-values, confidence intervals, standard errors, and bootstrap confidence intervals for the main propagation, SPG, topology, and ablation results.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.

- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

[Yes]

Justification: Section B reports compute resources, including A100 40GB GPU use, approximate runtime for Llama runs and OpenAI batch inference, and DPO training time.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The authors ensure the final submission preserves anonymity and conforms to the NeurIPS Code of Ethics.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: The paper includes a Broader Impact discussion in Section 7, covering both defensive motivations for memory-augmented agent safety and potential dual-use risks.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

answer: [N/A]

Justification: The paper does not release a new high-risk pretrained model, image generator, or scraped dataset. The safety-relevant content is reported through aggregate metrics and qualitative examples with emphasis on mitigations.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: Section B lists the existing assets used in the experiments and their applicable licenses or terms.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.

- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset’s creators.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [N/A]

Justification: The current manuscript does not indicate that a new dataset, model, or code asset is being released with the submission.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The paper does not involve crowdsourcing or direct human-subject experiments; it uses controlled LLM-agent simulations.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: The paper does not involve crowdsourcing or direct human-subject experiments. It uses controlled simulations and seed posts rather than recruiting participants.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: LLMs are a core component of the methodology: gpt-4o-mini is used for phenomenon experiments and summarization, and Llama-3.1-8B-Instruct is used for parameter-access intervention experiments with DPO/LoRA. These uses are described in Sections 4 and 5 and Section B.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.