

# sbt Reference Manual

## Contents

Preface . . . . .	3
<b>sbt</b> . . . . .	<b>3</b>
sbt . . . . .	3
. . . . .	3
Mac   sbt . . . . .	4
. . . . .	4
. . . . .	4
Windows   sbt . . . . .	4
. . . . .	4
Windows . . . . .	4
Linux   sbt . . . . .	4
. . . . .	4
Ubuntu   Debian . . . . .	4
Linux   RPM . . . . .	5
Gentoo . . . . .	6
Hello, World . . . . .	6
. . . . .	6
. . . . .	6
sbt . . . . .	7
. . . . .	7
. . . . .	7
. . . . .	7
sbt . . . . .	8
. . . . .	8
. . . . .	8
. . . . .	8
. . . . .	8
. . . . .	8
. . . . .	9
. . . . .	9
. . . . .	9
. . . . .	9
Tab . . . . .	9
. . . . .	10

.sbt	10
	10
	10
build.sbt	11
Keys	12
tasks settings	13
sbt Keys	13
build.sbt	14
bare .sbt	14
	14
Scope	15
Key	15
Scope	15
Scope	16
	16
sbt scope key	16
scoped key	17
scope	17
scope	19
scope	19
	20
	20
+= +=	20
key	20
+= +=	22
	22
	22
	23
	25
	25
	26
root	27
	28
	28
	28
	28
	28
	29
	30
	30
	30
	30
	31
	31
	35
	35

sbt	35
	36
.scala	37
	37
	37
sbt:	37
	38

## Preface

### sbt

sbt sbt

sbt

.sbt scopes

sbt

### sbt

sbt

- sbt
- hello world
- 
- 
- sbt sbt
- .sbt

Jar Shell Mac Windows Linux

sbt terminal encoding HTTP JVM

**Mac**    **sbt**

ZIP    TGZ

**Homebrew**

```
$ brew install sbt@1
```

**Macports**

```
$ port install sbt
```

**Windows**    **sbt**

ZIP    TGZ

**Windows**

msi

**Linux**    **sbt**

ZIP    TGZ

**Ubuntu**    **Debian**

DEB    sbt

Ubuntu    Debian    DEB  
Synaptic            sbt

DEB  
sudo

apt-get aptitude

```

echo "deb https://dl.bintray.com/sbt/debian /" | sudo tee -a /etc/apt/sources.list.d/sbt.list
sudo apt-key adv --keyserver hkps://keyserver.ubuntu.com:80 --recv 2EE0EA64E40A89B84B2DF7349
sudo apt-get update
sudo apt-get install sbt

sbt          Bintray Bintray      APT
sbt aptitude Synaptic          System Settings ->
Software & Updates -> Other Software

```




Figure 1: Ubuntu Software & Updates Screenshot

## Linux RPM

```

RPM sbt

Linux RPM RPM sbt sudo

curl https://bintray.com/sbt/rpm/rpm > bintray-sbt-rpm.repo
sudo mv bintray-sbt-rpm.repo /etc/yum.repos.d/
sudo yum install sbt

sbt Bintray Bintray RPM

sbt-launcher-package

```

## Gentoo

```
sbt          ebuild          sbt ebuilds          ebuilds sbt
emerge dev-java/sbt
```

## Hello, World

```
sbt
```

```
sbt          hello          hw.scala
object Hi {
  def main(args: Array[String]) = println("Hi!")
}
hello sbt run sbt Linux OS X
$ mkdir hello
$ cd hello
$ echo 'object Hi { def main(args: Array[String]) = println("Hi!") }' > hw.scala
$ sbt
...
> run
...
Hi!

sbt sbt

•
• src/main/scala src/main/java
• src/test/scala src/test/java
• src/main/resources src/test/resources
• lib jar

sbt Scala sbt run sbt console Scala REPL sbt
console classpath Scala
```

```
build.sbt          hello hello/build.sbt
lazy val root = (project in file("."))
  .settings(
    name := "hello",
```

```

    version := "1.0",
    scalaVersion := "2.12.4"
  )
.sbt          build.sbt
    jar      build.sbt      name version

sbt

    hello/project/build.properties      sbt      1.1.0
sbt.version=1.1.0
sbt  release  99%      project/build.properties      sbt

    sbt      Hello, World

    sbt  " "      Hello, World      hello      hello/build.sbt
hello/hw.scala hello

    hello/hw.scala      sbt Maven

src/
  main/
    resources/
      <files to include in main jar here>
    scala/
      <main Scala sources>
    java/
      <main Java sources>
  test/
    resources
      <files to include in test jar here>
    scala/
      <test Scala sources>
    java/
      <test Java sources>
src/

```

sbt

build.sbt sbt project project .scala .sbt

build.sbt  
project/  
Build.scala  
project/ .sbt .sbt

classes jars caches target

.gitignore  
target/  
/ / target/ project/target/

sbt sbt Hello, World

sbt  
\$ sbt  
sbt tab  
sbt compile  
> compile  
compile run exit Ctrl+D Unix Ctrl+Z Win-  
dows



```

sbt          sbt          sbt
$ sbt clean compile "testOnly TestA TestB"
testOnly    TestA TestB    clean compile testOnly

```

```

- - sbt ~
> ~ compile
~

```

```

sbt
<td><tt>clean</tt></td>
<td>      <tt>target</tt>    </td>

<td><tt>compile</tt></td>
<td>      <tt>src/main/scala</tt>

src/main/java
<td><tt>test</tt></td>
<td>      </td>

<td><tt>console</tt></td>
<td>      classpath  Scala    <tt>:quit</tt>

Ctrl+D Unix  Ctrl+Z Windows  sbt

<td><nobr><tt>run &lt; &gt;*</tt></nobr></td>
<td>  sbt      main class </td>

<td><tt>package</tt></td>
<td> <tt>src/main/resources</tt>    <tt>src/main/scala</tt>    <tt>src/main/java</tt>    c

<td><tt>help &lt; &gt;</tt></td>
<td>      </td>

<td><tt>reload</tt></td>
<td>      <tt>build.sbt</tt> <tt>project/*.scala</tt> <tt>project/*.sbt</tt>    )

```

Tab

```

tab  sbt      tab

```

```

sbt
<td><tt>!/tt></td>
<td>      </td>

<td><tt>!!</tt></td>
<td>      </td>

<td><tt>!:</tt></td>
<td>      </td>

<td><tt>!<n</tt></td>
<td>      <tt>n</tt>    </td>

<td><tt>!n</tt></td>
<td>  <tt>!:</tt>      <tt>n</tt>    </td>

<td><tt>!-n</tt></td>
<td>      n    </td>

<td><tt>!string</tt></td>
<td>      string    </td>

<td><tt>!<?string</tt></td>
<td>      string    </td>

```

## **.sbt**

```

sbt      “ ” build.sbt      sbt

```

1. .sbt
2. bare .sbt

```

.sbt      [bare .sbt    ][Bare-Def] .scala

```

```

.scala      project/

```

```

sbt      Project
build.sbt      Project

```

```

lazy val root = (project in file("."))
    immutable map
    name key
    sbt map
        Setting[T] T value Setting map map
        value map
        Setting[String]
lazy val root = (project in file("."))
    .settings(
        name := "hello"
    )
    Setting[String] name "hello" map map sbt map
    map sbt key value key key sbt
Settings map
    Project Setting[T] Setting[T] sbt map T
value

build.sbt

build.sbt Project settings scala

lazy val commonSettings = Seq(
    organization := "com.example",
    version := "0.1.0",
    scalaVersion := "2.12.4"
)

lazy val root = (project in file("."))
    .settings(
        commonSettings,
        name := "hello"
    )
    Setting Scala settings Scala
    val lazy val def build.sbt object class project/
Scala
    name version scalaVersion keys key SettingKey[T] TaskKey[T]
    InputKey[T] T value key

```

```

Keys    Setting[T] :=      Java

lazy val root = (project in file("."))
  .settings(
    name.:=("hello")
  )

Scala  name := "hello"      Scala

key name :=      Setting    Setting[String] String    name
SettingKey[String]    Setting[String]    sbt map      name
    "hello"

    value

lazy val root = (project in file("."))
  .settings(
    name := 42 //
  )

```

## Keys

### Types

key

- SettingKey[T] key value
- TaskKey[T] key *task* value
- InputKey[T] key task Input Tasks

### Keys

```

keys      Keys    build.sbt      import sbt.Keys._    name
sbt.Keys.name

```

### Keys

```

    settingKey taskKey inputKey    keys    key value    key
val      task hello    key

lazy val hello = taskKey[Unit](" task ")

.sbt    settings    vals defs    settings    vals
defs    settings

    lazy val    val

```

## Task vs Setting keys

```
TaskKey[T]    task  Tasks    compile  package    Unit Unit  Scala
void         task      package TaskKey[File] task      jar
           task  sbt    compile sbt      task
sbt  map  setting      name    task    compile -
    key   task    setting  "taskiness" (    key   property   value
```

## tasks settings

```
:=    setting    task    setting  value    task    task

    hello task
lazy val hello = taskKey[Unit]("An example task")

lazy val root = (project in file("."))
  .settings(
    hello := { println("Hello!") }
  )

    settings
lazy val root = (project in file("."))
  .settings(
    name := "hello"
  )
```

## Tasks Settings

```
task key    Setting  setting key    Setting  taskKey := 42
Setting[Task[T]]  settingKey := 42  Setting[T]    task key
T  value

T  Task[T]    setting    task    setting
```

## sbt Keys

```
sbt    task  name    task    compile    compile task compile
task  key

    setting key  name    task key  name setting key  value    task
key  name  task    value  show <task name>    <task name>
task    key name    camelCase    name  Scala
```

```

key      sbt      inspect <keyname>  inspect      setting
value    setting

```

## build.sbt

```
import build.sbt
```

```

import sbt._
import Keys._

scala Build Plugin scala

```

## bare .sbt

```

bare .sbt      Setting[_]      Project

name := "hello"
version := "1.0"
scalaVersion := "2.12.4"

```

```

jar lib/ build.sbt

val derby = "org.apache.derby" % "derby" % "10.4.1.3"

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0",
  scalaVersion := "2.12.4"
)

lazy val root = (project in file("."))
  .settings(
    commonSettings,
    name := "hello",
    libraryDependencies += derby
  )

```

## 10.4.1.3 Apache Derby

```

key libraryDependencies += := % += key
% Ivy ID

```

## Scope

scope .sbt

## Key

name key sbt map  
key “scope”

- key
- key compile main test
- Key packageOptions jar class packageBin  
packageSrc

key *name* scope

scoped key

sbt map settings map key *scope* key set-  
ting build.sbt scope key  
scope build.sbt scope

## Scope

*Scope* scope key

scope

- Projects
- Configurations
- Tasks

## Project Scope

settings keys

Project setting setting setting

## Configuration Scope

*configuration* classpath Configuration Ivy  
MavenScopes

sbt configurations

- Compile src/main/scala

- Test src/test/scala
- Runtime task run classpath

key configuration configuration task  
 key compile package run key key sourceDirectories scalacOptions  
 fullClasspath configuration

## Task Scope

Settings task task packageSrc setting packageOptions  
 task key packageSrc key packageOptions scope  
 task packageSrc packageBin packageDoc key artifactName  
 packageOptions key task

## Scope

scope task task Global  
 Global setting task Global setting task

scope key key  
 scope sbt scope key scope sbt scope Global  
 scope scope  
 scope scope  
 inspect key “ ”

## sbt scope key

sbt scope keys  
 {<build-uri><project-id>/config:intask::key  
 • {<build-uri><project-id> project project scope  
 <project-id>  
 • config configuration  
 • intask task  
 • key scope key  
 “\*” Global scope  
 scoped key



- project project
  - configuration task key configuration
- Configuration

### scoped key

- fullClasspath key scope project key configuration task scope
- test:fullClasspath configuration fullClasspath test configuration scope scope
- \*:fullClasspath configuration Global configuration
- doc::fullClasspath key fullClasspath doc task project configuration
- {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath project {file:/home/hp/checkout/hello/}default-aea33a {file:/home/hp/checkout/hello/} project project id default-aea33a configuration test task
- {file:/home/hp/checkout/hello/}/test:fullClasspath {file:/home/hp/checkout/hello/} project
- {./}/test:fullClasspath {./} project {./} Scala ThisBuild
- {file:/home/hp/checkout/hello/}/compile:doc::fullClasspath scope

### scope

```
sbt          inspect    key    scope    inspect test:fullClasspath

$ sbt
> inspect test:fullClasspath
[info] Task: scala.collection.Seq[sbt.Attributed[java.io.File]]
[info] Description:
[info]   The exported classpath, consisting of build products and unmanaged and managed, internal dependencies.
[info] Provided by:
[info]   {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath
[info] Dependencies:
[info]   test:exportedProducts
[info]   test:dependencyClasspath
[info] Reverse dependencies:
[info]   test:runMain
[info]   test:run
[info]   test:testLoader
[info]   test:console
[info] Delegates:
```

```

[info] test:fullClasspath
[info] runtime:fullClasspath
[info] compile:fullClasspath
[info] *:fullClasspath
[info] {.}/test:fullClasspath
[info] {.}/runtime:fullClasspath
[info] {.}/compile:fullClasspath
[info] {.}/*:fullClasspath
[info] */test:fullClasspath
[info] */runtime:fullClasspath
[info] */compile:fullClasspath
[info] */*:fullClasspath
[info] Related:
[info] compile:fullClasspath
[info] compile:fullClasspath(for doc)
[info] test:fullClasspath(for doc)
[info] runtime:fullClasspath

task .sbt      setting task      scala.collection.Seq[sbt.Attributed[java.io.File]]
“Provided by”  scoped key      {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath
test configuration {file:/home/hp/checkout/hello/}default-aea33a
project
“Dependencies”

sbt

• configuration runtime:fullClasspath compile:fullClasspath
  scoped key project “ project” task Global
• project “ project” task Global configuration
  Global *:fullClasspath
• project project {.} ThisBuild
• project Global */test:fullClasspath project current
  Global * “ project” project */test:fullClasspath
  test:fullClasspath
• project configuration Global */*:fullClasspath task
  Global */*:fullClasspath Global

inspect fullClasspath inspect test:fullClasspath con-
figuration sbt compile inspect compile:fullClasspath
inspect fullClasspath

inspect *:fullClasspath fullClasspath Global configuration

```

Configuration

```

scope

build.sbt  bare key      project configuration task  Global

lazy val root = (project in file("."))
.settings(
  name := "hello"
)

sbt  inspect name  {file:/home/hp/checkout/hello/}default-aea33a/*:name
project {file:/home/hp/checkout/hello/}default-aea33a  configu-
ration *      task

Keys      in  scope in      scope      name  Compile configuration

name in Compile := "hello"

name packageBin task

name in packageBin := "hello"

name scope  Compile configuration packageBin task

name in (Compile, packageBin) := "hello"

Global

name in Global := "hello"

name in Global scope Global scope Global task configuration
Global project Global */*:name {file:/home/hp/checkout/hello/}default-aea33a/*
Scala in := Scala Java

name.in(Compile).:=("hello")

```

```

scope

key      scope compile task  Compile Test configuration scope
scope

key compile      compile in Compile  compile in Test  compile
project scope    task configuration scope compile task

“      ”      scope      scope key      scope sbt
“ compile:compile ”

name key      key name scope scope packageOptions
in (Compile, packageBin) key name packageOptions key
name in key scope project global config global task

```

```

:= .sbt scope

.sbt Setting Setting sbt map Setting
sbt map map map sbt
setting map .sbt :=
:= Setting map name := "hello" map map
key name "hello"

+= +=

:= key SettingKey[T] T key se-
quence
• +=
• +=

key sourceDirectories in Compile Seq[File] key
src/main/scala source
sourceDirectories in Compile += new File("source")
sbt file()
sourceDirectories in Compile += file("source")
file() File
+=
sourceDirectories in Compile += Seq(file("sources1"), file("sources2"))
Seq(a, b, c, ...) Scala
source :=
sourceDirectories in Compile := Seq(file("sources1"), file("sources2"))

key

task setting value value := += +=
project organization

// name our organization after our project (both are SettingKey[String])
organization := name.value

```

```

// name is a Key[String], baseDirectory is a Key[File]
// name the project after the directory it's inside
name := baseDirectory.value.getName

    java.io.File      getName      baseDirectory

name := "project " + name.value + " from " + organization.value + " version " + version.value

    name      organization      version      name

name := baseDirectory.value.getName    name    baseDirectory
build.sbt    sbt    inspect name

[info] Dependencies:
[info] *:baseDirectory

    sbt    setting      setting      setting      task      task

        inspect compile      key compileInputs      inspect compileInputs
        key      compile    sbt    update      compile      sbt
update
sbt      key      key

:= +=    +=    key      sbt      “      ”      key
scope
sbt      sbt

key    task

    task    setting      task      task      Def.task := +=    +=

        classpath    source generator

sourceGenerators in Compile += Def.task {
  myGenerator(baseDirectory.value, (managedClasspath in Compile).value)
}

```

```

    task

    .sbt      :=      task key    Setting[Task[T]]    Setting[T] Set-
ting    Task    Task    Setting

    key    Keys

    val scalacOptions = taskKey[Seq[String]]("Options for the Scala compiler.")
    val checksums = settingKey[Seq[String]]("The list of checksums to generate and to verify for

    scalacOptions    checksums                key    task

    build.sbt    scalacOptions    checksums

    // scalacOptions task    checksums setting
    scalacOptions := checksums.value

    setting key    task key    setting key    task
    task

    // checksums setting    scalacOptions task
    checksums := scalacOptions.value

    +=    +=

    setting    task    key    :=

    cleanFiles += file("coverage-report-" + name.value + ".txt")

    .sbt    Scopes

    •    lib    jar
    •    repository

    jar    lib    classpath

    jar    lib    ScalaCheck Specs2 ScalaTest

    lib    classpaths    compile    test    run    console    classpath
    dependencyClasspath in Compile    dependencyClasspath in
    Runtime

    build.sbt    unmanagedBase key    lib

```

```

    custom_lib lib
unmanagedBase := baseDirectory.value / "custom_lib"
baseDirectory      baseDirectory      unmanagedBase
value
    unmanagedBase jar task unmanagedJars
task    unmanagedJars task    Compile configuration lib
unmanagedJars in Compile := Seq.empty[sbt.Attributed[java.io.File]]

sbt Apache Ivy      Ivy Maven

libraryDependencies Key
    libraryDependencies      Maven POM Ivy      sbt

    groupId artifactId revision
libraryDependencies += groupId % artifactID % revision
    Configuration val configuration
libraryDependencies += groupId % artifactID % revision % configuration
libraryDependencies Keys
val libraryDependencies = settingKey[Seq[ModuleID]]("Declares managed dependencies.")
    %      ModuleID      ModuleID      libraryDependencies
    sbt Ivy      sbt      Apache Derby      Maven2
libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3"
    build.sbt      update sbt Derby ~/.ivy2/cache/org.apache.derby/
compile update      update
    +=
libraryDependencies += Seq(
    groupId % artifactID % revision,
    groupId % otherID % otherRevision
)

libraryDependencies :=

```

```

%%      Scala

    groupID %% artifactID % revision      groupID % artifactID %
revision  groupID  %% sbt      Scala      %%
libraryDependencies += "org.scala-tools" % "scala-stm_2.11.1" % "0.3"
    scalaVersion 2.11.1      "org.scala-tools"  %%
libraryDependencies += "org.scala-tools" %% "scala-stm" % "0.3"

    Scala      jar

    Scala      %%      2.10.1      scalaVersion :=
"2.10.4"      %% 2.10.1      %%      Scala

```

## Ivy

```

groupID % artifactID % revision  revision      Ivy
"latest.integration" "2.9.+"  "[1.0,)"      "1.6.1"  Ivy

```

```

sbt      Maven2      resolver  Ivy

```

```

resolvers += name at location

```

```

at

```

```

resolvers += "Sonatype OSS Snapshots" at "https://oss.sonatype.org/content/repositories/snapshots"

```

```

resolvers key Keys

```

```

val resolvers = settingKey[Seq[Resolver]]("resolvers")

```

```

at      Resolver

```

```

sbt      Maven

```

```

resolvers += "Local Maven Repository" at "file://" + Path.userHome.absolutePath + "/.m2/repository"

```

```

resolvers += Resolver.mavenLocal

```



```

resolvers
sbt resolvers      externalResolvers
      externalResolvers  resolvers

```

### Per-configuration dependencies

```

      src/test/scala    Test configuration
      Test configuration classpath    Compile configuration    % "test"
libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3" % "test"
      Test configuration
libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3" % Test
      sbt      show compile:dependencyClasspath    derby jar      show
test:dependencyClasspath    derby jar
      ScalaCheck Specs2 ScalaTest    % "test"

```

```

.sbt

```

```

      jar
      Project lazy val
lazy val util = project
lazy val core = project
val      ID      ID      in
lazy val util = project.in(file("util"))
lazy val core = project in file("core")

```

To factor out common settings across multiple projects, create a sequence named `commonSettings` and call `settings` method on each project.

```

commonSettings      settings

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0",
  scalaVersion := "2.12.4"
)

lazy val core = (project in file("core"))
  .settings(
    commonSettings,
    // other settings
  )

lazy val util = (project in file("util"))
  .settings(
    commonSettings,
    // other settings
  )

  version

```

aggregate classpath

## Aggregation

Aggregation    aggregate    task    aggregated

```

lazy val root = (project in file(".")).aggregate(util, core)

lazy val util = project

lazy val core = project
  root    util  core      sbt
  root    task  update task

lazy val root = (project in file("."))
  .aggregate(util, core)
  .settings(
    aggregate in update := false
  )

```

```

)

[...]

aggregate in update update task scope key scopes
task task

```

## Classpath

```

dependsOn core classpath util core

lazy val core = project.dependsOn(util)

core util core util

dependsOn(bar, baz) dependsOn

configuration classpath

foo dependsOn(bar) foo compile configuration bar compile config-
uration dependsOn(bar % "compile->compile")

"compile->compile" -> "depends on" "test->compile" foo test
configuration bar compile configuration

->config ->compile dependsOn(bar % "test") foo test configu-
ration bar Compile configuration

"test->test" test test bar/src/test/scala
foo/src/test/scala

configuration dependsOn(bar % "test->test;compile->compile")

```

## root

```

sbt

hello-foo base = file("foo") foo foo
foo/Foo.scala foo/src/main/scala sbt foo

foo .sbt foo/build.sbt hello-foo scope

hello hello/build.sbt hello/bar/build.sbt hello/foo/build.sbt
version := "0.6" sbt show version

> show version
[info] hello-foo/*:version
[info] 0.7
[info] hello-bar/*:version
[info] 0.9

```

```

[info] hello/*:version
[info] 0.5

hello-foo/*:version    hello/foo/build.sbt  hello-bar/*:version
hello/bar/build.sbt   hello/*:version    hello/build.sbt    scoped
keys    version key    scope    build.sbt        build.sbt

        .sbt    .scala                .scala
        .scala
        project/*.scala  foo/project/Build.scala

```

```

sbt      projects      project <projectname>      task
compile      root
ID          task  subProjectID/compile

```

```

.sbt      .sbt      .sbt      project/      Scala

```

```

build.sbt

```

```

task      codeCoverage task

```

```

hello      sbt-site    hello/project/site.sbt    Ivy  ID
addSbtPlugin

addSbtPlugin("com.typesafe.sbt" % "sbt-site" % "0.7.0")

sbt-assembly    hello/project/assembly.sbt
addSbtPlugin("com.eed3si9n" % "sbt-assembly" % "0.11.2")

```

```
resolvers += Resolver.sonatypeRepo("public")
```

0.13.5 sbt

build.sbt

```
lazy val util = (project in file("util"))
  .enablePlugins(FooPlugin, BarPlugin)
  .settings(
    name := "hello-util"
  )
```

enablePlugins

disablePlugins util IvyPlugin build.sbt

```
lazy val util = (project in file("util"))
  .enablePlugins(FooPlugin, BarPlugin)
  .disablePlugins(plugins.IvyPlugin)
  .settings(
    name := "hello-util"
  )
```

sbt plugins

> plugins

In file:/home/jsuereth/projects/sbt/test-ivy-issues/  
sbt.plugins.IvyPlugin: enabled in scala-sbt-org  
sbt.plugins.JvmPlugin: enabled in scala-sbt-org  
sbt.plugins.CorePlugin: enabled in scala-sbt-org  
sbt.plugins.JUnitXmlReportPlugin: enabled in scala-sbt-org

plugins sbt sbt 3

1. CorePlugin: task
2. IvyPlugin:
3. JvmPlugin: Java/Scala

JUnitXmlReportPlugin junit-xml

sbt-site site.sbt

site.settings

```
// `util`      site
lazy val util = (project in file("util"))

// `core`      site
lazy val core = (project in file("core"))
  .settings(site.settings)
```

```
      ~/.sbt/1.0/plugins/      ~/.sbt/1.0/plugins/      classpath
sbt      ~/.sbt/1.0/plugins/      .sbt      .scala      project/

      ~/.sbt/1.0/plugins//build.sbt      addSbtPlugin()
```

- IDE sbt IDE
- web xsbt-web-plugin

```
sbt      .sbt
```

```
SettingKey TaskKey .sbt      InputKey
Keys
val scalaVersion = settingKey[String]("scala ")
val clean = taskKey[Unit]("      source      ")
```

```

        "scalaVersion"      "      scala      "
.sbt      T      SettingKey[T]      T      TaskKey [T]      .sbt
        "      "      batch

.sbt .scala      autoImport val      .sbt

:=

val sampleStringTask = taskKey[String]("A sample string task.")
val sampleIntTask = taskKey[Int]("A sample int task.")

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0-SNAPSHOT"
)

lazy val library = (project in file("library"))
  .settings(
    commonSettings,
    sampleStringTask := System.getProperty("user.home"),
    sampleIntTask := {
      val sum = 1 + 2
      println("sum: " + sum)
      sum
    }
  )

      value
      sbt      Scala      HTML      HTML
      HTML

sbt      API  IO

      value

sampeIntTask

sampleIntTask := {
  val sum = 1 + 2      // first
  println("sum: " + sum) // second
  sum                  // third
}

```

```

JVM    sum 3

      startServer stopServer  sampeIntTask

val startServer = taskKey[Unit]("start server")
val stopServer = taskKey[Unit]("stop server")
val sampleIntTask = taskKey[Int]("A sample int task.")
val sampleStringTask = taskKey[String]("A sample string task.")

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0-SNAPSHOT"
)

lazy val library = (project in file("library"))
  .settings(
    commonSettings,
    startServer := {
      println("starting...")
      Thread.sleep(500)
    },
    stopServer := {
      println("stopping...")
      Thread.sleep(500)
    },
    sampleIntTask := {
      startServer.value
      val sum = 1 + 2
      println("sum: " + sum)
      stopServer.value // THIS WON'T WORK
      sum
    },
    sampleStringTask := {
      startServer.value
      val s = sampleIntTask.value.toString
      println("s: " + s)
      s
    }
  )

sbt      sampleIntTask

> sampleIntTask
stopping...
starting...
sum: 3
[success] Total time: 1 s, completed Dec 22, 2014 5:00:00 PM

```






Figure 2: task-dependency

```
Scala      value      sampleIntTask startServer stopServer  sampleIntTask sbt
•  sampleIntTask
•
•
```

```
sbt      sampleStringTask

> sampleStringTask
stopping...
starting...
sum: 3
s: 3
[success] Total time: 1 s, completed Dec 22, 2014 5:30:00 PM

sampleStringTask startServer sampleIntTask  sampleIntTask  startServer
Scala            value      sampeStringTask
```




Figure 3: task-dependency

```
test      compile in Test test in Test
```

```

stopServer
sampleStringTask
stopServer sampleStringTask stopServer

lazy val library = (project in file("library"))
.settings(
  commonSettings,
  startServer := {
    println("starting...")
    Thread.sleep(500)
  },
  sampleIntTask := {
    startServer.value
    val sum = 1 + 2
    println("sum: " + sum)
    sum
  },
  sampleStringTask := {
    startServer.value
    val s = sampleIntTask.value.toString
    println("s: " + s)
    s
  },
  sampleStringTask := {
    val old = sampleStringTask.value
    println("stopping...")
    Thread.sleep(500)
    old
  }
)

sampleStringTask

> sampleStringTask
starting...
sum: 3
s: 3
stopping...
[success] Total time: 1 s, completed Dec 22, 2014 6:00:00 PM

```




Figure 4: task-dependency

## Scala

Scala    project/ServerUtil.scala

```
sampleIntTask := {  
  ServerUtil.startServer  
  try {  
    val sum = 1 + 2  
    println("sum: " + sum)  
  } finally {  
    ServerUtil.stopServer  
  }  
  sum  
}
```

build.sbt

## sbt

```
build.sbt        sbt        sbt        Scala        sbt  
project  
  sbt  
  ,        project/project/  
  
hello/                        #  
  
  Hello.scala                #        src/main/scala  
  
  build.sbt                # build.sbt    project/
```

```

project/          #

    Build.scala    #

    build.sbt      #      --project/project

project/          #

    Build.scala # project/project/
project/project/

    .scala  .sbt      build.sbt  Build.scala

project .scala      project/Dependencies.scala
import sbt._

object Dependencies {
  // Versions
  lazy val akkaVersion = "2.3.8"

  // Libraries
  val akkaActor = "com.typesafe.akka" %% "akka-actor" % akkaVersion
  val akkaCluster = "com.typesafe.akka" %% "akka-cluster" % akkaVersion
  val specs2core = "org.specs2" %% "specs2-core" % "2.4.17"

  // Projects
  val backendDeps =
    Seq(akkaActor, specs2core % Test)
}

Dependencies build.sbt      val      Dependencies._
import Dependencies._

lazy val commonSettings = Seq(
  version := "0.1.0",
  scalaVersion := "2.12.4"
)

lazy val backend = (project in file("backend"))
  .settings(
    commonSettings,

```

```
libraryDependencies += backendDeps
)
```

```
.scala
```

```
.scala      Scala
            build.sbt      project/*.scala      .scala      scala
```

```
project/*.scala
```

```
sbt          sbt  sbt
```

**sbt:**

- Scala Scala Programming in Scala Scala
- .sbt
- Setting sbt Setting task
- Setting key := += +=
- Setting sbt
- key
- *tasks* key value task Non-task
- Scopes
- key value scope
- scope configuration project task
- scope task configuration
- configuration Compile Test
- project “ ” scope
- scopes scope
- build.sbt .scala task
- sbt
- 
- addSbtPlugin project/plugins.sbt build.sbt

sbt

sbt