

sbt Reference Manual

Contents

Preface	4
sbt	4
sbt	4
.	4
Mac sbt	4
.	4
.	4
Windows sbt	5
.	5
Windows	5
Linux sbt	5
.	5
Ubuntu Debian	5
Linux RPM	7
Gentoo	7
Hello, World	7
.	7
.	8
sbt	8
.	8
.	8
.	9

sbt	9
.	9
.	9
.	10
.	10
.	10
.	10
.	11
Tab	11
.	11
.sbt	12
.	12
?	12
build.sbt	13
(Keys)	14
tasks settings	15
sbt Keys	15
build.sbt	16
bare .sbt	16
.	16
Scope	17
Key	17
Scope	17
Scope	18
.	18
sbt scope key	18
scoped key	19
scope	19
scope	21
scope	22
.	22

:	22
: += +=	22
key	23
: += +=	24
.	25
.	25
.	25
.	28
.	28
.	29
root	30
.	31
.	31
.	31
.	31
.	31
.	32
.	33
.	33
.	34
.	34
.	34
.	35
.	39
.	39
sbt	39
.	40
.scala	40
.	41
.	41
sbt:	41
.	41

Preface

sbt

sbt , sbt , ,

sbt

!

, .sbt ,scopes,

,

sbt !

sbt

sbt , :

- sbt
- [hello world](#)

—

—

- [sbt](#) sbt
- [.sbt](#)

, Jar Shell , , [Mac](#), [Windows](#), [Linux](#)

sbt , (terminal encoding),HTTP ,JVM

Mac sbt

[ZIP](#) [TGZ](#)

: ,

Homebrew

```
$ brew install sbt@1
```

Macports

```
$ port install sbt
```

Windows sbt

ZIP TGZ

Windows

msi

Linux sbt

ZIP TGZ

Ubuntu Debian

DEB sbt

```
Ubuntu Debian DEB , DEB , ( apt-get,aptitude)
( Synaptic) sbt( , sudo)
```

```
echo "deb https://dl.bintray.com/sbt/debian/" | sudo tee -a /etc/apt/sources.list.d/sbt.list
sudo apt-key adv --keyserver hkp://keyserver.ubuntu.com:80 --recv 2EE0EA64E40A89B84B2DF73499E8
sudo apt-get update
sudo apt-get install sbt
```

```
sbt Bintray, Bintray APT
sbt, aptitude Synaptic , System Settings ->
Software & Updates -> Other Software:
```



Figure 1: Ubuntu Software & Updates Screenshot

Linux RPM

RPM sbt

Linux RPM RPM sbt(, sudo)

```
curl https://bintray.com/sbt/rpm/rpm > bintray-sbt-rpm.repo
sudo mv bintray-sbt-rpm.repo /etc/yum.repos.d/
sudo yum install sbt
```

sbt Bintray, Bintray RPM

: [sbt-launcher-package](#)

Gentoo

sbt ebuild sbt [ebuilds](#) ebuilds sbt:

```
emerge dev-java/sbt
```

Hello, World

[sbt](#)

sbt hello , hw.scala:

```
object Hi {
  def main(args: Array[String]) = println("Hi!")
}
```

hello sbt, run sbt Linux OS X :

```
$ mkdir hello
$ cd hello
$ echo 'object Hi { def main(args: Array[String]) = println("Hi!") }' > hw.scala
$ sbt
...
> run
...
Hi!
```

```
,sbt      sbt      :

•
• src/main/scala src/main/java
• src/test/scala src/test/java
• src/main/resources src/test/resources
• lib jar

,sbt      Scala      sbt run      sbt console Scala REPL sbt
console      classpath,      Scala
```

```
build.sbt      ,      hello , hello/build.sbt      :

lazy val root = (project in file("."))
  .settings(
    name := "hello",
    version := "1.0",
    scalaVersion := "2.12.3"
  )

.sbt      build.sbt
jar , build.sbt      name version
```

```
sbt

hello/project/build.properties      sbt      ,      1.0.2:

sbt.version=1.0.2

sbt      release      99%      project/build.properties      sbt
```

```
sbt      Hello, World
```

```
sbt      ,“ ”      ,      Hello, World      hello ,      hello/build.sbt
hello/hw.scala, hello
```



```

    hello/hw.scala      ,      ,      sbt Maven      (      ):

src/
  main/
    resources/
      <files to include in main jar here>
    scala/
      <main Scala sources>
    java/
      <main Java sources>
  test/
    resources
      <files to include in test jar here>
    scala/
      <test Scala sources>
    java/
      <test Java sources>

src/      ,

sbt

    build.sbt  sbt  project  project  .scala ,  .sbt

build.sbt
project/
  Build.scala

  project/  .sbt ,  .sbt ,

(  classes,  jars,  ,caches  )  target

.gitignore (      ) :

target/

:      / (      )      / (      target/  project/target/ )

```

```
sbt      sbt      Hello, World
```

```
sbt      :
```

```
$ sbt
```

```
sbt      ( tab      )
```

```
, sbt      compile:
```

```
> compile
```

```
compile,      ,      run      exit      Ctrl+D (Unix)  Ctrl+Z (Win-  
dows)
```

```
sbt,      sbt ,      sbt :
```

```
$ sbt clean compile "testOnly TestA TestB"
```

```
,testOnly      TestA TestB      (clean, compile, testOnly)
```

```
- - , sbt      ~ ,      ,      :
```

```
> ~ compile
```

```
~
```

```

    sbt
clean
    ( target )
compile
    ( src/main/scala src/main/java )
test

console

    classpath Scala :quit, Ctrl+D (Unix), Ctrl+Z (Windows)
    sbt
run < >*
    sbt main class
package
    src/main/resources src/main/scala src/main/java class jar
help < >

,

reload
    (build.sbt, project/.scala, project/.sbt )

```

Tab

```

    tab sbt , tab ,

, sbt :

!

!!

!:
```

```
!n
    n
!n
    !:      n
!-n
    n
!string
    string
!?string
    string
```

.sbt

```
sbt , “ ” build.sbt sbt
```

1. .sbt
2. bare .sbt

```
(.sbt , , [bare .sbt ][Bare-Def] .scala
, .scala , project/ ,
```

?

```
sbt , Project
build.sbt Project , :
```

```
lazy val root = (project in file("."))
```

```
(immutable map)( )
, name key, ,
sbt map
```

```

    , Setting[T], T, (value) Setting (map) ,
      value ( , map — map )
    Setting[String], :

lazy val root = (project in file("."))
  .settings(
    name := "hello"
  )

Setting[String] ( ) name "hello" map map sbt map
  map,sbt , key , value key, key , sbt
Settings , map
: Project, Setting[T], Setting[T] sbt map ,T
value

build.sbt

build.sbt Project, settings scala
:

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0",
  scalaVersion := "2.12.3"
)

lazy val root = (project in file("."))
  .settings(
    commonSettings,
    name := "hello"
  )

Setting Scala settings , , Scala
  val,lazy val,def build.sbt object class project/
Scala
, name, version scalaVersion (keys) (key) SettingKey[T], TaskKey[T]
InputKey[T] , T value key
(Keys) Setting[T] := Java :
```

```

lazy val root = (project in file("."))
  .settings(
    name := ("hello")
  )

,Scala name := "hello" ( Scala , )

(key)name := Setting, Setting[String] String name
SettingKey[String] , Setting[String] sbt map name
, "hello"

value, :

lazy val root = (project in file("."))
  .settings(
    name := 42 //
  )

(Keys)

(Types) key:

• SettingKey[T]: key value( , )
• TaskKey[T]: key task value, ,
• InputKey[T]: key task Input Tasks

Keys keys Keys build.sbt import sbt.Keys._, name
sbt.Keys.name

Keys :settingKey,taskKey inputKey keys key value
key val , task hello key,

lazy val hello = taskKey[Unit](" task ")

.sbt (settings), vals defs (settings)
vals defs (settings)

: , lazy val val

```

```

Task vs Setting keys TaskKey[T] task Tasks compile
package Unit(Unit Scala void), task , package
TaskKey[File] task, jar
task, sbt compile,sbt task
sbt map (setting) , name; task , compile-
key task (setting) , "taskiness" ( ) key (prop-
erty), (value)

```

tasks settings

```

:= setting task setting, (value) task, task

, hello task:

lazy val hello = taskKey[Unit]("An example task")

lazy val root = (project in file("."))
.settings(
  hello := { println("Hello!") }
)

settings ,

lazy val root = (project in file("."))
.settings(
  name := "hello"
)

```

```

Tasks Settings , task key Setting setting key
Setting taskKey := 42 Setting[Task[T]] settingKey := 42
Setting[T] ;task key T (value)
T Task[T] : setting task, setting ,

```

sbt Keys

```

sbt , task name task compile compile task compile
task key

setting key name task key name,setting key (value) task
key name task (value); show <task name> <task name>
task key name camelCase, name Scala

key , sbt inspect <keyname> inspect , setting
value setting

```

build.sbt

```
import build.sbt ;
:

import sbt._
import Keys._

( , .scala , Build Plugin .scala )
```

bare .sbt

```
bare .sbt Setting[_] , Project

name := "hello"
version := "1.0"
scalaVersion := "2.12.3"

jar lib/( ), build.sbt , :

val derby = "org.apache.derby" % "derby" % "10.4.1.3"

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0",
  scalaVersion := "2.12.3"
)

lazy val root = (project in file("."))
  .settings(
    commonSettings,
    name := "hello",
    libraryDependencies += derby
  )

10.4.1.3 Apache Derby

key libraryDependencies := , % += key ,
% Ivy ID ,
, ,
```


Scope

scope [.sbt](#)

Key

```

    name key sbt map ,
, key , "scope"
:

• , key
• ,key compile main test
• Key packageOptions( jar ) , class packageBin,
  packageSrc

key name , scope
, scoped key

,sbt map settings , map key scope key set-
ting( build.sbt ) scope key

scope , , build.sbt scope

```

Scope

Scope , scope(, key)

scope :

- Projects
- Configurations
- Tasks

Project Scope , settings ,keys

Project , setting setting , setting

Configuration Scope *configuration* , classpath, Configuration

Ivy [MavenScopes](#)

sbt configurations:

- Compile (src/main/scala)

- Test (src/test/scala)
- Runtime task run classpath

```
, key configuration, configuration task
key:compile,package run; key key( sourceDirectories,scalacOptions
fullClasspath) configuration
```

```
Task Scope Settings task ,task packageSrc setting
packageOptions
, task key( packageSrc) key( packageOptions) scope
task(packageSrc,packageBin,packageDoc) key, artifactName
packageOptions key task
```

Scope

```
scope ( task task ), Global
Global : setting task Global, setting task
```

```
scope key , key
scope,sbt scope , key scope ,sbt scope( Global
scope scope)
scope , scope
inspect key “ ”
```

sbt scope key

```
,sbt ( )scope keys:
```

```
{<build-uri><project-id>/config:intask::key
```

- {<build-uri>}/<project-id> project project scope,
- <project-id>
- config configuration
- intask task
- key scope key

“*” , Global scope

scoped key, :

- project, project
- configuration task, key configuration

, [Configuration](#)

scoped key

- fullClasspath key, scope: project,key configuration task scope
- test:fullClasspath configuration, fullClasspath test configuration scope , scope
- *:fullClasspath configuration Global, configuration
- doc::fullClasspath key fullClasspath doc task ,project configuration
- {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath project, {file:/home/hp/checkout/hello/}default-aea33a ,{file:/home/hp/checkout/hello/} project, project id default-aea33a configuration test, task
- {file:/home/hp/checkout/hello/}/test:fullClasspath {file:/home/hp/checkout/hello/} project
- {./}/test:fullClasspath {./} project {./} Scala ThisBuild
- {file:/home/hp/checkout/hello/}/compile:doc::fullClasspath scope

scope

sbt , inspect key scope inspect test:fullClasspath,

\$ sbt

> inspect test:fullClasspath

[info] Task: scala.collection.Seq[sbt.Attributed[java.io.File]]

[info] Description:

[info] The exported classpath, consisting of build products and unmanaged and managed, internal

[info] Provided by:

[info] {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath

[info] Dependencies:

[info] test:exportedProducts

[info] test:dependencyClasspath

```

[info] Reverse dependencies:
[info]   test:runMain
[info]   test:run
[info]   test:testLoader
[info]   test:console
[info] Delegates:
[info]   test:fullClasspath
[info]   runtime:fullClasspath
[info]   compile:fullClasspath
[info]   *:fullClasspath
[info]   {.}/test:fullClasspath
[info]   {.}/runtime:fullClasspath
[info]   {.}/compile:fullClasspath
[info]   {.}/*:fullClasspath
[info]   */test:fullClasspath
[info]   */runtime:fullClasspath
[info]   */compile:fullClasspath
[info]   */*:fullClasspath
[info] Related:
[info]   compile:fullClasspath
[info]   compile:fullClasspath(for doc)
[info]   test:fullClasspath(for doc)
[info]   runtime:fullClasspath

```

```

, task( .sbt setting ) task scala.collection.Seq[sbt.Attributed[java.io.File]]
“Provided by” scoped key, {file:/home/hp/checkout/hello/}default-aea33a/test:fullClasspath
test configuration {file:/home/hp/checkout/hello/}default-aea33a
project )

```

```

“Dependencies” ;

```

```

; ,sbt :

```

- configuration(runtime:fullClasspath compile:fullClasspath)
 - scoped key ,project “ project” task Global
- project “ project” task Global ,configuration
 - Global(*:fullClasspath)
- project ,project {.} ThisBuild
- project Global(*/*:fullClasspath)(, project cur-
 - rent, Global ; :* “ project” project ; /*:fullClasspath
 - test:fullClasspath)
- project configuration Global(*/*:fullClasspath)(task
 - Global, /*:fullClasspath Global)

```

inspect fullClasspath( inspect test:fullClasspath ) con-
figuration ,sbt compile inspect compile:fullClasspath

```

```

inspect fullClasspath
    inspect *:fullClasspath      ,fullClasspath      Global configuration

    Configuration

    scope

    build.sbt      bare key,      project ,configuration task      Global:

lazy val root = (project in file("."))
    .settings(
        name := "hello"
    )

    sbt      inspect name      {file:/home/hp/checkout/hello/}default-aea33a/*:name
    , ,project      {file:/home/hp/checkout/hello/}default-aea33a, configu-
ration *( ),task      ( )

Keys      in      scope in      scope      ,      name      Compile configuration
,      :

name in Compile := "hello"

    name      packageBin task (      !      ):

name in packageBin := "hello"

    name      scope ,      Compile configuration      packageBin task :

name in (Compile, packageBin) := "hello"

    Global      :

name in Global := "hello"

(name in Global      scope      Global      scope      Global;task
configuration      Global,      project      Global,      ,      */*:name
{file:/home/hp/checkout/hello/}default-aea33a/*:name)

    Scala, :in :=      ,      Scala      ,      Java :

name.in(Compile).:=("hello")

,

```

scope

```

key      , scope ,compile task    Compile Test configuration scope
, scope

key compile , compile in Compile compile in Test compile
project scope task, configuration scope compile task

    " " , scope , scope key scope sbt
    ; " compile:compile?"

    ,name key , key name scope (scope ) ,packageOptions
in (Compile, packageBin) key name packageOptions key
name, ( in key, scope: project,global config,global task)

:= , .sbt scope

:

.sbt , Setting , Setting sbt ( map) Setting
sbt map map map sbt

setting map .sbt , :=

:= Setting map , name := "hello" map , map
key name "hello"

: += +=

:= , key SettingKey[T] T , , key se-
quence,

• +=
• +=

, key sourceDirectories in Compile Seq[File] key
src/main/scala source ( ), :

sourceDirectories in Compile += new File("source")

, sbt file() :

sourceDirectories in Compile += file("source")

```

```

(file()      File )
    +=      :

sourceDirectories in Compile += Seq(file("sources1"), file("sources2"))

Seq(a, b, c, ...) Scala
    source ,      := :

sourceDirectories in Compile := Seq(file("sources1"), file("sources2"))

    key

    task  setting      value      value      :=,+=  +=
    ,      project      organization

// name our organization after our project (both are SettingKey[String])
organization := name.value

    ,      :

// name is a Key[String], baseDirectory is a Key[File]
// name the project after the directory it's inside
name := baseDirectory.value.getName

    java.io.File      getName      baseDirectory

    ,

name := "project " + name.value + " from " + organization.value + " version " + version.value

    name      organization      version      , name

    name := baseDirectory.value.getName ,name      baseDirectory
build.sbt ,      sbt      ,      inspect name, ( ):

[info] Dependencies:
[info] *:baseDirectory

    sbt      setting      setting      setting      task,      task
    ,      inspect compile      key compileInputs,      inspect compileInputs
    key      compile , sbt      update      compile      sbt
    update

    ,sbt      key      ,      key      !

```

```

    :=, +=    +=    key    ,    ,sbt    ,    “    ”
    ,    key    scope
    sbt    ,    ;    ,sbt

    key    task    task    setting    task    task    Def.task
    taskValue :=, +=    +=

    ,    classpath    source generator

    sourceGenerators in Compile += Def.task {
      myGenerator(baseDirectory.value, (managedClasspath in Compile).value)
    }.taskValue

    task    .sbt    ,    :=    ,task key    Setting[Task[T]]
    Setting[T] Setting    Task    , Task    Setting

    key    (    Keys    ):

    val scalacOptions = taskKey[Seq[String]]("Options for the Scala compiler.")
    val checksums = settingKey[Seq[String]]("The list of checksums to generate and to verify for")

    (scalacOptions checksums    ,    key,    task)
    build.sbt scalacOptions checksums,    ,    :

    // scalacOptions task    checksums setting
    scalacOptions := checksums.value

    , setting key    task key    setting key    , task
    , task

    // checksums setting    scalacOptions task
    checksums := scalacOptions.value

    :=    +=

    setting    task    key,    :=    ,    ,    :

    cleanFiles += file("coverage-report-" + name.value + ".txt")

```



```

,      , .sbt ,Scopes
:

•      lib      jar
•      ,      (repository)

: jar      lib      ,      classpath      !
      jar      lib      , ScalaCheck,Specs2,ScalaTest
lib      classpaths( compile, test, run console )      classpath,
,      dependencyClasspath in Compile      dependencyClasspath in
Runtime
      ,      build.sbt      ,      unmanagedBase key,      lib
custom_lib      lib:

unmanagedBase := baseDirectory.value / "custom_lib"

baseDirectory      ,      baseDirectory      unmanagedBase,
value
      unmanagedBase      jar      task      unmanagedJars      ,
task      unmanagedJars task,      Compile configuration      ,      lib      :

unmanagedJars in Compile := Seq.empty[sbt.Attributed[java.io.File]]

sbt Apache Ivy      ,      Ivy      Maven      ,

libraryDependencies Key      ,      libraryDependencies
Maven POM      Ivy      ,      sbt
      ,      groupId, artifactId      revision      :

libraryDependencies += groupId % artifactID % revision

```

```

, Configuration val configuration:

libraryDependencies += groupId % artifactID % revision % configuration

libraryDependencies Keys :

val libraryDependencies = settingKey[Seq[ModuleID]]("Declares managed dependencies.")

% ModuleID , ModuleID libraryDependencies
, sbt( Ivy) sbt , ,Apache Derby Maven2 :

libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3"

build.sbt , update,sbt Derby ~/.ivy2/cache/org.apache.derby/ ( ,
compile update, update )
, += :

libraryDependencies += Seq(
  groupId % artifactID % revision,
  groupId % otherID % otherRevision
)

, libraryDependencies :=

%% Scala groupId %% artifactID % revision groupId %
artifactID % revision( groupId %),sbt Scala
%:

libraryDependencies += "org.scala-tools" % "scala-stm_2.11.1" % "0.3"

scalaVersion 2.11.1, ( "org.scala-tools" %):

libraryDependencies += "org.scala-tools" %% "scala-stm" % "0.3"

Scala , jar

Scala ; %% 2.10.1, scalaVersion
:= "2.10.4", %% 2.10.1 %% , Scala
, ( )

```

```

Ivy      groupId % artifactID % revision      revision      Ivy
          "latest.integration","2.9.+"      "[1.0,)",
"1.6.1"  Ivy

          ,sbt      Maven2          ,      resolver      Ivy
          :

resolvers += name at location

          at
          :

resolvers += "Sonatype OSS Snapshots" at "https://oss.sonatype.org/content/repositories/snapshots"

resolvers key Keys      :

val resolvers = settingKey[Seq[Resolver]]("      ")

at      Resolver
sbt      Maven      :

resolvers += "Local Maven Repository" at "file://" + Path.userHome.absolutePath + "/.m2/repository"

,      :

resolvers += Resolver.mavenLocal

          resolvers      ,
sbt resolvers      externalResolvers
,      ,      externalResolvers      resolvers

```

```

Per-configuration dependencies      ( src/test/scala , Test con-
figuration )

    Test configuration classpath      Compile configuration,    % "test":

libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3" % "test"

    Test configuration:

libraryDependencies += "org.apache.derby" % "derby" % "10.4.1.3" % Test

,      sbt      show compile:dependencyClasspath,      derby jar      show
test:dependencyClasspath,      derby jar

,      , ScalaCheck, Specs2 ScalaTest      % "test"

,      .sbt

,      ,

,      jar ,

Project lazy val      , :

lazy val util = project

lazy val core = project

val      ID      ID      in      ,      :

lazy val util = project.in(file("util"))

lazy val core = project in file("core")

```

To factor out common settings across multiple projects, create a sequence named `commonSettings` and call `settings` method on each project.

```

    ,    commonSettings    ,    settings

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0",
  scalaVersion := "2.12.3"
)

lazy val core = (project in file("core"))
  .settings(
    commonSettings,
    // other settings
  )

lazy val util = (project in file("util"))
  .settings(
    commonSettings,
    // other settings
  )

    version,    ,

    ,    :aggregate classpath

```

Aggregation Aggregation aggregate task aggregated ,

```

lazy val root = (project in file(".")).aggregate(util, core)

lazy val util = project

lazy val core = project

    ,root    util    core    ,    sbt,
    ,    root    ,    task    ,    update task:

lazy val root = (project in file(".")).
  .aggregate(util, core)
  .settings(

```

```

    aggregate in update := false
  )

[...]
```

aggregate in update update task scope key (scopes)

```

: task,task
```

Classpath dependsOn , core classpath util,
core:

```

lazy val core = project.dependsOn(util)

core util ; core ,util
, dependsOn(bar, baz) dependsOn
```

configuration classpath foo dependsOn(bar) foo compile
configuration bar compile configuration :dependsOn(bar %
"compile->compile")

```

"compile->compile" -> "depends on", "test->compile" foo test
configuration bar compile configuration
->config ->compile, dependsOn(bar % "test") foo test configu-
ration bar Compile configuration
"test->test" test test , bar/src/test/scala ,
foo/src/test/scala ,
configuration, , :dependsOn(bar % "test->test;compile->compile")
```

root

```

,sbt
hello-foo base = file("foo"), foo foo ,
foo/Foo.scala, foo/src/main/scala sbt foo
foo .sbt , foo/build.sbt, , hello-foo scope
hello , hello/build.sbt,hello/bar/build.sbt hello/foo/build.sbt
(version := "0.6") sbt show version ( ):
```

```

> show version
[info] hello-foo/*:version
[info] 0.7
[info] hello-bar/*:version
[info] 0.9
[info] hello/*:version
[info] 0.5

hello-foo/*:version    hello/foo/build.sbt ,hello-bar/*:version
hello/bar/build.sbt ,hello/*:version    hello/build.sbt      scoped
keys    version key    scope , build.sbt      build.sbt

        .sbt , .scala      ,      .scala
,      ,      .scala
,      project/*.scala    foo/project/Build.scala

sbt , projects , project <projectname>      task
compile,      root ,
ID      task, subProjectID/compile

.sbt .sbt .sbt , project/ Scala

,      build.sbt

,      task ,      codeCoverage task

hello ,      sbt-site , hello/project/site.sbt      Ivy ID
addSbtPlugin:

```

```

addSbtPlugin("com.typesafe.sbt" % "sbt-site" % "0.7.0")

    sbt-assembly,      hello/project/assembly.sbt :

addSbtPlugin("com.eed3si9n" % "sbt-assembly" % "0.11.2")

    ,                :

resolvers += Resolver.sonatypeRepo("public")

    ,

0.13.5    sbt,      ,

    ,      build.sbt :

lazy val util = (project in file("util"))
  .enablePlugins(FooPlugin, BarPlugin)
  .settings(
    name := "hello-util"
  )

enablePlugins

    disablePlugins      ,      util    IvyPlugin    ,    build.sbt :

lazy val util = (project in file("util"))
  .enablePlugins(FooPlugin, BarPlugin)
  .disablePlugins(plugins.IvyPlugin)
  .settings(
    name := "hello-util"
  )

    ,    sbt    plugins

:

> plugins
In file:/home/jsuereth/projects/sbt/test-ivy-issues/
  sbt.plugins.IvyPlugin: enabled in scala-sbt-org
  sbt.plugins.JvmPlugin: enabled in scala-sbt-org
  sbt.plugins.CorePlugin: enabled in scala-sbt-org
  sbt.plugins.JUnitXmlReportPlugin: enabled in scala-sbt-org

```



```

, plugins      sbt      sbt      3      :

1. CorePlugin:  task
2. IvyPlugin:
3. JvmPlugin:   Java/Scala

,JUnitXmlReportPlugin  junit-xml

, sbt-site , ,      site.sbt

site.settings

,      :

// `util`      site
lazy val util = (project in file("util"))

// `core`      site
lazy val core = (project in file("core"))
    .settings(site.settings)

,      ~/.sbt/1.0/plugins/      ~/.sbt/1.0/plugins/      classpath
sbt      , ~/.sbt/1.0/plugins/      .sbt      .scala      project/

,      ~/.sbt/1.0/plugins//build.sbt      addSbtPlugin()

,

:

• IDE ( sbt IDE)
• web , xsbt-web-plugin

, , ,

```

```

    , sbt , .sbt

SettingKey TaskKey .sbt InputKey
Keys :

val scalaVersion = settingKey[String]("scala ")
val clean = taskKey[Unit](" , source , ")

: ("scalaVersion") (" scala ")
.sbt , T SettingKey[T] T TaskKey [T] .sbt
, , " "( batch )
.sbt ,.scala autoImport val .sbt

, , ; := :

val sampleStringTask = taskKey[String]("A sample string task.")
val sampleIntTask = taskKey[Int]("A sample int task.")

lazy val commonSettings = Seq(
  organization := "com.example",
  version := "0.1.0-SNAPSHOT"
)

lazy val library = (project in file("library"))
.settings(
  commonSettings,
  sampleStringTask := System.getProperty("user.home"),
  sampleIntTask := {
    val sum = 1 + 2
    println("sum: " + sum)
    sum
  }
)

```

```

    ,      , value
    sbt ; Scala      , ,      , HTML,      , HTML
    (      HTML )
sbt      ,      API IO

    value ,      ,
sampleIntTask ,      :

sampleIntTask := {
    val sum = 1 + 2      // first
    println("sum: " + sum) // second
    sum                  // third
}

,JVM sum 3,

    startServer stopServer, sampleIntTask, :

val startServer = taskKey[Unit]("start server")
val stopServer = taskKey[Unit]("stop server")
val sampleIntTask = taskKey[Int]("A sample int task.")
val sampleStringTask = taskKey[String]("A sample string task.")

lazy val commonSettings = Seq(
    organization := "com.example",
    version := "0.1.0-SNAPSHOT"
)

lazy val library = (project in file("library"))
    .settings(
        commonSettings,
        startServer := {
            println("starting...")
            Thread.sleep(500)
        },
        stopServer := {
            println("stopping...")
            Thread.sleep(500)
        },
        sampleIntTask := {
            startServer.value

```

```

    val sum = 1 + 2
    println("sum: " + sum)
    stopServer.value // THIS WON'T WORK
    sum
  },
  sampleStringTask := {
    startServer.value
    val s = sampleIntTask.value.toString
    println("s: " + s)
    s
  }
)

sbt    sampleIntTask    :

> sampleIntTask
stopping...
starting...
sum: 3
[success] Total time: 1 s, completed Dec 22, 2014 5:00:00 PM

```



Figure 2: task-dependency

```

Scala    ,    value    ,    sampleIntTask startServer stopServer    sampleIntTask ,sbt    :

•    sampleIntTask    ( )
•    ,    ( )
•    ,    ( )

```

```

, sbt sampleStringTask

> sampleStringTask
stopping...
starting...
sum: 3
s: 3
[success] Total time: 1 s, completed Dec 22, 2014 5:30:00 PM

sampleStringTask startServer sampleIntTask , sampleIntTask startServer ,
Scala , , value , sampeStringTask :

```



Figure 3: task-dependency

```

, test , compile in Test test in Test

stopServer ? , stopServer sampleStringTask, stopServer
sampleStringTask

lazy val library = (project in file("library"))
.settings(
  commonSettings,
  startServer := {
    println("starting...")
    Thread.sleep(500)
  },
  sampleIntTask := {
    startServer.value
    val sum = 1 + 2
    println("sum: " + sum)
    sum
  },
  sampleStringTask := {
    startServer.value
    val s = sampleIntTask.value.toString
    println("s: " + s)
  }
)

```

```

    s
  },
  sampleStringTask := {
    val old = sampleStringTask.value
    println("stopping...")
    Thread.sleep(500)
    old
  }
)

,      sampleStringTask:

> sampleStringTask
starting...
sum: 3
s: 3
stopping...
[success] Total time: 1 s, completed Dec 22, 2014 6:00:00 PM

```



Figure 4: task-dependency

```

Scala                               Scala , project/ServerUtil.scala , :

sampleIntTask := {
  ServerUtil.startServer
  try {
    val sum = 1 + 2
    println("sum: " + sum)
  } finally {
    ServerUtil.stopServer
  }
  sum
}

,      ,

```

```

    ,
    ,
    ,
    ;

    , build.sbt,

sbt

build.sbt , sbt sbt Scala sbt ?
project , , project
    sbt
    , project/project/
    :

hello/ #

    Hello.scala # ( src/main/scala)

build.sbt # build.sbt project/

project/ #

    Build.scala # ,

build.sbt # --project/project ;

project/ # ;

    Build.scala # project/project/

! project/project/
, .scala .sbt , build.sbt Build.scala

```

```

project .scala          project/Dependencies.scala

import sbt._

object Dependencies {
  // Versions
  lazy val akkaVersion = "2.3.8"

  // Libraries
  val akkaActor = "com.typesafe.akka" %% "akka-actor" % akkaVersion
  val akkaCluster = "com.typesafe.akka" %% "akka-cluster" % akkaVersion
  val specs2core = "org.specs2" %% "specs2-core" % "2.4.17"

  // Projects
  val backendDeps =
    Seq(akkaActor, specs2core % Test)
}

Dependencies build.sbt      val      , Dependencies._

import Dependencies._

lazy val commonSettings = Seq(
  version := "0.1.0",
  scalaVersion := "2.12.3"
)

lazy val backend = (project in file("backend"))
  .settings(
    commonSettings,
    libraryDependencies ++= backendDeps
  )

,

.scala

.scala ,      Scala ,
      build.sbt , project/*.scala      .scala      scala

```


, project/*.scala ,

sbt, , sbt sbt
,

sbt:

- Scala , Scala [Programming in Scala](#),Scala
- [.sbt](#)
- Setting ,sbt Setting task
- Setting, key ::=,+= +=
- , ; , Setting sbt
- , key
- *tasks* , key value task Non-task
- [Scopes](#)
- key value, scope
- scope :configuration,project,task
- scope task configuration
- configuration , Compile Test
- project “ ” scope
- scopes scope
- build.sbt , .scala task
- sbt ,
-
- addSbtPlugin project/plugins.sbt (build.sbt)
- , , sbt
- !

sbt , !