

SUNGENE INDUSTRIAL IOT

Remote Monitoring & Data Acquisition

Remote monitoring solutions for water, energy
and industrial equipment

LoRaWAN . NB-IoT . RS485 . Modbus . 4G LTE

sungenelite.com | contact@sungenelite.com

Product Catalog 2026 - Edition v2

Remote monitoring, by scenario

Water Monitoring

Tank level monitoring, water leak detection and pump monitoring for water utilities, industrial facilities and agriculture - using LoRa / NB-IoT wireless sensors and gateways.

Energy Monitoring

Smart metering, energy data collection and solar site monitoring to spot loss, downtime and underperformance in time, across energy, solar and telecom sites.

Equipment Monitoring

Temperature monitoring, RS485 / Modbus data acquisition and alarm notification for remote equipment and industrial assets - pushed to operators, not discovered on the next site visit.

Environmental Monitoring

Weather stations, air quality, soil and rainfall sensing for agriculture, smart cities and ecological monitoring - solar-powered and wireless options for off-grid sites.

Where customers start their search

Tank Level Monitoring

Continuous remote level readings for tanks and reservoirs.

Pump Monitoring

Run status, faults and alarms for remote pumps.

Solar Site Monitoring

Production and asset data from distributed solar sites.

Remote Meter Reading

Automated meter reads over RS485 / wireless.

Equipment Alarm Notification

Temperature and status alarms pushed in real time.

Temperature & Humidity Controller

Switchgear and cabinet temperature & humidity controller that drives heaters and fans to prevent condensation, with RS485 Modbus for remote monitoring - DIN-rail and panel-mount versions.



Measurement	Temperature + humidity (multi-channel models)
Control	Heater + fan outputs (condensation / anti-dew)
Communication	RS485 (Modbus RTU)
Display	LED, setpoint & alarm
Power supply	AC/DC wide range (model dependent)
Application	Switchgear, ring main units, cabinets
Mounting	DIN-rail / panel-mount

Request a quote: contact@sungenelite.com

Protocol Gateway (RS485 <-> Ethernet)

Industrial DIN-rail protocol gateway bridging RS485 (Modbus) field devices to Ethernet / BACnet - for building, facility and equipment monitoring.



OS	Linux
Serial	2× RS485
Ethernet	1× 10/100M
Protocols	Modbus RTU/TCP, BACnet
Power supply	AC/DC 12-24V
Mounting	35mm DIN-rail

[Request a quote: contact@sungenelite.com](mailto:contact@sungenelite.com)

Modular Remote I/O System

Expandable DIN-rail remote I/O with PROFINET, EtherCAT and Modbus TCP couplers - for distributed data acquisition and control across facilities.



Couplers	PROFINET / EtherCAT / Modbus TCP
Modules	DI / DO / AI / AO, expandable
Ports	2× RJ45 + USB-C config
Power supply	DC 24V
Mounting	35mm DIN-rail

[Request a quote: contact@sungenelite.com](mailto:contact@sungenelite.com)

Multi-interface edge IoT gateway / controller with 4G, WiFi, GPS, RS485/RS232 and Ethernet - for on-site data acquisition, edge computing and cloud uplink.



Connectivity	4G / WiFi / GPS / Ethernet (WAN+LAN)
Serial	RS485 / RS232
Interfaces	USB, Type-C, HDMI
OS	Linux (edge computing)
Power supply	DC 12-24V
Mounting	DIN-rail

Request a quote: contact@sungenelite.com

Wireless Communication Gateway

DIN-rail wireless data terminal that collects RS485 / Modbus meter data and uploads it over 4G / LoRa to the cloud - the uplink for distributed energy and equipment monitoring.



Function	RS485 data acquisition + wireless uplink
Wireless	4G / LoRa (model dependent)
Serial	RS485 (Modbus RTU)
Indicators	Link / signal (RSSI) / comm LEDs
Power supply	Wide-range AC/DC
Mounting	35mm DIN-rail

Request a quote: contact@sungenelite.com

Ultrasonic Water Level Sensor

Non-contact ultrasonic level measurement for tanks, reservoirs and open channels - for remote water level monitoring.



Measurement	Ultrasonic (non-contact)
Range	0-15 m (model dependent)
Output	4-20mA / RS485 (Modbus)
Power supply	DC 24V
Display	LCD
Protection	IP65
Mounting	Top-mount

Request a quote: contact@sungenelite.com

LoRa Temperature & Humidity Sensor

Wireless LoRa temperature and humidity monitoring for rooms, cabinets and remote sites - with local LCD and long-range transmission.



Measurement	Temperature + Humidity
Communication	LoRa (wireless)
Range	Long-range, km-level (line of sight)
Display	Local LCD
Power supply	Battery / DC
Mounting	Wall-mount

Request a quote: contact@sungenelite.com

Solar-Powered Weather Station

Self-powered environmental monitoring station with ultrasonic weather sensor and solar panel - wind, rain, temperature, humidity and light for remote, solar and agricultural sites.



Parameters	Wind, rain, temperature, humidity, light
Sensor	Ultrasonic weather sensor
Power	Solar panel + battery (off-grid)
Communication	RS485 / LoRa / 4G (model dependent)
Enclosure	Outdoor, IP65
Mounting	Pole-mount

Request a quote: contact@sungenelite.com

Water Quality pH Sensor

Industrial pH electrode with RS485 / 4-20mA output for continuous water-quality monitoring in tanks, treatment plants and process water.



Parameter	pH (ORP / EC variants available)
Range	pH 0-14
Output	RS485 (Modbus) / 4-20mA
Cable	Industrial sealed cable
Application	Tanks, treatment, process water

Request a quote: contact@sungenelite.com

Vibration Sensor

Industrial vibration sensor with 4-20mA / RS485 output for pump, motor and rotating-equipment condition monitoring and alarms.




Measurement	Vibration (velocity / acceleration)
Output	4-20mA / RS485 (Modbus)
Application	Pumps, motors, fans, rotating equipment
Function	Condition monitoring + alarm
Mounting	Stud / magnetic base
Enclosure	Industrial metal

Request a quote: contact@sungenelite.com

Water Leak Detection Alarm

Wireless water leak detection alarm with probe and app notification - instant alerts for leaks under tanks, pumps and equipment.



Detection	Water leak (probe / cable)
Alert	Local siren + app push
Communication	WiFi (app)
Power	Battery
Settings	On/off, sensitivity
Application	Pump rooms, server rooms, basements

Request a quote: contact@sungenelite.com

Ultrasonic Weather Station

All-in-one ultrasonic weather sensor measuring wind speed, wind direction, temperature, humidity and air pressure - no moving parts, with RS485 Modbus output.



Parameters	Wind speed & direction, temperature, humidity, pressure (optional light / rainfall)
Wind speed	0-60 m/s
Wind direction	0-360°
Measurement	Ultrasonic, no moving parts
Output	RS485 (Modbus RTU)
Power supply	12-24 VDC
Protection	IP65, pole mount

Request a quote: contact@sungenelite.com

Wind Speed & Direction Sensor

Combined anemometer and wind vane for accurate wind speed and direction, with RS485 / 4-20 mA / pulse output options.



Wind speed range	0-60 m/s
Wind speed accuracy	±0.3 m/s
Wind direction	0-360°, 16 directions
Output	RS485 (Modbus) / 4-20 mA / voltage / pulse
Power supply	5-24 VDC
Material	Aluminium alloy, IP65

Request a quote: contact@sungenelite.com

Tipping-Bucket Rain Gauge

Tipping-bucket rainfall sensor with 0.1 mm resolution and RS485 / pulse output for weather and hydrology stations.



Resolution	0.1 mm
Measurement	Tipping bucket
Max intensity	? 4 mm/min
Caliber	dia. 200 mm
Output	RS485 (Modbus) / pulse
Power supply	5-24 VDC

Request a quote: contact@sungenelite.com

Pyranometer (Solar Radiation Sensor)

PV-grade pyranometer measuring total solar radiation (0-2000 W/m²) for solar plants, agriculture and meteorology.



Range	0-2000 W/m ²
Spectral range	300-3000 nm
Accuracy	±5%
Output	RS485 (Modbus) / 4-20 mA / 0-5 V
Power supply	5-24 VDC
Protection	IP65

Request a quote: contact@sungenelite.com

Soil Moisture, Temperature & EC Sensor

Buried 3-in-1 soil probe measuring volumetric moisture, temperature and electrical conductivity (EC) with RS485 Modbus output.



Parameters	Moisture, temperature, EC
Moisture	0-100%, $\pm 2-3\%$
Temperature	-40-80 °C
EC range	0-20000 $\mu\text{S}/\text{cm}$
Output	RS485 (Modbus)
Power supply	5-24 VDC
Probe	Stainless steel, IP68

Request a quote: contact@sungenelite.com

Air Quality Sensor

Outdoor multi-parameter air quality sensor monitoring PM2.5/PM10, CO2, temperature and humidity, with RS485 Modbus output.



Parameters	PM2.5 / PM10, CO2, temperature, humidity (optional CO / SO2 / NO2 / O3 / noise)
PM range	0-1000 µg/m³
CO2 range	0-5000 ppm
Output	RS485 (Modbus)
Power supply	12-24 VDC
Housing	Louvered, IP65, wall / pole mount

Request a quote: contact@sungenelite.com

Dissolved Oxygen Sensor

Online fluorescence (optical) dissolved-oxygen sensor for aquaculture, wastewater and surface water - RS485 Modbus, no membrane or electrolyte.



Method	Fluorescence (optical)
DO range	0-20 mg/L
Accuracy	±0.3 mg/L
Temperature	0-60 °C
Output	RS485 (Modbus) / 4-20 mA
Power supply	9-24 VDC
Protection	IP68

Request a quote: contact@sungenelite.com

Turbidity Sensor

Online optical turbidity sensor (90° scattered light) for drinking water, wastewater and environmental monitoring - RS485 Modbus.



Range	0-1000 NTU (optional 0-4000)
Method	90° scattered light
Accuracy	±5%
Output	RS485 (Modbus) / 4-20 mA
Power supply	9-24 VDC
Protection	IP68, immersion

Request a quote: contact@sungenelite.com

Water Conductivity (EC) Sensor

Online conductivity / TDS / salinity sensor for water and wastewater monitoring - RS485 Modbus output.



Range	0-20000 $\mu\text{S}/\text{cm}$ (optional higher)
Accuracy	$\pm 1.5\%$ FS
Temperature	0-60 $^{\circ}\text{C}$
Output	RS485 (Modbus) / 4-20 mA
Power supply	9-24 VDC
Protection	IP68

Request a quote: contact@sungenelite.com

Radar Water Level Sensor

Non-contact radar level sensor for rivers, reservoirs, channels and tanks - unaffected by foam, vapour or fouling, with RS485 Modbus output.



Method	Non-contact radar (FMCW)
Range	0-30 m (model dependent)
Accuracy	±3 mm
Output	RS485 (Modbus) / 4-20 mA
Power supply	12-24 VDC
Protection	IP67

Request a quote: contact@sungenelite.com

Atmospheric Multi-Parameter Sensor

Compact radiation-shielded sensor measuring air temperature, humidity, barometric pressure, illuminance and CO2 - RS485 Modbus output.



Parameters	Temperature, humidity, pressure, illuminance, CO2
Temperature	-40-80 °C
Pressure	300-1100 hPa
CO2 range	0-5000 ppm
Output	RS485 (Modbus)
Power supply	12-24 VDC
Housing	Radiation shield, IP65

Request a quote: contact@sungenelite.com

Leaf Wetness Sensor

Surface leaf-wetness sensor for crop disease forecasting and smart irrigation in greenhouses and orchards - RS485 Modbus output.



Measurement	Leaf surface wetness / dew
Output range	0-100% wetness
Temperature	-40-80 °C
Output	RS485 (Modbus)
Power supply	12-24 VDC
Protection	IP65

Request a quote: contact@sungenelite.com

Split-Core Current Sensor

Clip-on split-core current sensor for non-invasive energy and load monitoring - install without disconnecting existing wiring.



Type	Split-core (clip-on)
Input	AC/DC up to 50A (model dependent)
Output	4-20mA / 0-5V / RS485 (model dependent)
Accuracy	0.5%
Installation	Clip-on, no rewiring
Mounting	Panel / DIN

Request a quote: contact@sungenelite.com

Electromagnetic Flow Meter

Flanged electromagnetic flow meter with RS485 / 4-20mA output for water and conductive-liquid flow measurement in pipelines.



Measurement	Electromagnetic
Medium	Water / conductive liquids
Output	4-20mA / RS485 (Modbus)
Connection	Flanged (DN model dependent)
Display	Local LCD
Protection	IP65 / IP68

Request a quote: contact@sungenelite.com

Three-Phase Smart Energy Meter

Three-phase four-wire kWh energy meter with RS485 (Modbus) for remote energy data collection and sub-metering across facilities.



Type	Three-phase four-wire
Voltage	3×230/400V
Current	3×10(100)A
Communication	RS485 (Modbus)
Standards	IEC 62052 / 62053
Display	LCD, Class 1

Request a quote: contact@sungenelite.com

Multifunction Power Meter

Panel-mount three-phase multifunction power meter measuring voltage, current, power, power factor, frequency and energy, with RS485 Modbus for remote energy monitoring and sub-metering.



Measurement	V, A, kW, kvar, PF, Hz, kWh (three-phase)
Accuracy	Class 0.5S (energy)
Communication	RS485 (Modbus RTU)
Inputs	Via CT / direct (model dependent)
Display	Backlit LCD
I/O	Optional DI / DO / 4-20mA
Mounting	Panel-mount (72 / 96 / 120 mm)

Request a quote: contact@sungenelite.com

Wireless IoT Energy Meter

DIN-rail three-phase energy meter with built-in wireless (4G / LoRa / WiFi) for direct cloud upload - no separate gateway needed, ideal for distributed sub-metering and remote sites.



Measurement	V, A, kW, PF, kWh (three-phase)
Wireless	4G / LoRa / WiFi (model dependent)
Wired	RS485 (Modbus) optional
Cloud	Direct platform upload, no gateway
Input	Direct or via CT
Display	LCD
Mounting	35mm DIN-rail

Request a quote: contact@sungenelite.com

DIN-Rail Three-Phase Energy Meter

Compact DIN-rail three-phase multifunction energy meter with RS485 Modbus - for panel sub-metering in solar, EV-charging, building and industrial energy management.



Type	Three-phase multifunction, DIN-rail
Measurement	V, A, kW, kvar, PF, Hz, kWh
Accuracy	Class 0.5S (energy)
Communication	RS485 (Modbus RTU)
Input	Direct 80A / via CT (model dependent)
Display	Backlit LCD
Mounting	35mm DIN-rail (7 modules)

Request a quote: contact@sungenelite.com

Electrical Fire Monitor (Residual Current)

DIN-rail electrical fire monitoring unit that continuously watches residual (leakage) current and circuit temperature, alarming on faults - with RS485 Modbus for remote electrical-safety monitoring of distribution boxes and cabinets.



Monitoring	Residual current + temperature (multi-channel)
Function	Leakage / over-temperature alarm, electrical fire prevention
Communication	RS485 (Modbus RTU)
Display	LCD + status indicators
Alarm	Audible + relay output
Application	Distribution boxes, cabinets, switchgear
Mounting	35mm DIN-rail

Request a quote: contact@sungenelite.com

Build your Industrial IoT business with SunGene

Distributor Program

Resell SunGene gateways, sensors and controllers in your region with distributor pricing and stock support.

System Integrator Program

Specify and integrate our devices into your monitoring projects with technical and documentation support.

OEM / Private Label Program

Put your brand on proven hardware with flexible MOQ and ODM/OEM customization.

Why partner with SunGene

Taiwan-based service . China manufacturing network . Fast OEM support . Low MOQ . English communication . Export experience

Let's talk

Email: contact@sungenelite.com

WhatsApp: +86 181 4413 2078

WeChat: +86 181 4413 2078

LinkedIn: [linkedin.com/company/108298466](https://www.linkedin.com/company/108298466)

Web: sungenelite.com

SunGene Co., Ltd. - Taiwan-based Industrial IoT partner with an ODM/OEM network and China supply chain, serving distributors, system integrators and industrial customers worldwide.