The Open Master Hearing Aid (openMHA)

4.6.2

Documentation of openMHA plugins (openMHA)



© 2005-2018 by HörTech gGmbH, Marie-Curie-Str. 2, D-26129 Oldenburg, Germany



LICENSE AGREEMENT

This file is part of the HörTech Open Master Hearing Aid (openMHA) Copyright © 2005 2006 2007 2008 2009 2010 2012 2013 2014 2015 2016 HörTech gGmbH. Copyright © 2017 2018 HörTech gGmbH.

openMHA is free software: you can redistribute it and/or modify it under the terms of the GNU Affero General Public License as published by the Free Software Foundation, version 3 of the License.

openMHA is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Affero General Public License, version 3 for more details.

You should have received a copy of the GNU Affero General Public License, version 3 along with openMHA. If not, see http://www.gnu.org/licenses/>.

Contents

1	Plugi	n category 'AC-variables'	1
	1.1	ac2lsl	1
	1.2	ac2osc	2
	1.3	ac2wave	3
	1.4	acConcat wave	
	1.5		5
	1.6	acPooling wave	
	1.7	acsave	
	1.8	acSteer	
	1.9	save spec	
		- 1	
	1.10	save_wave	_
2	Pluai	n category 'adaptive'	2
_	2.1	lpc	
	2.2	lpc_bl_predictor	
		. – –	
	2.3	lpc_burg-lattice	Э
3	Pluai	n category 'analysis'	7
•	3.1	acTransform wave	
	3.2	droptect	
	3.2	droptect	0
4	Pluai	n category 'beamforming'	ሰ
•	4.1	adm	_
	4.2	steerbf	
	4.2	Steeldi	
5	Plugi	n category 'binaural'	3
	5.1	coherence	
			_
6	Plugi	n category 'core'	5
	6.1	identity	5
7	Plugi	n category 'directional' 20	_
	7.1	doasvm_classification	6
	7.2	doasvm_feature_extraction	7
8	_	n category 'example'	
	8.1	example1	
	8.2	example2	0
	8.3	example3	0
	8.4	example4	1
	8.5	example5	2
	8.6	example6	3
9	Plugi	n category 'feedback' 34	4
	9.1	fshift_hilbert	4
	9.2	prediction_error	5
10	Plugi	n category 'filter' 3	7
	10.1	combinechannels	7
	10.2	fftfilterbank	8
	10.3	iirfilter	1

	10.4	nlms_wave	ŀ2
11	Plugi	category 'generator'	14
	11.1	noise	14
	11.2	plingploing	15
			16
12	Dlugi	a category 'level'	17
12	_		• <i>•</i> 17
			50
		_	53
		·	54
	12.4		
	12.5		56
	12.6		57
	12.7	transducers 5	58
13	_	5	3
	13.1	timoSmooth	3
14	Plugi	category 'overlapadd'	35
			35
		·	38
		_ •	39
	14.4		70
	14.5	spec2wave	_
			- 73
45	Div		,,
15			75
		downsample	
	15.2	upsample 7	6
16	Plugi	category 'signalflow' 7	77
	16.1	addsndfile	7
		altplugs	79
	16.3	analysispath	30
	16.4		32
	16.5	delay	33
	16.6	fader_wave	34
	16.7		35
	16.8		37
	16.9		38
		1 0	90
			91
4-	Her -		.~
17			92
	17.1		92
	17.2	- y	93
	17.3		94
	17.4		95
	17.5	noisePowProposedScale	97
	17.6		98

1 Plugin category 'AC-variables'

1.1 ac2lsl

Send AC variables as LSL messages.

1.1.0.1 Detailed description

This plugin provides a mechanism to send ac variables over the network using the lab streaming layer (lsl). Currently no user-defined types are supported.

1.1.0.2 Supported domains

The MHA plugin ac21s1 supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

1.1.0.3 Categories

AC-variables

1.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
vars	vector <string></string>	List of AC variables to be saved, empty	[]
		for all.	
rt_strict	bool	abort if used in real-time thread?	yes
activate	bool	send frames to network?	yes
skip	int	Number of frames to skip after sending	0
		Range: [0,]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.2 ac2osc

Send AC variables as OSC messages over udp.

1.2.0.1 Detailed description

Send AC variables as OSCvariables using the UDP transport layer. The variable "vars" can be used to select variables from the AC space for sending. The sending of variables can be verified using the open source tool "dump_osc". When selecting an AC variable, a target path can be specified using the colon delimiter, e.g.:

```
vars = [level:/mhalevels]
```

1.2.0.2 Supported domains

The MHA plugin aclose supports these signal domains:

- · waveform to waveform
- spectrum to spectrum

1.2.0.3 Categories

AC-variables

1.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
host	string	OSC server host name	localhost
port	string	OSC server port	7777
ttl	int	Time-to-live of UDP packages (1 =	1
		subnet)	
vars	vector <string></string>	List of AC variables to be saved, empty	[]
		for all. A colon may be used to specify	
		target address.	
mode	keyword_list	record mode	pause
		Range: [rec pause]	
skip	int	number of frames to skip after sending	0
		Range: [0,]	
rt_strict	bool	abort if used in real-time thread?	yes

Variables of sub-parser mhaconfig_in:

1.3 ac2wave

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.3 ac2wave

Mix the main input signal with a waveform stored into AC variables. Main and AC signal can be attenuated or delayed by integer fragments.

Spectral input is discarded and replaced by a zero signal.

1.3.0.1 Supported domains

The MHA plugin ac2wave supports these signal domains:

- · waveform to waveform
- spectrum to waveform

1.3.0.2 Categories

AC-variables

1.3.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
name	string	AC variable name	
gain_in	float	Linear gain for main input signal	0
gain_ac	float	Linear gain for AC input signal	1
delay_in	int	Delay of main input signal in fragments	0
		Range: [0,[
delay_ac	int	Delay of AC input signal in fragments	0
		Range: [0,[

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.4 acConcat_wave

Concatenating two or more waveforms into one

1.4.0.1 Detailed description

This plugin concatenates two or more waveforms in the given order into a new waveform all living in the AC space.

1.4.0.2 Supported domains

The MHA plugin acConcat_wave supports these signal domains:

· waveform to waveform

1.5 acmon 5

1.4.0.3 Categories

AC-variables

1.4.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
num_AC	int	Number of waveforms to be concate- nated	15
		Range: [1,28]	
prefix_names_AC	string	Prefix of the names of the waveforms to be concatenated	vGCC_ac
samples_AC	vector <int></int>	Lengths of the waveforms to be con- catenated	
name_conAC	string	Name of the concatenated waveform	vGCC_con_AC

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.5 acmon

This algorithm converts AC variables into parsable monitor variables.

1.5.0.1 Supported domains

The MHA plugin acmon supports these signal domains:

- · waveform to waveform
- spectrum to spectrum

1.5.0.2 Categories

AC-variables

1.5.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
varlist	vector <string></string>	complete list of variables	(monitor)
dimensions	vector <string></string>	variable dimensions in AC space	(monitor)
dispmode	keyword_list	display mode of variables	vector
		Range: [vector matrix]	
recmode	keyword_list	record mode	cont
		Range: [cont snapshot]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.6 acPooling_wave

Pooling of several consecutive time frames

1.6.0.1 Detailed description

This plugin computes an average over several consecutive frames using several different approaches (max, sum, mean, ...). Subsequently, the maximum of the average frame is delivered as well. The plugin receives the frames through the ac space and deliveres the averaged frame as well as its maximum to the ac space.

1.6.0.2 Supported domains

The MHA plugin acPooling_wave supports these signal domains:

waveform to waveform

1.6.0.3 Categories

AC-variables

1.6.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
numsamples	int	This parameter determines the length of the wave to be pooled in samples Range:]0,360]	33
pooling_wndlen	int	This parameter determines the length of the pooling window in msec. Range: [0,5000]	300
pooling_type	keyword_list	This parameter determines the pooling method applied to the pooling window. Range: [max sum mean]	mean
upper_threshold	float	This parameter sets a threshold for finding the maximum probability. If the maximum is above this threshold, it is taken, even if it is not in the neighbourhood of the last estimated direction. Range: [0,1]	0.75
lower_threshold	float	This parameter sets a threshold for finding the minimum probability. If the maximum probability is below this threshold, the estimated direction of the last iteration is taken. Range: [0,1]	0
neighbourhood	int	This parameter defines the neighbourhood of the allowed change of the estimated direction between iterations1 means no neighbourhood. Range: [-1,360]	2
alpha	float	This parameter simulates the forgetting effect by weighting the frames within the pooling window, e.g. $p(n + 1) = (1 - alpha) * p(n) + alpha * p_new. 0 means no weighting. Range: [0,1]$	0.1
p_name	string	The name of the AC variable of the frame, which is going to be pooled.	р
pool_name	string	The name of the AC variable of the averaged (pooled) frame.	pool
max_pool_ind_name	string	The name of the AC variable for the in- dex of the maximum of the averaged frames	pool_max
like_ratio_name	string	The name of the AC variable for the likelihood ratios of the averaged frames	like_ratio

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.7 acsave

Save chain data to text or Matlab 4 files.

Usage:

- 1. set up file name and type
- 2. set the maximal length. This will start the recording.
- 3. Set "flush" to yes to save recorded frames. This will overwrite previously written data.

File name and type can be changed at any time and has to be valid when sending the flush command. Changing the list of variables also starts the recording with the currently configured recording length (previously recorded data might be overwritten). Issueing the 'flush' command frees allocated memory.

1.7.0.1 Detailed description

The 'acsave' plugin can save numeric algorithm communication variables (AC variables) into files. The files can have plain text, MATLAB 4.x or MATLAB script format. Each signal frame represents a row. The number of columns is gathered at preparation time. If a variable size is increased after preparation, only the part available at preparation time is stored. If the size is decreased, it is zero-padded to the original size.

To save the data to disk, first set up file name and type. Then setting the maximal length will start the recording. At any time, set 'flush' to yes in order to save the recorded frames. This will overwrite previously written data.

File name and type can be changed at any time and have to be valid when sending the flush command.

1.8 acSteer 9

1.7.0.2 Supported domains

The MHA plugin acsave supports these signal domains:

- · waveform to waveform
- spectrum to spectrum

1.7.0.3 Categories

AC-variables

1.7.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
fileformat	keyword_list	file format of output file	txt
		Range: [txt mat4 m]	
name	string	output file name	
reclen	float	maximal recording length in seconds	10
		Range: [0,]	
flush	bool	flush the buffers to disk	no
vars	vector <string></string>	list of variables to be saved (empty:	[]
		save all)	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.8 acSteer

Steering Vector Loading Plugin

1.8.0.1 Detailed description

The acsteer plugin loads a file containing pre-computed steering filters (e.g. MVDR filters) to be used within a beamformer. The steering filters can be monaural (**nrefmic = 1**) or binaural (**nrefmic = 2**). The whole file consists of a column vector of concatenated steering vectors, which are formatted in the order of **angle** and **channel**. This means that the first channel vector of the first angle is followed by the second channel vector of the first angle until the last channel. The channel vectors of the first angle are followed by the channel vectors of the second angle and so an and so forth.

If the steering filters have been computed for two reference microphones, the steering filters of the second reference microphone just follow the ones for the first microphone and have the same format.

This plugin is typically located between a localization plugin (e.g. <code>doasvm_classification</code>) and a beamforming plugin (e.g. <code>steerbf</code>). The localization plugin estimates the source direction and saves it in an AC variable. This plugin reads the saved direction from the corresponding AC variable and saves the corresponding steering vector to the AC space, which is used by the succeeding beamforming plugin for steering the beam towards that particular direction.

The configuration variable **nrefmic** indicates the number of different reference microphone settings, for which the filters were computed. For each reference microphone and each possible DOA angle and each input channel one filter should be provided so that

$$nsteerchan = nrefmix * nchan * nangle$$
 (1)

1.8.0.2 Supported domains

The MHA plugin acSteer supports these signal domains:

· spectrum to spectrum

1.8.0.3 Categories

AC-variables

1.8.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
steerFile	string	Name of the input file where the steer-	steerfile.bin
		ing vectors are saved	
acSteerName1	string	Name of the AC variable where the	acSteerLeft
		steering vectors of the first (left) refer-	
		ence microphone are saved	
acSteerName2	string	Name of the AC variable where the	acSteerRight
		steering vectors of the second (right)	
		reference microphone are saved	
nsteerchan	int	Number of channels in each steering	4
		vector	
nrefmic	int	Number of reference microphones	1
		Range:]0,2]	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.9 save_spec

Save signal spectrum to AC variable

1.9.0.1 Supported domains

The MHA plugin save_spec supports these signal domains:

· spectrum to spectrum

1.9.0.2 Categories

AC-variables

1.9.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

1.10 save_wave

Save signal waveform to AC variable

1.10.0.1 Supported domains

The MHA plugin save_wave supports these signal domains:

• waveform to waveform

1.10.0.2 Categories

AC-variables

1.10.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)

Variables of sub-parser mhaconfig_in:

Type	Description	Default
int	Number of audio channels	(monitor)
string		(monitor)
	MHA_SPECTRUM)	
int	Fragment size of waveform data	(monitor)
int	Window length of spectral data	(monitor)
int	FFT length of spectral data	(monitor)
float	Sampling rate in Hz	(monitor)
	int string int int int	int Number of audio channels string Signal domain (MHA_WAVEFORM or MHA_SPECTRUM) int Fragment size of waveform data int Window length of spectral data int FFT length of spectral data

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

2 Plugin category 'adaptive'

2.1 lpc

This plugin implements the linear predictive coding analysis (LPC) by using the Levinson-Durbin recursion.

2.1.0.1 Detailed description

This plugin estimates the autocorrelation of each block. It then produces the inverse filter using the Levinson-Durbin recursion.

2.1.0.2 Supported domains

The MHA plugin lpc supports these signal domains:

· waveform to waveform

2.1.0.3 Categories

adaptive

2.1.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
lpc_order	int	LPC filter order	20
		Range: [0,500]	
lpc_buffer_size	int	Size of the buffer in samples for which	21
		the autocorrelation matrix will be com-	
		puted	
		Range:]0,501]	
shift	bool	Refill the LPC buffer completely with	yes
		new input signal by ignoring the old	
		samples (no) or shift the old buffer as	
		large as the block size of the input sig-	
		nal and read in the current input signal (yes).	
comp each iter	int	Reestimate the LPC coefficients each	1
	-	<pre><comp each="" iter=""> iterations, default</comp></pre>	
		value is 1	
		Range:]0,]	
norm	bool	Normalize the auto correlation matrix	no
		with the LPC order	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

2.2 lpc_bl_predictor

This plugin performs forward and backward linear prediction using the Burg - Lattice algorithm for computing the next value of a given time series.

The estimated forward and backward linear predictionn parameters are saved in th AC space.

2.2.0.1 Detailed description

This plugin computes the forward and backward LPC estimates using the Burg-Lattice algorithm given the κ (sometimes also called μ) parameter precomputed using the <code>lpc_burg-lattice</code> plugin. The estimation of the forward and backward linear prediction parameters is performed using the following equations: For each forward and backward linear prediction parameter f(m) and b(m), where m in $[2\cdots P]$, P being the lpc order

$$f(m) = f(m-1) + \kappa(m,2) * b(m-1,2)$$
 (2)

$$b(m,1) = b(m-1,2) + \kappa(m,2) * f(m-1)$$
(3)

. In this implementation κ from the previous is used. Note that the second index of κ is 2.

2.2.0.2 Supported domains

The MHA plugin lpc_bl_predictor supports these signal domains:

· waveform to waveform

2.2.0.3 Categories

adaptive

2.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
lpc_order	int	LPC order defines the number of coffe-	21
		cients to be estimated	
		Range:]0,]	
name_kappa	string	Name of the kappa parameter of the	km
		Burg-Lattice algorithm in the AC do-	
		main to be used for the joint estimation	
		of more than one time series	
name_lpc_f	string	Name of the forward LPC estimate of	name_lpc_f
		the Burg-Lattice algorithm in the AC	
		domain	
name_lpc_b	string	Name of the backward LPC estimate	name_lpc_b
		of the Burg-Lattice algorithm in the AC	
		domain	
name_f	string	Name of the forward linear prediction	
		parameter	
name_b	string	Name of the backward linear prediction	
		parameter	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

2.3 lpc_burg-lattice

This plugin estimates the linear predictive coding coefficients for estimating the next sample value of a time series using the Burg-Lattice approach.

The estimated parameters are saved in the AC space.

2.3.0.1 Detailed description

This plugin estimates the parameters for the forward and backward linear prediction using the Burg - Lattice algorithm. The previous estimate of the κ parameter is saved in the AC space for future use in the <code>lpc_bl_predictor</code> plugin to estimate several time-series sharing the same κ values.

For the estimation of κ the following series of equations are used: For each κ in $[2 \cdots P]$, P being the lpc order

$$dm(m-1) = \lambda * dm(m-1) + (1-\lambda) * (f(m-1)^2 + b(m-1,2)^2)$$
 (4)

$$nm(m-1) = \lambda * nm(m-1) + (1-\lambda) * -2 * f(m-1) * b(m-1,2)$$
 (5)

$$km(m,1) = \frac{nm(m-1)}{dm(m-1)}.$$
(6)

Note that the previous estimate of κ , which is given by $\kappa(m,2)$ is saved in the AC space.

2.3.0.2 Supported domains

The MHA plugin lpc_burg-lattice supports these signal domains:

· waveform to waveform

2.3.0.3 Categories

adaptive

2.3.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
lpc_order	int	LPC order defines the number of coffe-	21
		cients to be estimated	
		Range:]0,]	
name_kappa	string	Name of the kappa parameter of the	km
		Burg-Lattice algorithm in the AC do-	
		main to be used for the joint estimation	
		of more than one time series	
name_f	string	Name of the forward linear prediction	
		parameter	
name_b	string	Name of the backward linear prediction	
		parameter	
lambda	float	Forgetting factor for the linear predictor	0.99375
		Range: [0,1]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

3 Plugin category 'analysis'

3.1 acTransform_wave

Transform Plugin Between Coordinate Systems for Waveforms

3.1.0.1 Detailed description

This plugin transforms a waveform in the AC space from one coordinate system into another. For this it receives an angle also saved in the AC space. Then, the plugin rotates the axes into the direction of the given angle.

3.1.0.2 Supported domains

The MHA plugin acTransform_wave supports these signal domains:

· waveform to waveform

3.1.0.3 Categories

analysis

3.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
ang_name	string	This parameter has the name of the AC variable having the rotation angle	head_ang
raw_p_name	string	This parameter has the name of the AC variable having the waveform to be rotated	p
raw_p_max_name	string	This parameter has the name of the AC variable having the maximum of the waveform to be rotated	p_max
rotated_p_name	string	This parameter has the name of the AC variable having the waveform after rotation	rotated_p
rotated_p_max_name	string	This parameter has the name of the AC variable having the maximum of the waveform after rotation	rotated_p_max
numsamples	int	This parameter determines the length of the wave to be pooled in samples. Range:]0,360]	73
to_from	bool	This parameter tells whether the rotation will be performed to the given angle or from it	yes

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Type	Description	Default
int	Number of audio channels	(monitor)
string	Signal domain (MHA_WAVEFORM or	(monitor)
	MHA_SPECTRUM)	
int	Fragment size of waveform data	(monitor)
int	Window length of spectral data	(monitor)
int	FFT length of spectral data	(monitor)
float	Sampling rate in Hz	(monitor)
	string int int int	int Number of audio channels string Signal domain (MHA_WAVEFORM or MHA_SPECTRUM) int Fragment size of waveform data int Window length of spectral data int FFT length of spectral data

3.2 droptect

Plugin detects dropouts in channels that have a constant spectrum

3.2 droptect 19

3.2.0.1 Supported domains

The MHA plugin droptect supports these signal domains:

• spectrum to spectrum

3.2.0.2 Categories

analysis

3.2.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
dropouts	vector <int></int>	Number of dropouts detected since last	(monitor)
		reset or start	
consecutive_dropouts	vector <int></int>	Number of consecutive dropouts	(monitor)
blocks	int	Number of blocks processed since last	(monitor)
		reset or start	
reset	bool	Setting to yes clears number of	no
		dropouts and blocks	
threshold	float	Threshold level in dB. All blocks be-	50
		low this threshold are considered to be	
		dropouts	
tau	float	Time constant for filtering power spec-	0.2
		tra	
filtered_powspec_mon	matrix <float></float>	Floating average of power spectrum	(monitor)
level_mon	float	current level	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

4 Plugin category 'beamforming'

4.1 adm

Adaptive differential microphone

4.1.0.1 Detailed description

This plugin implements one or more adaptive first-order differential microphones, each based on the output of two omnidirectional microphones, e.g. two hearing-aid microphones (cf. Elko & Nguyen Pong, 1995). This is achieved by first subtracting the outputs of the two omnidirectional microphones with fixed delays to create a forward-facing and a backward-facing cardioid microphone, respectively; then, in a second step, the signal from the backward-facing cardioid is amplified by a variable gain factor and subtracted from the signal from the forward-facing cardioid. Finally, a lowpass filter and a filter compensating for comb-filter effect is applied to the output signal.

The gain factor, beta, is determined adaptively such that the power of the output signal is minimized, under the constraint that the null of the ADM is located in the rear half-plane. The adaptation step size, mu_beta, can be chosen in order to find the optimal combination of adaptation speed and accuracy.




Figure 1 Output signals illustrating convergence of the ADM algorithm for three different values of mu_beta (input signal: white Gaussian noise exactly from behind)

4.1.0.2 Supported domains

The MHA plugin adm supports these signal domains:

· waveform to waveform

4.1.0.3 Categories

beamforming multichannel

4.2 steerbf 21

4.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
front_channels	vector <int></int>	Channel indices for front microphones Range: [0,[[0 1]
rear_channels	vector <int></int>	Channel indices for rear microphones Range: [0,[[2 3]
distances	vector <float></float>	Distance between front and rear microphones Range: [0.0008,0.08]	[0.0108 0.0108]
lp_order	int	Filter order of FIR lowpass filter Range: [46,128]	46
decomb_order	int	Filter order of FIR comb compensation filter Range: [46,128]	54
bypass	int	If 1, output front microphones directly; if 2, output rear microphones directly Range: [0,2]	0
beta	float	Explicit fixed beta (-1 for adaptive filtering)	-1
mu_beta	vector <float></float>	Adaptation step size for each set of ADMs (e.g. left and right) Range: [0,]	[0.0001 0.0001]
tau_beta	vector <float></float>	time constant / s of low pass filter for averaging power of output signal (used for adaptation) Range: [0,]	[0.05 0.05]
coeff_lp	vector <float></float>	Lowpass coefficients	(monitor)
coeff_decomb	vector <float></float>	Decomb coefficients	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

4.2 steerbf

Steerable Beamformer

4.2.0.1 Detailed description

Implements frequency-domain beamformer processing (filter and sum) using externally provided filters. A plugin called acSteer can be used to provide the filter coefficients. The filter coefficients to be read are saved as a waveform object in the AC space. Each channel of this object corresponds to a different steering angle. The steering angle is typically determined in real-time by a localization plugin (e.g. doasvm_classification). In this case, the index to the corresponding steering direction is read from the AC space. Note that the number of available filters should be consistent with the number of possible steering directions to be estimated. The configuration variable **angle_src** keeps the name of the AC variable for the estimated steering direction. The steering angle can also be fixed in the configuration time using the configuration variable **angle_ind**.

4.2.0.2 Supported domains

The MHA plugin steerbf supports these signal domains:

· spectrum to spectrum

4.2.0.3 Categories

beamforming

4.2.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
bf_src	string	Provides the beamforming filters encoded as a block matrix: [chanXnan-gle,nfreq].	
angle_ind	int	Sets the steering angle in filtering. Range: [0,1000]	0
angle_src	string	If initialized, provides an int-AC variable of steering index.	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

5 Plugin category 'binaural'
5.1 coherence
Coherence filter
5.1.0.1 Supported domains
The MHA plugin coherence supports these signal domains:
spectrum to spectrum
5.1.0.2 Categories
binaural filter noise-reduction

5.1.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
unit	keyword_list	Frequency unit	Hz
		Range: [Hz kHz Oct Oct/3 Bark Erb	
		ERB_Glasberg1990]	
f	vector <float></float>	Frequencies	[]
f_hz	vector <float></float>	Frequencies in Hz	(monitor)
fscale	keyword_list	frequency scale of filter bank	linear
		Range: [linear bark log erb ERB_Glasberg1990]	
ovltype	keyword list	filter overlap type	rect
Ovitype	Reyword_nst	Range: [rect linear hanning exp gauss]	1001
plateau	float	relative plateau width	0
platoad	liout	Range: [0,1[
ftype	keyword list	frequency entry type	center
31.	-, =	Range: [center edge]	
normalize	bool	normalize broadband output amplitude	no
fail_on_nonmonotonic	bool	Fail if frequency entries are non-	yes
		monotonic (otherwise sort)	
fail_on_unique_bins	bool	Fail if center frequencies share the	yes
·		same FFT bin.	
cf	vector <float></float>	final center frequencies in Hz	(monitor)
ef	vector <float></float>	final edge frequencies in Hz	(monitor)
cLTASS	vector <float></float>	Bandwidth level correction for LTASS	(monitor)
		noise in dB	
shapes	matrix <float></float>	Frequency band shapes	(monitor)
tau_unit	keyword_list	tau unit	seconds
		Range: [seconds periods]	
tau	vector <float></float>	Averaging time constant	[0.04]
		Range: [0,]	F 4 3
alpha	vector <float></float>	Gain exponent	[1]
11 11		Range: [0,]	
limit	float	gain limit / dB (zero: no limit)	0
		Range: [,0]	[0.4]
mapping	vector <float></float>	mapping interval of coherence estima-	[0 1]
		tor to coherence (min max) Range: [0,1]	
avorago	keyword list	average mode	ipd
average	veamora_iist	Range: [ipd spec]	ipu
invert	bool	Invert filter after mapping, before expo-	no
	2001	nent.	110
Itgcomp	bool	Long term gain compensation?	no
Itgtau	vector <float></float>	Long term gain estimation time con-	[1]
		stant / s	
		Range: [0,]	
staticgain	vector <float></float>	Static gain in frequency bands / dB	[0]
delay	int	Delay between analysis and filter (de-	0
		lay of gains), in fragments.	
		Range: [0,]	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

6 Plugin category 'core'

6.1 identity

6.1.0.1 Detailed description

The simplest openMHA plugin.

This plugin does nothing.

6.1.0.2 Supported domains

The MHA plugin identity supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

6.1.0.3 Categories

core

6.1.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

7 Plugin category 'directional'

7.1 doasym_classification

Support vector machine (SVM) plugin for computing the direction of arrival (DOA) probabilities

7.1.0.1 Detailed description

This plugin loads the parameters of a pre-trained SVM and computes the probabilities for given range of directions of arrival (DOA). These probabilities take a value within the interval of [0,1]. Higher probability for a certain DOA indicates higher possibility of a source coming from that particular DOA.

7.1.0.2 Supported domains

The MHA plugin doasvm_classification supports these signal domains:

· waveform to waveform

7.1.0.3 Categories

directional

7.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
angles	vector <float></float>	The angles for which the SVM model	[]
		has been trained	
W	matrix <float></float>	The separation planes of the model.	[[]]
b	vector <float></float>	The model bias.	[]
Х	vector <float></float>	The sigmoid probability mapping pa-	[]
		rameter x.	
у	vector <float></float>	The sigmoid probability mapping pa-	[]
		rameter y.	
p_name	string	The name of the AC variable for the	р
		vector of probabilities of the DOA es-	
		timation.	
max_p_ind_name	string	The name of the AC variable for the in-	p_max
		dex of the maximum probability of the	
		DOA estimation	
vGCC_name	string	The name of the AC variable for the	vGCC_ac
		GCC matrix, which is computed by an-	
		other plugin	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

7.2 doasym_feature_extraction

Plugin for computing the generalized cross correlation with phase transform (GCC-PHAT)

7.2.0.1 Detailed description

This plugin computes the generalized cross correlation with phase transform (GCC-PHAT). The input to this plugin is a stereo time domain signal. The GCC-PHAT matrix is saved into the AC space.

7.2.0.2 Supported domains

The MHA plugin doasvm_feature_extraction supports these signal domains:

· waveform to waveform

7.2.0.3 Categories

directional

7.2.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
fftlen	int	The length of the FFT window	160
		Range: [0,[
max_lag	int	Maximum lag in samples between mi-	20
		crophones (setup-dependent)	
		Range: [0,[
nupsample	int	The amount the GCC-PHAT spectrum	4
		is oversampled	
		Range: [0,[
vGCC_name	string	The name of the AC variable for saving	vGCC_ac
		the GCC matrix in	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8 Plugin category 'example'

8.1 example1

8.1.0.1 Detailed description

The **simplest** example of an openMHA plugin.

This plugin scales one channel of the input signal, working in the time domain.

8.1.0.2 Supported domains

The MHA plugin example1 supports these signal domains:

· waveform to waveform

8.1.0.3 Categories

example

8.1.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8.2 example2

This plugin multiplies the sound signal in one audio channel by a factor

8.2.0.1 Supported domains

The MHA plugin example2 supports these signal domains:

· waveform to waveform

8.2.0.2 Categories

example

8.2.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
channel	int	Index of audio channel to scale. Indices start from 0. Range: [0,[0
factor	float	The scaling factor that is applied to the selected channel. Range: [0,[0.1

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8.3 example3

This plugin multiplies the sound signal in one audio channel by a factor

8.4 example4 31

8.3.0.1 Supported domains

The MHA plugin example3 supports these signal domains:

· waveform to waveform

8.3.0.2 Categories

example

8.3.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
channel	int	Index of audio channel to scale. Indices start from 0. Only channels with even indices may be scaled. Range: [0,[0
factor	float	The scaling factor that is applied to the selected channel. Range: [0,[0.1
prepared	int	State of this plugin: 0 = unprepared, 1 = prepared	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8.4 example4

This plugin multiplies the sound signal in one audio channel by a factor. It works in the spectral domain.

8.4.0.1 Supported domains

The MHA plugin <code>example4</code> supports these signal domains:

• spectrum to spectrum

8.4.0.2 Categories

example

8.4.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
channel	int	Index of audio channel to scale. Indices start from 0. Only channels with even indices may be scaled. Range: [0,[0
factor	float	The scaling factor that is applied to the selected channel. Range: [0,[0.1
prepared	int	State of this plugin: 0 = unprepared, 1 = prepared	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8.5 example5

example plugin configuration structure

8.6 example6 33

8.5.0.1 Supported domains

The MHA plugin example5 supports these signal domains:

• spectrum to spectrum

8.5.0.2 Categories

example

8.5.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
channel	int	channel number to be scaled	0
		Range: [0,[
factor	float	scale factor	1
		Range: [0,2]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

8.6 example6

example plugin configuration structure

8.6.0.1 Supported domains

The MHA plugin example6 supports these signal domains:

· waveform to waveform

8.6.0.2 Categories

example

8.6.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
channel	int	channel in which the RMS level is mea-	0
		sured	
		Range: [0,[

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

9 Plugin category 'feedback'

9.1 fshift_hilbert

Pitch shifter

9.1.0.1 Supported domains

The MHA plugin fshift_hilbert supports these signal domains:

· spectrum to spectrum

9.1.0.2 Categories

feedback

9.1.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
df	vector <float></float>	frequency to shift the bins / Hz	[40]
fmin	float	lower boundary for frequency shifter	4000
		Range: [0,]	
fmax	float	upper boundary for frequency shifter	16000
		Range: [0,]	
irslen	int	Bandpass: maximum length of cut off	1
		filter response	
		Range: [1,]	
phasemode	keyword_list	Bandpass: mode of gain smoothing	none
		Range: [none linear minimal]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

9.2 prediction_error

Prediction error model for adaptive feedback cancellation

9.2.0.1 Detailed description

This plugin computes the prediction error model to perform adaptive feedback cancellation. The prediction error method produces and estimate of the feedback path by minimizing the measured and the predicted output signals.

9.2.0.2 Supported domains

The MHA plugin prediction_error supports these signal domains:

· waveform to waveform

9.2.0.3 Categories

feedback

9.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
rho	float	convergence coefficient	0.01
		Range:]0,2]	
С	float	stabilization parameter	1e-05
		Range:]0,]	
ntaps	int	number of taps in filter	32
		Range:]0,]	
gains	vector <float></float>	Gain in dB	[0]
		Range: [-60,60]	_
name_e	string	Name of the AC variable for saving the	E
	-1.7	prediction error	_
name_f	string	Name of the AC variable for saving the	F
nome Inc	atrina	adapive filter Name of the AC variable for the LPC	Inc
name_lpc	string	coefficients	lpc
lpc_order	int	Length of the lpc filter	20
ipo_order	1110	Range:]0,1024]	20
pred_err_delay	vector <int></int>	Delay in the forward path	[96]
prod_on_doldy	700101 (1111)	Range:]0,[[00]
delay_w	vector <int></int>	Delay in the adaptive filtering path due	[130]
		to the microphone and loudspeaker	,
		transducers	
		Range: [0,[
delay_d	vector <int></int>	Delay in the adaptive filtering path for	[161]
		the LPC	
		Range: [0,[
n_no_update	int	Number of iterations without updating	0
		the filter coefficients	
		Range: [0,1024[

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

10 Plugin category 'filter'

10.1 combinechannels

Channel combiner

10.1.0.1 Detailed description

Several filter channels can be combined into one or more outputchannels by summing the input channels. This plugin is intended as a filter resynthesis of linear-phase filter banks.

The input signalis expected to have a non-interleaved channel order, i.e., first allbands of first output channel, then all bands of second channel, etc.

10.1.0.2 Supported domains

The MHA plugin combinechannels supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

10.1.0.3 Categories

filter

10.1.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
outchannels	int	Number of output channels	1
		Range: [1,]	
interleaved	bool	Input signal has interleaved channel	no
		order?	
channel_gain_name	string	Name of channel gain AC variable	
		(looked up during prepare, can be	
		empty)	
element_gain_name	string	Name of element wise gain AC variable	
		(looked up during waveform process,	
		can be empty)	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

10.2 fftfilterbank

FFT based filterbank with overlapping filters

10.2.0.1 Detailed description

This plugin implements a linear phase filterbank based on FFT spectrum. Each filter bank channel is stored into an own audio channel. The number of output channels of this plugin is the number of frequency bands times the number of input channels.

Please use the iFFT plugin *spec2wave* (p. 72) to get the waveform signal of the filterbank output. The *matrixmixer* (p. 85) plugin or *combinechannels* (p. 37) can be used for resynthesis.

10.2 fftfilterbank 39

The filters are calculated by applying filter weights to each FFT bin. These weights (filter shapes) depend on the settings of the use_edges variable. If center is selected, the frequency interval between the lower neighbour center frequency and the desired center frequency is mapped to the interval [-1,0] and between the desired center frequency and the upper neightbour to the interval [0,1]. These mappings are linear on the given frequency scale so that a value of 0.5 denotes the middle between two neighboured center frequencies on the given frequency scale. The filter weights are calculated with the configured crossing function on this interval, see next figure for details. Please note that the filters are not necessarily symmetric (symmetry is achieved only if the center frequencies are equally spaced on the desired frequency scale). The lowest and highest filter channels include the full range from zero to the center frequency or from the center frequency to the nyquist frequency, respectively.

If edge is selected, then the frequency axis is transformed to be linear on the desired frequency scale. The interval between two edge frequencies is mapped to [-0.5,0.5]. Now, the filter shape function (rectangular, linear/sawtooth, hanning) is applied to the frequency axis. This results in symmetric filters on the desired frequency scale.




Figure 2 Schematic plot of overlapping filters




Figure 3 Example filter shapes with center frequencies configured

10.2.0.2 Supported domains

The MHA plugin fftfilterbank supports these signal domains:

- · waveform to waveform
- spectrum to spectrum

10.2.0.3 Categories

filter




Figure 4 Example filter shapes with edge frequencies configured

10.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
unit	keyword_list	Frequency unit	Hz
		Range: [Hz kHz Oct Oct/3 Bark Erb	
		ERB_Glasberg1990]	
f	vector <float></float>	Frequencies	[]
f_hz	vector <float></float>	Frequencies in Hz	(monitor)
fscale	keyword_list	frequency scale of filter bank	linear
		Range: [linear bark log erb ERB_Glasberg1990]	
ovltype	keyword list	filter overlap type	rect
ovitype	keyword_list	Range: [rect linear hanning exp gauss]	rect
plateau	float	relative plateau width	0
pialeau	lioat	Range: [0,1[0
ftype	keyword list	frequency entry type	center
пуре	Reyword_list	Range: [center edge]	Certier
normalize	bool	normalize broadband output amplitude	no
fail on nonmonotonic	bool	Fail if frequency entries are non-	yes
	2001	monotonic (otherwise sort)	,00
fail_on_unique_bins	bool	Fail if center frequencies share the	yes
' _		same FFT bin.	*
cf	vector <float></float>	final center frequencies in Hz	(monitor)
ef	vector <float></float>	final edge frequencies in Hz	(monitor)
cLTASS	vector <float></float>	Bandwidth level correction for LTASS	(monitor)
		noise in dB	
shapes	matrix <float></float>	Frequency band shapes	(monitor)
fftlen	int	FFT length of filterbank (affects time	128
		domain only)	
		Range: [2,]	
phasemodel	keyword_list	Phase model (affects time domain	linear
		only)	
		Range: [minimal linear]	
irswnd	parser	IRS window function (affects time do-	(see below)
		main only)	
return_imag	bool	Return imaginary part? Re-	no
		sults are stored in AC variable	
		' <plugname>_imag'.</plugname>	

10.3 iirfilter 41

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser irswnd:

Name	Type	Description	Default
type	keyword_list	Window type.	hanning
		Range: [rect hanning hamming black-	
		man bartlett user]	
user	vector <float></float>	User provided window (used if window	[]
		type==user).	

10.3 iirfilter

IIR filter

10.3.0.1 Detailed description

The 'iirfilter' plugin implements a generic IIR filter (direct form II). The coefficients have the same names as in MATLAB. Due to different internal implementations and numeric resolutions, filters may be instable with coefficients which are stable in MATLAB.

10.3.0.2 Supported domains

The MHA plugin iirfilter supports these signal domains:

· waveform to waveform

10.3.0.3 Categories

filter

10.3.0.4 Configuration variables

Name	Туре	Description	Default
Α	vector <float></float>	recursive filter coefficients	[1]
В	vector <float></float>	non-recursive filter coefficients	[1]

10.4 nlms_wave

This plugin adaptively estimates the coefficients of a filter by means of the NLMS algorithm.

The estimated filter is stored into an AC variable named by the algorithm configuration name or by the configuration variable name_f and the input signal is filtered by the current filter and returned as the output signal of the plugin.

10.4.0.1 Detailed description

This plugin implements the NLMS algorithm for re-estimating the coefficients of an adaptive filter in each iteration. The estimated filter coefficients are saved in an AC variable having the same name as the plugin in the current configuration. The name of this AC variable can also be set differently by setting the configuration variable **name_f**. The input signal is filtered by the filter estimated in the current iteration and returned as the current output of the plugin from within the processing callback. The estimation of the filter coefficients is performed using the update rule given as in the following:

$$e[k] = y[k-1] - f[k-1]u[k-1]$$
(7)

$$f[k] = f[k-1] + rho/(|u|^2 + c)u[k-1]e[k],$$
(8)

where e is the error signal, y is the desired signal and u is the input signal. All three signals are read from the AC space. For this, the configuration variables $\mathbf{name_e}$, $\mathbf{name_d}$ and $\mathbf{name_u}$ should be set. The error signal can also be computed within the plugin given the other two signals, when the corresponding configuration variable is left empty. The plugin can be configured to use also the current sample u[k] of the input signal in the estimation by asigning the configuration variable $\mathbf{estimtype}$ to the value $\mathbf{current}$. However in the default case ($\mathbf{previous}$), the previous values as long as the filter (\mathbf{ntaps}) but the current one are used.

10.4.0.2 Supported domains

The MHA plugin nlms_wave supports these signal domains:

· waveform to waveform

10.4.0.3 Categories

filter

10.4.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
rho	float	convergence coefficient	0.01
		Range:]0,2]	
С	float	stabilization parameter	1e-05
		Range:]0,]	
ntaps	int	number of taps in filter	32
		Range:]0,]	
name_u	string	Name of input signal U	
name_d	string	Name of desired signal D	
normtype	keyword_list	Normalization type	default
		Range: [none default sum]	
estimtype	keyword_list	Estimation type defined whether the current value of the input signal u[k] will	previous
		be incorporated in the estimation of the	
		filter coefficients or not. Default value	
		(previous) does not.	
		Range: [previous current]	
lambda_smoothing_power	float	Recursive smoothing constant for sum	0.9
		normalization	
		Range: [0,1[
name_e	string	Name of error signal E	
name_f	string	Name of the AC variable for saving the	
		adapive filter	
n_no_update	int	Number of iterations without updating the filter coefficients	0

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

11 Plugin category 'generator'

11.1 noise

white noise generator

Waveform and spectral domain are supported. Please note that only in the waveform domain, real continuous white noise is created. In the spectral domain, some modulation and spectral shaping might occur.

11.1.0.1 Supported domains

The MHA plugin noise supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

11.1.0.2 Categories

generator

11.1.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
lev	float	noise RMS level in dB SPL	0
mode	keyword_list	operation mode	add
		Range: [add replace]	
frozennoise_length	float	Length of frozen noise in s, or 0 for run-	0
		ning noise.	
		Range: [0,]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

11.2 plingploing

plingploing algorithm.

11.2.0.1 Detailed description

This plugin creates music (jazz-inspired chord sequence).

11.2.0.2 Supported domains

The MHA plugin plingploing supports these signal domains:

· waveform to waveform

11.2.0.3 Categories

generator

11.2.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
level	float	Output level in dB SPL	70
pitch	float	Bass pitch in Hz	415
		Range: [1,]	
fun1_key	float	minimum interval of second tone rela-	3
		tive to bass, in semitones	
fun1_range	float	randomized interval of second tone,	2
		added to fun1_key, in semitones	
		Range: [0,]	
fun2_key	float	minimum interval of third tone relative	5
		to bass, in semitones	
fun2_range	float	randomized interval of third tone,	2
		added to fun2_key, in semitones	
		Range: [0,]	
bpm	float	beats per minute	200
		Range: [1,]	
minlen	float	minimum note length / beats	1
		Range: [1,]	
maxlen	float	maximum note length / beats	5
		Range: [1,]	
bassmod	float	bass key modulation depth	5
bassperiod	float	bass key modulation period	28

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

11.3 sine

Sine wave generator.

11.3.0.1 Supported domains

The MHA plugin sine supports these signal domains:

· waveform to waveform

11.3.0.2 Categories

generator

11.3.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
lev	float	sine RMS level in dB SPL FF	0
f	float	Frequency in Hz	0
		Range: [0,[
mode	keyword_list	Replace input signal with tone or mix	replace
		tone into input signal	
		Range: [replace mix]	
channels	vector <int></int>	List of audio channels to feed with tone	[]
		(all other audio channels are not af-	
		fected)	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

12 Plugin category 'level'

12.1 dc

dynamic compression

12.1.0.1 Detailed description




Figure 5 Input-output function of one channel in the dc dynamic compression algorithm.

The plugin *dc* is a multiband dynamic range compression plugin. One compression function (input-output function) is applied to each audio channel. Frequency-dependent compression can be achieved by using the *fftfilterbank* plugin in conjunction with this plugin. The input-level dependent gain function is determined by a gain table containing the gain values applied in different channels and frequency bands. Between the points of the gain table linear interpolation is used. For gains outside of the range of the gaintable a linear extrapolation based on the two nearest points is used. If spectral processing is used, the input level (abscissa of the input-output function, cf. Fig. 5) is determined by an attack- and release-filter of the short time

RMS level L_{st} , given in dB (SPL). The attack filter L_a is a first order low pass filter. The release filter L_{in} is a maximum tracker, i.e.

$$L_{a} = \langle 20 \log_{10}(L_{st}) \rangle_{\tau_{attack}}$$
 (9)

$$L_{in} = \max(L_{a}, \langle L_{a} \rangle_{\tau_{release}})$$
 (10)

$$L_{in} = \max(L_a, \langle L_a \rangle_{\tau}, \qquad) \tag{10}$$

The gain table is given as a matrix with $n_f \cdot n_{ch}$ rows, where n_f is the number of frequency bands and n_{ch} is the number of channels. The order of row indices is $0...n_f...n_f \cdot n_{ch}$. The x-values for the n-th column of the gain table are given as $x_n = gtmin + gtstep \cdot n$. See also Fig. 5. A configuration fragment reproducing Fig. 5 could be:

```
algos = [fftfilterbank dc combinechannels]
fftfilterbank.ftype = center
fftfilterbank.f = [200 2000]
fftfilterbank.ovltype = rect
fftfilterbank.fscale = bark
dc.gtmin=[20 20]
dc.qtstep=[40 40]
dc.gtdata = [[40 30 -10]; [40 30 -10];]
dc.tau_attack = [0.005 0.005]
dc.tau_rmslev = [0.005 0.005]
dc.tau_decay = [0.015 0.015]
dc.combinechannels.name = fftfilterbank_channels
```

In this configuration it is assumed that one audio channel is configured. All variables of dc have two entries, one for each frequency band.

12.1.0.2 Supported domains

The MHA plugin dc supports these signal domains:

- waveform to waveform
- · spectrum to spectrum

12.1.0.3 Categories

level compression

12.1 dc 49

12.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
powersum	bool	Input level is summed accross chan-	no
		nels	
gtdata	matrix <float></float>	gaintable data in dB gains	[[]]
gtmin	vector <float></float>	input level for first gain entry in dB SPL	[]
gtstep	vector <float></float>	level step size in dB	[]
tau_rmslev	vector <float></float>	RMS level averaging time constant in s	[]
tau_attack	vector <float></float>	attack time constant in s	[]
tau_decay	vector <float></float>	decay time constant in s	[]
fb	string	Name of fftfilterbank plugin. Used to	fftfilterbank
		extract frequency information.	
chname	string	name of audio channel number vari-	
		able (empty: broadband)	
bypass	bool	bypass dynamic compression	no
clientid	string	Client ID of last fit	
gainrule	string	Gain rule of last fit	
preset	string	Preset name of last fit	
modified	int	Flag if configuration has been modified	(monitor)
max_level_difference	matrix <float></float>	maximum level difference in dB be-	[[]]
		tween adjacent bands	
		Range: [0,[
level_in	vector <float></float>	input level of last block / dB SPL	(monitor)
level_in_filtered	vector <float></float>	input level after time-constant filters / dB SPL	(monitor)
cf	vector <float></float>	nominal center frequencies of filter-	(monitor)
		bank bands	,
ef	vector <float></float>	edge frequencies of filterbank bands	(monitor)
band_weights	vector <float></float>	Weights of the individual frequency	(monitor)
		bands. Computed as (sum of squared	
		fft-bin-weigths) / num_frames.	
use_wbinhib	bool	Use wideband inhibition?	no
wbinhib	parser		(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser wbinhib:

Name	Type	Description	Default
weights	vector <float></float>	weighting of neighbour frequencies	[1 2 4 4 4 2 1]
dl_map_min	float	mapping of level/broadband level ratio (in dB) into inhibition ratio, lower value means full inhibition	-8
dl_map_max	float	mapping of level/broadband level ratio (in dB) into inhibition ratio, upper value means no inhibition	2
I_min	float	level threshold, inhibition starts above this level	40
g_scale	matrix <float></float>	scaling factor of inhibition gain	[[1]]

12.2 dc simple

Simple dynamic compression scheme

12.2.0.1 **Detailed description**

The plugin dc simple is a multiband dynamic compression. One compression function (inputoutput function) is applied to each audio channel; multiple frequency bands can be used via the fftfilterbank plugin. The level dependent gain function is determined by the gains at 50 and 80 dB (G50 and G80). To reduce noise, an expansion is applied below a noise gate level. See also Fig. 6.

If spectral processing is used, the input level (x-axis of the input-output function) is determined by an attack- and release-filter of the short time RMS level L_{st} given in dB (SPL)The attack filter is a first order low pass filter. The release filter is a maximum tracker, i.e.

$$L_a = \langle 20 \log_{10}(L_{st}) \rangle_{\pi} \tag{11}$$

$$L_a = \langle 20 \log_{10}(L_{st}) \rangle_{\tau_{attack}}$$

$$L_{in} = \max(L_a, \langle L_a \rangle_{\tau_{release}})$$
(11)

The input level is divided into three sections. In each section the input level L_{in} is transformed linearly into a gain G on a log-log scale: $G_{dB} = (m-1)L_{in} + n$, where m is the slope of the input-output function, and n is an offset. Between expansion threshold and limiter threshold, mand n are given by the gain at 50 and 80 dB. In the section below the expansion threshold, mis the expansion slope, and above the limiter threshold, m is zero. n is chosen to result in a continuous input-output function.

All variables are vectors with one entry for each input channel (number of audio channels times number of frequency bands).

An example configuration of a chain with dynamic compression could be:

```
algos = [fftfilterbank dc_simple combinechannels]
fftfilterbank.ftype = center
fftfilterbank.f = [250 1000 4000]
fftfilterbank.ovltype = rect
fftfilterbank.fscale = bark
```




Figure 6 Input-output function of one channel in the *dc_simple* dynamic compression algorithm.

```
dc_simple.g50 = [10 25 40 11 31 55]
dc_simple.g80 = [5 15 10 5 21 19]
dc_simple.expansion_threshold = [20 20 20 20 20 20 20]
dc_simple.expansion_slope = [4 4 4 4 4 4]
dc_simple.limiter_threshold = [120 120 120 120 120 120]
dc_simple.tau_attack = [0.005 0.005 0.005 0.005 0.005 0.005]
dc_simple.tau_decay = [0.015 0.015 0.015 0.015 0.015 0.015]
combinechannels.name = fftfilterbank_channels
```

In this configuration it is assumed that two audio channels are configured, i.e. all variables of *dc_simple* have three entries for the first audio channel and three for the second audio channel.

12.2.0.2 Supported domains

The MHA plugin dc_simple supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

12.2.0.3 Categories

level compression

12.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
g50	vector <float></float>	Gain in dB at 50 dB input level	[0]
		Range: [-80,80]	
g80	vector <float></float>	Gain in dB at 80 dB input level	[0]
		Range: [-80,80]	
maxgain	vector <float></float>	Maximal amplification in dB	[80]
expansion_threshold	vector <float></float>	expansion threshold in dB	[0]
expansion_slope	vector <float></float>	expansion slope of input-output func-	[1]
		tion in dB/dB	
		Range:]0,10]	
limiter_threshold	vector <float></float>	limiter threshold in dB	[100]
tau_attack	vector <float></float>	attack time constant in s	[0.005]
		Range: [0,]	
tau_decay	vector <float></float>	decay time constant in s	[0.05]
		Range: [0,]	
bypass	bool	bypass dynamic compression	no
clientid	string	Client ID of last fit	
gainrule	string	Gain rule of last fit	
preset	string	Preset name of last fit	
modified	int	Flag if configuration has been modified	(monitor)
level	vector <float></float>	Input level in dB	(monitor)
gain	vector <float></float>	Applied gain in dB	(monitor)
filterbank	string	Name of fftfilterbank plugin. Used to	
		extract frequency information.	
cf	vector <float></float>	center frequencies of the frequency	(monitor)
		bands [Hz]	
ef	vector <float></float>	edge frequencies of the frequency	(monitor)
		bands [Hz]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

12.3 fftfbpow 53

12.3 fftfbpow

FFT based filterbank analysis with overlapping filters

12.3.0.1 Detailed description

This plugin implements a filterbank based on FFT spectrum. The power in each filter bank channel is calculated and stored into an AC variable. The input signal is passed through unmodified.

For details on the filter shapes, please see description of plugin fftfilterbank (section 10.2 on page 38).

12.3.0.2 Supported domains

The MHA plugin fftfbpow supports these signal domains:

· spectrum to spectrum

12.3.0.3 Categories

level

12.3.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
unit	keyword_list	Frequency unit Range: [Hz kHz Oct Oct/3 Bark Erb ERB_Glasberg1990]	Hz
f	vector <float></float>	Frequencies	[]
f_hz	vector <float></float>	Frequencies in Hz	(monitor)
fscale	keyword_list	frequency scale of filter bank Range: [linear bark log erb ERB_Glasberg1990]	linear
ovltype	keyword_list	filter overlap type Range: [rect linear hanning exp gauss]	rect
plateau	float	relative plateau width Range: [0,1[0
ftype	keyword_list	frequency entry type Range: [center edge]	center
normalize	bool	normalize broadband output amplitude	no
fail_on_nonmonotonic	bool	Fail if frequency entries are non- monotonic (otherwise sort)	yes
fail_on_unique_bins	bool	Fail if center frequencies share the same FFT bin.	yes
cf	vector <float></float>	final center frequencies in Hz	(monitor)
ef	vector <float></float>	final edge frequencies in Hz	(monitor)
cLTASS	vector <float></float>	Bandwidth level correction for LTASS noise in dB	(monitor)
shapes	matrix <float></float>	Frequency band shapes	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

12.4 multibandcompressor

Multiband compressor framework based on level in overlapping filter bands.

12.4.0.1 Detailed description

multibandcompressor provides a complete framework for dynamic range compression in multiple frequency bands.

It contains the same filterbank as the fftfilterbank plugin (see there for documentation of the filterbank) and combines the frequency bands again after the compression.

For the actual dynamic range compression, multibandcompressor can load any other plugin using the field plugin_name. Common choices for this plugin would be dc_simple or dc.

Note that the dynamic range compression receives a pseudo time signal where the sampling rate is the rate of the block processing, i.e. in each channel and band, there is exactly 1 signal sample for every block. These samples are a sparse, non-negative representation of the actual signal in the respective frequency band: The magnitude of each sample is chosen by multibandcompressor so that the level computed from this sparse signal is the same as the level computed from the full signal for this frequency band.

The dynamic range compression will then apply gain (or attenuation) to the sparse signal in each frequency band. The gain applied to the sparse signal is measured by multibandcompressor and eventually applied to the respective full signal.

Before the compressor gain is applied to the full signal, it may be modified by the after-burner built into the multibandcompressor plugin (sub-parser 'burn'): The purpose of the after-burner is to enforce a configurable Maximum Power Output (MPO) for each frequency band, and to compensate for drains and confluxes of sound energy through vents and open fittings. Note that compensating for drains in this way can easily lead to feedback howling and should be done with caution. The after-burner can be disabled by setting burn.bypass=yes.

12.4.0.2 Supported domains

The MHA plugin ${\tt multibandcompressor}$ supports these signal domains:

• spectrum to spectrum

12.4.0.3 Categories

level compressor

12.4.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
unit	keyword_list	Frequency unit	Hz
		Range: [Hz kHz Oct Oct/3 Bark Erb	
		ERB_Glasberg1990]	
f	vector <float></float>	Frequencies	[]
f_hz	vector <float></float>	Frequencies in Hz	(monitor)
fscale	keyword_list	frequency scale of filter bank	linear
		Range: [linear bark log erb ERB_Glasberg1990]	
ovltype	keyword_list	filter overlap type	rect
		Range: [rect linear hanning exp gauss]	
plateau	float	relative plateau width	0
		Range: [0,1[
ftype	keyword_list	frequency entry type	center
		Range: [center edge]	
normalize	bool	normalize broadband output amplitude	no
fail_on_nonmonotonic	bool	Fail if frequency entries are non-	yes
		monotonic (otherwise sort)	
fail_on_unique_bins	bool	Fail if center frequencies share the	yes
		same FFT bin.	
cf	vector <float></float>	final center frequencies in Hz	(monitor)
ef	vector <float></float>	final edge frequencies in Hz	(monitor)
cLTASS	vector <float></float>	Bandwidth level correction for LTASS noise in dB	(monitor)
shapes	matrix <float></float>	Frequency band shapes	(monitor)
plugin_name	string	Plugin name	
burn	parser		(see below)

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser burn:

Name	Туре	Description	Default
f	vector <float></float>	Sample frequencies of data / Hz.	[1000]
		Range: [0,]	
drain	vector <float></float>	Drain caused by vent / dB.	[0]
conflux	vector <float></float>	Conflux caused by vent / dB.	[-120]
maxgain	vector <float></float>	Maximum allowed gain / dB.	[80]
mpo	vector <float></float>	Maximum allowed output level / dB	[120]
		SPL (see notes in plugin doc).	
taugain	float	Time constant of afterburn gain modi-	0.2
		fier lowpass / s.	
		Range: [0,]	
commit	keyword_list	Commit changes of configuration vari-	commit
		ables.	
		Range: [commit]	
bypass	bool	Bypass afterburn stage.	no

12.5 rmslevel

This algorithm displays block based RMS level informations. Results are stored in these AC variables (replace 'rmslevel' by the configured plugin name):

rmslevel_level_db rmslevel_peak_db rmslevel_level rmslevel_peak

12.5.0.1 Supported domains

The MHA plugin rmslevel supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

12.5.0.2 Categories

level

12.6 softclip 57

12.5.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

12.6 softclip

The softclipper implements a broad band dynamic compression above a given level.

12.6.0.1 Supported domains

The MHA plugin softclip supports these signal domains:

· waveform to waveform

12.6.0.2 Categories

level

12.6.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
tau_decay	float	time constant of decay filter	0.05
		Range: [0,[
tau_attack	float	time constant of attack filter	0.002
		Range: [0,[
start	float	entry point of time domain soft clipping	110
		(dB)	
slope	float	slope of input-output table above start	0.125
		(dB/dB)	
		Range: [0,]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

12.7 transducers

Signal level calibration plugin.

12.7.0.1 Detailed description

Some plugins in the MHA expect the input signal to be calibrated to sound pressure level in Pascal. This plugin converts AD and DA converter levels to SPL in Pa and also allows for a FIR filters for mircophone and receiver equalization.

12.7 transducers 59

A schematic calibration rule for the MHA

- 1. Measure frequency response of hearing aid microphones and receiver.
- 2. Create FIR filter coefficients for frequency response equalization for microphones and receiver, configure the FIR coefficients of this plugin correspondingly.
- 3. Play an acoustic reference signal of a known SPL level to the microphone, adjust the 'calib_in.peaklevel' variable until the internal level meter (e.g. rmslevel, p. 56) shows the same level.
- 4. Create a test tone in the MHA (e.g. with 'noise', p. 44, or 'sine', p. 46) of a given level, and adjust the variable 'calib_out.peaklevel' until the same acoustic level is measured at the receiver.

Besides the signal calibration, this plugin also contains a soft-limiter in the output path, and a quantization module. The soft-limiter acts as a fast broadband compressor, and can be configured correspondingly. The quantisation module limits the signal to the interval [-1,1] and optionally reduces the resolution, by this quantization rule:

$$y = floor(2^{(N-1)}x)2^{-(N-1)}$$
(13)

N is the number of bits, x the input signal and y the output signal.

12.7.0.2 Supported domains

The MHA plugin transducers supports these signal domains:

· waveform to waveform

12.7.0.3 Categories

level

12.7.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugin_name	string	Plugin name	
calib_in	parser	calibration module	(see below)
calib_out	parser	calibration module	(see below)

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser calib_in:

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
nbits	int	Number of bits to simulate, or zero for	0
		limiting only	
		Range: [0,32]	
fir	matrix <float></float>	FIR filter coefficients, one row for each	[[]]
		channel	
peaklevel	vector <float></float>	Reference peak level in dB (0 dB FS	[]
		corresponds to this SPL level)	
speechnoise	parser		(see below)
tau_level	float	Time constant in seconds for RMS	0.125
		level meter	
		Range:]0,10]	
rmslevel	vector <float></float>	RMS level in dB at input (after calibra-	(monitor)
		tion or addition of noise)	
config	parser		(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser speechnoise:

Name	Туре	Description	Default
mode	keyword_list	Playback mode and level of speech	off
		shaped noise	
		Range: [off on olnoise	
		LTASS_combined LTASS_female	
		LTASS_male white pink brown	
		TEN_SPL TEN_SPL_250_8k	
		TEN_SPL_50_16k sin125 sin250	
		sin500 sin1k sin2k sin4k sin8k]	
level	float	Test signal level in dB SPL	80
		Range: [0,120]	
channels	vector <int></int>	Channels where to playb speech noise	[]
		signal	
		Range: [0,]	

Variables of sub-parser config:

Name	Type	Description	Default
srate	float	Actual sampling rate / Hz	(monitor)
fragsize	int	Actual fragment size / samples	(monitor)
channels	int	Actual number of channels	(monitor)

Variables of sub-parser calib_out:

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
speechnoise	parser		(see below)
peaklevel	vector <float></float>	Reference peak level in dB (0 dB FS corresponds to this SPL level)	
fir	matrix <float></float>	FIR filter coefficients, one row for each channel	[[]]
softclip	parser	'Hardware' softclipper	(see below)
nbits	int	Number of bits to simulate, or zero for	0
		limiting only	
		Range: [0,32]	
do_clipping	bool	Will the soft/ hard clipping be executed	no
tau_level	float	Time constant in seconds for RMS	0.125
		level meter	
		Range:]0,10]	
rmslevel	vector <float></float>	RMS level in dB at output (before cali-	(monitor)
		bration or addition of noise)	
config	parser		(see below)

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser speechnoise:

Name	Туре	Description	Default
mode	keyword_list	Playback mode and level of speech shaped noise	off
		Range: [off on olnoise LTASS_combined LTASS_female LTASS_male white pink brown TEN_SPL TEN_SPL_250_8k TEN_SPL_50_16k sin125 sin250 sin500 sin1k sin2k sin4k sin4k]	
level	float	Test signal level in dB SPL Range: [0,120]	80
channels	vector <int></int>	Channels where to playb speech noise signal Range: [0,]	

$\label{thm:parser_softclip:parser} \begin{picture}(100,00) \put(0,0){\line(0,0){100}} \put(0,0){\l$

Name	Type	Description	Default
tau_attack	float	attack filter time constant / s	0.002
		Range: [0,]	
tau_decay	float	decay filter time constant / s	0.005
		Range: [0,]	
threshold	float	start point on linear scale (hard clipping	0.6
		at 1.0)	
		Range: [0,]	
hardlimit	float	hard limit	1
		Range:]0,]	
slope	float	compression factor	0.5
		Range: [0,1]	
linear	bool	input/output function is linear on linear	no
		(yes) or logarithmic (no) scale	
tau_clip	float	clipping meter time constant / s	1
		Range: [0,]	
clipped	float	clipped ratio	(monitor)
max_clipped	float	maximum allowed clipped ratio	1
		Range: [0,1]	

Variables of sub-parser config:

Name	Type	Description	Default
srate	float	Actual sampling rate / Hz	(monitor)
fragsize	int	Actual fragment size / samples	(monitor)
channels	int	Actual number of channels	(monitor)

13 Plugin category 'noise'
13.1 timoSmooth
Cepstral smoothing single-channel noise reduction
13.1.0.1 Detailed description
Implements the single-channel noise reduction scheme found in Breithaupt, Gerkmann, and Martin, A Novel A Priori SNR Estimation Approach Based on Selective Cepstro-temporal Smoothing.
13.1.0.2 Supported domains
The MHA plugin timoSmooth supports these signal domains:
spectrum to spectrum
13.1.0.3 Categories
noise reduction

13.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
xi_min_db	float	Minimum a priori SNR for a bin in dB(power) Range: [-50,50]	-27
f0_low	float	Lower limit for F0 detection in Hz Range: [0,400]	70
f0_high	float	Upper limit for F0 detection in Hz Range: [0,400]	300
delta_pitch	float	Quefrency half-width of pitch-set in samps Range: [0,20]	2
lambda_thresh	float	Pitch detection threshold for smooth cepstrum in magnitude Range: [0,3]	0.2
alpha_pitch	float	Alpha value to set for pitch range Range: [0,4]	0.15
beta_const	float	AR coeff for smoothing of alphas(smoothing-factors)	0.96
kappa_const	float	Exponential bias correction constant for a priori SNR estimate Range: [0,1]	0.2886
gain_min_db	float	Minimum gain in dB for a frequency bin Range: [-30,0]	-17
win_f0	vector <float></float>	Window coefficients for cepstral smoothing window Range: [0,1]	[0.0207 0.0656 0.1664 0.2473 0.24
alpha_const_vals	vector <float></float>	Piecewise values for steady-state alphas Range: [0,2]	[0.2 0.4 0.92]
alpha_const_limits_hz	vector <float></float>	Limits for steady-state alphas given in Hz Range: [0,10000]	[93.75 625]
noisePow_name	string	Name of est. noise spectrum in AC space	noisePowProposedScale
spp	parser	Subparser for exporting SPP	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser spp:

Name	Type	Description	Default
prior_q	float	priorQ for computing GLR and SPP from local SNR	0.5
		Range: [0,2]	
xi_opt_db	float	xiOpt in dB for computing GLR and SPP from local SNR Range: [0,40]	15

14 Plugin category 'overlapadd'

14.1 overlapadd

Waveform to spectrum overlap add and FFT method. Audio data is collected up to wndlen, than windowed with the given window function, zero padded up to fftlength (symmetric zero padding or asymmetric zero padding possible), and Fast-Fourier-transformed. All parameter changes take effect after the next prepare call.

14.1.0.1 Detailed description

This plugin transforms fragmented waveform data into short time Fourier transformed audio (STFT), and after processing by spectral processing plugins back to the time domain. This overlap-add mechanism is similar to that from Allen (1977): First, the waveform signal is windowed with a window function, e.g., a Hanning window. In each processing frame, the window is shifted by the fragment size of the input waveform. Missing parts of the signal are taken from the past. The windowed signal is padded with zeros on both sides up to the FFT length, to avoid aliasing when filters are applied in the frequency domain. The impulse response of the applied filter can have the length of the zero padding; if the impulse response is longer, later parts of the impulse response will be mapped to the beginning of the fragment (temporal aliasing). Linear phase filters (real gains in the frequency domain) produce symmetric impulse responses and therefore require symmetric zero padding. The zero padded signal is now fast Fourier transformed. Parameters are FFT length N, window length M and the fragment size P. Typical values for the window length are M = 2P or M = 4P. The Hanning window used in the first step is $w_1(k) = \frac{1}{2}(1 - \cos(2\pi k/M))$, the windowed signal is

$$x_w(m,k) = w_1(k) \cdot x(m \cdot P + k), \tag{14}$$

with k = 0, ..., M - 1 and the fragment index m.

After processing and inverse Fourier transformation, Hanning ramps are applied to the signal to avoid discontinuities in case of temporal aliasing, and thus reducing the artifacts. The length

of the Hanning ramps are a fraction p of half the zero-padding length (N-M)/2. If p=1, the entire zero-padded parts are smoothed with Hanning ramps. p=0 means, that no Hanning ramps are applied to the signal. This allows an exact reproduction in those cases, where the local impulse response of the filter (represented by all algorithms between FFT and inverse FFT) is shorter than the zero padding length. The windowing in both stages of the overlap-add mechanism is plotted in Fig. 7 for M=2P (50% overlap).

The total delay between input and output of a real-time system with fragment size P and an overlap-add based linear-phase filter, is the window length plus half the zero-padding length, or M+(N-M)/2, plus an additional delay needed for the signal processing, and plus a delay generated by the AD/DA converters (e.g., anti-aliasing filter delay). In an offline system, the complete input signal is available in advance, and thus the delay of the overlap-add method is determined only by the relative shift between output and input signal, which is (M+N)/2-P (equal to N/2 in case of 50% overlap, i.e. M=2P). Contrary to a real-time system, the delay of an offline system depends on the amount of overlap.




Figure 7 Windowing in the overlap-add method with 50% overlap and zero-padding. In the upper panel, the windowed input signal before applying the FFT is schematically plotted. In the lower panel, the same time interval after inverse FFT is shown. The shaded segment is the fragment which is read from the input stream (upper panel) and written to the output stream (lower panel) in one processing cycle. The delay between input and output signal is the length of leading zeros plus the window length.




Figure 8 Windowing in the overlap-add method, as in Fig. 7, but with post-windowing and without zero-padding. In this setup, W^{α} is applied before FFT and $W^{1-\alpha}$ is used for post-windowing. The delay between input and output signal is the window length.

14.1.0.2 Supported domains

The MHA plugin overlapadd supports these signal domains:

· waveform to waveform

14.1.0.3 Categories

overlapadd

14.1.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugin_name	string	Plugin name	
fftlen	int	FFT length	512
		Range: [1,]	
wnd	parser	window type	(see below)
zerownd	parser	zero padding post window type	(see below)
prescale	float	scaling factor (pre-scaling)	(monitor)
postscale	float	scaling factor (post-scaling)	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser wnd:

Name	Туре	Description	Default
type	keyword_list	Window type.	hanning
		Range: [rect hanning hamming black-	
		man bartlett user]	
user	vector <float></float>	User provided window (used if window	[]
		type==user).	
len	int	window length/samples	400
		Range: [1,]	
pos	float	window position (0 = beginning, 0.5 =	0.5
		symmetric zero padding, 1 = end)	
		Range: [0,1]	
exp	float	window exponent to be applied to all	1
		elements of window function	

Variables of sub-parser zerownd:

Name	Type	Description	Default
type	keyword_list	Window type.	rect
		Range: [rect hanning hamming black-man bartlett user]	
user	vector <float></float>	User provided window (used if window	[]
		type==user).	

14.2 shadowfilter_begin

Save signal spectrum to AC variable

14.2.0.1 Detailed description

The plugins 'shadowfilter_begin' and 'shadowfilter_end' (section 14.3) are designed to measure the gains produced by any spectral plugins and apply those gains to audio channels not passed to the algorithm. This method can be used to process a mixed signal, but apply the same gains to the unmixed signal parts seperately. For a stereo mixed signal, this can be done by reading the mixed signal from channels 1 and 2, the desired signal from channels 3 and 4, and the competing signal from channels 5 and 6. The 'shadowfilter_begin' plugin hides channels 3 to 6 from the plugin, and remembers the input spectrae for all channels. The 'shadowfilter_end' plugin compares the processed output signal (channels 1 and 2) with its input spectrum and derives complex gains produced by the algorithm (without any knowledge of the algorithm). The same gains are applied to channels 3 to 6.

14.2.0.2 Supported domains

The MHA plugin shadowfilter_begin supports these signal domains:

spectrum to spectrum

14.2.0.3 Categories

overlapadd

14.2.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
nch	int	number of processing channels	1
		Range: [1,[
ntracks	int	number of input sources, each with nch	1
		audio channels	
		Range: [1,[

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

14.3 shadowfilter_end

Compute spectral gains seen since shadowfilter_begin, apply gains to other tracks

14.3.0.1 Detailed description

See section 14.2 for a description of the shadow filter method. The 'shadowfilter_end' plugin creates an AC variable shadowfilter_gains, which contains the complex gains created by the algorithm.

14.3.0.2 Supported domains

The MHA plugin shadowfilter_end supports these signal domains:

spectrum to spectrum

14.3.0.3 Categories

overlapadd

14.3.0.4 Configuration variables

Name	Type	Description			Default
mhaconfig_in	parser	Input configuration			(see below)
mhaconfig_out	parser	Output configuration	า		(see below)
basename	string	configuration nam ter_begin	ie o	shadowfil-	shadowfilter_begin

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

14.4 smoothgains_bridge

Gain smoothing for reduction of filter length

14.4.0.1 Detailed description

The overlap-add framework allows filter lengths of the zero padding length. Longer filters will result in artifacts caused by circular aliasing. Artifacts can be reduced by either applying Hanning ramps to the zero-padded blocks after filtering, or by shortening the impulse response of the filter, and thus implicitely reducing the frequency resolution. This plugin reduces the filter length to match exactly the zero-padding length. It can either keep the phase (mode=linear_phase), and reduce causal and a-causal parts of the impulse response, or apply a minimum phase filter phase, and cut the causal part of the filter. The window position in the overlap-add framework has to be configured appropriately: For linear phase mode, a symmetric window position is required, i.e., wnd.pos=0.5. To allow minimal phase filters, an asymmetric window position (wnd.pos=0) is needed. Using minimal phase filters will destroy the phase, but reduces the algorithmic delay.

14.4.0.2 Supported domains

The MHA plugin smoothgains_bridge supports these signal domains:

• spectrum to spectrum

14.4.0.3 Categories

overlapadd filter

14.4.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugin_name	string	Plugin name	
mode	keyword_list	Gain smoothing mode	linear_phase
		Note: Appropriate settings of window	
		position are required (linear_phase:	
		0.5, minimal_phase: 0)	
		Range: [off linear_phase mini-	
		mal_phase]	
irswnd	parser	Impulse response window function	(see below)
epsilon	float	Epsilon for safe division by zero (avoid	1e-18
		inf)	
		Range: [1.1e-19,]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser irswnd:

Name	Туре	Description	Default
type	keyword_list	Window type.	hanning
		Range: [rect hanning hamming black-man bartlett user]	
user	vector <float></float>	User provided window (used if window	[]
		type==user).	

14.5 spec2wave

spectrum to waveform iFFT plugin Performs inverse FFT, postwindowing, hanning ramps at zero-padding, overlap-add, normalization. Note that normalization only works for mod(wndlen,fragsize)=0. Also note that postwindowing only works for wndpos=0.5. Alway set ramplen=0 here if wndpos!=0 in the corresponding wave2spec.

14.5.0.1 Detailed description

This plugin calculates the inverse FFT and overlap add resynthesis. The parameters are taken from the framework overlap add parameters. After the inverse Fourier transform, hanning window ramps are applied to the previously zero-padded regions.

14.5.0.2 Supported domains

The MHA plugin spec2wave supports these signal domains:

· spectrum to waveform

14.5.0.3 Categories

overlapadd

14.5.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
ramplen	float	Relative length of post windowing han-	1
		ning ramps (for centered analysis win-	
		dow)	
		Range: [0,1]	
wndtype	keyword_list	window type	rect
		Range: [rect bartlett hanning hamming	
		blackman user]	
wndexp	float	window exponent to be applied to all	1
		elements of window function	
userwnd	vector <float></float>	user provided window	[]

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

14.6 wave2spec

Waveform to spectrum overlap add and FFT method.

Audio data is collected up to wndlen, then windowed with the given window function, zero padded up to fftlen (symmetric zero padding or asymmetric zero padding possible), and fast-Fourier-transformed (FFT).

14.6.0.1 Detailed description

This plugin performs the domain transformation from time-domain waveform signal to short-time Fourier transform (STFT) signal in the spectral domain. This plugin can be used as the analysis part of a complete overlap-add procedure. Audio signal data is collected up to the length of the analysis window. The hop-size is equal to the audio block size that this plugin receives. Window size and FFT length are configurable through the configuration variables of this plugin.

The shape of the analysis window is also configurable: Several pre-defined window shapes can be selected, and also a completely user-defined window shape. In addition, a configurable exponent can be applied to all samples of the window before it is used.

During processing, the input data samples are multiplied with the samples of the analysis window, zero padded to the FFT length and Fourier transformed. Please note that usually the window shift is less than the window length. For this reason, the short time fourier transform does not exactly correspond to the current input waveform block: the analysis window contains samples from the current as well as from previous invocation(s). The absolute window shift is identical to the fragment size, e.g. to achieve a window shift of 50%, configure a fragment size of wndlen/2.

A copy of the output spectrum is stored in the AC space in a variable of same name as the configured plugin name. To access the spectrum in AC space from the code of self-developed other plugins, the function $MHA_AC::get_var_spectrum()$ can be used. See the open-MHAdeveloper manual or the header file $mha_algo_comm.h$ for details.

Please refer to section 14.1 for a description of the overlap-add method that is also followed by this plugin, wave2spec.

Example configurations for the wave2spec plugin are available in the short-time-fourier-transform examples directory, and in the matlab/octave tests exercising this plugin in the mhatest directory. These test files are executed together with the other system-level tests when invoking make test. Please note that you need to have the signal processing package installed in order to sucessfully execute all tests for this plugin.¹

¹In octave, the package can be installed with pkg install -forge control signal from within octave.

14.6.0.2 Supported domains

The MHA plugin wave2spec supports these signal domains:

- · waveform to waveform
- waveform to spectrum

14.6.0.3 Categories

overlapadd

14.6.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
fftlen	int	FFT lengths	512
		Range: [1,]	
wndlen	int	window length/samples	400
		Range: [1,]	
wndpos	float	window position (0 = beginning, 0.5 =	0.5
		symmetric zero padding, 1 = end)	
		Range: [0,1]	
wndtype	keyword_list	window type	hanning
		Range: [rect bartlett hanning hamming	
		blackman user]	
wndexp	float	window exponent to be applied to all	1
		elements of window function	
userwnd	vector <float></float>	user provided window	[]
return_wave	bool	return input waveform signal, store	no
		spectrum only to AC	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

15 Plugin category 'resample'

15.1 downsample

Downsampling by integer fractions

15.1.0.1 Supported domains

The MHA plugin downsample supports these signal domains:

· waveform to waveform

15.1.0.2 Categories

resample signalflow

15.1.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
ratio	int	downsampling ratio	3
		Range: [1,]	
antialias	parser	IIR filter structure	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser antialias:

Name	Туре	Description	Default
Α	vector <float></float>	recursive filter coefficients	[1]
В	vector <float></float>	non-recursive filter coefficients	[1]

15.2 upsample

Upsampling by integer fractions

15.2.0.1 Supported domains

The MHA plugin upsample supports these signal domains:

· waveform to waveform

15.2.0.2 Categories

resample signalflow

15.2.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
ratio	int	upsampling ratio	3
		Range: [1,]	
antialias	parser	IIR filter structure	(see below)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser antialias:

Name	Туре	Description	Default
Α	vector <float></float>	recursive filter coefficients	[1]
В	vector <float></float>	non-recursive filter coefficients	[1]

16 Plugin category 'signalflow'

16.1 addsndfile

Add data from a sound file to some channels of input signal.

The sound file is read into memory and scaled to a given peak level, i.e. the RMS level of an abstract signal with 0 dB full scale. Changing any parameter will start playing the file from the beginning. Playback of the file starts only after the complete file has been read. If the sound file has fewer channels then the 'channels' vector has elements, then the file channels will be repeated.

16.1.0.1 Detailed description

Add data from a sound file to some channels of input signal.

The sound file is read into memory and scaled to a given peak level, i.e. the RMS level of an abstract signal with 0 dB full scale. Changing any parameter will start playing the file from the beginning. Playback of the file starts only after the complete file has been read. If the sound file has fewer channels then the 'channels' vector has elements, then the file channels will be repeated. The addsndfile plugin does not change the number of MHA audio channels. If you specify a channel index \geq the number of MHA audio channels, then the channel from the sound file will not be used.

16.1.0.2 Supported domains

The MHA plugin addsndfile supports these signal domains:

· waveform to waveform

16.1.0.3 Categories

signalflow

16.1.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
path	string	Optional path to sound file	
filename	string	File name of the sound file.	
loop	bool	Infinitely loop the playback of the sound file	yes
level	float	Level in dB (SPL) of the input file	0
levelmode	keyword_list	Level mode Range: [relative peak rms rms_limit40]	relative
resamplingmode	keyword_list	Resampling mode Range: [dont_resample_permissive dont_resample_strict do_resample]	do_resample
channels	vector <int></int>	Output signal channels in which to store the individual sound file channels. Output channel indices start from 0. Note: The addsndfile plugin does not change the number of MHA audio channels. If you specify a channel index >= the number of MHA audio channels, then that channel from the sound file will not be used. Range: [0,]	[0]
mode	keyword_list	Playback mode Range: [add replace input mute]	add
ramplen	float	Length of hanning ramp at level changes in seconds Range: [0,]	0
startpos	int	Starting position in samples, loop will begin from zero Range: [0,]	0
mapping	vector <int></int>	Channel mapping	(monitor)
filechannels	int	Number of channels in current file	(monitor)
mhachannels	int	Number of MHA channels at plugin position	(monitor)
active	int	indicates whether sound is currently	(monitor)
		played back	
search_pattern	string vector <string></string>	played back Search pattern for file list Available files	*.wav

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

16.2 altplugs 79

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.2 altplugs

Configure alternative plugins.

16.2.0.1 Detailed description

The plugin <code>altplugs</code> allows configuration of alternative plugins. The plugin used for processing can be selected via the <code>select</code> variable at any time. Any plugins can be used as alternative plugins, with the only limitations that input and output domain and signal dimension is equal for all alternative plugins. Plugins can be renamed using the ":" operator.

This plugin is automatically located by the graphical user interface t mhacontrol and used for an algorithm selection panel.

16.2.0.2 Supported domains

The MHA plugin altplugs supports these signal domains:

- waveform to waveform
- · waveform to spectrum
- spectrum to waveform
- spectrum to spectrum

16.2.0.3 Categories

signalflow

16.2.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
use_own_ac	bool	Use own AC space for each plug (yes),	no
		or share parents space (no). Must be	
		set before plugs.	
plugs	vector <string></string>	List of plugins	[]
add	string	Add a plugin into list	
delete	string	Delete a plugin from list	
ramplen	float	Ramp length in seconds	0
		Range: [0,]	
select	keyword_list	Select a plugin for processing	(none)
		Range: [(none)]	
labels	vector <string></string>	List of plugin labels.	(monitor)

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.3 analysispath

Split-up of signal analysis and filtering, with asychronous processing of filter path and threadsafe exchange of filter parameters as AC variables.

16.3.0.1 Detailed description

In many signal processing scenarios, the signal analysis requires larger block sizes and more processing time than the filtering itself. If the filters do not change rapidly, the filter coefficients can be processed independently from the filter process. This is realized in this plugin: A copy of the input signal is stored in a double buffer, which is then processed asynchronously in a thread with lower priority. At the same time, a snapshot of the AC space (or a subset of it) can be transferred from the analysis thread to the main processing thread.

Please note that the AC variables which should be copied to the processing thread must exist after the prepare() callback and should not change their size during run-time.




Figure 9 Schematic signal flow in the analysis path scenario.

16.3.0.2 Supported domains

The MHA plugin analysispath supports these signal domains:

· waveform to waveform

16.3.0.3 Categories

signalflow

16.3.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugname	string	inner plugin name, receives adapted fragment size	
fragsize	int	fragment size of inner plugin	200
		Range: [1,]	
fifolen	int	length of double buffer in inner frag-	10
		ment size	
		Range: [1,]	
priority	int	SCHED_FIFO priority (<0 for no real-	-1
		time scheduling)	
acvars	vector <string></string>	Names of AC variables to be copied	[]
		back to processing thread (empty: all)	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.4 db

Synchronous double buffer plugin.

16.4.0.1 Detailed description

The double buffer plugin allows changes of fragment size. It has an outer layer (e.g. framework) and an inner layer (e.g. MHA kernel, plugin). A configurable fragment size is used on the inner side, which is independent from the outer fragment size. The input data is buffered, and the data is processed when enough samples are available. The configuration of the inner plugin is available via the plug prefix.

Please note that double buffering adds an extra delay of the audio stream. If both fragment sizes are identical, the double buffering is bypassed.




Figure 10 Concept of the double buffer plugin. The outer fragments, provided by the framework, are split up into smaller fragments for processing in the kernel. For a continuous output stream, an extra delay is needed, i.e. the first fragment is filled with zeros at the beginning.

16.4.0.2 Warning:

If the inner fragment size is larger than the outer fragment size, the maximal processing time is limited by the shorter fragment size. This results in a maximal processor usage determined by the ratio of outer to inner fragment size. This problem holds not for offline processing. As an alternative, the asynchronous double-buffer plugin <code>dbasync</code> (section ??) can be used, which processes the double-buffered signal in a separate thread. That plugin should be preferred for real-time processing. If the inner thread should only be used for signal analysis, please refer to the plugin <code>analysispath</code> (section 16.3).

16.5 delay 83

16.4.0.3 Supported domains

The MHA plugin db supports these signal domains:

· waveform to waveform

16.4.0.4 Categories

signalflow

16.4.0.5 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugin_name	string	Plugin name	
fragsize	int	fragment size of client plugin	200
		Range: [0,]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.5 delay

Delay line

16.5.0.1 Supported domains

The MHA plugin delay supports these signal domains:

· waveform to waveform

16.5.0.2 Categories

signalflow

16.5.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
delay	vector <int></int>	delay in samples, one entry for each channel Range: [0,[[0 0]

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.6 fader_wave

Apply level

16.6.0.1 Supported domains

The MHA plugin fader_wave supports these signal domains:

· waveform to waveform

16.6.0.2 Categories

signalflow gain

16.7 matrixmixer 85

16.6.0.3 Configuration variables

Name	Туре	Type Description	
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
gain	vector <float></float>	Gain (linear)	[1]
ramplen	float	Length of hanning ramp at gain changes in seconds Range: [0,]	0

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.7 matrixmixer

Matrix mixer plugin, can mix multiple input channels into any number of output channels with configurable weights.

16.7.0.1 Detailed description

The matrixmixer plugin can combine the signal from multiple input channels into any number of output channels, with defined mixing weights.

Example: To combine the two channels of a stereo signal into a single (mono) channel, configure the matrixmixer plugin configuration variable m as

$$m = [[1.0 1.0]]$$

which causes the first and the second channel to be multiplied with a weight of 1 before they are mixed (by adding them together) to form a single output channel.

It is also possible to mix the channels with weights different from 1:

```
m = [[1 \ 0.5]]
```

This attenuates the second channel by multiplying all samples in that channel with 0.5 before mixing it with the first channel. The configuration variable m expects a matrix of float values. The examples above showed a matrix with only one row, which resulted in only one output channel being produced by the matrixmixer plugin. To produce more output channels, more rows (separated by semicolons)² can be specified for matrix m:

```
m = [[1 \ 0]; [0 \ 1]]
```

This is the identity matrix for two channels. This matrix does not change the signal.

The following setting demonstrates how matrixmixer can be used to change the order of audio channels in a multi-channel signal. This example swaps the first two channels:

```
m = [[0 1]; [1 0]]
```

The next setting creates a 4-channel signal output from a stereo signal, where the first two channels are the original stereo channels, the third is the sum of the two stereo channels, and the fourth output channel is the difference of the two stereo channels³:

```
m = [[0 1]; [1 0]; [1 1]; [1 -1]]
```

The following example duplicates a single input channel to two output channels:

```
m = [[1];[1]]
```

To summarize, you need to configure the variable m with a matrix with float values. The matrix needs to have as many columns as the matrixmixer receives input channels, and as many rows as you want matrixmixer to produce output channels.

Example configurations and example input files are contained in the matrixmixer examples directory. Please refer to the README file in this directory for an explanation of the different examples.

A matlab/octave test exercising the matrixmixer plugin in six different configurations can be found in the mhatest directory in file test_matrixmixer.m. This test file is executed together with the other system-level tests when invoking make test.

16.7.0.2 Supported domains

The MHA plugin matrixmixer supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

²In openMHA configuration, a matrix is specified as a vector of vectors, where the subsequent row vectors are separated by semicolons. For details, refer to the subsection on multidimensional variables in the openMHA application manual.

³The combination of the sum and the difference of the two channels of a stereo signal is known as the mid-side signal and used for stereo transmission in FM radio. We combine it here with the original stereo signal for the sole purpose of demonstrating the creation of more output channels than input channels with the matrixmixer plugin.

16.8 mhachain 87

16.7.0.3 Categories

signalflow mixing panning

16.7.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
m	matrix <float></float>	Mixer matrix, one row vector for each output channel. The number of columns must match the number of input channels.	[[1 0];[0 1]]

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.8 mhachain

MHA Chain

16.8.0.1 Detailed description

Load a sequence of plugins. During processing, the signal is passed from plugin to plugin, and may change its domain or dimension.

If profiling is switched on, the cumulative time spent in the processing callback of each plugin is stored in a monitor variable.

The complete chain can be replaced by other algorithms during run-time if the default configuration is valid for processing and if the output domain or dimension does not change by replacing the chain.

16.8.0.2 Supported domains

The MHA plugin mhachain supports these signal domains:

- · waveform to waveform
- · waveform to spectrum
- spectrum to waveform
- · spectrum to spectrum

16.8.0.3 Categories

signalflow

16.8.0.4 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
use_profiling	bool	use profiling method	no
algos	vector <string></string>	list of plugins	[]

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.9 resampling

Synchronous resampling plugin.

16.9.0.1 Detailed description

A bridge type resampling plugin. The signal is converted to target sampling rate and fragment size. The converted signal is processed by the child plugin. The processed signal is then converted back to the original sampling rate and fragment size. The input data is buffered, and the data is processed when enough samples are available.

Please note that double buffering adds an extra delay of the audio stream. If both fragment sizes are identical, the double buffering is bypassed.

16.9.0.2 Warning:

A synchronous resampling ringbuffer such as this causes varying computational loads in the outer processing buffer. It is therefore not real-time safe.

16.9.0.3 Supported domains

The MHA plugin resampling supports these signal domains:

· waveform to waveform

16.9.0.4 Categories

signalflow

16.9.0.5 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
plugin_name	string	Plugin name	
srate	float	sampling rate of client plugin	44100
		Range:]0,]	
fragsize	int	fragment size of client plugin	200
		Range:]0,]	
nyquist_ratio	float	lowpass filter cutoff frequency / lower	0.85
		nyquist frequency	
		Range:]0,]	
irslen_outer2inner	float	filter lenth 1st resampling / sec	0.0007
		Range:]0,]	
irslen_inner2outer	float	filter lenth 2nd resampling / sec	0.0007
		Range:]0,]	

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.10 route

Signal router plugin.

Arguments are the input signal source names (AC variables) followed by a colon, followed by the channel number, starting at zero. Empty names correspond to the direct input.

An AC variable will be created if the AC output dimension is not zero. Example: out = $[:0:1 \times :0]$ x:1] ac = [:2:3] returns a four channel output signal containing first two direct input channels, and the first two channels of the AC variable "x". An AC variable is created with the third and fourth channel of the direct input.

16.10.0.1 Supported domains

The MHA plugin route supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

16.10.0.2 Categories

signalflow

16.10.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
out	vector <string></string>	direct output	[]
ac	vector <string></string>	AC output	[]

Variables of sub-parser mhaconfig_in:

16.11 split 91

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

16.11 split

Split audio signal into channel groups and have them processed by different plugins in parallel

16.11.0.1 Detailed description

The plugin 'split' takes a multi-channel input signal and splits it up into separate chains of groups of channels. After processing of each chain, the output channels are merged into a multi-channel output signal. The order of the audio channels is left unchanged.

16.11.0.2 Supported domains

The MHA plugin split supports these signal domains:

- waveform to waveform
- · waveform to spectrum
- · spectrum to waveform
- · spectrum to spectrum

16.11.0.3 Categories

signalflow

16.11.0.4 Configuration variables

Name	Туре	Description	Default
algos	vector <string></string>	List of plugins which process the different groups of audio channels.	
channels	vector <int></int>	Number of channels processed by the respective plugins. Range: [0,[O
thread_platform	keyword_list	Thread platform to use. posix is the native linux thread platform, win32 is the native thread platform on windows, dummy means that all processing is performed in a single thread. Range: [posix win32 dummy]	posix
worker_thread_scheduler	keyword_list	Scheduler used for worker threads. Only used for posix threads. Suggested setting is: The same as present in framework_thread_scheduler after prepare. Range: [SCHED_OTHER SCHED_RR SCHED_FIFO]	SCHED_OTHER
worker_thread_priority	int	Priority assigned to worker threads. Suggested setting is: The same as present in framework_thread_priority afterpreparing the MHA. The default thread priority given here is invalid. No attempt will be made to set the priority of the threads if this value remains unchanged.	99999999
framework_thread_scheduler	string	Scheduler used by the framework's processing thread. Only valid after first signal processing callback.	(monitor)
framework_thread_priority	int	Priority of the frameworks processing thread. Only valid after first signal processing callback.	(monitor)
delay	bool	activates parallel processing of plugins at the cost of one block of additional delay	no

17 Uncategorized plugins

17.1 cpuload

cpu load generator. CPU load is proportional to number of channels, number of frames, and factor

17.1.0.1 Supported domains

The MHA plugin cpuload supports these signal domains:

- · waveform to waveform
- spectrum to spectrum

17.1.0.2 Categories

other

17.1.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
factor	float	cpu load factor. Values > 1 increase cpu load, values < 1 decrease it Range: [0,]	1
use_sine	bool	Whether to use the sine function. If not, table interpolation will be used	yes

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or MHA_SPECTRUM)	(monitor)
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

17.2 delaysum

delay and sum plugin. Mixes all channels into a single output channel after applying channel-specific weights and delays.

17.2.0.1 Detailed description

This plugin allows to delay and sum multiple input channels using individual delays and weights. After each channel is delayed it is multiplied with the given weight and then added to the single output channel.

17.2.0.2 Supported domains

The MHA plugin ${\tt delaysum}$ supports these signal domains:

· waveform to waveform

17.2.0.3 Categories

other

17.2.0.4 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
weights	vector <float></float>	weights of channels. Each entry is multiplied to its respective channel. Needs one entry per channel.	[1 1]
delay	vector <int></int>	delay in number of frames. The nth channel is delayed by the number of frames found in the nth entry. Range: [0,]	[0 0]

Variables of sub-parser mhaconfig_in:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

17.3 fader_spec

fader

17.4 gain 95

17.3.0.1 Supported domains

The MHA plugin fader_spec supports these signal domains:

· spectrum to spectrum

17.3.0.2 Categories

other

17.3.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
tau	float	fader duration in seconds	1
		Range: [0,[
gains	vector <float></float>		[1 1]

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

17.4 gain

Gain plugin:

Apply a gain to each channel

17.4.0.1 Supported domains

The MHA plugin gain supports these signal domains:

- · waveform to waveform
- · spectrum to spectrum

17.4.0.2 Categories

other

17.4.0.3 Configuration variables

Name	Туре	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
min	float	Minimal gain	-16
		Range: [,0]	
max	float	Maximal gain	16
		Range: [0,]	
bbgain	float	Broadband gain in dB (setting of broad	0
		band gain overrides band gain)	
		Range: [-16,16]	
gains	vector <float></float>	Gain in dB	[0]
		Range: [-16,16]	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

17.5 noisePowProposedScale

noise power estimator after Gerkmann (2012)

Copyright © 2011 Author: Timo Gerkmann and Richard Hendriks Royal Institute of Technology (KTH) Delft university of Technology

17.5.0.1 Supported domains

The MHA plugin noisePowProposedScale supports these signal domains:

· spectrum to spectrum

17.5.0.2 Categories

other

17.5.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
alphaPH1mean	float	low pass filter coefficient for PH1mean Range: [0,1[0.9
alphaPSD	float	low pass filter coefficient for PSD Range: [0,1[0.8
q	float	a priori probability of speech presence Range: [0,1]	0.5
xiOptDb	float	optimal fixed a priori SNR for SPP esti- mation	15

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Туре	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

98 REFERENCES

17.6 wavrec

wav file recorder

17.6.0.1 Supported domains

The MHA plugin wavrec supports these signal domains:

· waveform to waveform

17.6.0.2 Categories

other

17.6.0.3 Configuration variables

Name	Type	Description	Default
mhaconfig_in	parser	Input configuration	(see below)
mhaconfig_out	parser	Output configuration	(see below)
fifolen	int	Length of FIFO in samples	262144
		Range: [2,]	
minwrite	int	Minimal write length (must be less then	65536
		fifolen)	
		Range: [1,]	
prefix	string	Path (including path delimiter) and file	
		prefix	
use_date	bool	Use date and time (yes), or only prefix	yes
		(no)	
record	bool	Record session. Each write access	no
		with argument "yes" will start a new file	
		with current time and date as a name.	

Variables of sub-parser mhaconfig_in:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

Variables of sub-parser mhaconfig_out:

Name	Type	Description	Default
channels	int	Number of audio channels	(monitor)
domain	string	Signal domain (MHA_WAVEFORM or	(monitor)
		MHA_SPECTRUM)	
fragsize	int	Fragment size of waveform data	(monitor)
wndlen	int	Window length of spectral data	(monitor)
fftlen	int	FFT length of spectral data	(monitor)
srate	float	Sampling rate in Hz	(monitor)

References

Index

AC-variables (plugin category)	db (MHA plugin), 82
ac2lsl, 1	dc (MHA plugin), 47
ac2osc, 2	dc_simple (MHA plugin), 50
ac2wave, 3	delay (MHA plugin), 83
acConcat_wave, 4	delaysum (MHA plugin), 93
acmon, 5	directional (plugin category)
acPooling_wave, 6	doasym_classification, 26
acsave, 8	doasym_feature_extraction, 27
acSteer, 9	doasym classification (MHA plugin), 26
save_spec, 11	doasym_feature_extraction (MHA plugin), 27
save_wave, 12	downsample (MHA plugin), 75
ac2lsl (MHA plugin), 1	droptect (MHA plugin), 18
ac2osc (MHA plugin), 2	are present (in the president), the
ac2wave (MHA plugin), 3	example (plugin category)
acConcat_wave (MHA plugin), 4	example1, 29
	example2, 30
acmon (MHA plugin), 5	example3, 30
acPooling_wave (MHA plugin), 6	example4, 31
acsave (MHA plugin), 8	example5, 32
acSteer (MHA plugin), 9	example6, 33
acTransform_wave (MHA plugin), 17	example1 (MHA plugin), 29
adaptive (plugin category)	example2 (MHA plugin), 30
lpc, 13	example3 (MHA plugin), 30
lpc_bl_predictor, 14	example4 (MHA plugin), 31
lpc_burg-lattice, 15	example5 (MHA plugin), 32
addsndfile (MHA plugin), 77	example6 (MHA plugin), 33
adm (MHA plugin), 20	examples (iii ii i plagiii), se
altplugs (MHA plugin), 79	fader_spec (MHA plugin), 94
analysis (plugin category)	fader_wave (MHA plugin), 84
acTransform_wave, 17	feedback (plugin category)
droptect, 18	fshift_hilbert, 34
analysispath (MHA plugin), 80	prediction_error, 35
	fftfbpow (MHA plugin), 53
beamforming (plugin category)	fftfilterbank (MHA plugin), 38
adm, 20	filter (plugin category)
steerbf, 21	coherence, 23
binaural (plugin category)	combinechannels, 37
coherence, 23	fftfilterbank, 38
	iirfilter, 41
coherence (MHA plugin), 23	nlms_wave, 42
combinechannels (MHA plugin), 37	smoothgains_bridge, 70
compression (plugin category)	fshift_hilbert (MHA plugin), 34
dc, 47	<u>.</u>
dc_simple, 50	gain (MHA plugin), 95
compressor (plugin category)	gain (plugin category)
multibandcompressor, 54	fader_wave, 84
core (plugin category)	generator (plugin category)
identity, 25	noise, 44
cpuload (MHA plugin), 92	plingploing, 45

100 INDEX

sine, 46	ac2lsl, 1
	ac2osc, 2
identity (MHA plugin), 25	ac2wave, 3
iirfilter (MHA plugin), 41	acConcat_wave, 4
lovel (plugin estagory)	acmon, 5
level (plugin category) dc, 47	acPooling_wave, 6
•	acsave, 8
dc_simple, 50	acSteer, 9
fftfbpow, 53	acTransform_wave, 17
multibandcompressor, 54 rmslevel, 56	addsndfile, 77
·	adm, 20
softclip, 57	altplugs, 79
transducers, 58	analysispath, 80
lpc (MHA plugin), 13	coherence, 23
lpc_bl_predictor (MHA plugin), 14	combinechannels, 37
lpc_burg-lattice (MHA plugin), 15	cpuload, 92
matrixmixer (MHA plugin), 85	db, 82
mhachain (MHA plugin), 87	dc, 47
mixing (plugin category)	dc_simple, 50
matrixmixer, 85	delay, 83
multibandcompressor (MHA plugin), 54	delaysum, 93
multichannel (plugin category)	doasym_classification, 26
adm, 20	doasym_feature_extraction, 27
ddiii, 2 0	downsample, 75
nlms_wave (MHA plugin), 42	droptect, 18
noise (MHA plugin), 44	example1, 29
noise (plugin category)	example2, 30
timoSmooth, 63	example3, 30
noise-reduction (plugin category)	example4, 31
coherence, 23	example5, 32
noisePowProposedScale (MHA plugin), 97	example6, 33
	fader_spec, 94
other (plugin category)	fader_wave, 84
cpuload, 92	fftfbpow, 53
delaysum, 93	fftfilterbank, 38
fader_spec, 94	fshift_hilbert, 34
gain, 95	gain, 95
noisePowProposedScale, 97	identity, 25
wavrec, 98	iirfilter, 41
overlapadd (MHA plugin), 65	lpc, 13
overlapadd (plugin category)	lpc_bl_predictor, 14
overlapadd, 65	lpc_burg-lattice, 15
shadowfilter_begin, 68	matrixmixer, 85
shadowfilter_end, 69	mhachain, 87
smoothgains_bridge, 70	multibandcompressor, 54
spec2wave, 72	nlms wave, 42
wave2spec, 73	noise, 44
panning (plugin category)	noisePowProposedScale, 97
matrixmixer, 85	overlapadd, 65
plingploing (MHA plugin), 45	plingploing, 45
plugin	prediction_error, 35
. •	- , -

INDEX 101

resampling, 88	steerbf (MHA plugin), 21
rmslevel, 56	timoSmooth (MHA plugin), 63
route, 90	transducers (MHA plugin), 58
save_spec, 11 save_wave, 12	
shadowfilter_begin, 68	upsample (MHA plugin), 76
shadowfilter_end, 69	wave2spec (MHA plugin), 73
sine, 46	wavrec (MHA plugin), 98
smoothgains_bridge, 70	wavioo (iii ii i piagiii),
softclip, 57	
spec2wave, 72	
split, 91	
steerbf, 21	
timoSmooth, 63	
transducers, 58 upsample, 76	
wave2spec, 73	
wavrec, 98	
prediction_error (MHA plugin), 35	
reduction (plugin category)	
timoSmooth, 63	
resample (plugin category) downsample, 75	
upsample, 76	
resampling (MHA plugin), 88	
rmslevel (MHA plugin), 56	
route (MHA plugin), 90	
anne (MITA plugia) 11	
save_spec (MHA plugin), 11 save_wave (MHA plugin), 12	
shadowfilter_begin (MHA plugin), 68	
shadowfilter_end (MHA plugin), 69	
signalflow (plugin category)	
addsndfile, 77	
altplugs, 79	
analysispath, 80	
db, 82	
delay, 83	
downsample, 75	
fader_wave, 84 matrixmixer, 85	
mhachain, 87	
resampling, 88	
route, 90	
split, 91	
upsample, 76	
sine (MHA plugin), 46	
smoothgains_bridge (MHA plugin), 70	
softclip (MHA plugin), 57	
spec2wave (MHA plugin), 72	
split (MHA plugin), 91	