

# Python 数据处理

刘德华

2023 年 6 月 20 日

## 1 基本技能

1.0.1 以 `openml` 中的数据集 `diabetes` 为例，计算不同 `class` 分类下，`age` 的中位数。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml

[2]: # 获取数据
data = fetch_openml(
    data_id=37,
    as_frame=True,
    parser="pandas"
)["frame"]

[3]: # 查看数据集的前五行
data.head()
```

	preg	plas	pres	skin	insu	mass	pedi	age	class
0	6	148	72	35	0	33.6	0.627	50	tested_positive
1	1	85	66	29	0	26.6	0.351	31	tested_negative
2	8	183	64	0	0	23.3	0.672	32	tested_positive
3	1	89	66	23	94	28.1	0.167	21	tested_negative
4	0	137	40	35	168	43.1	2.288	33	tested_positive

```
[4]: # 分组计算平均数
data.groupby(by="class")["age"].agg("median")

[4]: class
tested_negative    27.0
tested_positive    36.0
Name: age, dtype: float64
```

1.0.2 以 `openml` 中的数据集 `diabetes` 为例，查找第五大的年龄是多少岁。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml

[2]: # 获取数据
data = fetch_openml(
    data_id=37,
    as_frame=True,
    parser="pandas"
)["frame"]

[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      preg  plas  pres  skin  insu  mass  pedi  age      class
0       6   148   72   35    0  33.6  0.627  50  tested_positive
1       1    85   66   29    0  26.6  0.351  31  tested_negative
2       8   183   64    0    0  23.3  0.672  32  tested_positive
3       1    89   66   23   94  28.1  0.167  21  tested_negative
4       0   137   40   35  168  43.1  2.288  33  tested_positive
```

```
[4]: # 降序排列后取出第四个
data["age"].sort_values(ascending=False).iloc[3]
```

```
[4]: 69
```

**1.0.3** 以 `openml` 中的数据集中 `diabetes` 为例，新建一个 `id` 列，划分为两个子数据集，两个数据集的样本量是一样的，只是变量不同。

**1.0.4** 将这两个的子数据集打乱顺序，按照 `id` 合并。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=37,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      preg  plas  pres  skin  insu  mass  pedi  age      class
0       6   148   72   35    0  33.6  0.627  50  tested_positive
1       1    85   66   29    0  26.6  0.351  31  tested_negative
2       8   183   64    0    0  23.3  0.672  32  tested_positive
3       1    89   66   23   94  28.1  0.167  21  tested_negative
4       0   137   40   35  168  43.1  2.288  33  tested_positive
```

```
[4]: # 新建一列 id
data["id"] = range(1,data.shape[0]+1)
```

```
[5]: # 按照 preg 排序，打乱顺序
data1 = data.loc[:, ["preg", "plas", "pres", "class", "id"]].
    ↪sort_values(by=["preg"])
# 按照 age 排序，打乱顺序
data2 = data.loc[:, ["skin", "insu", "mass", "pedi", "age", "id"]].
    ↪sort_values(by=["age"])
```

```
[6]: data1.head()
```

```
[6]:      preg  plas  pres          class  id
      467    0   97   64  tested_negative  468
      109    0   95   85  tested_positive  110
      452    0   91   68  tested_negative  453
      449    0  120   74  tested_negative  450
      448    0  104   64  tested_positive  449
```

```
[7]: data2.head()
```

```
[7]:      skin  insu  mass  pedi  age  id
      255    35    0  33.6  0.543  21  256
      60     0    0   0.0  0.304  21   61
      102    0    0  22.5  0.262  21  103
      182   20   23  27.7  0.299  21  183
      623   27  115  43.5  0.347  21  624
```

```
[8]: # 按照 id 合并
newdata = data1.merge(data2, on="id")
# 按照 id 排序
newdata.sort_values(by=["id"], inplace=True)
newdata.head()
```

```
[8]:      preg  plas  pres          class  id  skin  insu  mass  pedi  age
      587    6  148   72  tested_positive    1    35    0  33.6  0.627  50
      233    1   85   66  tested_negative    2    29    0  26.6  0.351  31
      665    8  183   64  tested_positive    3     0    0  23.3  0.672  32
      212    1   89   66  tested_negative    4    23   94  28.1  0.167  21
      101    0  137   40  tested_positive    5    35  168  43.1  2.288  33
```

### 1.0.5 以 openml 中的数据 1StudentPerformance 为例，求数学分数 math score 的排名

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      gender  race/ethnicity  parental level of education  lunch \
0  female          group B          bachelor's degree  standard
1  female          group C          some college          standard
```

2	female	group B	master\'s degree	standard
3	male	group A	associate\'s degree	free/reduced
4	male	group C	some college	standard

  

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: # 按照 max 方法进行排序
res1 = data["math score"].rank(method="max")
res1.sort_values().iloc[:12]
```

```
[4]: 59      1.0
980     2.0
17      3.0
787     4.0
145     5.0
842     6.0
338     7.0
466     8.0
91      10.0
363     10.0
327     11.0
528     14.0
Name: math score, dtype: float64
```

```
[5]: # 按照 min 方法进行排序
res2 = data["math score"].rank(method="min")
res2.sort_values().iloc[:12]
```

```
[5]: 59      1.0
980     2.0
17      3.0
787     4.0
145     5.0
842     6.0
338     7.0
466     8.0
91      9.0
363     9.0
327    11.0
528    12.0
Name: math score, dtype: float64
```

```
[6]: # 按照 dense 方法进行排序
res3 = data["math score"].rank(method="dense")
res3.sort_values().iloc[:12]
```

```
[6]: 59      1.0
     980      2.0
     17      3.0
     787      4.0
     145      5.0
     842      6.0
     338      7.0
     466      8.0
     91       9.0
     363      9.0
     327     10.0
     528     11.0
     Name: math score, dtype: float64
```

1.0.6 以 openml 中的数据集中 StudentPerformance 为例，求数学分数 math score 连续出现 3 次的分数。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

test preparation course  math score  reading score  writing score
0              none          72          72          74
1        completed          69          90          88
2              none          90          95          93
```

3	none	47	57	44
4	none	76	78	75

```
[4]: # 一步差分结果, 删除缺失值
diff1 = data["math score"].diff().dropna()
diff1
```

```
[4]: 1      -3.0
     2      21.0
     3     -43.0
     4      29.0
     5      -5.0
     ...
    995      25.0
    996     -26.0
    997      -3.0
    998       9.0
    999       9.0
Name: math score, Length: 999, dtype: float64
```

```
[5]: # 找到为零的那些元素, 表示重复两次出现的值
diff1_zero = diff1[diff1==0]
diff1_zero
```

```
[5]: 384      0.0
     390      0.0
     432      0.0
     437      0.0
     453      0.0
     518      0.0
     537      0.0
     550      0.0
     565      0.0
     747      0.0
     797      0.0
     925      0.0
     948      0.0
Name: math score, dtype: float64
```

```
[6]: # 再对一步差分结果中零的索引进行差分, 若为零, 则说明是三个连续值
result = pd.Series(diff1_zero.index).diff().dropna()
result[result==0]
```

```
[6]: Series([], dtype: float64)
```

**1.0.7** 以 `openml` 中的数据集 `1StudentPerformance` 为例, 求阅读分数 `reading score` 中出现次数大于 1 的重复值。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[8]: # 找出 reading score 值相同的行
dup_bool = data["reading score"].duplicated()
res = data["reading score"][dup_bool]
res
```

```
[8]: 6      95
    13     72
    21     75
    22     54
    26     54
    ..
   995     99
   996     55
   997     71
   998     78
```



```
999      86
Name: reading score, Length: 928, dtype: int64
```

**1.0.8** 以 `openml` 中的数据集中 `1StudentPerformance` 为例，求 `reading score` 中重复值各自出现的次数。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education   lunch \
0  female      group B      bachelor's degree   standard
1  female      group C      some college   standard
2  female      group B      master's degree   standard
3   male      group A  associate's degree  free/reduced
4   male      group C      some college   standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 频数统计
counts = data["reading score"].value_counts()
# 取出频数大于 1 的值
results = counts[counts > 1]
# 按照 reading score 的数值排序
res_sort = results.sort_index(ascending=False)
res_sort
```

```
[4]: 100      17
     99       3
     97       5
     96       4
```

```

95      8
      ..
37      3
34      4
31      2
29      2
24      2
Name: reading score, Length: 66, dtype: int64

```

**1.0.9** 以 `openml` 中的数据集 `1StudentPerformance` 为例，求 `math score` 中分数为零的样本。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

```

```

      test preparation course  math score  reading score  writing score
0              none          72          72          74
1      completed          69          90          88
2              none          90          95          93
3              none          47          57          44
4              none          76          78          75

```

```

[4]: # 数学分数为零的样本
data[data["math score"] == 0]

```

```

[4]:   gender race/ethnicity parental level of education      lunch \
59  female      group C              some high school  free/reduced

```

	test preparation course	math score	reading score	writing score
59	none	0	17	10

**1.0.10** 以 openml 中的数据集合 1StudentPerformance 为例，删除 writing score 中分数相同的样本。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard
```

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: newdata = data.drop_duplicates(subset=["writing score"])
print("删除 writing score 重复值后的样本量: ", newdata.shape, sep="\n")
newdata.head()
```

删除 writing score 重复值后的样本量:  
(77, 8)

```
[4]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
```

4	male	group C	some college	standard
---	------	---------	--------------	----------

  

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

**1.0.11** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，找到下一个 **math score** 分数比上一个高的样本值。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

[3]:	gender	race/ethnicity	parental level of education	lunch \
0	female	group B	bachelor's degree	standard
1	female	group C	some college	standard
2	female	group B	master's degree	standard
3	male	group A	associate's degree	free/reduced
4	male	group C	some college	standard

  

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: # 一步差分结果
diff_res = data["math score"].diff().dropna()
# 从一步差分结果的索引找到这些样本
data.loc[diff_res[diff_res > 0].index, ].head()
```

```
[4]: gender race/ethnicity parental level of education      lunch \
2  female      group B      master\'s degree      standard
4   male      group C      some college      standard
6  female      group B      some college      standard
8   male      group D      high school  free/reduced
10  male      group C      associate\'s degree      standard

test preparation course  math score  reading score  writing score
2          none          90          95          93
4          none          76          78          75
6    completed          88          95          92
8    completed          64          64          67
10         none          58          54          52
```

**1.0.12** 以 openml 中的数据集合 1StudentPerformance 为例，找到 writing score 中分数大于 90 的样本。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]: gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

test preparation course  math score  reading score  writing score
0          none          72          72          74
1    completed          69          90          88
2          none          90          95          93
3          none          47          57          44
4          none          76          78          75
```

```
[4]: # 分数大于 90 的样本
data[data["writing score"] > 90].head()
```

```
[4]:      gender race/ethnicity parental level of education      lunch \
2    female      group B      master\'s degree      standard
6    female      group B              some college      standard
94   female      group B              some college      standard
106  female      group D      master\'s degree      standard
110  female      group D      associate\'s degree  free/reduced

      test preparation course  math score  reading score  writing score
2              none          90          95          93
6      completed          88          95          92
94              none          79          86          92
106             none          87         100         100
110      completed          77          89          98
```

**1.0.13** 以 openml 中的数据集 1StudentPerfromance 为例，统计各个民族的人数。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      gender race/ethnicity parental level of education      lunch \
0    female      group B      bachelor\'s degree      standard
1    female      group C              some college      standard
2    female      group B      master\'s degree      standard
3     male      group A      associate\'s degree  free/reduced
4     male      group C              some college      standard

      test preparation course  math score  reading score  writing score
0              none          72          72          74
1      completed          69          90          88
2              none          90          95          93
3              none          47          57          44
```

4	none	76	78	75
---	------	----	----	----

```
[4]: # 分组统计频数
data["race/ethnicity"].value_counts()
```

```
[4]: group C    319
      group D    262
      group B    190
      group E    140
      group A     89
      Name: race/ethnicity, dtype: int64
```

**1.0.14** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，寻找 `math score` 中只出现一次的最大数值。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education    lunch \
0  female      group B      bachelor's degree    standard
1  female      group C              some college    standard
2  female      group B      master's degree    standard
3   male      group A      associate's degree  free/reduced
4   male      group C              some college    standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 寻找唯一值，再从唯一值中求最大值
data["math score"].unique().max()
```

```
[4]: 100
```

**1.0.15** 以 `openml` 中的数据集 `1StudentPerfromance` 为例，将 `reading score` 中数值为 `59` 的全部修改为 `60`。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none           72           72           74
1        completed           69           90           88
2              none           90           95           93
3              none           47           57           44
4              none           76           78           75
```

```
[4]: # 将 reading score 为 59 的替换为 60
print("替换之前，数字 60 的个数为：", data["reading score"].value_counts().loc[60,])
data["reading score"].replace(to_replace=59, value=60, inplace=True)
print("替换之后，数字 60 的个数为：", data["reading score"].value_counts().loc[60,])
```

替换之前，数字 60 的个数为： 21

替换之后，数字 60 的个数为： 38

**1.0.16** 以 `openml` 中的数据集 `CSM` 为例，计算评分 `Ratings` 前 10 的电影到底有多少人喜欢？

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```



```
[2]: # 获取数据
data = fetch_openml(
    data_id=42371,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:
```

	Year	Ratings	Genre	Gross	Budget	Screens	Sequel	Sentiment	\
0	2014	6.3	8	9130	4000000.0	45.0	1	0	
1	2014	7.1	1	192000000	50000000.0	3306.0	2	2	
2	2014	6.2	1	30700000	28000000.0	2872.0	1	0	
3	2014	6.3	1	106000000	110000000.0	3470.0	2	0	
4	2014	4.7	8	17300000	3500000.0	2310.0	2	0	

  

	Views	Likes	Dislikes	Comments	Aggregate.Followers
0	3280543	4632	425	636	1120000.0
1	583289	3465	61	186	12350000.0
2	304861	328	34	47	483000.0
3	452917	2429	132	590	568000.0
4	3145573	12163	610	1082	1923800.0

```
[4]: # 按照 Rating 降序排列, 取出前 10 对应的 Likes 数
data.sort_values(by=["Ratings"], ascending=False).iloc[:10,][["Ratings", "Likes"]]
```

```
[4]:
```

	Ratings	Likes
55	8.7	16635
166	8.6	4632
155	8.6	17541
174	8.3	13030
175	8.3	12607
158	8.2	1023
45	8.2	1390
212	8.2	18398
46	8.1	8567
129	8.1	11748

**1.0.17** 以 `openml` 中的数据集 **CSM** 为例, 将数据集按照评分 **Ratings** 作为第一因子降序排列, **Likes** 作为第二因子升序排列。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=42371,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      Year  Ratings  Genre      Gross      Budget  Screens  Sequel  Sentiment  \
0  2014      6.3      8      9130  4000000.0      45.0      1      0
1  2014      7.1      1  192000000  50000000.0     3306.0      2      2
2  2014      6.2      1   30700000  28000000.0     2872.0      1      0
3  2014      6.3      1  106000000  110000000.0     3470.0      2      0
4  2014      4.7      8   17300000   3500000.0     2310.0      2      0
```

```
      Views  Likes  Dislikes  Comments  Aggregate.Followers
0  3280543  4632      425      636      1120000.0
1   583289  3465       61      186     12350000.0
2   304861   328       34       47      483000.0
3   452917  2429      132      590      568000.0
4  3145573 12163      610     1082     1923800.0
```

```
[4]: # 多字段排序，升降序排列
res = data.sort_values(by=["Ratings", "Likes"], ascending=[False, True])
res.head()
```

```
[4]:      Year  Ratings  Genre      Gross      Budget  Screens  Sequel  Sentiment  \
55  2014      8.7      2  188000000  165000000.0     3561.0      1      2
166 2015      8.6     12  345000000  175000000.0     3946.0      1      2
155 2014      8.6      3   13100000   3300000.0      42.0      1      2
175 2015      8.3      9  135000000  28000000.0     2757.0      1      5
174 2015      8.3      1  153000000  150000000.0     3702.0      4     -4
```

```
      Views  Likes  Dislikes  Comments  Aggregate.Followers
55  5421705 16635      751     4316      1865000.0
166 1438926  4632      262      496      232000.0
155 7750223 17541      631     2760      858000.0
175  848970 12607      237     1560      55618.0
174 2732371 13030      497     1774      768700.0
```

**1.0.18** 以 `openml` 中的数据集合 **CSM** 为例，将数据集的行索引修改为 **Movie{i}**。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=42371,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      Year  Ratings  Genre      Gross      Budget  Screens  Sequel  Sentiment  \
0  2014      6.3      8      9130  4000000.0      45.0      1          0
1  2014      7.1      1  192000000  50000000.0     3306.0      2          2
2  2014      6.2      1   30700000  28000000.0     2872.0      1          0
3  2014      6.3      1  106000000  110000000.0     3470.0      2          0
4  2014      4.7      8   17300000   3500000.0     2310.0      2          0

      Views  Likes  Dislikes  Comments  Aggregate.Followers
0  3280543  4632      425      636      1120000.0
1   583289  3465       61      186     12350000.0
2   304861   328       34       47      483000.0
3   452917  2429      132      590      568000.0
4  3145573 12163      610     1082     1923800.0
```

```
[4]: # 重新设置行索引
data.index = ["Movie{}".format(i) for i in range(1, data.shape[0]+1)]
data.head()
```

```
[4]:      Year  Ratings  Genre      Gross      Budget  Screens  Sequel  \
Movie1  2014      6.3      8      9130  4000000.0      45.0      1
Movie2  2014      7.1      1  192000000  50000000.0     3306.0      2
Movie3  2014      6.2      1   30700000  28000000.0     2872.0      1
Movie4  2014      6.3      1  106000000  110000000.0     3470.0      2
Movie5  2014      4.7      8   17300000   3500000.0     2310.0      2

      Sentiment  Views  Likes  Dislikes  Comments  Aggregate.Followers
Movie1          0  3280543  4632      425      636      1120000.0
Movie2          2   583289  3465       61      186     12350000.0
Movie3          0   304861   328       34       47      483000.0
Movie4          0   452917  2429      132      590      568000.0
```

Movie5	0	3145573	12163	610	1082	1923800.0
--------	---	---------	-------	-----	------	-----------

**1.0.19** 以 openml 中的数据集合 CSM 为例，将数据集的部分列名进行修改。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=42371,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:
```

	Year	Ratings	Genre	Gross	Budget	Screens	Sequel	Sentiment	\
0	2014	6.3	8	9130	4000000.0	45.0	1	0	
1	2014	7.1	1	192000000	50000000.0	3306.0	2	2	
2	2014	6.2	1	30700000	28000000.0	2872.0	1	0	
3	2014	6.3	1	106000000	110000000.0	3470.0	2	0	
4	2014	4.7	8	17300000	3500000.0	2310.0	2	0	

  

	Views	Likes	Dislikes	Comments	Aggregate.Followers
0	3280543	4632	425	636	1120000.0
1	583289	3465	61	186	12350000.0
2	304861	328	34	47	483000.0
3	452917	2429	132	590	568000.0
4	3145573	12163	610	1082	1923800.0

```
[4]: # 列重新命名
data.columns = [
    "年份",
    "评分",
    "类型",
    "gross",
    "预算",
    "screens",
    "续集",
    "感情",
    "观看次数",
    "喜欢人数",
    "不喜欢人数",
```

```

    "评论数",
    "粉丝数"
]
data.head()

```

```

[4]:      年份  评分  类型      gross      预算  screens  续集  感情  观看次数  \
      ↪喜欢人数  \
0  2014  6.3   8      9130   4000000.0   45.0    1    0  3280543  4632
1  2014  7.1   1  192000000  50000000.0  3306.0    2    2   583289  3465
2  2014  6.2   1   30700000  28000000.0  2872.0    1    0   304861   328
3  2014  6.3   1  106000000  110000000.0  3470.0    2    0   452917  2429
4  2014  4.7   8   17300000   3500000.0   2310.0    2    0  3145573  12163

      不喜欢人数  评论数      粉丝数
0      425     636   1120000.0
1       61     186  12350000.0
2       34      47   483000.0
3      132     590   568000.0
4      610    1082  1923800.0

```

**1.0.20** 以 `openml` 中的数据集 CSM 为例，从数据集中无放回地随机抽取 50 个样本，计算评分 **Ratings** 的平均值。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=42371,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:      Year  Ratings  Genre      Gross      Budget  Screens  Sequel  Sentiment  \
0  2014      6.3      8      9130   4000000.0   45.0      1      0
1  2014      7.1      1  192000000  50000000.0  3306.0      2      2
2  2014      6.2      1   30700000  28000000.0  2872.0      1      0
3  2014      6.3      1  106000000  110000000.0  3470.0      2      0
4  2014      4.7      8   17300000   3500000.0   2310.0      2      0

      Views  Likes  Dislikes  Comments  Aggregate.Followers

```

0	3280543	4632	425	636	1120000.0
1	583289	3465	61	186	12350000.0
2	304861	328	34	47	483000.0
3	452917	2429	132	590	568000.0
4	3145573	12163	610	1082	1923800.0

```
[4]: # 随机抽样平均值
data["Ratings"].sample(n=50, replace=False).mean()
```

```
[4]: 6.534
```

**1.0.21** 以 openml 中的数据集 1StudentPerformance 为例，计算 math score 大于 60 且小于 90 的人数。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard
```

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: # 查找满足条件的样本
res = data[(data["math score"] > 60) & (data["math score"] < 90)]
# 计算样本量
res.shape[0]
```

[4]: 603

**1.0.22** 以 openml 中的数据集中 StudentPerformance 为例,找到 math score 小于 reading score 小于 writing score 的人。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 修改列名, 为了使用 query 语法
data.columns = data.columns[:5].to_list() + ["math_score", "reading_score", "writing_score"]
# 该查询方法直接是列名表达式
newdata = data.query("math_score < reading_score < writing_score")
newdata.head()
```

```
[4]:  gender race/ethnicity parental level of education      lunch \
14  female      group A      master\'s degree      standard
15  female      group C      some high school      standard
19  female      group C      associate\'s degree  free/reduced
27  female      group C      bachelor\'s degree      standard
29  female      group D      master\'s degree      standard
```

	test preparation course	math_score	reading_score	writing_score
14	none	50	53	58
15	none	69	75	78
19	none	54	58	61
27	none	67	69	75
29	none	62	70	75

**1.0.23** 以 openml 中的数据集 1StudentPerformance 为例, 查找 math score 中是否存在零分。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor's degree      standard
1  female      group C              some college      standard
2  female      group B      master's degree      standard
3   male      group A      associate's degree  free/reduced
4   male      group C              some college      standard
```

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: 0 in data["math score"]
```

```
[4]: True
```



**1.0.24** 以 `openml` 中的数据集合 `1StudentPerformance` 为例, 查找 `math score` 的数值属于 `reading score` 的样本。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0                none         72         72         74
1          completed         69         90         88
2                none         90         95         93
3                none         47         57         44
4                none         76         78         75
```

```
[4]: # 修改列名, 为了使用 query 语法
data.columns = data.columns[:5].to_list() + ["math", "reading", "writing"]
res = data.query("math in reading")
res.head()
```

```
[4]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math  reading  writing
0                none      72      72      74
1          completed      69      90      88
```

2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

**1.0.25** 以 openml 中的数据集中 StudentPerformance 为例, 查找 race/ethnicity 为 groupA 和 groupB 的人。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor's degree      standard
1  female      group C      some college      standard
2  female      group B      master's degree      standard
3   male      group A      associate's degree  free/reduced
4   male      group C      some college      standard

test preparation course  math score  reading score  writing score
0          none          72          72          74
1      completed          69          90          88
2          none          90          95          93
3          none          47          57          44
4          none          76          78          75
```

```
[4]: # 修改列名
data["race"] = data["race/ethnicity"].copy()
# 删除原来的列
data.drop(columns=["race/ethnicity"], inplace=True)
res = data.query("race in ['group A', 'group C']")
res.head()
```

```
[4]:  gender parental level of education      lunch test preparation course \
1  female      some college      standard      completed
3   male      associate's degree  free/reduced      none
```

```

4      male      some college      standard      none
10     male      associate\'s degree      standard      none
13     male      some college      standard      completed

```

```

      math score  reading score  writing score  race
1           69           90           88  group C
3           47           57           44  group A
4           76           78           75  group C
10          58           54           52  group C
13          78           72           70  group A

```

**1.0.26** 以 openml 中的数据集合 1StudentPerformance 为例，将列名 **math score** 修改为 **MathScore**，将 **reading score** 修改为 **ReadingScore**，将 **writing score** 修改为 **WritingScore**。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[ ]: # 查看数据集的前五行
data.head()

```

```

[ ]:  gender  race/ethnicity  parental level of education  lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

```

```

      test preparation course  math score  reading score  writing score
0           none           72           72           74
1      completed           69           90           88
2           none           90           95           93
3           none           47           57           44
4           none           76           78           75

```

```

[ ]: # 修改列名
data.rename(columns={
    "math score": "MathScore",

```

```

    "reading score": "ReadingScore",
    "writing score": "WritingScore",
}, inplace=True)
data.head()

```

**1.0.27** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，将数据集随机地拆分为三块，再从三个子集中分别进行重抽样，将所得到的结果按行合并。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education   lunch \
0  female      group B      bachelor\'s degree   standard
1  female      group C              some college   standard
2  female      group B      master\'s degree   standard
3   male      group A      associate\'s degree free/reduced
4   male      group C              some college   standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75

```

```

[4]: # 数据集划分
from sklearn.model_selection import train_test_split
# 第一次划分
df_train, df_test = train_test_split(data, test_size=0.3, random_state=1)
# 第二次划分
df_train1, df_test1 = train_test_split(df_train, test_size=0.3, random_state=2)
# 重抽样
sample1 = df_train1.sample(n=100, replace=True)
sample2 = df_test1.sample(n=100, replace=True)

```

```
sample3 = df_test.sample(n=100, replace=True)
# 按行合并
newdata = pd.concat([sample1, sample2, sample3], axis=0)
newdata.head()
```

```
[4]:      gender race/ethnicity parental level of education      lunch \
497  female      group D      some college free/reduced
384  female      group A      some high school free/reduced
487  female      group C  associate\'s degree free/reduced
273  female      group D      some college      standard
728  female      group D      high school free/reduced

      test preparation course  math score  reading score  writing score
497      completed          59          78          76
384      none              38          43          43
487      none              60          75          74
273      none              65          70          71
728      none              73          92          84
```

**1.0.28** 以 `openml` 中的数据集中 `1StudentPerformance` 为例，将数据集进行三次重抽样，将所得到的结果按行合并（每次重抽样的结果可能有样本值是相同的，合并时需要特别注意，我们这里重新设置行索引）。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:      gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A  associate\'s degree free/reduced
4   male      group C      some college      standard

      test preparation course  math score  reading score  writing score
```

0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[8]: # 重抽样
sample1 = data.sample(n=100, replace=True, random_state=1)
sample2 = data.sample(n=100, replace=True, random_state=2)
sample3 = data.sample(n=100, replace=True, random_state=3)
# 按行合并, 忽略行索引, 重新给定索引
newdata = pd.concat([sample1, sample2, sample3], axis=0, ignore_index=True)
newdata.head()
```

```
[8]:   gender race/ethnicity parental level of education      lunch \
0  female      group D      some high school  free/reduced
1   male      group D  associate\'s degree    standard
2  female      group C  bachelor\'s degree  free/reduced
3  female      group A  associate\'s degree  free/reduced
4   male      group B      high school    standard

   test preparation course  math score  reading score  writing score
0          none           50           64           59
1          none           80           75           77
2          none           67           75           72
3          none           41           51           48
4  completed           76           62           60
```

**1.0.29** 以 `openml` 中的数据集中 `1StudentPerformance` 为例, 将数据集拆分成两个子集 (变量拆分), 样本是从原数据集中重抽样所得, 将这两个子集按列合并, 默认键是行索引 `index`。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]: gender race/ethnicity parental level of education lunch \
0 female group B bachelor's degree standard
1 female group C some college standard
2 female group B master's degree standard
3 male group A associate's degree free/reduced
4 male group C some college standard
```

```
test preparation course math score reading score writing score
0 none 72 72 74
1 completed 69 90 88
2 none 90 95 93
3 none 47 57 44
4 none 76 78 75
```

```
[4]: # 重抽样
data1 = data.iloc[:, :4].sample(n=50, replace=True, random_state=1)
data2 = data.iloc[:, 4:].sample(n=50, replace=True, random_state=2)
# 按列合并, 默认的 key 是 Index, 取并集, 以缺失值填充
newdata1 = pd.concat([data1, data2], axis=1, join="outer")
newdata1.head()
```

```
[4]: gender race/ethnicity parental level of education lunch \
37 female group D some high school free/reduced
235 male group D associate's degree standard
908 female group C bachelor's degree free/reduced
72 female group A associate's degree free/reduced
767 male group B high school standard
```

```
test preparation course math score reading score writing score
37 NaN NaN NaN NaN
235 NaN NaN NaN NaN
908 NaN NaN NaN NaN
72 NaN NaN NaN NaN
767 NaN NaN NaN NaN
```

```
[5]: # 按列合并, 默认的 key 是 Index, 取交集, 无缺失值
newdata2 = pd.concat([data1, data2], axis=1, join="inner")
newdata2.head()
```

```
[5]: gender race/ethnicity parental level of education lunch \
534 male group B high school standard
```

```
test preparation course math score reading score writing score
534 completed 73 69 68
```

**1.0.30** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，将列 `gender` 取出来转为 `dataframe` 对象。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

   test preparation course  math score  reading score  writing score
0             none         72             72             74
1      completed         69             90             88
2             none         90             95             93
3             none         47             57             44
4             none         76             78             75
```

```
[4]: # Series 转 Dataframe
data["gender"].to_frame()
```

```
[4]:   gender
0  female
1  female
2  female
3   male
4   male
..    ...
995 female
996  male
997 female
998 female
999 female
```



[1000 rows x 1 columns]

**1.0.31** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，统计不同 `race` 和不同性别下数学成绩的平均值。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

   test preparation course  math score  reading score  writing score
0             none         72           72           74
1      completed         69           90           88
2             none         90           95           93
3             none         47           57           44
4             none         76           78           75
```

```
[4]: # 在不同的分组下，计算数学成绩平均值
data.groupby(by=["gender", "race/ethnicity"])["math score"].agg("mean")
```

```
[4]: gender  race/ethnicity
female  group A      58.527778
        group B      61.403846
        group C      62.033333
        group D      65.248062
        group E      70.811594
male    group A      63.735849
        group B      65.930233
        group C      67.611511
```

```

        group D          69.413534
        group E          76.746479
Name: math score, dtype: float64

```

**1.0.32** 以 `openml` 中的数据集 `1StudentPerformance` 为例, 统计不同 `race` 和不同性别下阅读成绩的中位数。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75

```

```

[4]: # 数据透视表
pd.pivot_table(
    data,
    values="reading score",
    index="gender",
    columns="race/ethnicity",
    aggfunc="median"
)

```

```
[4]: race/ethnicity  group A  group B  group C  group D  group E
gender
female           67.5    71.5    73.0    74.0    76.0
male             61.0    62.0    66.0    68.0    73.0
```

**1.0.33** 以 openml 中的数据集 1StudentPerformance 为例，统计不同 race 和不同性别，不同的 parental level of education 下，写作成绩的方差。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education   lunch \
0  female      group B      bachelor\'s degree   standard
1  female      group C              some college   standard
2  female      group B      master\'s degree   standard
3   male      group A      associate\'s degree free/reduced
4   male      group C              some college   standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 数据透视表
pd.pivot_table(
    data,
    values="writing score",
    index=["gender", "parental level of education"],
    columns="race/ethnicity",
    aggfunc="var"
)
```

```
[4]: race/ethnicity          group A      group B      group C  \
gender parental level of education
female associate\'s degree    260.966667    152.221344    144.846465
      bachelor\'s degree      94.333333     59.290909    158.426154
      high school            219.476190    231.485450    210.171264
      master\'s degree        112.500000    171.200000    157.571429
      some college            167.696429    236.352381    220.390592
      some high school        358.711111    284.874459    314.109788
male   associate\'s degree    244.125000    217.911765    211.751894
      bachelor\'s degree    161.527778    180.777778    223.170330
      high school            120.654545    234.892105    129.466132
      master\'s degree              NaN              NaN    126.060606
      some college            396.722222    233.922078    262.640000
      some high school        150.131868    186.495833     85.447619

race/ethnicity          group D      group E
gender parental level of education
female associate\'s degree    215.449275    192.970588
      bachelor\'s degree    214.858974    387.333333
      high school            181.441176    207.659091
      master\'s degree        228.780952    306.666667
      some college            110.063866    152.229167
      some high school        232.090000    387.766667
male   associate\'s degree    149.435385    226.147619
      bachelor\'s degree    203.095238    141.267857
      high school            158.396011    109.833333
      master\'s degree         47.071429              NaN
      some college            163.741935    144.368421
      some high school        173.156667    276.931818
```

**1.0.34** 以 `openml` 中的数据集 `1StudentPerformance` 为例，统计不同 **race** 和不同性别，不同的 **parental level of education** 下，样本的数量，并给出边际值（也是数量）。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

[3]: # 查看数据集的前五行

```
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

  test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

[4]: # 数据透视表

```
pd.pivot_table(
    data,
    values="writing score",
    index=["gender", "parental level of education"],
    columns="race/ethnicity",
    aggfunc="count",
    margins=True,
    margins_name="样本总数"
)
```

```
[4]: race/ethnicity      group A  group B  group C  group D \
gender parental level of education
female associate\'s degree         6      23      45      24
      bachelor\'s degree         3      11      26      13
      high school              7      28      30      17
      master\'s degree          2       5       7      15
      some college             8      15      44      35
      some high school        10      22      28      25
male   associate\'s degree         8      18      33      26
      bachelor\'s degree         9       9      14      15
      high school             11      20      34      27
      master\'s degree          1       1      12       8
      some college            10      22      25      32
      some high school        14      16      21      25
样本总数                89      190      319      262

race/ethnicity      group E  样本总数
gender parental level of education
```

female	associate\'s degree	18	116
	bachelor\'s degree	10	63
	high school	12	94
	master\'s degree	7	36
	some college	16	118
	some high school	6	91
male	associate\'s degree	21	106
	bachelor\'s degree	8	55
	high school	10	102
	master\'s degree	1	23
	some college	19	108
	some high school	12	88
样本总数		140	1000

**1.0.35** 以 `openml` 中的数据集 `1StudentPerformance` 为例, 计算 `gender` 和 `race/ethnicity` 的二维列联表。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

test preparation course  math score  reading score  writing score
0          none          72          72          74
1      completed          69          90          88
2          none          90          95          93
3          none          47          57          44
4          none          76          78          75
```

```
[4]: # 列联表
pd.crosstab(
    index=data["gender"],
    columns=data["race/ethnicity"]
)
```

```
[4]: race/ethnicity  group A  group B  group C  group D  group E
gender
female           36     104     180     129     69
male             53      86     139     133     71
```

**1.0.36** 以 `openml` 中的数据集中 `1StudentPerformance` 为例，计算 `gender` 和 `race/ethnicity` 和 `lunch` 的三维频率列联表，并给出边际值。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 列联表
pd.crosstab(
    index=[data["gender"], data["lunch"]], # 必须是列表形式
    columns=data["race/ethnicity"],
```

```

        normalize=True,
        margins=True,
        margins_name="合计比例"
    )

```

```

[4]: race/ethnicity      group A  group B  group C  group D  group E  合计比例
gender lunch
female free/reduced    0.014    0.039    0.062    0.051    0.023  0.189
      standard        0.022    0.065    0.118    0.078    0.046  0.329
male   free/reduced    0.022    0.030    0.052    0.044    0.018  0.166
      standard        0.031    0.056    0.087    0.089    0.053  0.316
合计比例              0.089    0.190    0.319    0.262    0.140  1.000

```

**1.0.37** 以 `openml` 中的数据集中 `StudentPerformance` 为例，对数学成绩 `math score` 离散化分组。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none        72           72           74
1        completed        69           90           88
2              none        90           95           93
3              none        47           57           44
4              none        76           78           75

```

```

[4]: # 离散变量分组
pd.cut(data["math score"], bins=10)

```



```
[4]: 0      (70.0, 80.0]
      1      (60.0, 70.0]
      2      (80.0, 90.0]
      3      (40.0, 50.0]
      4      (70.0, 80.0]
      ...
      995    (80.0, 90.0]
      996    (60.0, 70.0]
      997    (50.0, 60.0]
      998    (60.0, 70.0]
      999    (70.0, 80.0]
Name: math score, Length: 1000, dtype: category
Categories (10, interval[float64, right]): [(-0.1, 10.0] < (10.0, 20.0] < (20.0,
30.0] < (30.0, 40.0] ... (60.0, 70.0] < (70.0, 80.0] < (80.0, 90.0] < (90.0,
100.0]]
```

**1.0.38** 以 openml 中的数据集中 **StudentPerformance** 为例，对 **gender** 进行虚拟变量化。

```
[1]: # 导入数据集获取工具
      from sklearn.datasets import fetch_openml
      # 导入数据分析库
      import pandas as pd
```

```
[2]: # 获取数据
      data = fetch_openml(
          data_id=43255,
          as_frame=True,
          parser="pandas"
      )["frame"]
```

```
[3]: # 查看数据集的前五行
      data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

      test preparation course  math score  reading score  writing score
0              none          72          72          74
1      completed          69          90          88
2              none          90          95          93
3              none          47          57          44
4              none          76          78          75
```

```
[4]: # 生成虚拟变量
dummy = pd.get_dummies(data["gender"], prefix="性别")
dummy
```

```
[4]:      性别 _female  性别 _male
0          1         0
1          1         0
2          1         0
3          0         1
4          0         1
..      ...      ...
995        1         0
996        0         1
997        1         0
998        1         0
999        1         0
```

[1000 rows x 2 columns]

```
[5]: # 从虚拟变量的 dataframe 转为正常的一列 dataframe
newdata = pd.from_dummies(dummy)
newdata
```

```
[5]:      性别 _female
0      性别 _female
1      性别 _female
2      性别 _female
3      性别 _male
4      性别 _male
..      ...
995  性别 _female
996  性别 _male
997  性别 _female
998  性别 _female
999  性别 _female
```

[1000 rows x 1 columns]

**1.0.39** 以 openml 中的数据集 1StudentPerformance 为例，对 gender 转为因子类型。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 变量因子化
newdata, index = pd.factorize(data["gender"])
newdata[:10]
```

```
[4]: array([0, 0, 0, 1, 1, 0, 0, 1, 1, 0], dtype=int64)
```

```
[5]: index
```

```
[5]: CategoricalIndex(['female', 'male'], categories=['female', 'male'],
    ordered=False, dtype='category')
```

**1.0.40** 以 openml 中的数据集 1StudentPerformance 为例，将宽数据转为长数据。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
```

```
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

test preparation course  math score  reading score  writing score
0          none          72          72          74
1      completed          69          90          88
2          none          90          95          93
3          none          47          57          44
4          none          76          78          75
```

```
[4]: # 宽数据转为长数据
data.iloc[:5, [0,1,5,6]].melt(id_vars=["gender", "race/ethnicity"])
```

```
[4]:  gender race/ethnicity      variable  value
0  female      group B      math score      72
1  female      group C      math score      69
2  female      group B      math score      90
3   male      group A      math score      47
4   male      group C      math score      76
5  female      group B      reading score      72
6  female      group C      reading score      90
7  female      group B      reading score      95
8   male      group A      reading score      57
9   male      group C      reading score      78
```

**1.0.41** 以 openml 中的数据集 1StudentPerformance 为例, 将 gender 的字符串全部大写, 将 race/ethnicity 的字符串全部小写。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
```

```
parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:  gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C      some college      standard

  test preparation course  math score  reading score  writing score
0                none        72           72           74
1             completed        69           90           88
2                none        90           95           93
3                none        47           57           44
4                none        76           78           75
```

```
[4]: # 字符串大小写
data["gender"].str.upper()
```

```
[4]: 0      FEMALE
1      FEMALE
2      FEMALE
3      MALE
4      MALE
...
995    FEMALE
996     MALE
997    FEMALE
998    FEMALE
999    FEMALE
Name: gender, Length: 1000, dtype: object
```

```
[5]: data["race/ethnicity"].str.lower()
```

```
[5]: 0      group b
1      group c
2      group b
3      group a
4      group c
...
995    group e
996    group c
997    group c
```

```

998     group d
999     group d
Name: race/ethnicity, Length: 1000, dtype: object

```

**1.0.42** 以 openml 中的数据集 1StudentPerformance 为例，计算 lunch 列字符串中字符的个数。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

```

```

      test preparation course  math score  reading score  writing score
0              none          72          72          74
1      completed          69          90          88
2              none          90          95          93
3              none          47          57          44
4              none          76          78          75

```

```

[4]: # 字符个数
data["lunch"].str.len()

```

```

[4]: 0      8
     1      8
     2      8
     3     12
     4      8
     ..
    995      8
    996     12

```

```

997    12
998     8
999    12
Name: lunch, Length: 1000, dtype: int64

```

**1.0.43** 以 openml 中的数据集合 1StudentPerformance 为例，将 race/ethnicity 中的字符串空格去除。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor's degree      standard
1  female      group C              some college      standard
2  female      group B      master's degree      standard
3   male      group A      associate's degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75

```

```

[4]: # 去除空格
data["race/ethnicity"].str.replace(" ", "")

```

```

[4]: 0      groupB
1      groupC
2      groupB
3      groupA
4      groupC
...
995     groupE

```

```

996    groupC
997    groupC
998    groupD
999    groupD
Name: race/ethnicity, Length: 1000, dtype: object

```

**1.0.44** 以 `openml` 中的数据集 `1StudentPerformance` 为例，将 `race/ethnicity` 的字符串按照空格分割成列表。

```

[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd

```

```

[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]

```

```

[3]: # 查看数据集的前五行
data.head()

```

```

[3]:   gender race/ethnicity parental level of education    lunch \
0  female      group B      bachelor\'s degree    standard
1  female      group C          some college    standard
2  female      group B      master\'s degree    standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C          some college    standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1        completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75

```

```

[4]: # 分割为列表
strlist = data["race/ethnicity"].str.split(" ")
strlist

```

```

[4]: 0    [group, B]
     1    [group, C]
     2    [group, B]
     3    [group, A]

```



```

4      [group, C]
      ...
995    [group, E]
996    [group, C]
997    [group, C]
998    [group, D]
999    [group, D]
Name: race/ethnicity, Length: 1000, dtype: object

```

```
[5]: # 获取分割的列表的第二个元素
      strlist.str[1]
```

```

[5]: 0      B
      1      C
      2      B
      3      A
      4      C
      ..
995    E
996    C
997    C
998    D
999    D
Name: race/ethnicity, Length: 1000, dtype: object

```

**1.0.45** 以 `openml` 中的数据集合 `1StudentPerformance` 为例，将 `race/ethnicity` 的字符串按照空格分割成列表，并将列表中的各个元素作为列加入到 `dataframe` 中。

```
[1]: # 导入数据集获取工具
      from sklearn.datasets import fetch_openml
      # 导入数据分析库
      import pandas as pd
```

```
[2]: # 获取数据
      data = fetch_openml(
          data_id=43255,
          as_frame=True,
          parser="pandas"
      )["frame"]
```

```
[3]: # 查看数据集的前五行
      data.head()
```

```

[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C      some college      standard

```

2	female	group B	master\'s degree	standard
3	male	group A	associate\'s degree	free/reduced
4	male	group C	some college	standard

  

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: # 分割为列表
strlist = data["race/ethnicity"].str.split(" ", expand=True)
strlist
```

```
[4]:      0  1
0   group B
1   group C
2   group B
3   group A
4   group C
..    ... ..
995 group E
996 group C
997 group C
998 group D
999 group D
```

[1000 rows x 2 columns]

**1.0.46** 以 `openml` 中的数据集 `1StudentPerformance` 为例，将 `parental level of education` 的字符串中的反斜杠去掉。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 去掉反斜杠, 使用替换
data["parental level of education"].iloc[0]
```

```
[4]: "bachelor\\'s degree"
```

```
[5]: # 使用正则表达式替换
data["parental level of education"].str.replace("\\", "", regex=True)
```

```
[5]: 0      bachelor's degree
1      some college
2      master's degree
3      associate's degree
4      some college
...
995     master's degree
996     high school
997     high school
998     some college
999     some college
Name: parental level of education, Length: 1000, dtype: object
```

**1.0.47** 以 `openml` 中的数据集合 `1StudentPerformance` 为例, 将 `math score`, `reading score` 和 `writing score` 三列合并为一列, 以逗号分隔。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard

   test preparation course  math score  reading score  writing score
0              none         72           72           74
1      completed         69           90           88
2              none         90           95           93
3              none         47           57           44
4              none         76           78           75
```

```
[4]: # 列之间的合并
newS = data["math score"].astype("string").str.cat(data["reading score"].
    ↳astype("string"), sep=",").str.cat(data["writing score"].astype("string"),
    ↳sep=",")
newS
```

```
[4]: 0      72,72,74
1      69,90,88
2      90,95,93
3      47,57,44
4      76,78,75
...
995    88,99,95
996    62,55,55
997    59,71,65
998    68,78,77
999    77,86,86
Name: math score, Length: 1000, dtype: string
```

## 1.0.48 对含有缺失值的列进行求和和求乘积，看看结果如何

```
[1]: import pandas as pd
import numpy as np
```

```
[2]: # 生成 dataframe
df = pd.DataFrame(
    np.random.randn(5, 3),
    index=["a", "c", "e", "f", "h"],
    columns=["one", "two", "three"],
)
df["four"] = "bar"
df["five"] = df["one"] > 0
df = df.reindex(["a", "b", "c", "d", "e", "f", "g", "h"])
df
```

```
[2]:
```

	one	two	three	four	five
a	0.271842	-0.350975	0.194960	bar	True
b	NaN	NaN	NaN	NaN	NaN
c	-0.104840	-0.469391	-0.410844	bar	False
d	NaN	NaN	NaN	NaN	NaN
e	-0.059557	0.436472	-0.792940	bar	False
f	0.575772	-0.903377	0.192159	bar	True
g	NaN	NaN	NaN	NaN	NaN
h	-1.555696	0.607744	-0.759766	bar	False

```
[3]: # 计算含有缺失值的列的和，默认是跳过缺失值
df["one"].sum()
```

```
[3]: -0.8724777568039623
```

```
[4]: # 不跳过缺失值，那么得到的和就是 NaN
df["two"].sum(skipna=False)
```

```
[4]: nan
```

```
[5]: # 计算含有缺失值的列的积，默认是跳过缺失值
df["one"].prod()
```

```
[5]: -0.0015203634461877212
```

```
[6]: # 不跳过缺失值，那么得到的积就是 NaN
df["two"].prod(skipna=False)
```

```
[6]: nan
```

**1.0.49** 对含有缺失值的列进行填充，将缺失值以其他的值替换

```
[1]: import pandas as pd
import numpy as np
```

```
[2]: # 生成 dataframe
df = pd.DataFrame(
    np.random.randn(5, 3),
    index=["a", "c", "e", "f", "h"],
    columns=["one", "two", "three"],
)
df["four"] = "bar"
df["five"] = df["one"] > 0
df = df.reindex(["a", "b", "c", "d", "e", "f", "g", "h"])
df
```

```
[2]:
```

	one	two	three	four	five
a	1.010471	1.775946	0.116074	bar	True
b	NaN	NaN	NaN	NaN	NaN
c	-0.709978	0.945866	1.369733	bar	False
d	NaN	NaN	NaN	NaN	NaN
e	0.010790	0.209315	1.177950	bar	True
f	0.028884	1.194446	-0.041722	bar	True
g	NaN	NaN	NaN	NaN	NaN
h	1.731725	0.499953	-0.015604	bar	True

```
[3]: # 以均值替换
df["one"].fillna(df["one"].mean())
```

```
[3]: a    1.010471
b    0.414378
c   -0.709978
d    0.414378
e    0.010790
f    0.028884
g    0.414378
h    1.731725
Name: one, dtype: float64
```

**1.0.50** 对含有缺失值的列或者行删除。

```
[1]: import pandas as pd
import numpy as np
```

```
[2]: # 生成 dataframe
df = pd.DataFrame(
    np.random.randn(5, 3),
```

```

index=["a", "c", "e", "f", "h"],
columns=["one", "two", "three"],
)
df["four"] = "bar"
df["five"] = df["one"] > 0
df = df.reindex(["a", "b", "c", "d", "e", "f", "g", "h"])
df

```

```

[2]:
      one      two      three four  five
a  1.105184  0.696500  1.024294  bar   True
b         NaN         NaN         NaN  NaN   NaN
c  0.286259 -1.286451  1.746801  bar   True
d         NaN         NaN         NaN  NaN   NaN
e  0.283374 -0.699082  1.299307  bar   True
f -0.698294  0.484663  1.120755  bar  False
g         NaN         NaN         NaN  NaN   NaN
h -2.119560  0.173416  0.700130  bar  False

```

```

[3]: # 删除含有缺失值的行，存在缺失值就删除
df.dropna(axis=0, how="any")

```

```

[3]:
      one      two      three four  five
a  1.105184  0.696500  1.024294  bar   True
c  0.286259 -1.286451  1.746801  bar   True
e  0.283374 -0.699082  1.299307  bar   True
f -0.698294  0.484663  1.120755  bar  False
h -2.119560  0.173416  0.700130  bar  False

```

```

[4]: # 删除含有缺失值的列，全部都是缺失值才删除
df.dropna(axis=1, how="all")

```

```

[4]:
      one      two      three four  five
a  1.105184  0.696500  1.024294  bar   True
b         NaN         NaN         NaN  NaN   NaN
c  0.286259 -1.286451  1.746801  bar   True
d         NaN         NaN         NaN  NaN   NaN
e  0.283374 -0.699082  1.299307  bar   True
f -0.698294  0.484663  1.120755  bar  False
g         NaN         NaN         NaN  NaN   NaN
h -2.119560  0.173416  0.700130  bar  False

```

**1.0.51** 对含有缺失值的列进行计数，求非缺失值的个数。

```

[1]: import pandas as pd
import numpy as np

```

```
[2]: # 生成 dataframe
df = pd.DataFrame(
    np.random.randn(5, 3),
    index=["a", "c", "e", "f", "h"],
    columns=["one", "two", "three"],
)
df["four"] = "bar"
df["five"] = df["one"] > 0
df = df.reindex(["a", "b", "c", "d", "e", "f", "g", "h"])
df
```

```
[2]:
```

	one	two	three	four	five
a	-0.126636	-1.491391	0.700825	bar	False
b	NaN	NaN	NaN	NaN	NaN
c	0.981905	-1.506363	0.082841	bar	True
d	NaN	NaN	NaN	NaN	NaN
e	-0.383442	1.491860	-0.551062	bar	False
f	-0.182666	0.236521	0.678531	bar	False
g	NaN	NaN	NaN	NaN	NaN
h	0.984269	-0.652942	-1.957255	bar	True

```
[3]: # 求非缺失值的个数
df["one"].count()
```

```
[3]: 5
```

**1.0.52** 对含有缺失值的列进行插值。

```
[1]: import pandas as pd
import numpy as np
```

```
[2]: # 生成 dataframe
df = pd.DataFrame(
    np.random.randn(5, 3),
    index=["a", "c", "e", "f", "h"],
    columns=["one", "two", "three"],
)
df["four"] = "bar"
df["five"] = df["one"] > 0
df = df.reindex(["a", "b", "c", "d", "e", "f", "g", "h"])
df
```

```
[2]:
```

	one	two	three	four	five
a	0.957477	0.356867	1.238439	bar	True
b	NaN	NaN	NaN	NaN	NaN
c	-1.194969	-0.859723	-2.106189	bar	False
d	NaN	NaN	NaN	NaN	NaN



```
e 0.327321 0.633526 -0.024933 bar True
f 1.027312 0.586582 0.242355 bar True
g      NaN      NaN      NaN NaN NaN
h 0.095649 0.213300 0.137504 bar True
```

```
[3]: # 线性插值
df["one"].interpolate()
```

```
[3]: a    0.957477
     b   -0.118746
     c   -1.194969
     d   -0.433824
     e    0.327321
     f    1.027312
     g    0.561480
     h    0.095649
     Name: one, dtype: float64
```

## 2 强化技能

**2.0.1** 以 `openml` 中的数据集 `1StudentPerformance` 为例，新建一列 `id` 表示不同学生的编号，创建一个矩阵，矩阵的第  $i$  行第  $j$  列是第  $i$  个学生的数学成绩 `math score` 减去第  $j$  个学生的数学成绩的结果。使用 `for` 循环对 `dataframe` 的元素一个一个赋值，赋值方式使用 `loc` 和 `at`，对比时间消耗。为了节省时间，限制  $1 \leq i, j \leq 200$ 。

```
[1]: # 导入数据集获取工具
from sklearn.datasets import fetch_openml
# 导入数据分析库
import pandas as pd
```

```
[2]: # 获取数据
data = fetch_openml(
    data_id=43255,
    as_frame=True,
    parser="pandas"
)["frame"]
```

```
[3]: # 查看数据集的前五行
data.head()
```

```
[3]:   gender race/ethnicity parental level of education      lunch \
0  female      group B      bachelor\'s degree      standard
1  female      group C              some college      standard
2  female      group B      master\'s degree      standard
3   male      group A      associate\'s degree  free/reduced
4   male      group C              some college      standard
```

	test preparation course	math score	reading score	writing score
0	none	72	72	74
1	completed	69	90	88
2	none	90	95	93
3	none	47	57	44
4	none	76	78	75

```
[4]: # 新建 id 列
data["id"] = ["ID{}".format(i) for i in range(1, data.shape[0]+1)]
```

```
[5]: %%timeit
# 新建一个 dataframe
resdf1 = pd.DataFrame(columns=data["id"], index=data["id"])
for i in range(1, 201):
    for j in range(1, 201):
        resdf1.at["ID{}".format(i), "ID{}".format(j)] = data.at[i-1, "math score"]
        ↪- data.at[j-1, "math score"]
```

2.66 s ± 95.1 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)

```
[6]: %%timeit
# 新建一个 dataframe
resdf2 = pd.DataFrame(columns=data["id"], index=data["id"])
for i in range(1, 201):
    for j in range(1, 201):
        resdf2.loc["ID{}".format(i), "ID{}".format(j)] = data.loc[i-1, "math_
        ↪score"] - data.loc[j-1, "math score"]
```

6.97 s ± 270 ms per loop (mean ± std. dev. of 7 runs, 1 loop each)