

List comprehensions

PYTHON DATA SCIENCE TOOLBOX (PART 2)



Hugo Bowne-Anderson
Data Scientist at DataCamp

Populate a list with a for loop

```
nums = [12, 8, 21, 3, 16]
new_nums = []
for num in nums:
    new_nums.append(num + 1)
print(new_nums)
```

```
[13, 9, 22, 4, 17]
```

A list comprehension

```
nums = [12, 8, 21, 3, 16]  
new_nums = [num + 1 for num in nums]  
print(new_nums)
```

```
[13, 9, 22, 4, 17]
```

For loop and list comprehension syntax

```
new_nums = [num + 1 for num in nums]
```

```
for num in nums:  
    new_nums.append(num + 1)  
print(new_nums)
```

```
[13, 9, 22, 4, 17]
```

List comprehension with range()

```
result = [num for num in range(11)]  
print(result)
```

```
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

List comprehensions

- Collapse for loops for building lists into a single line
- Components
 - Iterable
 - Iterator variable (represent members of iterable)
 - Output expression

Nested loops (1)

```
pairs_1 = []  
for num1 in range(0, 2):  
    for num2 in range(6, 8):  
        pairs_1.append(num1, num2)  
print(pairs_1)
```

```
[(0, 6), (0, 7), (1, 6), (1, 7)]
```

- How to do this with a list comprehension?

Nested loops (2)

```
pairs_2 = [(num1, num2) for num1 in range(0, 2) for num2 in range(6, 8)]  
print(pairs_2)
```

```
[(0, 6), (0, 7), (1, 6), (1, 7)]
```

- Tradeoff: readability

Let's **practice!**

PYTHON DATA SCIENCE TOOLBOX (PART 2)

Advanced comprehensions

PYTHON DATA SCIENCE TOOLBOX (PART 2)



Hugo Bowne-Anderson
Data Scientist at DataCamp

Conditionals in comprehensions

- Conditionals on the iterable

```
[num ** 2 for num in range(10) if num % 2 == 0]
```

```
[0, 4, 16, 36, 64]
```

- Python documentation on the `%` operator: The `%` (modulo) operator yields the remainder from the division of the first argument by the second.

```
5 % 2
```

```
1
```

```
6 % 2
```

```
0
```

Conditionals in comprehensions

- Conditionals on the output expression

```
[num ** 2 if num % 2 == 0 else 0 for num in range(10)]
```

```
[0, 0, 4, 0, 16, 0, 36, 0, 64, 0]
```

Dict comprehensions

- Create dictionaries
- Use curly braces `{}` instead of brackets `[]`

```
pos_neg = {num: -num for num in range(9)}  
print(pos_neg)
```

```
{0: 0, 1: -1, 2: -2, 3: -3, 4: -4, 5: -5, 6: -6, 7: -7, 8: -8}
```

```
print(type(pos_neg))
```

```
<class 'dict'>
```

Let's practice!

PYTHON DATA SCIENCE TOOLBOX (PART 2)

Introduction to generator expressions

PYTHON DATA SCIENCE TOOLBOX (PART 2)



Hugo Bowne-Anderson
Data Scientist at DataCamp

Generator expressions

- Recall list comprehension

```
[2 * num for num in range(10)]
```

```
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
```

- Use `()` instead of `[]`

```
(2 * num for num in range(10))
```

```
<generator object <genexpr> at 0x1046bf888>
```


List comprehensions vs. generators

- List comprehension - returns a list
- Generators - returns a generator object
- Both can be iterated over

Printing values from generators (1)

```
result = (num for num in range(6))  
for num in result:  
    print(num)
```

```
0  
1  
2  
3  
4  
5
```

```
result = (num for num in range(6))  
print(list(result))
```

```
[0, 1, 2, 3, 4, 5]
```

Printing values from generators (2)

```
result = (num for num in range(6))
```

- Lazy evaluation

```
print(next(result))
```

0

```
print(next(result))
```

1

```
print(next(result))
```

2

```
print(next(result))
```

3

```
print(next(result))
```

4

Generators vs list comprehensions

```
IPython Shell  Slides  ▼
In [1]: [num for num in range(10**1000000)]
In [2]:
```

Generators vs list comprehensions

```
IPython Shell  Slides  ▾  
In [1]: [num for num in range(10**1000000)]  
In [2]:
```

```
IPython Shell  Slides  ▾  
  
The code took too long to execute.  
If the problem persists, please report an issue.  
  
Restart Session
```

Generators vs list comprehensions

```
IPython Shell  Slides  ▼
In [1]: (num for num in range(10**1000000))
Out[1]: <generator object <genexpr> at 0x7f8c2447a7d8>

In [2]: |
```

Conditionals in generator expressions

```
even_nums = (num for num in range(10) if num % 2 == 0)  
print(list(even_nums))
```

```
[0, 2, 4, 6, 8]
```

Generator functions

- Produces generator objects when called
- Defined like a regular function - `def`
- Yields a sequence of values instead of returning a single value
- Generates a value with `yield` keyword

Build a generator function

- sequence.py

```
def num_sequence(n):  
    """Generate values from 0 to n."""  
    i = 0  
    while i < n:  
        yield i  
        i += 1
```

Use a generator function

```
result = num_sequence(5)  
print(type(result))
```

```
<class 'generator'>
```

```
for item in result:  
    print(item)
```

```
0  
1  
2  
3  
4
```

Let's practice!

PYTHON DATA SCIENCE TOOLBOX (PART 2)

Wrapping up comprehensions and generators.

PYTHON DATA SCIENCE TOOLBOX (PART 2)



Hugo Bowne-Anderson
Data Scientist at DataCamp

Re-cap: list comprehensions

- Basic

```
[output expression for iterator variable in iterable]
```

-  advanced

```
[output expression +  
conditional on output for iterator variable in iterable +  
conditional on iterable]
```

Let's practice!

PYTHON DATA SCIENCE TOOLBOX (PART 2)