

SWIFT FINALE

EXTENSIONS

- ▶ Allow us to extend our classes, structs and enums

EXTENSIONS

- ▶ Allow us to extend our classes, structs and enums
- ▶ Very convenient to keep code in logic groups

EXTENSIONS

- ▶ Allow us to extend our classes, structs and enums
- ▶ Very convenient to keep code in logic groups
- ▶ Can be used to conform protocols

EXTENSIONS

- ▶ Allow us to extend our classes, structs and enums
- ▶ Very convenient to keep code in logic groups
- ▶ Can be used to conform protocols
- ▶ Can add new methods, computed properties, inits, subscripts, nested types

EXTENSIONS

- ▶ Allow us to extend our classes, structs and enums
- ▶ Very convenient to keep code in logic groups
- ▶ Can be used to conform protocols
- ▶ Can add new methods, computed properties, inits, subscripts, nested types
- ▶ Can't add new stored properties!

```
extension Player {  
    func login() {  
        // some new code  
    }  
  
    var displayName: String {  
        return "Mr. \(name)"  
    }  
}
```

NESTED TYPES

- ▶ You can nest types inside each other to make more convenient structure of code or name spacing

NESTED TYPES

- ▶ You can nest types inside each other to make more convenient structure of code or name spacing

```
enum GeneralConstants {  
  
    // MARK: - UI  
  
    enum UI {  
        static let segmentedControlHeight: CGFloat = 54  
        static let collectionSectionHeaderHeight: CGFloat = 45  
        static let animationTransitionDuration: TimeInterval = 0.3  
    }  
}
```


NESTED TYPES

- ▶ You can nest types inside each other to make more convenient structure of code or name spacing

```
enum GeneralConstants {  
  
    // MARK: - UI  
  
    enum UI {  
        static let segmentedControlHeight: CGFloat = 54  
        static let collectionSectionHeaderHeight: CGFloat = 45  
        static let animationTransitionDuration: TimeInterval = 0.3  
    }  
}
```

```
GeneralConstants.UI.segmentControlHeight
```

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed
- ▶ Every var should have value after init()

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed
- ▶ Every var should have value after init()
- ▶ Super.init() should come first

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed
- ▶ Every var should have value after init()
- ▶ Super.init() should come first
- ▶ Convenience init() should call some of main init()

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed
- ▶ Every var should have value after init()
- ▶ Super.init() should come first
- ▶ Convenience init() should call some of main init()
- ▶ init?() - is failable init that can return nil

INIT

- ▶ There are a lot of rules, but you should remember:
- ▶ You can have as much inits as needed
- ▶ Every var should have value after init()
- ▶ Super.init() should come first
- ▶ Convenience init() should call some of main init()
- ▶ init?() - is failable init that can return nil
- ▶ required init() should be implemented in subclasses

DEINIT

- ▶ Deinit allows us clear some resources, close files and other stuff before the class object is gone

DEINIT

- ▶ Deinit allows us clear some resources, close files and other stuff before the class object is gone
- ▶ Object is deinitiated when nobody has reference to it

DEINIT

- ▶ Deinit allows us clear some resources, close files and other stuff before the class object is gone
- ▶ Object is deinitiated when nobody has reference to it

```
class Player {  
    var coinsInPurse: Int  
    init(coins: Int) {  
        coinsInPurse = Bank.distribute(coins: coins)  
    }  
    func win(coins: Int) {  
        coinsInPurse += Bank.distribute(coins: coins)  
    }  
    deinit {  
        Bank.receive(coins: coinsInPurse)  
    }  
}
```

ERROR HANDLING

- ▶ Function that may throw errors should be marked with 'throws'

ERROR HANDLING

- ▶ Function that may throw errors should be marked with 'throws'
- ▶ To handle errors we put throwing functions inside do-catch block

ERROR HANDLING

- ▶ Function that may throw errors should be marked with 'throws'
- ▶ To handle errors we put throwing functions inside do-catch block
- ▶ You can ignore errors with try! or try? - they will return optional values

ERROR HANDLING

- ▶ Function that may throw errors should be marked with 'throws'
- ▶ To handle errors we put throwing functions inside do-catch block
- ▶ You can ignore errors with try! or try? - they will return optional values
- ▶ You can catch some specific and casted errors if needed

ERROR HANDLING

```
enum ValidationError: Error {  
    case notValidAge  
    case notValidEmail  
}
```

ERROR HANDLING

```
enum ValidationError: Error {  
    case notValidAge  
    case notValidEmail  
}
```

```
func validateInput() throws {  
  
}
```


ERROR HANDLING

```
enum ValidationError: Error {  
    case notValidAge  
    case notValidEmail  
}
```

```
func validateInput() throws {  
  
}
```

```
func validateInput() throws {  
    guard let age = Int(ageTextField.text!) else {  
        throw ValidationError.notValidAge  
    }  
  
    guard let email = emailTextField.text, email.count > 3 else {  
        throw ValidationError.notValidEmail  
    }  
    |  
    // success
```

ERROR HANDLING

```
enum ValidationError: Error {  
    case notValidAge  
    case notValidEmail  
}
```

```
func validateInput() throws {  
  
}
```

```
func validateInput() throws {  
    guard let age = Int(ageTextField.text!) else {  
        throw ValidationError.notValidAge  
    }  
  
    guard let email = emailTextField.text, email.count > 3 else {  
        throw ValidationError.notValidEmail  
    }  
    |  
    // success
```

```
func savePressed() {  
    do {  
        try validateInput()  
        createNewUser()  
    } catch let error {  
        print(error)  
        // validation failed  
    }  
}
```



HERE IT COMES

makeameme.org

Closures

HERE IT COMES

makeameme.org

CLOSURES

- ▶ Self-contained blocks of code that can be passed around

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name
- ▶ They are reference type!!!

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name
- ▶ They are reference type!!!
- ▶ Closures capture and hold values inside its body

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name
- ▶ They are reference type!!!
- ▶ Closures capture and hold values inside its body
- ▶ Lightweight syntax

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name
- ▶ They are reference type!!!
- ▶ Closures capture and hold values inside its body
- ▶ Lightweight syntax
- ▶ Used everywhere in iOS programming

CLOSURES

- ▶ Self-contained blocks of code that can be passed around
- ▶ Have no name
- ▶ They are reference type!!!
- ▶ Closures capture and hold values inside its body
- ▶ Lightweight syntax
- ▶ Used everywhere in iOS programming
- ▶ Functions are special types of closures

CLOSURES

```
graph LR; A[GLOBAL FUNCTION] --> B[NESTED FUNCTION]; B --> C[CLOSURE];
```

GLOBAL
FUNCTION

NESTED FUNCTION

CLOSURE

CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

CLOSURES SYNTAX

```
{ (parameters) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

```
reversedNames = names.sorted(by: { s1, s2 in return s1 > s2 } )
```

CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

```
reversedNames = names.sorted(by: { s1, s2 in return s1 > s2 } )
```

```
reversedNames = names.sorted(by: { s1, s2 in s1 > s2 } )
```


CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

```
reversedNames = names.sorted(by: { s1, s2 in return s1 > s2 } )
```

```
reversedNames = names.sorted(by: { s1, s2 in s1 > s2 } )
```

```
reversedNames = names.sorted(by: { $0 > $1 } )
```

CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

```
reversedNames = names.sorted(by: { s1, s2 in return s1 > s2 } )
```

```
reversedNames = names.sorted(by: { s1, s2 in s1 > s2 } )
```

```
reversedNames = names.sorted(by: { $0 > $1 } )
```

```
reversedNames = names.sorted(by: >)
```

CLOSURES SYNTAX

```
{ ( parameters ) -> return type in  
    statements  
}
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in  
    return s1 > s2  
})
```

```
reversedNames = names.sorted(by: { s1, s2 in return s1 > s2 } )
```

```
reversedNames = names.sorted(by: { s1, s2 in s1 > s2 } )
```

```
reversedNames = names.sorted(by: { $0 > $1 } )
```

```
reversedNames = names.sorted(by: >)
```


Wow!

CLOSURES USAGE

- ▶ Pass it to another class / object


CLOSURES USAGE

- ▶ Pass it to another class / object



CLOSURES USAGE

- ▶ Pass it to another class / object



- ▶ Something happens in object 2 and instead of calling object 1 func, it just executes closure, without knowing context

CLOSURES USAGE

- ▶ High order functions like map, flatmap, filter, reduce

CLOSURES USAGE

- ▶ High order functions like map, flatmap, filter, reduce

```
let numberStrings = ["12", "15", "34", "55"]
let numbers = numberStrings
    .compactMap { Int($0) } // convert
    .filter { $0 > 30 }     // filter biggest numbers
    .reduce(0, +)          // sum them
```


CLOSURES USAGE

- ▶ High order functions like map, flatmap, filter, reduce

```
let numberStrings = ["12", "15", "34", "55"]
let numbers = numberStrings
    .compactMap { Int($0) } // convert
    .filter { $0 > 30 }     // filter biggest numbers
    .reduce(0, +)          // sum them
```

```
reversedNames = names.sorted(by: { (s1: String, s2: String) -> Bool in
    return s1 > s2
})
```

TRAILING CLOSURES

- ▶ If closure param is last in function we can not specify call label

```
func funcWithClosure(closure: () -> Void) {  
    // some internal code  
    closure()  
}  
  
funcWithClosure(closure: {  
    print("No so swifty")  
})  
  
funcWithClosure {  
    print("That's trailing closure")  
}
```

Very nice used with
async callbacks

CLOSURES ARE REFERENCE TYPE

- ▶ That means they are living their own life
- ▶ Values they captured can only be changed inside their body
- ▶ They create strong reference to class that has created them (more on that later)

That stuff can create a
lot of memory leaks

ESCAPING CLOSURES

- ▶ Used when closure is executed after function returns
- ▶ It can be call to server

```
func callAPI(at url: String, completion: @escaping (String) -> Void ) {  
    runAsyncTask {  
        // this code is executed after return from function  
        completion("API call result")  
    }  
  
    // func returns at this point  
}
```

There is also Autoclosures

NOT COVERED TOPICS

- ▶ Generics

NOT COVERED TOPICS

- ▶ Generics
- ▶ Memory management

NOT COVERED TOPICS

- ▶ Generics
- ▶ Memory management
- ▶ Opaque types

NOT COVERED TOPICS

- ▶ Generics
- ▶ Memory management
- ▶ Opaque types
- ▶ Property wrappers

NOT COVERED TOPICS

- ▶ Generics
- ▶ Memory management
- ▶ Opaque types
- ▶ Property wrappers
- ▶ Async/await