



CEILING

Exposed Deck- Exposed floor or roof deck no applied finish

Exposed Painted Deck with Acoustic Absorber - Exposed floor deck with applied paint finish unless other noted - colour TBC. Class 'A' acoustic absorber to soffit in accordance with Acoustic Report. Heradesign superfine 1200x600x25mm AK-01 directly fixed to CD channel with Acoustic backfill

Exposed Deck - Exposed roof deck painted matt black finish

MF plasterboard - MF plasterboard system with access panels to suit M+E

MR MF plasterboard - Moisture resistant MF plasterboard system with access panels to suit M+E

Acoustic Suspended Ceiling - 600X600 mineral fibre suspended acoustic tile ceiling system, Class 'C' sound absorption. - Armstrong Bioguard Acoustic tiles, Tegular edge. 24mm grid and perimeter trim.. Shadow batten painted 9010 to perimeters of all suspended ceilings.

Laboratory Suspended Ceiling - 600X600 mineral fibre hygienic, acoustic suspended tile system, Class 'C' sound absorption. Armstrong Bioguard Acoustic tiles, Tegular edge. 24mm grid and perimeter trim.. Shadow batten painted 9010 to perimeters of all suspended ceilings.

Catering Suspended Ceiling- 600X600 mineral fibre hygienic suspended tile system. Armstrong Bioguard Acoustic tiles, Board (square) edge. Non-corrosive 24mm grid and perimeter trim.

40 dB EMC (Electro Magnetic) shielding ceiling by specialist EMC specialist fit out contractor) refer to Outline Specification.

100 dB EMC (Electro Magnetic) shielding ceiling by specialist EMC specialist fit out contractor) refer to Outline Specification.

Plenum - MF plasterboard lining to form sealed plenum under lecture theatre - refer to acoustic report.

Lecture Theatre Ceiling - Suspended MF acoustic ceiling rafts with return edge. Refer to Acoustic Report. Three separate zone rafts (see section). Class 'A' zone - Knaufl Regula solid board Class 'A' zone - Heradesign Superfine 1200x600x25mm AK-01 directly fixed to CD-Channel with Acoustic backfill. Return edge profile to Heradesign boards. Colour TBC Class 'C' zone - Heradesign Superfine 1200x600x25mm AK-01 directly fixed to CD-Channel. Return edge profile to Heradesign boards. Colour TBC

Replacement Ceiling subject to client confirmation
Acoustic Suspended Ceiling - 600X600 mineral fibre suspended acoustic tile ceiling system, Class 'C' sound absorption. - Armstrong Bioguard Acoustic tiles, Tegular edge. 24mm grid and perimeter trim.. Shadow batten painted 9010 to perimeters of all suspended ceilings.

Anechoic - anechoic foam lined chamber by specialist fitout contractor

Existing - No additional works to existing ceiling .

Heradesign wood wool panels fitted to timber or CD Channel. in colour TBC. with return edge profile to rafts to screen plant/fittings over. Areas of Heradesign shown are in accordance with AECOM acoustic report Unless Noted Otherwise

Area to be under-drawn with 1 x15mm Wallboard on MF system to form a minimum 200mm void with minimum 25mm mineral wool in the void. Where any services or other fixings penetrate the plasterboard it is important that the penetration is fully sealed.

P09	19.08.16	Updated to lay-in grid to WCs. Ceilings updated to reflect VE
P08	18.05.16	Under-drawn areas shown in accordance with Acousticians requirements
P07	09.11.15	Updated to perforated plasterboard treatment. Key updated
P06	14.10.15	Updated to show acoustic panel treatment. Key updated.
P05	13.10.15	Updated to reflect revised planning application. Key updated.
P04	04.08.15	Amended Stage 3+ information
P03	14.08.15	Updated to reflect updated plans
P02	08.06.15	Employers requirement issue
P01	10.04.15	Drawing created

rev	date	comment
-----	------	---------

project
ECM, University of Lincoln

MA job no
2400

drawing number
EC-MA-00-03-DR-A-35048

phase name / status / revision
Phase 2 Third Floor Ceiling Finishes- 1:200@A1 S2-P09

purpose of issue
PRELIMINARY

scale
1:200@A1

architecture / interiors / landscape
Email - info@maber.co.uk
Tel - 0115 3416555
maber.co.uk
Issuing office
Nottingham

UNLESS OTHERWISE SPECIFIED, ALL CEILINGS TO BE 3M ABOVE F.F.L.

GENERAL NOTE:
Painted Ceiling - minimum 1 mist coat and 2 full coats Dulux vinyl matt Emulsion (RAL 9010). All Shower room areas to be painted in Dulux Diamond Matt (RAL 9010).
Access hatches - painted metal access hatch, face laid flush with adjacent ceiling finishes, beaded frame with budget lock. Flush beaded edges with no visible frame.

SCALE

PHASE 2

do not scale from this drawing- dimensions and levels to be checked on site by the contractor- all dimensions in millimetres unless otherwise noted - all levels in metres unless otherwise noted

The title, copyright and confidential information in this document belongs to Maber Associates Limited. Copyright. All rights reserved. You may not reproduce this document or disclose it to others without the consent of Maber Associates Limited