Selenium - Java Cheat Sheet

Locating Elements - By

id:

```
driver.findElement(By.id("idValue"));
```

name:

```
driver.findElement(By.name("nameValue"));
```

cssSelector:

```
driver.findElement(By.cssSelector("input[type='submit]”));
```

XPath:

```
driver.findElement(By.xpath("//input[@type='submit']"));
```

tagName:

driver.findElement(By.tagName ("html tagName"));

className:

driver.findElement(By.className ("classValue"));

linkText:

driver.findElement(By.linkText ("Sale"));

partialLinkText:

driver.findElement(By.partialLinkText ("link text"));

Selenium Navigators

Navigate to URL:

driver.get("https://alphabin.co/");

OR

driver.navigate.to("https://alphabin.co/");

Refresh Page:

driver.navigate().refresh();

Navigate forward in browser:

driver.navigate().forward();

Navigate back in browser:

driver.navigate().back();

Alerts

Accept an alert:

```
driver.switchTo().alert().accept();
```

Dismiss an alert:

```
driver.switchTo().alert().dismiss();
```

Enter text in an alert box:

```
driver.switchTo().alert().sendKeys("Alphabin");
```

Retrieve alert text:

```
driver.switchTo().alert().getText();
```

iFrame

by index: → index start from 0

```
driver.switchTo().frame(0);
```

id/name:

```
driver.switchTo().frame("id or name of the iFrame");
```

web element (locators):

```
WebElement middleFrame = driver.findElement(By.xpath("//frame[@name='left']"));
driver.switchTo().frame(middleFrame);
```

Actions

Step 1: Create the action object:

Actions actions=new Actions(driver);

Step 2: Locate the WebElement you want to work on:

driver.switchTo().frame("id or name of the iFrame");

Step 3: Perform the action on the WebElement

Right click:
actions.contextClick(element).perform();
Hover over:
actions.moveToElement(element).perform();
Double Click:
actions.doubleClick(element).perform();
Mouse Hover:
actions.moveToElement(element).build().perform();

Was This Helpful

alphabin.co