

Unit IG2: Risk assessment

Declaration: By submitting this assessment (Parts 1 – 4) for marking I declare that it is entirely my own work. I understand that falsely claiming that the work is my own is malpractice and can lead to NEBOSH imposing severe penalties (see the NEBOSH Malpractice Policy for further information).

Important note: You must refer to the document 'Unit IG2: risk assessment – Guidance and information for learners and Learning Partners' while completing all parts of this assessment. Your Learning Partner should provide you with a copy, but it can also be downloaded from the relevant resources section for this qualification on the NEBOSH website.

Part 1: Background

You should aim to complete this section in 150 - 200 words.

Topic	Comments
Name of organisation*	Yorks Pvt Ltd (Boat yard)
Site location*	Male
Number of workers	207
General description of the organisation	Yorks Pvt Ltd is a boatyard it has expanded significantly into one of the Maldives most trusted and established providers in the marine and hospitality sectors were maintenance of luxury yacht and speed boat, diving boat, supply boats were they carry out fibers works and engine maintenance it is a designated industrial island approximately southwest of Maldives reclaimed from barren land and dedicated to heavy industries is a designated industrial island approximately 9.5 km southwest of Maldives, reclaimed from barren land and dedicated to heavy industries is a designated industrial island approximately southwest reclaimed from barren land and dedicated to heavy industries Boatyard includes dry dock maintenance, Fiber glass works, workshops, welding plants, chemical godowns The most of the customers are resorts The shift pattern is 10 hours a day were docking and other activities are only carried out in day time were all the staffs are permanent workers includes administrative, Engineering, Finance and it is remote island
Description of the area to be included in the risk assessment	Risk assessments for Yorks's boatyard includes the whole work site
Any other relevant information	Integrated which risks from industrial activities were the supervisors and HSE officers are responsible for this works site were one of the busiest boat yards in the country

* If you're worried about confidentiality, you can invent a false name and location for your organisation but, all other information provided must be factual.

You should aim to complete this section in 100 - 200 words.

Note: this section can be completed after you have completed your risk assessment.

Outline how the risk assessment was carried out this should include: • sources of information consulted; • who you spoke to; and • how you identified: - the hazards; - what is already being done; and - any additional controls/actions that may be required.	Used iterative baseline establishment impact matrices likelihood/severity rating low-medium-high alternatives analysis and gap analysis against benchmarks which can be taken as the standards I started by looking around the work shop it was monsoon season with heavy winds I spoke with the workshop mechanics about the weather impact and other docking activities on visual inspections there are some unsafety practices are done like the workers are not wearing gloves the fiberglass dust is directly entering in to the workshops and other godowns and have checked the safety documents and history of risk assessment and company policies Already on work site Regular site inspections and audits were carried out and performance checks included monthly testing of 74 fire extinguishers, as well as routine air, water, and noise monitoring, with results compared against standards. All actions Should be including toolbox talks and daily pre work briefs were caried out Further controls like fiber glass vacuuming system can be included so the dust inhaling can be avoided The above points have helped me for risk assesment
---	---

Part 2: Risk Assessment

Organisation name: Yorks Boat Yard

Date of assessment: 14/12/2025

Scope of risk assessment: Dry Docking and maintenance activities

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
Hazard Slips – wet floor (oils, chemicals)	Technicians and operators had fractures or head injuries increased during monsoons	On-slip mats on walkways housekeeping	Engineering controls involves Perform bi-weekly hazard hunts install guardrails on all elevated platforms; provide anti-slip training and boots.	1 month	Manager
	Operations in night is a major cause as of low visibility	Schedules arrest harnesses for heights less than 2m signage for hazards.	Leak Prevention Maintain all equipment and machinery regularly to prevent leaks of oils, chemicals, or other liquids onto walking surfaces.	2 weeks	Supervisor
	Workers harmed at various departments as a part of poor manual handling	Belt attachment is there but still there is lag with PPEs	Spill Management Implement clear procedures for immediate cleanup of any spills using appropriate neutralizing or absorbent materials as specified in the Safety Data Sheet	1 week	Supervisor
			Proper Storage Keep all hazardous materials in approved, marked containers within dry, ventilated storage areas that are kept free of clutter to prevent tripping while handling containers. Secondary	1 week	HSE officer
			Containment Use drip trays, bunds, or exhausts on machinery to catch contaminants before they reach the floor.	2 weeks	Supervisor
			communication and safe walking techniques, such as taking short	2 Days	HSE officer

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
			steps with feet pointed slightly outward on slippery surfaces.		
Hazard substance Chemical Inhalation Exposure - to Fumes (Welding, Fiberglass) Respiratory hazards from solvent vapors and particulates.	On-site workers staff, primarily male technicians via acute irritation/chronic respiratory issues 67% Fabricators and Laminated Parts Workers Exposed to styrene and polyester epoxy resins used in fiberglass boat construction. Mechanics and Engine Fitters Exposed to diesel and gasoline exhaust, which contains toxic carbon monoxide, nitrogen dioxide, and sulfur dioxide. Sandblasters: Inhale silica dust or beryllium used in abrasive blasting for surface preparation.	Mandatory PPE (masks, gloves) per Guidelines daily health screenings in worker Camps ventilation in workshops activity-based hazard training.	Upgrade to filtered exhaust systems in enclosed repair areas introduce Annual spirometry testing for exposed workers rotate shifts to limit exposure Assess and identify inhalation hazards, including measuring airborne contaminant levels. Apply a hierarchy of controls, prioritizing elimination or reduction at the source and then implementing controls that reduce exposures. Multimedia Provide engineering controls such as effective ventilation that removes contaminants from the workers' breathing zones. Provide appropriate respiratory protective equipment when other controls do not reduce exposure to	6 months 1 year 1 week 2 months	Health and Safety officer Manager Chief Engineer Site Engineer

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	Cleaners: Exposed to fumes from strong degreasers, detergents, and chlorinated solvents. Complaints in visitors' contractors during repairs.		acceptable levels, and manage its selection, fit, maintenance, and use. Train workers on the risks, control measures, and proper use of controls and personal protection, and regularly review control effectiveness		
Noise from Equipment	Workshop technicians and hoist operators are noise-induced hearing loss nearby workers cumulative exposure Production workers and fabricators using high-intensity machinery like grinders, routers, and power saws are at the highest risk for irreversible noise-induced hearing loss and permanent tinnitus. Bystanders and auxiliary staff, such as supervisors, electricians laborers working near fabrication zones, suffer	Noise monitoring at stations Ear protection issued equipment maintenance schedules signage for high-noise zones	Engineering control involves Implement acoustic enclosures on hoists conduct noise mapping for full yard provide annual audiometric exams Prioritize purchasing quieter, modern tools and ensure all machinery is regularly serviced to prevent the excessive rattling and screeching caused by worn or loose parts. Install sound-absorbing barriers or acoustic curtains around the loudest work areas, such as grinding stations, to stop noise from traveling across the yard and affecting other workers. Administrative control on Rotate staff tasks throughout the day so that no single person spends an entire shift in	3 months 4 months 5 Months 2 weeks	Maintenance supervisor Maintenance Engineer Manager Supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	Maintenance and site staff, like those moving heavy equipment or fixing docks, are frequently hurt by the environment itself, such as slipping on oily ramps, tripping over tools in cluttered walkways Outside contractors and visitors, including delivery drivers or boat owners, can easily be harmed because they aren't familiar with the yard's specific layout and might accidentally wander into a hazardous zone or a confined space. The entire workforce suffers when basic needs aren't met, such as when there isn't enough clean drinking water, decent restrooms, or a quiet, clean place to take a break away from the noise and dust of the yard.	paint solvents during lamination and spraying. Clearly marked pedestrian walkways and the using overhead cable hangers help keep floor spaces clear of the clutter and trailing hoses that commonly cause trips and falls. Basic welfare facilities, including designated clean areas for breaks and hand-washing stations, are provided to ensure workers can remove hazardous chemicals and dust before eating or leaving the site.	painters deserve protection from invisible toxins like A cluttered floor is a constant mental and physical strain by using overhead cable hangers and keeping walkways clear of hoses you remove the invisible trip hazards that catch maintenance staff off guard Ensuring ramps are degreased and areas are brightly lit creates an environment where staff can focus on their jobs without fear of a sudden fall Dignity Through Proper Welfare Facilities Basic needs are human rights Providing clean quiet break rooms away from the noise and dust along with accessible restrooms and fresh water allows the body and mind to recover Handwashing stations worker should have to eat their lunch with chemicals or resins still on their skin Mentorship	1 Month 2 Months 1 Month 2 Months	Manager\HSE officer Supervisor Manager HSE officer

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
Working At Heights	Primary Workers at Height Those directly performing tasks such as rigging hull painting or welding face the highest risk of fatal falls from masts scaffolds or elevated vessel structures	Belts Protection Helmets with chin straps to protect against falls and falling objects and nonslip footwear for stability on wet or oily surfaces	Use ground-level alternatives such as pre-assembling components, telescopic tools or drones/remote cameras for inspections so workers don't need to climb unnecessarily	8 Months	Manager
	Ground Level Personnel Workers and labourers below can be seriously injured by tools debris or materials accidentally dropped from elevated work zones	Life Jackets Mandatory for work over or near water to the risk of drown in body harnesses with shock absorbing lanyards	Use scaffolding in preference to ladders where possible. Ensure all scaffolding is erected on firm, level ground, is stable, and has appropriate guardrails and toe boards. Precautions and emergency plans should be pre evaluated	3 Months	Engineering manager
	Vessel Crew and Shore Staff Crew members and stevedores using ladders or gangways for access are at risk of falling into the water which introduces the unique boatyard hazard of drowning		Communication devices should be included in checklist weekly to ensure proper communication	2 Weeks	HSE officer
	Visitors and Untrained Persons Third parties such as inspectors or		Workers should be given backup strips	1 Week	Engineering supervisor
				1 week	HSE officer

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	boat owners may be harmed if they enter danger areas without proper awareness of fragile surfaces or unprotected edges				
Electrical Hazards	Electricians and general staff	Lockout tagout procedures	Upgrade to weatherproof enclosures for all outdoor outlets conduct electrical safety audits quarterly train on arc flash risks.	3 Months	Site Engineer
Leakages	Shocks burns, or electrocution amplified in humid monsoon weather	Annual wiring inspections	Use GroundFault Circuit Interrupters	1 Month	Supervisor
Extension wire coat tangled and lefted in wet floors	Frontline Operators Workers using power tools grinders sprayers are at the highest risk of electrocution if they touch live parts or if current leaks through wet connectors and skin		Ensure that electrical outlets in potentially wet areas boatyards are protected by ground testers These devices can quickly shut off power if they detect a dangerous ground fault significantly reducing the risk of electric shock	2 Months	Engineering manager
	Maintenance Staff Those repairing machinery or moving through behind the scenes areas may encounter faulty wiring or damaged insulation hidden by clutter		Proper Cable Management Keep electrical cords and cables off the ground Use stands hangers or cable protectors to prevent damage to insulation and reduce tripping hazards	2 Months	Supervisor
	Pedestrians Visitors Anyone walking through		Regular Equipment Inspection Establish a routine for visually	2 weeks	supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	the area including delivery drivers or office staffs at risk of secondary injuries such as falling into a hazard or dropping heavy items after tripping over tangled extension cord		inspecting all electrical tools cords and equipment before each use Consider Lower Voltage for Portable Tools Where practical utilize lower voltage systems Ensure Competence and Follow Safe Work Practices on training Only individuals with appropriate training and qualifications should perform electrical work	1 week 1 months 1 week	Supervisor HSE officer HSE officer
Heavy lifting, awkward postures,	Laborers and technicians through strains Back injuries repetitive stress long-term disability	Manual handling training; mechanical aids like trolleys ergonomic assessments per EHS Guidelines	Introduce job rotation and stretching programs procure adjustable lifting aids for engine work Baseline ergonomic surveys	3 Months 2 Months 1 Month	Manager/HSE officer Supervisor HSE/Officer
Work equipment	operators and signallers crane driver's risk	Ensured all lifting operations are planned by a competent person and risk assessed before work begins	Develop rescue plan with fire services	3 months	Supervisor
Lifting Cranes and docking trollies	structural failure or cabin entrapment while riggers and signallers face being		Annual confined training certification on equipment	1 year	Chief Engineer HSE officer

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	struck by swinging loads if communication fails or slings break Ground level workers boat cleaners and painters can be crushed or struck by falling cargo or the complete collapse of cranes if the ground is unstable or equipment is overloaded vessel crew under new ship crew members are at higher risk during on board lifting operations	All cranes and lifting equipment are inspected before use and maintained and thoroughly examined on schedule Only trained and competent operators' riggers and signalers are carrying out lifting tasks with clear communication methods Workers clear of suspended loads and establish exclusion zones around cranes and trollies during lifting Ensure loads do not exceed safe working loads and verify ground stability and environmental conditions before lifting	Upgraded equipment training Regular Toolbox talks Ensure Proper communication coordination with in operators to avoid delays and financial loss	2 years 1 Week 1 week	Chief engineer Supervisor Supervisor
Biological contaminant Sewage over flow	Front level Workers, Mechanics, operators, Painters Hull cleaners suffer respiratory infections from aerosolized marine	Dis infectant is sprayed still no remedy is seen Lifting stations monitoring checklist is followed up	Ensure good hygiene practices by providing handwashing stations and clean welfare facilities renew Appropriate PPE such as gloves coveralls and masks when handling	1 Month 2 Weeks	Manager Supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
	toxins and bacteria during high-pressure washing of bio fouled vessels Sanitation staff contract water-borne diseases like hepatitis through accidental contact while managing sewage pump-out stations Interior detailers develop occupational asthma by inhaling toxic mold spores that in damp enclosed boat cabins and bilges		waste or contaminated water Segregate store and dispose of biological waste Provide training on biological hazards like mould bacteria bird droppings and contaminated water Implement pest control measures to manage rodents' insects and birds Provide health surveillance for workers exposed to biological risks including vaccinations where required Improve ventilation in enclosed spaces like cabins hulls and storage rooms	1 week 1 Week 1 month 1 month	Engineering manager HSE officer Chief Engineer HSE officer
Hazardous substances Fire/Explosions	workers and visitors via burns, smoke inhalation, or blast injuries Property damage to vessels/yard off-site affected by smoke dispersion	Fire extinguishers and suppression systems no smoking zones hot work permits flammable storage cabinets	Install automatic sprinkler systems in workshops; conduct monthly fire drills with external responders Audit resin/peroxide storage for exothermal risks separate and store Flammable liquids in designated ventilated flammable storage cabinets Before welding or grinding provide fire extinguishers fire blankets and fixed	2 Months 6 Months 1 Month	Manager/ HSE officer Engineering Manager Supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
			suppression systems near work zones and ensure workers are trained to use them maintain good ventilation during Use of solvents and resins to prevent vapour build up implement regular inspections housekeeping and spill control procedures to prevent leaks		
Vibration Fiber Sanding with sander and hammer tools	Workers, Engineers who are working inside engine room	Soft bed cushioning is provided for operators	Use low vibration tools and ensure they are properly maintained Limit exposure time by rotating tasks between workers Provide anti vibration gloves and ensure workers keep a loose Train workers on vibration risks and safe operating techniques Monitor vibration exposure levels regularly and keep health surveillance records Use damping materials or mounting systems to reduce tool vibration	3 months 2 Months 1 Month 1 Week 1 Month 1 Month	Supervisor Supervisor Supervisor HSE officer Supervisor/HSE Officer Supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
Hazardous substance Fiberglass toxic intake	Laminators Workers directly applying resins and laying fiberglass mats are at the highest risk They often experience higher rates of chronic cough and impaired lung function Sanding and Grinding Technicians Personnel who sand hardened hulls release significant amounts of dust This dust can penetrate deep into the lungs if not controlled by vacuum systems Nearby Workers Non laminators Maintenance Staff Those cleaning up work areas may disturb settled dust leading to secondary exposure	Worn out PPE are used by the workers Air quality detectors are fixed inside workspaces Several Exhaust are out of order	Mandatory Full Body PPE Personnel should wear loose-fitting long-sleeved clothing or disposable coveralls gloves and head coverings to prevent fibers from embedding in the skin or hair Specialized Respiratory Protection Standard dust masks are often insufficient for fine glass fibers and resin vapours use approved respirators equipped with filters and organic vapor cartridges Decontamination Zones Establish dedicated clean zones for eating and resting Workers must wash exposed skin with soap and warm water before taking breaks Filtered Cleanup Prohibit dry sweeping or using compressed air to clean workspaces Use industrial vacuums or damp cloths to remove settled dust safely	6 Months 6 Months 3 Months 1 Month	Supervisor Manager Engineering Manager Supervisor

Hazard category and hazard	Who might be harmed and how?	What are you already doing?	What further controls/actions are required?	Timescales for further actions to be completed (within ...)	Responsible person's job title
Bio - Chemical hazard includes Fiber resin, fiber glass hardener chemicals acetone are released when sanding	Respiratory problems for worker and visitors	They are using low standard mask which chemicals can be airborne and enter in to workers	Providing respiratory masks can minimize the chemical intake	1 month	Manager
			Provide suitable PPE including respirators chemical resistant gloves goggles and protective suits	2 Month	Engineering manager \
			Ensure good general ventilation in enclosed spaces such as cabins hulls and workshops	1 Month	Supervisor
			Train workers on chemical hazards correct mixing procedures and safe handling techniques	1 Week	HSE officer
			Provide safety data sheets and ensure workers understand the key hazards and control measures	2 Weeks	HSE Officer
			Rotate tasks to reduce prolonged exposure to chemicals and dust	2 Months	Engineering manager
			Provide health surveillance where workers are regularly exposed to chemical vapours or dust	1 Month	HSE officer

Part 3: Prioritise 3 actions with justification for the selection

Suggested word counts

Moral, general legal and financial arguments for all actions: 300 to 350 words

For EACH action:

Specific legal arguments: 100 to 150 words

Likelihood AND severity: 75 to 150 words

How effective the action is likely to be in controlling the risk: 100 to 150 words

Moral, general legal and financial arguments for ALL actions

Moral, general legal and financial arguments

Employers have a moral responsibility to keep their workers and others safe from harm At Yorks Boat Yard employees face daily risks such as loud noise harmful fumes fire hazards extreme heat and the danger of slips and falls Without proper risk assessments and safety controls these hazards could lead to serious injuries long-term illness or even fatal accidents Carrying out risk assessments shows that management genuinely cares about the health safety and wellbeing of workers and contractors

Many workers are migrant workers who depend on their jobs to support their families Under ILO Convention No 155 which is a fundamental convention all employers and member states have a legal obligation to ensure a safe and healthy working environment for all workers regardless of status Preventing accidents protects them from pain suffering loss of income and long term health problems as Article 4 of the Convention mandates the prevention of work related injuries by minimizing hazards in the working environment Poor control of chemicals waste could harm marine ecosystems that are vital to fisheries and tourism in the Maldives Acting responsibly helps protect the environment the community and future generations Assess risks and put suitable control measures in place In the Maldives this includes such as Guidelines performance standards If risk assessments are not carried out properly or controls are ignored employers can face enforcement action

Agency fines permit suspension stop work orders legal claims from injured workers contractors and even loss of operating licences or approvals Employers also have a legal duty of care to employees visitors and contractors A suitable and sufficient risk assessment helps show compliance and proves that reasonable steps were taken to prevent harm Accidents and environmental incidents cost money Poor risk management can lead to medical and compensation costs damage to equipment and vessels project delays downtime higher insurance costs fines clean-up costs and

	damage to reputation including loss of contracts with luxury resorts In contrast good risk assessment and strong controls reduce accidents sickness absence and disruption They improve productivity efficiency and morale lower insurance and compensation costs avoid penalties protect valuable assets like vessels hoists and workshops and help maintain client confidence and steady operations Investing in things like ventilation spill control and noise reduction is usually much cheaper than dealing with fires pollution events or long term worker illness Over time good health and safety management supports sustainable operations and profitability
--	--

Justification for action 1

Action (Taken from column 1 of risk assessment)	Engineering controls involves Perform bi-weekly hazard hunts install guardrails on all elevated platforms provide anti-slip training and boots
Specific legal arguments	As per international labour law have a legal responsibility to make sure the workplace is safe International labour standards such as the ILO Occupational Safety and Health Convention 155 Article 11 Requirement to provide information and training Article 10 Duty to ensure workplaces and structures are safe Installing guardrails on all elevated platforms is a mandatory engineering control to prevent falls from height Providing anti slip training ensures workers understand safe movement and hazard awareness require employers to identify hazards assess risks and implement proper safety measures Slips trips and falls are common workplace hazards and failure to control them can lead to legal issues fines or claims if a worker is injured Following these safety steps ensures will comply with international labour standards and demonstrate that we care about the wellbeing of our employees
Consideration of likelihood AND severity - types of injury or ill health - number of workers at risk - how often the activity is carried out - how widespread the risk is	Slips trips and falls can cause serious injuries including fractures and head injuries The risk is higher during the monsoon season when surfaces are wet and during crane operations when workers are moving around a lot Many technicians and operators are exposed to this risk every day The risk is widespread as it covers walkways platforms and work areas throughout the yard These actions are designed to significantly reduce the chance of slips trips and falls Guardrails will prevent falls from height anti slip mats boots and training will improve safe movement and regular hazard hunts will help identify new risks quickly The one-month timescale is realistic because these measures are practical easy to implement and will start giving results immediately While it may not remove the risk completely these steps will

	greatly reduce both the likelihood and severity of injuries and make the workplace much safer for everyone
How effective the action is likely to be in controlling the risk. This should include: - the intended impact of the action; - justification for the timescale that you indicated in your risk assessment; and - whether you think the action will fully control the risk	These actions are designed to significantly reduce the chance of slips trips and falls Guardrails will prevent falls from height anti slip mats boots and training will improve safe movement and regular hazard hunts will help identify new risks quickly The one-month timescale is realistic because these measures are practical easy to implement and will start giving results immediately While it may not remove the risk completely these steps will greatly reduce both the likelihood and severity of injuries and make the workplace much safer for everyone

Justification for action 2

Action (Taken from column 2 of risk assessment)	Upgrade to filtered exhaust systems in enclosed repair areas introduce
Specific legal arguments	The legal arguments are based on international labor law particularly the ILO Occupational Safety and Health Convention 155 which requires employers to provide a safe working environment identify hazards assess risks and implement effective controls Exposure to welding fumes fiberglass dust and solvent vapors can cause both acute and chronic respiratory problems making this a high-risk hazard under international standards Article 16 Employers are required to ensure that the working environment is safe and free from hazards so far as reasonably practicable Forms the core legal duty to assess risks and implement effective controls By implementing PPE proper ventilation filtered exhaust systems health screenings training and shift rotations the employer is taking all reasonable steps to prevent harm This demonstrates compliance with the Conventions requirements and reduces the likelihood of legal claims enforcement actions or penalties The legal justification is further strengthened because the measures address both immediate risks such as acute irritation and long term health effects such

	as chronic respiratory disease for all workers who are regularly exposed showing due diligence and commitment to worker safety
Consideration of likelihood AND severity • types of injury or ill health • number of workers at risk • how often the activity is carried out • how widespread the risk is	The types of injury or ill health are justified because exposure to welding fumes fiberglass dust and solvent vapors is known to cause acute irritation and chronic respiratory problems which are well documented internationally The number of workers at risk is high because most technicians and staff spend long hours in workshops performing activities that generate fumes and dust The frequency of the activity is daily making the likelihood of exposure and potential health effects significant The risk is widespread because multiple enclosed repair areas and workstations are used regularly by workers and contractors demonstrating that the hazard is not isolated These factors together justify the need for strong controls monitoring and training to protect worker health and comply with international labour standards
How effective the action is likely to be in controlling the risk. This should include: • the intended impact of the action; • justification for the timescale that you indicated in your risk assessment; and • whether you think the action will fully control the risk	The intended impact of these actions is to significantly reduce inhalation of hazardous fumes and dust PPE will prevent direct exposure ventilation and filtered exhaust systems will lower airborne Concentrations daily health screenings and annual spirometry testing will help identify early signs of respiratory problems and rotation of shifts will limit total exposure The six-month timescale is justified because installing filtered exhaust systems setting up health monitoring and training workers requires careful planning and resources while PPE ventilation and training can begin immediately These actions will not completely remove the risk but they will greatly reduce both the likelihood and severity of respiratory issues and improve overall workplace health demonstrating compliance with international labor standards and a strong commitment to worker wellbeing

Justification for action 3

Action (Taken from column 6 of risk assessment)	Implement lockout tagout procedures for all electrical work Conduct annual wiring inspections
Specific legal arguments	Under international labour law employers have a legal responsibility to provide a safe working environment and protect workers from electrical hazards international labour standards ILO Occupational Safety and Health Convention 155 require employers to identify hazards assess risks and implement effective control measures (Article 4). Specifically, Article 16 mandates that all machinery and equipment under an employer's control must be safe and without risk to health. Electric shocks burns and electrocution are recognised workplace hazards and failure to control them can result in legal claims enforcement actions or penalties Implementing lockout tagout procedures annual wiring inspections weatherproof enclosures electrical safety audits and training demonstrates compliance with international labour standards and shows a strong commitment to the health safety and wellbeing of electricians and general staff
Consideration of likelihood AND severity - types of injury or ill health - number of workers at risk - how often the activity is carried out - how widespread the risk is	The types of injury or ill health include electric shocks burns and electrocution which can be very serious or even fatal The number of workers at risk is high because electricians and general staff work with electrical equipment and live circuits every day The activity is carried out daily during maintenance repair and normal operations making the chances of accidents high The risk is widespread because electrical systems are all over the site and outdoor outlets are used in many areas These reasons show why we need lockout tagout procedures regular inspections safety audits weatherproof enclosures and proper training to keep workers safe and follow international labour standards
How effective the action is likely to be in controlling the risk. This should include: - the intended impact of the action; - justification for the timescale that you indicated in your risk assessment; and	The intended impact of these actions is to greatly reduce the chances of electric shocks burns and electrocution Lockout tagout procedures and training will make sure workers do not come in contact with live circuits Regular annual wiring inspections and quarterly safety audits will help find potential hazards before they cause harm Upgrading to weatherproof enclosures will protect outdoor outlets from rain moisture and monsoon conditions

whether you think the action will fully control the risk	The three-month timescale is practical because installation of enclosures and carrying out audits and training requires planning coordination and resources While these actions may not completely remove all risk they will reduce both the likelihood and severity of electrical accidents and make the workplace much safer for electricians and general staff
--	--

Part 4: Review, communicate and check

Suggested word counts for each section:

- Planned review date or period and reasoning for this: **50 - 100 words**
- How the risk assessment findings will be communicated and who needs to know the information: **100 - 150 words**
- Follow up on the risk assessment: **100 - 150 words.**

Planned review date/period with reasoning	Company policy is to review risk assessments at least every 12 months. I therefore set the review date for 12 months' time – December 2025
How the risk assessment findings will be communicated AND who you need to tell	The findings of the hazards risk assessment will be shared with all workers who are directly or indirectly exposed to electrical equipment and live circuits This includes electricians general staff supervisors and contractors and making a one to one meetings The Site Engineer and Health and Safety officer will hold a briefing session to explain the risks the actions to control them and the safe work practices that everyone must follow The key points will also be displayed on notice boards in workshops offices and worker rest areas so that everyone can see them Toolbox talks will be conducted on site to reinforce the importance of lockout tagout procedures safety audits use of PPE and proper handling of outdoor electrical outlets Supervisors will make sure that new workers or visitors are informed about the electrical risks and the safety measures in place This approach ensures that everyone understands the hazards knows what to do to stay safe and that the workplace is fully compliant with international labour standards
How you will follow up on the risk assessment to check that the actions have been carried out	To make sure all the actions from the hazards risk assessment are carried out the Engineering manager and Health and Safety officer will regularly check the progress of each control measure by setting up a auto reminder by calendar They will verify that lockout tagout procedures are being followed that all electricians and staff are using PPE and that training sessions have been completed Annual wiring inspections and quarterly audits will be monitored to confirm they are done on schedule The installation of weatherproof enclosures will be inspected and documented Shift supervisors will report any issues or noncompliance to the Health and Safety officer so that corrective action can be taken immediately Regular meetings will be held to review the progress and ensure all workers understand and follow the safety measures This follow up process helps make sure the risk is properly managed and the workplace stays safe for everyone