
Using Generative Adversarial Networks as the model of an estimation of distribution algorithm

1 Description

Estimation of Distribution Algorithms (EDAs, [1, 2, 3]) are optimization algorithms that use probabilistic models to capture the most relevant features of the solutions with higher values. EDAs have been applied to a variety of optimization problems from domains such as Bioinformatics [4], Energy [5, 6], vehicle [7] design, etc.

Recently, Generative Adversarial Networks (GANs) [8] have been proposed as an alternative to classical probabilistic models in the context of EDAs [9]. The reported results show that GAN-EDA is not competitive, neither in the number of fitness evaluations required, nor in the computational effort. However, the application of GAN as suggested in [8] does not exhaust the possibilities of GAN as models.

2 Objectives

The goal of the project is to implement in Python an estimation of distribution algorithm that uses a generative adversarial network. The work presented in [9] can be take as a reference of how to insert GAN in EDAs. The project should test the implemented algorithm it in the optimization of different functions (see [9] for examples of functions).

As in other projects, a report should describe the characteristics of the design, implementation, and results. A Jupyter notebook should include calls to the implemented function that illustrate the way it works.

3 Suggestions

- The *DEAP* library <https://code.google.com/p/deap/> could be used as a basis to create the EDA. One EDA (UMDA) is implemented as part of this library. Different implementations of GANs in *tensorflow* are available <https://github.com/carpedm20/DCGAN-tensorflow>, <https://github.com/ckmarkoh/GAN-tensorflow>. Implementations in *keras* <https://github.com/bstriner/keras-adversarial> are also available. Therefore it is possible to combine these implementations to complete the project.
- As part of the comparison other classes of models based on DNNs could also be included as models of the EDAs.

References

- [1] H. Mühlenbein. The equation for response to selection and its use for prediction. *Evolutionary Computation*, 5(3):303–346, 1997.
- [2] P. Larrañaga and J. A. Lozano, editors. *Estimation of Distribution Algorithms. A New Tool for Evolutionary Computation*. Kluwer Academic Publishers, Boston/Dordrecht/London, 2002.

- [3] J. A. Lozano, P. Larrañaga, I. Inza, and E. Bengoetxea, editors. *Towards a New Evolutionary Computation: Advances on Estimation of Distribution Algorithms*. Springer, 2006.
- [4] R. Armañanzas, I. Inza, R. Santana, Y. Saeys, J. L. Flores, J. A. Lozano, Y. Van de Peer, R. Blanco, V. Robles, C. Bielza, and P. Larrañaga. A review of estimation of distribution algorithms in bioinformatics. *BioData Mining*, 1(6):doi:10.1186/1756-0381-1-6, 2008.
- [5] Márcio Henrique da Silva and Roberto Schirru. A self-adaptive quantum PBIL method for the nuclear reload optimization. *Progress in Nuclear Energy*, 74:103–109, 2014.
- [6] Komla Folly. Parallel PBIL applied to power system controller design. *Journal of Artificial Intelligence and Soft Computing Research*, 3(3):215–223, 2013.
- [7] Wencong Su and Mo-Yuen Chow. Performance evaluation of an EDA-based large-scale plug-in hybrid electric vehicle charging algorithm. *Smart Grid, IEEE Transactions on*, 3(1):308–315, 2012.
- [8] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.
- [9] Malte Probst. Generative adversarial networks in estimation of distribution algorithms for combinatorial optimization. *CoRR*, abs/1509.09235, 2015.