
Fusing animal images using deep learning

1 Description

Adversarial Networks [1], Variational Autoencoders [2] and other generative DNNs allow to learn generative models able to reproduce distributions. They have been successfully applied to create artificial images that resemble real images. Convolutional neural networks [3, 4, 5, 6, 7] have been also applied to manipulate artistic images. For example, they have been used for style transfer [8, 9, 10, 11] or image translation [12, 13].

2 Objectives

Chimeras are mythical animals formed from parts of various animals. The goal of this project is to design and implement a deep learning approach (any of those mentioned in the previous section) for naturally fusing images of different animals (e.g., cats and horses) to create a “chimera”.

The student should: 1) Select an appropriate DNN architecture. 2) Select convenient image datasets. 3) Implement the learning procedure that produces as output the fused images. 4) Although the evaluation of this project will be based on the quality of the images produced, a metric to evaluate whether the images are actually the fusion of the two animals can be also implemented.

As in other projects, a report should describe the characteristics of the design, implementation, and results. A Jupyter notebook should include calls to the implemented function that illustrate the way it works.

3 Suggestions

- Read the relevant bibliography about style transfer and image translation [8, 9, 10, 11, 12, 13].
- Implementations can use any Python library that implements DNNs.

References

- [1] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.
- [2] Diederik P Kingma and Max Welling. Auto-encoding variational Bayes. *CoRR*, abs/1312.6114, 2013.
- [3] Dan C Ciresan, Ueli Meier, Jonathan Masci, Luca Maria Gambardella, and Jürgen Schmidhuber. Flexible, high performance convolutional neural networks for image classification. In *IJCAI Proceedings-International Joint Conference on Artificial Intelligence*, volume 22, page 1237. Barcelona, Spain, 2011.
- [4] Yangqing Jia, Evan Shelhamer, Jeff Donahue, Sergey Karayev, Jonathan Long, Ross Girshick, Sergio Guadarrama, and Trevor Darrell. Caffe: Convolutional architecture for fast feature embedding. In *Proceedings of the 22nd ACM international conference on Multimedia*, pages 675–678. ACM, 2014.

- [5] Yoon Kim. Convolutional neural networks for sentence classification. *CoRR*, abs/1408.5882, 2014.
- [6] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.
- [7] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.
- [8] Alex J Champandard. Semantic style transfer and turning two-bit doodles into fine artworks. *CoRR*, abs/1603.01768, 2016.
- [9] Leon A Gatys, Alexander S Ecker, and Matthias Bethge. A neural algorithm of artistic style. *arXiv preprint arXiv:1508.06576*, 2015.
- [10] Leon A Gatys, Alexander S Ecker, and Matthias Bethge. Image style transfer using convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2414–2423, 2016.
- [11] Fujun Luan, Sylvain Paris, Eli Shechtman, and Kavita Bala. Deep photo style transfer. *arXiv preprint arXiv:1703.07511*, 2017.
- [12] Hao Dong, Paarth Neekhara, Chao Wu, and Yike Guo. Unsupervised image-to-image translation with generative adversarial networks. *arXiv preprint arXiv:1701.02676*, 2017.
- [13] He Zhang, Vishwanath Sindagi, and Vishal M Patel. Image de-raining using a conditional generative adversarial network. *arXiv preprint arXiv:1701.05957*, 2017.