SK ProFund

Step-by-step setup, running and editing guide • Windows + XAMPP + VS Code

You need a Windows computer for these instructions. The code is already written; you do not need to type every file again. This is a browser-based website using PHP, HTML, CSS, JavaScript and MySQL.

1. Install the programs

Install **XAMPP with PHP 8.2 or newer** and **Visual Studio Code**. This guide assumes XAMPP is installed in **C:\xampp**.

Official downloads: apachefriends.org and code.visualstudio.com.

2. Download your application code

Open the application branch on GitHub, then select **Code → Download ZIP**. Make sure the selected branch is **skprofund-web-app**, not main.

Open the SK ProFund application branch

3. Extract the ZIP

Right-click the downloaded ZIP and choose **Extract All**. Rename the extracted project folder to **Skprofund-system**.

4. Move the project into XAMPP

Move the folder to this location:

```
C:\xampp\htdocs\Skprofund-system
```

Open it and check that **app**, **bin**, **config**, **database**, **public** and **README.md** are directly inside. Avoid an extra nested project folder.

Open the project

Steps 5–7 • Editor, services and database

5. Open the code in VS Code

Open VS Code. Select **File → Open Folder**, then choose:

```
C:\xampp\htdocs\Skprofund-system
```

The Explorer sidebar should show your project folders. Click a folder or file to view the code.

6. Start Apache and MySQL

Open the **XAMPP Control Panel**. Click **Start** beside both **Apache** and **MySQL**. Keep the control panel open while developing.

Apache runs PHP and serves the pages. MySQL stores the records. HTML, CSS and JavaScript are loaded automatically by your browser; you do not start them separately.

7. Import the database

Open your browser and enter:

```
http://localhost/phpmyadmin
```

- Select **Import**.
- Select **Choose File**.
- Choose **database/schema.sql** inside your project folder.
- Click **Go** or **Import**.
- Confirm that the **skprofund** database appears in the left sidebar.

Import the SQL once into a fresh installation. It creates the database, tables and five role definitions. It does not create login accounts or sample financial records. Do not re-import over existing work.

Configure and sign in

Steps 8–10 • Private settings and the first Admin

8. Create your local configuration

In VS Code, open **config**. Copy **example.php** and rename the copy to **local.php**. Replace its contents with the following and press **Ctrl + S**:

```
<?php
return [
    'dsn' => 'mysql:host=127.0.0.1;port=3306;'
           . 'dbname=skprofund;charset=utf8mb4',
    'user' => 'root',
    'password' => '',
    'storage' => 'C:/xampp/skprofund-private',
];
```

These settings assume default local XAMPP MySQL access. If you configured a password or another port, use your actual settings. Keep local.php private and do not upload it to GitHub.

9. Create the receipt upload folder

In Windows File Explorer, create this folder outside **htdocs**:

```
C:\xampp\skprofund-private
```

Receipt images will be stored here. Apache must be able to write to this folder.

10. Create your Admin account

In VS Code, select **Terminal → New Terminal**. Enter each command separately:

```
cd C:\xampp\htdocs\Skprofund-system
C:\xampp\php\php.exe bin\create-admin.php
```

Enter your full name, email and a password of at least **12 characters**. Password input may be visible in the terminal, so do this privately. An active Admin already existing will stop this command.

Run and test the website

Steps 11–13 • Initial setup and a complete workflow

11. Open your website

With Apache and MySQL running, enter this address in your browser:

```
http://localhost/Skprofund-system/public/
```

Choose **SK Officials**, then sign in using the Admin account you created. This entry also serves Admin, Chairperson and Treasurer accounts.

12. Configure your system

• As Admin, open **Settings** and add project categories.

• Add your fund sources.

• Open **Manage Users** and create Chairperson, Treasurer and SK Official accounts.

• Assign the correct role to each account. Give temporary passwords privately; new users must change them at first login.

13. Test a complete workflow

Use fictional test records first. Log out and sign in with the appropriate account for each action:

1. Official: Submit a project proposal.

2. Chairperson: Approve the proposal, then separately approve public viewing.

3. Treasurer: Record authorized funds received and submit an allocation request.

4. Chairperson: Approve the allocation.

5. Treasurer: Submit a fund-release request.

6. Chairperson: Approve the release.

7. Treasurer: Record an expense; enter receipt date, supplier/payee, amount and reference; upload the receipt image.

8. All relevant users: Check the project and financial summaries. The remaining balance should update from database records.

Initial lists and financial totals are empty until records are entered. Youth/Residents can browse approved public projects without signing in. GitHub and Google Drive store the code; they do not run the PHP/MySQL website.

Start editing your code

Step 14 • Make one change, save, refresh and test

14. Make your first small change

• Open **public/assets/css/app.css**.

• Near the beginning, find the teal color declaration below.

• Change its color value, then press **Ctrl + S**.

• Refresh the website in your browser to see the change.

```
--teal:#77afb7;
```

Where to make other changes

Page text and forms
app/pages/

Colors, spacing and responsive layouts
public/assets/css/app.css

Menus, dialogs and browser interactions
public/assets/js/app.js

Login, approvals and saving records
app/actions.php

Shared header and sidebar
app/layout.php

Database structure
database/schema.sql

Changing schema.sql does not update an existing database automatically. Back up the database before making schema changes, and use a reviewed migration rather than deleting real records.

If something does not work

• **Page not found:** check the folder name and the /public/ URL.

• **Database unavailable:** check that MySQL is running, the SQL import succeeded, and local.php matches your settings.

• **Receipt upload fails:** check folder permissions and use JPEG, PNG or WebP under 5 MB. In php.ini, use upload_max_filesize of at least 5M and post_max_size of at least 12M; restart Apache after edits.

• **Apache/MySQL will not start:** inspect the XAMPP logs for a port conflict or startup error.

Always run through localhost. Double-clicking PHP files or using VS Code Live Server will not run the backend correctly. Keep Apache and MySQL running while using the system.