Setting Up the Menu (menu.xml)

Inside the menu xml file you'll find a tree-like structure for setting up the menu. Below is an example of what a page's settings look like:

```
<page>
        <menuTitle>HOME</menuTitle>
        <deepLinkURL>home</deepLinkURL>
        <urlTarget>_self</urlTarget>
        <bgURL>images/backgrounds/wall.jpg</bgURL>
        <bgAlign>tl</bgAlign>
        <moduleURL>banner.swf</moduleURL>
        <modulePos>mc</modulePos>
        <moduleType>customModule</moduleType>
        <moduleXML>xml/banner.xml</moduleXML>
</page>
```

- menuTitle = the title of the menu item
- deepLinkURL = the deep-link url page name
- urlTarget = the window target if an external link is to be called
- bgURL = the url of your background image
- bgAlign = the background image alignment
- moduleURL = the module to load in for the page
- modulePos = the module's position
- moduleType = the type of module to load in. see below for options
- moduleXML = the url of the module's xml file

ACCEPTED PARAMETERS FOR "bgAlign"

tl = top-left
tc = top-center
tr = top-right
lc = left-center
mc = middle-center
rc = right-center
bl = bottom-left
bc = bottom-center
br = bottom-right

ACCEPTED PARAMETERS FOR "modulePos"

longText:
1. "left"
2. "center"
3. "right"

gallery:
1. "lc" (left-center)

portfolio:
1. "tc" (top-center)

news:
1. "lc" (left-center)

banner:
1. "tl" (top-left)
2. "tc" (top-center)
3. "tr" (top-right)
4. "lc" (left-center)
5. "mc" (middle-center)
6. "rc" (right-center
7. "bl" (bottom-left)
8. "bc" (bottom-center)
9. "br" (bottom-right)

contact:
1. "tl" (top-left)
2. "tc" (top-center)
3. "tr" (top-right)
4. "lc" (left-center)
5. "mc" (middle-center)
6. "rc" (right-center)
7. "bl" (bottom-left)
8. "bc" (bottom-center)
9. "br" (bottom-right)

ACCEPTED PARAMETERS FOR " moduleType"

1. "customModule" (a module that came with the Q)
2. "yourSwf" (your own swf, this can be a single image as well)

SPECIAL NOTES:

- A static image or 3rd party swf can be loaded as a module.
- If a 3rd party swf is loaded, the moduleXML parameter will be ignored
- If you wish to not load in a module (for example a menu item that has a sub-menu), write null for all parameters except the "menuTitle"
- deepLinkURL will be converted to lower-case
- deepLinkURL will be joined to one string/word. For example: "my photos" would become "myphotos". However, "my_photos" would remain "my_photos"

Please refer to the module xml files located in the "module help" folder to continue...