

Semantic Design

The following is what I call a 'semantic design' for Nu's scripting system (as well as an unrelated replacement for micro-services called MetaFunctions). The concept of a semantic design is inspired by Conal Elliot's denotational design - <https://www.youtube.com/watch?v=bmKYiUOEo2A>. The difference is that semantic design does not connect back to an existing language such as mathematics but is instead built upon an orthogonal set of axiomatic definitions.

Whereas denotational design is a more thorough design treatment that is used in greenfield development to yield high-precision design artifacts, semantic design works well for projects that don't satisfy any simple denotational design, such as those that are already far into their implementation.

To specify semantic designs generally, I've created a meta-language called ADELA (for Axiomatic Design Language). First, we present the definition of ADELA, then the semantic design for Nu and MetaFunctions in terms of ADELA.

Adela Language Definition

Axiom := Axiom[!] "Informal definition."

where ! denotes intended effectfulness

Meaning Type := A -> ... -> Z

where A ... Z are **Type Expressions**

Meaning Defn := f (a : A) ... (z : Z) : R = **Sentence** | **Axiom**

where f is the **Meaning Identifier**
and a ... z are **Parameter Identifiers**
and A ... Z, R are **Type Expressions**

Sentence := **Example**: f a (g b)

where f and g are a **Meaning Identifiers**
and a and b are **Parameter Identifiers**

Product := MyProd<...> = **A** | (A : **A**, ..., Z : **Z**) | **Axiom**

where MyProd<...> is the **Product Identifier**
and A ... Z are **Field Identifiers**
and **A** ... **Z** are **Type Expressions**

Sum := MySum<...> =
 | A of (**A** | **Axiom**)
 | ...
 | Z of (**Z** | **Axiom**)

where MySum<...> is the **Sum Identifier**
and A ... Z are **Case Identifiers**
and **A** ... **Z** are **Type Expressions**

Type Identifier := **Product Identifier** | **Sum Identifier**

Type Expression := **Meaning Type** | **Type Identifier**

where A ... Z are **Type Expressions**

Type Parameters := **Type Identifier**<
 A, ..., Z;
 A<A, ..., Z>; ...; **Z**<...>>

where A ... Z are **Type Expressions**
and **A** ... **Z** are **Category Identifiers** used for
constraining A ... Z

Category := category MyCat<...> =
 | f = A
 | ...
 | g = Z

where MyCat<...> is the **Category Identifier**
and f ... g are **Equivilence Identifiers**
and A ... Z are **Type Expressions**

Witness := witness **A** =
 | f (a : A) ... (z : Z) : R = **Sentence** | **Axiom**
 | ...
 | g (a : A) ... (z : Z) : R = **Sentence** | **Axiom**

where **A** is a **Category Identifier**
and f ... g are **Equivilence Identifiers**
and a ... z are **Parameter Identifiers**
and A ... Z, R are **Type Expressions**

Categorization := **Rule:** *iff type A has a witness for category **A**; type A is allowable for type parameter constrained to category **A***

```
fun a b ... z -> expr := \a (\b (... \z.expr))
```

```
a -> b := _ = (_ : a) : b
```

Adela Language Prelude

```
Unit = Axiom "The empty value."
```

```
category Semigroup<a> =  
  | append = a -> a -> a
```

```
category Monoid<a; Semigroup<a>> =  
  | empty = a
```

Nu Semantic Design

Relation = Axiom "Indexes a simulant or event relative to the local simulant."

Address = Axiom "Indexes a global simulant or event."

Name = Axiom "Indexes a property of a simulant."

Stream<a> = Axiom "A stream of values."

eventStream<a> : Address -> Stream<a> = Axiom "Construct a stream of values from event data."

foldStream<a, b> : (b -> a -> b) -> Stream<a> -> b = Axiom "Fold over a stream."

productStream<a, b> : Stream<a> -> Stream -> Stream<a, b> = Axiom "Combines two streams into a single product stream"

sumStream<a, b> : Stream<a> -> Stream -> Stream<(a, b)> = Axiom "Combines two streams into a single sum stream."

get<a> : Name -> Relation -> a = Axiom "Retrieves a property of a simulant indexed by Relation."

getAsStream<a> : Name -> Relation -> Stream<a> = Axiom "Construct a stream of values from a simulant property."

set<a> : Name -> Relation -> a -> a = Axiom! "Updates a property of a simulant indexed by Relation, then returns its value."

setToStream<a> name relation stream = foldStream (fun _ -> set<a> name relation) stream

Semantic Design for MetaFunctions (a replacement for micro-services - unrelated to Nu)

Symbol = Axiom "Symbolic type such as the one defined by Prime."

Vsync<a> = Axiom "Potentially asynchronous monad such as the one defined by Prime."

IPAddress = String // a network address

Port = Int // a network port

Endpoint = (IPAddress, Port)

Intent = String // the intended meaning of a MetaFunction (indexes functionality from a provider)

Container = Intent -> Symbol -> Vsync<Symbol>

Provider = Endpoint | Container

MetaFunction = Provider -> Intent -> Symbol -> Vsync<Symbol>

makeContainer (asynchronounous : Bool) (gitUrl : String) (envDeps : Map<String, Any>) : Container = Axiom "Make a container configured with its Vsync as asynchronous or not, built from source pulled from the givern GIT url, and provided the given environmental dependencies."

attachDebugger (container : Container) = Axiom! "Attach debugger to code called inside the given container."

call (mfn : MetaFunction) provider intent args : Vsync<Symbol> = mfn provider intent args