Reflection

1. Since my file name is Exercise1.java, from the original “public class BadLogin extends JFrame and public class BadLogin” (line 4 – line 5) and “public static void main String {new BadLogin}” (line 45), I change all the BadLogin to Exercise1

```
4   public class Exercise1 extends JFrame {
5       public Exercise1() {
```

```
44      public static void main(String[] args) {
45          SwingUtilities.invokeLater(() -> new Exercise1());
```

2. Added paddings on the panel to make the login windows looks like a real website (line 11- 29)

```
11          JPanel mainPanel = new JPanel(new GridLayout(rows: 3, cols: 2, hgap: 10, vgap: 10));
12          mainPanel.setBorder(BorderFactory.createEmptyBorder(top: 15, left: 15, bottom: 15, right: 15));
13
14          JLabel l1 = new JLabel(text: "帳號:");
15          JTextField t1 = new JTextField();
16
17          JLabel l2 = new JLabel(text: "密碼:");
18          JPasswordField t2 = new JPasswordField();
19
20          JButton btn = new JButton(text: "登入");
21
22          mainPanel.add(l1);
23          mainPanel.add(t1);
24          mainPanel.add(l2);
25          mainPanel.add(t2);
26          mainPanel.add(new JLabel());
27          mainPanel.add(btn);
28
29          add(mainPanel);
```

3. Using JPasswordField instead of JTextField to for password input security (line 14-18)

```
14          JLabel l1 = new JLabel(text: text: "帳號:");
15          JTextField t1 = new JTextField();
16
17          JLabel l2 = new JLabel(text: text: "密碼:");
18          JPasswordField t2 = new JPasswordField();
```

4. There was no “setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE)” so when the user closes the windows, the Java process would not be terminated which is a crucial operation. Added it on my code on line 8.

```
8           setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
```