

# Лабораторная работа № 2.4 «Рекурсивный спуск»

6 мая 2024 г.

Сергей Виленский, ИУ9-62Б

## Цель работы

Целью данной работы является изучение алгоритмов построения парсеров методом рекурсивного спуска.

## Индивидуальный вариант

Объявления типов и констант в Паскале:

В record'e точка с запятой разделяет поля и после case дополнительный end не ставится. См. <https://bernd-oppolzer.de/PascalReport.pdf>, третья с конца страница.

```
Type
  Coords = Record x, y: INTEGER end;
Const
  MaxPoints = 100;
type
  CoordsVector = array 1..MaxPoints of Coords;

(* графический и текстовый дисплеи *)
const
  Heigh = 480;
  Width = 640;
  Lines = 24
  Columns = 80;
type
  BaseColor = (red, green, blue, highlited);
  Color = set of BaseColor;
  GraphicScreen = array 1..Heigh of array 1..Width of Color;
  TextScreen = array 1..Lines of array 1..Columns of
    record
      Symbol : CHAR;
```

```

        SymColor : Color;
        BackColor : Color
    end;

{ определения токенов }
TYPE
    Domain = (Ident, IntNumber, RealNumber);
    Token = record
        fragment : record
            start, following : record
                row, col : INTEGER
            end
        end;
    end;
    case tokType : Domain of
        Ident : (
            name : array 1..32 of CHAR
        );
        IntNumber : (
            intval : INTEGER
        );
        RealNumber : (
            realval : REAL
        )
    end;

    Year = 1900..2050;

    List = record
        value : Token;
        next : ^List
    end;

```

Ключевые слова и идентификаторы не чувствительны к регистру.

## Реализация

### Лексическая структура

Лексическая структура в порядке убывания приоритетов доменов

```

TypeIdentifier    -> INTEGER
                  | BOOLEAN
                  | REAL
                  | CHAR
                  | TEXT
ConstantIdentifier -> Identifier

```

```

Identifier      -> Letter (Letter|Digit)*
Letter          -> [a-zA-Z]
UnsignedInteger -> Digit+
UnsignedNumber  -> UnsignedInteger (. Digit+)? (E [+
]? UnsignedInteger)?
Digit           -> [0-9]

```

## Грамматика языка

```

# program
Program -> Block

# block
Block -> KW_CONST BlockConstSequence Block
      | KW_TYPE BlockTypeSequence Block
      | ε
BlockConstSequence -> BlockConst
                   | BlockConst BlockConstSequence
BlockConst -> IDENTIFIER '=' Constant ';'
BlockTypeSequence -> BlockType
                   | BlockType BlockTypeSequence
BlockType -> IDENTIFIER '=' Type ';'

# field list
FieldList -> IdentifierWithTypeList
           | IdentifierWithTypeList ';' CaseBlock
IdentifierWithTypeList -> IdentifierWithType
                       | IdentifierWithType ';' IdentifierWithTypeList
IdentifierWithType -> IdentifierList ':' Type
CaseBlock -> KW_CASE IDENTIFIER ':' TypeIdentifier KW_OF CaseVariantSequence
CaseVariantSequence -> CaseVariant
                   | CaseVariant ';' CaseVariantSequence
CaseVariant -> ConstantList ':' '(' FieldList ')'
ConstantList -> Constant
              | Constant ',' ConstantList

# type
Type -> SimpleType
     | '^' TypeIdentifier
     | KW_PACKED TypeAfterPacked
     | TypeAfterPacked

TypeAfterPacked -> KW_ARRAY SimpleTypeList KW_OF Type
                | KW_FILE KW_OF Type
                | KW_SET KW_OF SimpleType
                | KW_RECORD FieldList KW_END

```

```

SimpleTypeList -> SimpleType
                | SimpleType ',' SimpleTypeList

# simple type
SimpleType -> TypeIdentifier
            | '(' IdentifierList ')'
            | Constant '.' '.' Constant
TypeIdentifier -> CommonTypeIdentifier
                | IDENTIFIER
CommonTypeIdentifier -> KW_INTEGER
                    | KW_BOOLEAN
                    | KW_REAL
                    | KW_CHAR
                    | KW_TEXT
IdentifierList -> IDENTIFIER
                | IDENTIFIER ',' IdentifierList

# constant
Constant -> UnarSign ConstantIdentifier
            | ConstantIdentifier
            | UnarSign UNSIGNED_NUMBER
            | UNSIGNED_NUMBER
            | '\\' CHAR_SEQUENCE '\\'
UnarSign -> '+'
            | '-'
ConstantIdentifier -> IDENTIFIER

```

## Программная реализация

### Parser/Block/Block.ref

```

*$FROM Parser/Block/BlockConstSequence
*$FROM Parser/Block/BlockTypeSequence
$EXTERN BlockConstSequence, BlockTypeSequence;

$ENTRY Block {
    /* Block -> KW_CONST BlockConstSequence Block */
    () (KW_CONST e.C) e.Tokens t.Errs
        = <Block ((KW_CONST e.C)) e.Tokens t.Errs>;

    ((KW_CONST e.C)) (BlockConstSequence e.B) e.Tokens t.Errs
        = <Block ((KW_CONST e.C) (BlockConstSequence e.B)) e.Tokens t.Errs>;
    ((KW_CONST e.C)) e.Tokens t.Errs
        = <Block ((KW_CONST e.C)) <BlockConstSequence () e.Tokens t.Errs>>;

    ((KW_CONST e.C) t.BS) (Block e.B) e.Tokens t.Errs

```

```

        = <Block ((KW_CONST e.C) t.BS (Block e.B)) e.Tokens t.Errs>;
((KW_CONST e.C) t.BS) e.Tokens t.Errs
    = <Block ((KW_CONST e.C) t.BS) <Block () e.Tokens t.Errs>>;

((KW_CONST e.C) t.BS t.B) e.Tokens t.Errs
    = (Block (KW_CONST BlockConstSequence Block) (KW_CONST e.C) t.BS t.B) e.Tokens t.Errs;

/* Block -> KW_TYPE BlockTypeSequence Block */
() (KW_TYPE e.T) e.Tokens t.Errs
    = <Block ((KW_TYPE e.T)) e.Tokens t.Errs>;

((KW_TYPE e.T)) (BlockTypeSequence e.B) e.Tokens t.Errs
    = <Block ((KW_TYPE e.T) (BlockTypeSequence e.B)) e.Tokens t.Errs>;
((KW_TYPE e.T)) e.Tokens t.Errs
    = <Block ((KW_TYPE e.T)) <BlockTypeSequence () e.Tokens t.Errs>>;

((KW_TYPE e.T) t.BS) (Block e.B) e.Tokens t.Errs
    = <Block ((KW_TYPE e.T) t.BS (Block e.B)) e.Tokens t.Errs>;
((KW_TYPE e.T) t.BS) e.Tokens t.Errs
    = <Block ((KW_TYPE e.T) t.BS) <Block () e.Tokens t.Errs>>;

((KW_TYPE e.T) t.BS t.B) e.Tokens t.Errs
    = (Block (KW_TYPE BlockTypeSequence Block) (KW_TYPE e.T) t.BS t.B) e.Tokens t.Errs;

/* Block -> ε */
() e.Tokens t.Errs
    = (Block ()) e.Tokens t.Errs;
}

```

#### Parser/Block/BlockConst.ref

```

*$FROM Parser/Constant/Constant
$EXTERN Constant;

$ENTRY BlockConst {
    /* BlockConst -> IDENTIFIER '=' Constant ';' */
    () (IDENTIFIER e.I) e.Tokens t.Errs
        = <BlockConst ((IDENTIFIER e.I)) e.Tokens t.Errs>;
    () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <BlockConst ()
            e.Tokens (e.Errs (t.Start BlockConst '.'
                Unexpected t.Type '.'
                Expected '[' IDENTIFIER '].'
                Skipped '.'))>;
    () '$' (e.Errs)
        = (BlockConst ())
}

```

```

'$'
(e.Errs ((EOF) BlockConst '.'
    Unexpected End Of File '.'
    Expected '[' IDENTIFIER '].'
    Terminated '.'));

(t.I) ('=' e.E) e.Tokens t.Errs
= <BlockConst (t.I ('=' e.E)) e.Tokens t.Errs>;
(t.I) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
= <BlockConst (t.I)
    ('=' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
    e.Tokens (e.Errs (t.Start BlockConst '.'
        Unexpected t.Type '.'
        Expected '[' '=' '].'
        Inserted '.'))>;
(t.I) '$' (e.Errs)
= <BlockConst (t.I)
    ('=' ((0 0) (0 0))) '$'
    (e.Errs ((EOF) BlockConst '.'
        Unexpected End Of File '.'
        Expected '[' '=' '].'
        Inserted '.'))>;

(t.I t.E) (Constant e.C) e.Tokens t.Errs
= <BlockConst (t.I t.E (Constant e.C)) e.Tokens t.Errs>;
(t.I t.E) e.Tokens t.Errs
= <BlockConst (t.I t.E) <Constant () e.Tokens t.Errs>>;

(t.I t.E t.C) (';' e.S) e.Tokens t.Errs
= <BlockConst (t.I t.E t.C (';' e.S)) e.Tokens t.Errs>;
(t.I t.E t.C) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
= <BlockConst (t.I t.E t.C)
    (';' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
    e.Tokens (e.Errs (t.Start BlockConst '.'
        Unexpected t.Type '.'
        Expected '[' ';' '].'
        Inserted '.'))>;
(t.I t.E t.C) '$' (e.Errs)
= <BlockConst (t.I t.E t.C)
    (';' ((0 0) (0 0))) '$'
    (e.Errs ((EOF) BlockConst '.'
        Unexpected End Of File '.'
        Expected '[' ';' '].'
        Inserted '.'))>;

(t.I t.E t.C t.S) e.Tokens t.Errs

```

```

    = (BlockConst (IDENTIFIER '=' Constant ';' ) t.I t.E t.C t.S) e.Tokens t.Errs;
}

```

#### Parser/Block/BlockConstSequence.ref

```

*$FROM Parser/Block/BlockConst
$EXTERN BlockConst;

$ENTRY BlockConstSequence {
    /* BlockConstSequence -> BlockConst BlockConstSequence */
    () (BlockConst e.B) e.Tokens t.Errs
        = <BlockConstSequence ((BlockConst e.B)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <BlockConstSequence () <BlockConst () e.Tokens t.Errs>>;

    (t.B) (BlockConstSequence e.BS) e.Tokens t.Errs
        = <BlockConstSequence (t.B (BlockConstSequence e.BS)) e.Tokens t.Errs>;
    (t.B) (IDENTIFIER e.I) e.Tokens t.Errs
        = <BlockConstSequence (t.B) <BlockConstSequence () (IDENTIFIER e.I) e.Tokens t.Errs>>;

    (t.B t.BS) e.Tokens t.Errs
        = (BlockConstSequence (BlockConst BlockConstSequence) t.B t.BS) e.Tokens t.Errs;

    /* BlockConstSequence -> BlockConst */
    (t.B) e.Tokens t.Errs
        = (BlockConstSequence (BlockConst) t.B) e.Tokens t.Errs;
}

```

#### Parser/Block/BlockType.ref

```

*$FROM Parser/Type/Type
$EXTERN Type_;

$ENTRY BlockType {
    /* BlockType -> IDENTIFIER '=' Type ';' */
    () (IDENTIFIER e.I) e.Tokens t.Errs
        = <BlockType ((IDENTIFIER e.I)) e.Tokens t.Errs>;
    () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <BlockType ()
            e.Tokens (e.Errs (t.Start BlockType '.'
                Unexpected t.Type '.'
                Expected '[' IDENTIFIER ']').'
                Skipped '.'))>;
    () '$' (e.Errs)
        = (BlockType (EOF))
            '$'

```

```

        (e.Errs ((EOF) BlockType '.'
            Unexpected End Of File '.'
            Expected '[' IDENTIFIER '].'
            Terminated '.'));

(t.I) ('=' e.E) e.Tokens t.Errs
    = <BlockType (t.I ('=' e.E)) e.Tokens t.Errs>;
(t.I) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <BlockType (t.I)
        ('=' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start BlockType '.'
            Unexpected t.Type '.'
            Expected '[' '=' '].'
            Inserted '.'))>;
(t.I) '$' (e.Errs)
    = <BlockType (t.I)
        ('=' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) BlockType '.'
            Unexpected End Of File '.'
            Expected '[' '=' '].'
            Inserted '.'))>;

(t.I t.E) (Type e.C) e.Tokens t.Errs
    = <BlockType (t.I t.E (Type e.C)) e.Tokens t.Errs>;
(t.I t.E) e.Tokens t.Errs
    = <BlockType (t.I t.E) <Type_ () e.Tokens t.Errs>>;

(t.I t.E t.C) (';' e.S) e.Tokens t.Errs
    = <BlockType (t.I t.E t.C (';' e.S)) e.Tokens t.Errs>;
(t.I t.E t.C) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <BlockType (t.I t.E t.C)
        (';' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start BlockType '.'
            Unexpected t.Type '.'
            Expected '[' ';' '].'
            Inserted '.'))>;
(t.I t.E t.C) '$' (e.Errs)
    = <BlockType (t.I t.E t.C)
        (';' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) BlockType '.'
            Unexpected End Of File '.'
            Expected '[' ';' '].'
            Inserted '.'))>;

(t.I t.E t.C t.S) e.Tokens t.Errs
    = (BlockType (IDENTIFIER '=' Type ';') t.I t.E t.C t.S) e.Tokens t.Errs;

```



```
}
```

### **Parser/Block/BlockTypeSequence.ref**

```
*$FROM Parser/Block/BlockType  
$EXTERN BlockType;
```

```
$ENTRY BlockTypeSequence {  
  /* BlockTypeSequence -> BlockType BlockTypeSequence */  
  () (BlockType e.B) e.Tokens t.Errs  
    = <BlockTypeSequence ((BlockType e.B)) e.Tokens t.Errs>;  
  () e.Tokens t.Errs  
    = <BlockTypeSequence () <BlockType () e.Tokens t.Errs>>;  
  
  (t.B) (BlockTypeSequence e.BS) e.Tokens t.Errs  
    = <BlockTypeSequence (t.B (BlockTypeSequence e.BS)) e.Tokens t.Errs>;  
  (t.B) (IDENTIFIER e.I) e.Tokens t.Errs  
    = <BlockTypeSequence (t.B) <BlockTypeSequence () (IDENTIFIER e.I) e.Tokens t.Errs>>;  
  
  (t.B t.BS) e.Tokens t.Errs  
    = (BlockTypeSequence (BlockType BlockTypeSequence) t.B t.BS) e.Tokens t.Errs;  
  
  /* BlockTypeSequence -> BlockType */  
  (t.B) e.Tokens t.Errs  
    = (BlockTypeSequence (BlockType) t.B) e.Tokens t.Errs;  
}
```

### **Parser/Constant/Constant.ref**

```
*$FROM Parser/Constant/UnarSign  
*$FROM Parser/Constant/ConstantIdentifier  
$EXTERN UnarSign, ConstantIdentifier;
```

```
$ENTRY Constant {  
  /* Constant -> UnarSign ConstantIdentifier */  
  () (UnarSign e.U) e.Tokens t.Errs  
    = <Constant ((UnarSign e.U)) e.Tokens t.Errs>;  
  () ('+' e.P) e.Tokens t.Errs  
    = <Constant () <UnarSign () ('+' e.P) e.Tokens t.Errs>>;  
  () ('-' e.M) e.Tokens t.Errs  
    = <Constant () <UnarSign () ('-' e.M) e.Tokens t.Errs>>;  
  
  ((UnarSign e.U)) (ConstantIdentifier e.C) e.Tokens t.Errs  
    = <Constant ((UnarSign e.U) (ConstantIdentifier e.C)) e.Tokens t.Errs>;  
  ((UnarSign e.U)) (IDENTIFIER e.I) e.Tokens t.Errs  
    = <Constant ((UnarSign e.U)) <ConstantIdentifier () (IDENTIFIER e.I) e.Tokens t.Errs>>;
```

```

((UnarSign e.U) (ConstantIdentifier e.C)) e.Tokens t.Errs
  = (Constant (UnarSign ConstantIdentifier) (UnarSign e.U) (ConstantIdentifier e.C)) e.Tokens t.Errs

/* Constant -> ConstantIdentifier */
() (ConstantIdentifier e.C) e.Tokens t.Errs
  = <Constant ((ConstantIdentifier e.C)) e.Tokens t.Errs>;
() (IDENTIFIER e.I) e.Tokens t.Errs
  = <Constant () <ConstantIdentifier () (IDENTIFIER e.I) e.Tokens t.Errs>>;

((ConstantIdentifier e.C)) e.Tokens t.Errs
  = (Constant (ConstantIdentifier) (ConstantIdentifier e.C)) e.Tokens t.Errs;

/* Constant -> UnarSign UNSIGNED_NUMBER */
((UnarSign e.U)) (UNSIGNED_NUMBER e.UN) e.Tokens t.Errs
  = <Constant ((UnarSign e.U) (UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs>;
((UnarSign e.U)) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <Constant ((UnarSign e.U))
    e.Tokens (e.Errs (t.Start Constant '.'
      Unexpected t.Type '.'
      Expected '[' ConstantIdentifier or UNSIGNED_NUMBER ']'.
      Skipped '.'))>;
((UnarSign e.U)) '$' (e.Errs)
  = (Constant (EOF))
    '$'
    (e.Errs ((EOF) Constant '.'
      Unexpected End Of File '.'
      Expected '[' ConstantIdentifier or UNSIGNED_NUMBER ']'.
      Terminated '.'));

((UnarSign e.U) (UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs
  = (Constant (UnarSign UNSIGNED_NUMBER) (UnarSign e.U) (UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs;

/* Constant -> UNSIGNED_NUMBER */
() (UNSIGNED_NUMBER e.UN) e.Tokens t.Errs
  = <Constant ((UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs>;

((UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs
  = (Constant (UNSIGNED_NUMBER) (UNSIGNED_NUMBER e.UN)) e.Tokens t.Errs;

/* Constant -> '\\' CHAR_SEQUENCE '\\' */
() ('\\' e.C1) e.Tokens t.Errs
  = <Constant (('\\' e.C1)) e.Tokens t.Errs>;

(('\\' e.C1)) (CHAR_SEQUENCE e.CS) e.Tokens t.Errs
  = <Constant (('\\' e.C1) (CHAR_SEQUENCE e.CS)) e.Tokens t.Errs>;

```

```

(('\' e.C1)) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <Constant (('\' e.C1))
    e.Tokens (e.Errs (t.Start Constant '.'
      Unexpected t.Type '.'
      Expected '[' CHAR_SEQUENCE '].'
      Skipped '.'))>;
(('\' e.C1)) '$' (e.Errs)
  = (Constant (EOF))
    '$'
    (e.Errs ((EOF) Constant '.'
      Unexpected End Of File '.'
      Expected '[' CHAR_SEQUENCE '].'
      Terminated '.'));

(('\' e.C1) t.CS) ('\' e.C2) e.Tokens t.Errs
  = <Constant (('\' e.C1) t.CS ('\' e.C2)) e.Tokens t.Errs>;
(('\' e.C1) t.CS) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <Constant (('\' e.C1) t.CS)
    ('\' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
    e.Tokens (e.Errs (t.Start Constant '.'
      Unexpected t.Type '.'
      Expected '[' \' '].'
      Inserted '.'))>;
(('\' e.C1) t.CS) '$' (e.Errs)
  = <Constant (('\' e.C1) t.CS)
    ('\' ((0 0) (0 0))) '$'
    (e.Errs ((EOF) Constant '.'
      Unexpected End Of File '.'
      Expected '[' \' '].'
      Inserted '.'))>;

(('\' e.C1) t.CS t.C2) e.Tokens t.Errs
  = (Constant ('\' CHAR_SEQUENCE '\') (('\' e.C1) t.CS t.C2) e.Tokens t.Errs) e.Tokens t.E

() (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <Constant ()
    e.Tokens (e.Errs (t.Start Constant '.'
      Unexpected t.Type '.'
      Expected '[' UnarSign or ConstantIdentifier or UNSIGNED_NUMBER or \' '].'
      Skipped '.'))>;
() '$' (e.Errs)
  = (Constant (EOF))
    '$'
    (e.Errs ((EOF) Constant '.'
      Unexpected End Of File '.'

```

```

        Expected '[' UnarSign or ConstantIdentifier or UNSIGNED_NUMBER or '\\' '].'
        Terminated '.');
    }

```

#### Parser/Constant/ConstantIdentifier.ref

```

$ENTRY ConstantIdentifier {
    /* ConstantIdentifier -> IDENTIFIER */
    () (IDENTIFIER e.I) e.Tokens t.Errs
        = <ConstantIdentifier ((IDENTIFIER e.I)) e.Tokens t.Errs>;
    () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <ConstantIdentifier ()
            e.Tokens (e.Errs (t.Start ConstantIdentifier '.'
                Unexpected t.Type '.'
                Expected '[' IDENTIFIER '].'
                Skipped '.'))>;
    () '$' (e.Errs)
        = (ConstantIdentifier (EOF))
            '$'
            (e.Errs ((EOF) ConstantIdentifier '.'
                Unexpected End Of File '.'
                Expected '[' IDENTIFIER '].'
                Terminated '.'));

    (t.I) e.Tokens t.Errs
        = (ConstantIdentifier (IDENTIFIER) t.I) e.Tokens t.Errs;
}

```

#### Parser/Constant/UnarSign.ref

```

$ENTRY UnarSign {
    /* UnarSign -> '+' */
    () ('+' e.P) e.Tokens t.Errs
        = <UnarSign (('+' e.P)) e.Tokens t.Errs>;

    (('+' e.P)) e.Tokens t.Errs
        = (UnarSign ('+') ('+' e.P)) e.Tokens t.Errs;

    /* UnarSign -> '-' */
    () ('-' e.M) e.Tokens t.Errs
        = <UnarSign (('-' e.M)) e.Tokens t.Errs>;

    (('-' e.M)) e.Tokens t.Errs
        = (UnarSign ('-') ('-' e.M)) e.Tokens t.Errs;

    () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)

```

```

    = <UnarSign ()
      e.Tokens (e.Errs (t.Start UnarSign '.'
        Unexpected t.Type '.'
        Expected '[' '+' or '-' '].'
        Skipped '.'))>;
  () '$' (e.Errs)
    = (UnarSign (EOF))
      '$'
      (e.Errs ((EOF) UnarSign '.'
        Unexpected End Of File '.'
        Expected '[' '+' or '-' '].'
        Terminated '.'));
}

```

#### Parser/FieldList/CaseBlock.ref

```

*$FROM Parser/SimpleType/TypeIdentifier
*$FROM Parser/FieldList/CaseVariantSequence
$EXTERN TypeIdentifier, CaseVariantSequence;

$ENTRY CaseBlock {
  /* CaseBlock -> KW_CASE IDENTIFIER ':' TypeIdentifier KW_OF CaseVariantSequence */
  () (KW_CASE e.C) e.Tokens t.Errs
    = <CaseBlock ((KW_CASE e.C)) e.Tokens t.Errs>;
  () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CaseBlock ()
      (KW_CASE (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
      e.Tokens (e.Errs (t.Start CaseBlock '.'
        Unexpected t.Type '.'
        Expected '[' KW_CASE '].'
        Inserted '.'))>;
  () '$' (e.Errs)
    = <CaseBlock ()
      (KW_CASE ((0 0) (0 0))) '$'
      (e.Errs ((EOF) CaseBlock '.'
        Unexpected End Of File '.'
        Expected '[' KW_CASE '].'
        Inserted '.'))>;

  (t.C) (IDENTIFIER e.I) e.Tokens t.Errs
    = <CaseBlock (t.C (IDENTIFIER e.I)) e.Tokens t.Errs>;
  (t.C) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CaseBlock (t.C)
      e.Tokens (e.Errs (t.Start CaseBlock '.'
        Unexpected t.Type '.'
        Expected '[' IDENTIFIER '].'

```

```

        Skipped '.)')>;
(t.C) '$' (e.Errs)
    = (CaseBlock (EOF))
      '$'
      (e.Errs ((EOF) CaseBlock '.'
                Unexpected End Of File '.'
                Expected '[' IDENTIFIER '].'
                Terminated '.)'));

(t.C t.I) (':' e.D) e.Tokens t.Errs
    = <CaseBlock (t.C t.I (':' e.D)) e.Tokens t.Errs>;
(t.C t.I) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CaseBlock (t.C t.I)
      (':' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
      e.Tokens (e.Errs (t.Start CaseBlock '.'
                        Unexpected t.Type '.'
                        Expected '[' ':' '].'
                        Inserted '.)')>;
(t.C t.I) '$' (e.Errs)
    = <CaseBlock (t.C t.I)
      (':' ((0 0) (0 0))) '$'
      (e.Errs ((EOF) CaseBlock '.'
                Unexpected End Of File '.'
                Expected '[' ':' '].'
                Inserted '.)')>;

(t.C t.I t.D) (TypeIdentifier e.T) e.Tokens t.Errs
    = <CaseBlock (t.C t.I t.D (TypeIdentifier e.T)) e.Tokens t.Errs>;
(t.C t.I t.D) e.Tokens t.Errs
    = <CaseBlock (t.C t.I t.D) <TypeIdentifier () e.Tokens t.Errs>>;

(t.C t.I t.D t.T) (KW_OF e.O) e.Tokens t.Errs
    = <CaseBlock (t.C t.I t.D t.T (KW_OF e.O)) e.Tokens t.Errs>;
(t.C t.I t.D t.T) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CaseBlock (t.C t.I t.D t.T)
      (KW_OF (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
      e.Tokens (e.Errs (t.Start CaseBlock '.'
                        Unexpected t.Type '.'
                        Expected '[' KW_OF '].'
                        Inserted '.)')>;
(t.C t.I t.D t.T) '$' (e.Errs)
    = <CaseBlock (t.C t.I t.D t.T)
      (KW_OF ((0 0) (0 0))) '$'
      (e.Errs ((EOF) CaseBlock '.'
                Unexpected End Of File '.'
                Expected '[' KW_OF '].'

```

```

        Inserted '.'))>;

(t.C t.I t.D t.T t.O) (CaseVariantSequence e.CV) e.Tokens t.Errs
    = <CaseBlock (t.C t.I t.D t.T t.O (CaseVariantSequence e.CV)) e.Tokens t.Errs>;
(t.C t.I t.D t.T t.O) e.Tokens t.Errs
    = <CaseBlock (t.C t.I t.D t.T t.O) <CaseVariantSequence () e.Tokens t.Errs>>;

(t.C t.I t.D t.T t.O t.CV) e.Tokens t.Errs
    = (CaseBlock (KW_CASE IDENTIFIER ':' TypeIdentifier KW_OF CaseVariantSequence)
        t.C t.I t.D t.T t.O t.CV) e.Tokens t.Errs;
}

```

### Parser/FieldList/CaseVariant.ref

```

*$FROM Parser/FieldList/ConstantList
*$FROM Parser/FieldList/FieldList
$EXTERN ConstantList, FieldList;

$ENTRY CaseVariant {
    /* CaseVariant -> ConstantList ':' '(' FieldList ')' */
    () (ConstantList e.C) e.Tokens t.Errs
        = <CaseVariant ((ConstantList e.C)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <CaseVariant () <ConstantList () e.Tokens t.Errs>>;

    (t.C) (':' e.D) e.Tokens t.Errs
        = <CaseVariant (t.C (':' e.D)) e.Tokens t.Errs>;
    (t.C) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <CaseVariant (t.C)
            (':' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
            e.Tokens (e.Errs (t.Start CaseVariant '.'
                Unexpected t.Type '.'
                Expected '[' ':' '].')
                Inserted '.'))>;
    (t.C) '$' (e.Errs)
        = <CaseVariant (t.C)
            (':' ((0 0) (0 0))) '$'
            (e.Errs ((EOF) CaseVariant '.'
                Unexpected End Of File '.'
                Expected '[' ':' '].')
                Inserted '.'))>;

    (t.C t.D) '(' (e.B) e.Tokens t.Errs
        = <CaseVariant (t.C t.D '(' (e.B)) e.Tokens t.Errs>;
    (t.C t.D) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <CaseVariant (t.C t.D)

```

```

        ('(' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start CaseVariant '.'
            Unexpected t.Type '.'
            Expected '[' '\(' ']').'
            Inserted '.'))>;
(t.C t.D) '$' (e.Errs)
    = <CaseVariant (t.C t.D)
        ('(' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) CaseVariant '.'
            Unexpected End Of File '.'
            Expected '[' '\(' ']').'
            Inserted '.'))>;

(t.C t.D t.B) (FieldList e.F) e.Tokens t.Errs
    = <CaseVariant (t.C t.D t.B (FieldList e.F)) e.Tokens t.Errs>;
(t.C t.D t.B) e.Tokens t.Errs
    = <CaseVariant (t.C t.D t.B) <FieldList () e.Tokens t.Errs>>;

(t.C t.D t.B t.F) (')' e.BC) e.Tokens t.Errs
    = <CaseVariant (t.C t.D t.B t.F (')' e.BC)) e.Tokens t.Errs>;
(t.C t.D t.B t.F) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CaseVariant (t.C t.D t.B t.F)
        (')' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start CaseVariant '.'
            Unexpected t.Type '.'
            Expected '[' '\)' ']').'
            Inserted '.'))>;
(t.C t.D t.B t.F) '$' (e.Errs)
    = <CaseVariant (t.C t.D t.B t.F)
        (')' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) CaseVariant '.'
            Unexpected End Of File '.'
            Expected '[' '\)' ']').'
            Inserted '.'))>;

(t.C t.D t.B t.F t.BC) e.Tokens t.Errs
    = (CaseVariant (ConstantList ':' '(' FieldList ')') t.C t.D t.B t.F t.BC) e.Tokens t.Errs;
}

```

#### **Parser/FieldList/CaseVariantSequence.ref**

```

*$FROM Parser/FieldList/CaseVariant
$EXTERN CaseVariant;

$ENTRY CaseVariantSequence {
    /* CaseVariantSequence -> CaseVariant ';' CaseVariantSequence */

```



```

() (CaseVariant e.C) e.Tokens t.Errs
  = <CaseVariantSequence ((CaseVariant e.C)) e.Tokens t.Errs>;
() e.Tokens t.Errs
  = <CaseVariantSequence () <CaseVariant () e.Tokens t.Errs>>;

(t.C) (';' e.D) e.Tokens t.Errs
  = <CaseVariantSequence (t.C (';' e.D)) e.Tokens t.Errs>;

(t.C t.D) (CaseVariantSequence e.CS) e.Tokens t.Errs
  = <CaseVariantSequence (t.C t.D (CaseVariantSequence e.CS)) e.Tokens t.Errs>;
(t.C t.D) e.Tokens t.Errs
  = <CaseVariantSequence (t.C t.D) <CaseVariantSequence () e.Tokens t.Errs>>;

(t.C t.D t.CS) e.Tokens t.Errs
  = (CaseVariantSequence (CaseVariant ';' CaseVariantSequence) t.C t.D t.CS) e.Tokens t.Errs

/* CaseVariantSequence -> CaseVariant */
(t.C) e.Tokens t.Errs
  = (CaseVariantSequence (CaseVariant) t.C) e.Tokens t.Errs;
}

```

#### **Parser/FieldList/ConstantList.ref**

```

*$FROM Parser/Constant/Constant
$EXTERN Constant;

$ENTRY ConstantList {
  /* ConstantList -> Constant ',' ConstantList */
  () (Constant e.C) e.Tokens t.Errs
    = <ConstantList ((Constant e.C)) e.Tokens t.Errs>;
  () e.Tokens t.Errs
    = <ConstantList () <Constant () e.Tokens t.Errs>>;

  (t.C) (',' e.CM) e.Tokens t.Errs
    = <ConstantList (t.C (',' e.CM)) e.Tokens t.Errs>;

  (t.C t.CM) (ConstantList e.CL) e.Tokens t.Errs
    = <ConstantList (t.C t.CM (ConstantList e.CL)) e.Tokens t.Errs>;
  (t.C t.CM) e.Tokens t.Errs
    = <ConstantList (t.C t.CM) <ConstantList () e.Tokens t.Errs>>;

  (t.C t.CM t.CL) e.Tokens t.Errs
    = (ConstantList (Constant ',' ConstantList) t.C t.CM t.CL) e.Tokens t.Errs;

  /* ConstantList -> Constant */
  (t.C) e.Tokens t.Errs

```

```

    = (ConstantList (Constant) t.C) e.Tokens t.Errs;
}

```

#### **Parser/FieldList/FieldList.ref**

```

*$FROM Parser/FieldList/IdentifierWithTypeList
*$FROM Parser/FieldList/CaseBlock
$EXTERN IdentifierWithTypeList, CaseBlock;

$ENTRY FieldList {
    /* FieldList -> IdentifierWithTypeList ';' CaseBlock */
    () (IdentifierWithTypeList e.I) e.Tokens t.Errs
        = <FieldList ((IdentifierWithTypeList e.I)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <FieldList () <IdentifierWithTypeList () e.Tokens t.Errs>>;

    (t.I) (';' e.C) e.Tokens t.Errs
        = <FieldList (t.I (';' e.C)) e.Tokens t.Errs>;

    (t.I t.C) (CaseBlock e.CB) e.Tokens t.Errs
        = <FieldList (t.I t.C (CaseBlock e.CB)) e.Tokens t.Errs>;
    (t.I t.C) (KW_CASE e.CB) e.Tokens t.Errs
        = <FieldList (t.I t.C) <CaseBlock () (KW_CASE e.CB) e.Tokens t.Errs>>;

    (t.I t.C t.CB) e.Tokens t.Errs
        = (FieldList (IdentifierWithTypeList ';' CaseBlock) t.I t.C t.CB) e.Tokens t.Errs;

    /* FieldList -> IdentifierWithTypeList */
    (t.I) e.Tokens t.Errs
        = (FieldList (IdentifierWithTypeList) t.I) e.Tokens t.Errs;
}

```

#### **Parser/FieldList/IdentifierWithType.ref**

```

*$FROM Parser/SimpleType/IdentifierList
*$FROM Parser/Type/Type
$EXTERN IdentifierList, Type_;

$ENTRY IdentifierWithType {
    /* IdentifierWithType -> IdentifierList ':' Type */
    () (IdentifierList e.I) e.Tokens t.Errs
        = <IdentifierWithType ((IdentifierList e.I)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <IdentifierWithType () <IdentifierList () e.Tokens t.Errs>>;

    (t.I) (':' e.D) e.Tokens t.Errs

```

```

        = <IdentifierWithType (t.I (';' e.D)) e.Tokens t.Errs>;
(t.I) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <IdentifierWithType (t.I)
        (';' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start IdentifierWithType '.'
            Unexpected t.Type '.'
            Expected '[' ':' '].'
            Inserted '.'))>;
(t.I) '$' (e.Errs)
    = <IdentifierWithType (t.I)
        (';' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) IdentifierWithType '.'
            Unexpected End Of File '.'
            Expected '[' ':' '].'
            Inserted '.'))>;

(t.I t.D) (Type e.T) e.Tokens t.Errs
    = <IdentifierWithType (t.I t.D (Type e.T)) e.Tokens t.Errs>;
(t.I t.D) e.Tokens t.Errs
    = <IdentifierWithType (t.I t.D) <Type_ () e.Tokens t.Errs>>;

(t.I t.D t.T) e.Tokens t.Errs
    = (IdentifierWithType (IdentifierList ':' Type) t.I t.D t.T) e.Tokens t.Errs;
}

```

#### **Parser/FieldList/IdentifierWithTypeList.ref**

```

*$FROM Parser/FieldList/IdentifierWithType
$EXTERN IdentifierWithType;

$ENTRY IdentifierWithTypeList {
    /* IdentifierWithTypeList -> IdentifierWithType ';' IdentifierWithTypeList */
    () (IdentifierWithType e.I) e.Tokens t.Errs
        = <IdentifierWithTypeList ((IdentifierWithType e.I)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <IdentifierWithTypeList () <IdentifierWithType () e.Tokens t.Errs>>;

    (t.I) (';' e.C) e.Tokens t.Errs
        = <IdentifierWithTypeList (t.I (';' e.C)) e.Tokens t.Errs>;

    (t.I t.C) (IdentifierWithTypeList e.IL) e.Tokens t.Errs
        = <IdentifierWithTypeList (t.I t.C (IdentifierWithTypeList e.IL)) e.Tokens t.Errs>;
    (t.I t.C) (IDENTIFIER e.ID) e.Tokens t.Errs
        = <IdentifierWithTypeList (t.I t.C)
            <IdentifierWithTypeList () (IDENTIFIER e.ID) e.Tokens t.Errs>>;
    (t.I t.C) e.Tokens t.Errs

```

```

    = (IdentifierWithTypeList (IdentifierWithType) t.I) t.C e.Tokens t.Errs;

(t.I t.C t.IL) e.Tokens t.Errs
    = (IdentifierWithTypeList (IdentifierWithType ';' IdentifierWithTypeList) t.I t.C t.IL)
      e.Tokens t.Errs;

/* IdentifierWithTypeList -> IdentifierWithType */
(t.I) e.Tokens t.Errs
    = (IdentifierWithTypeList (IdentifierWithType) t.I) e.Tokens t.Errs;
}

```

#### **Parser/Program/Program.ref**

```

*$FROM Parser/Block/Block
$EXTERN Block;

$ENTRY Program {
    /* Program -> Block */
    () (Block e.B) e.Tokens t.Errs
        = <Program ((Block e.B)) e.Tokens t.Errs>;
    () e.Tokens t.Errs
        = <Program () <Block () e.Tokens t.Errs>>;

    (t.B) e.Tokens t.Errs
        = (Program (Block) t.B) e.Tokens t.Errs;
}

```

#### **Parser/SimpleType/CommonTypeIdIdentifier.ref**

```

$ENTRY CommonTypeIdIdentifier {
    /* CommonTypeIdIdentifier -> KW_INTEGER */
    () (KW_INTEGER e.I) e.Tokens t.Errs
        = <CommonTypeIdIdentifier ((KW_INTEGER e.I)) e.Tokens t.Errs>;

    ((KW_INTEGER e.I)) e.Tokens t.Errs
        = (CommonTypeIdIdentifier (KW_INTEGER) (KW_INTEGER e.I)) e.Tokens t.Errs;

    /* CommonTypeIdIdentifier -> KW_BOOLEAN */
    () (KW_BOOLEAN e.B) e.Tokens t.Errs
        = <CommonTypeIdIdentifier ((KW_BOOLEAN e.B)) e.Tokens t.Errs>;

    ((KW_BOOLEAN e.B)) e.Tokens t.Errs
        = (CommonTypeIdIdentifier (KW_BOOLEAN) (KW_BOOLEAN e.B)) e.Tokens t.Errs;

    /* CommonTypeIdIdentifier -> KW_REAL */
    () (KW_REAL e.R) e.Tokens t.Errs

```

```

        = <CommonTypeIdentifier ((KW_REAL e.R)) e.Tokens t.Errs>;

((KW_REAL e.R)) e.Tokens t.Errs
    = (CommonTypeIdentifier (KW_REAL) (KW_REAL e.R)) e.Tokens t.Errs;

/* CommonTypeIdentifier -> KW_CHAR */
() (KW_CHAR e.C) e.Tokens t.Errs
    = <CommonTypeIdentifier ((KW_CHAR e.C)) e.Tokens t.Errs>;

((KW_CHAR e.C)) e.Tokens t.Errs
    = (CommonTypeIdentifier (KW_CHAR) (KW_CHAR e.C)) e.Tokens t.Errs;

/* CommonTypeIdentifier -> KW_TEXT */
() (KW_TEXT e.T) e.Tokens t.Errs
    = <CommonTypeIdentifier ((KW_TEXT e.T)) e.Tokens t.Errs>;

((KW_TEXT e.T)) e.Tokens t.Errs
    = (CommonTypeIdentifier (KW_TEXT) (KW_TEXT e.T)) e.Tokens t.Errs;

() (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <CommonTypeIdentifier ()
        e.Tokens (e.Errs (t.Start CommonTypeIdentifier '.'
            Unexpected t.Type '.'
            Expected '[' KW_INTEGER or KW_BOOLEAN or KW_REAL or KW_CHAR or KW_TEXT '].
            Skipped '.)>;
() '$' (e.Errs)
    = (CommonTypeIdentifier (EOF))
        '$'
        (e.Errs ((EOF) CommonTypeIdentifier '.'
            Unexpected End Of File '.'
            Expected '[' KW_INTEGER or KW_BOOLEAN or KW_REAL or KW_CHAR or KW_TEXT '].
            Terminated '.)>;
}

```

#### **Parser/SimpleType/IdentifierList.ref**

```

$ENTRY IdentifierList {
    /* IdentifierList -> IDENTIFIER ',' IdentifierList */
    () (IDENTIFIER e.I) e.Tokens t.Errs
        = <IdentifierList ((IDENTIFIER e.I)) e.Tokens t.Errs>;
    () (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
        = <IdentifierList ()
            e.Tokens (e.Errs (t.Start IdentifierList '.'
                Unexpected t.Type '.'
                Expected '[' IDENTIFIER '].
                Skipped '.)>;
}

```

```

() '$' (e.Errs)
  = (IdentifierList (EOF))
    '$'
    (e.Errs ((EOF) IdentifierList '.'
              Unexpected End Of File '.'
              Expected '[' IDENTIFIER ']'
              Terminated '.'));

(t.I) (' ' e.C) e.Tokens t.Errs
  = <IdentifierList (t.I (' ' e.C)) e.Tokens t.Errs>;

(t.I t.C) (IdentifierList e.IL) e.Tokens t.Errs
  = <IdentifierList (t.I t.C (IdentifierList e.IL)) e.Tokens t.Errs>;
(t.I t.C) e.Tokens t.Errs
  = <IdentifierList (t.I t.C) <IdentifierList () e.Tokens t.Errs>>;

(t.I t.C t.IL) e.Tokens t.Errs
  = (IdentifierList (IDENTIFIER ' ' IdentifierList) t.I t.C t.IL) e.Tokens t.Errs;

/* IdentifierList -> IDENTIFIER */
(t.I) e.Tokens t.Errs
  = (IdentifierList (IDENTIFIER) t.I) e.Tokens t.Errs;
}

```

### Parser/SimpleType/SimpleType.ref

```

*$FROM Parser/SimpleType/TypeIdentifier
*$FROM Parser/SimpleType/IdentifierList
*$FROM Parser/Constant/Constant
$EXTERN TypeIdentifier, IdentifierList, Constant;

$ENTRY SimpleType {
  /* SimpleType -> TypeIdentifier */
  () (TypeIdentifier e.T) e.Tokens t.Errs
    = <SimpleType ((TypeIdentifier e.T)) e.Tokens t.Errs>;
  () (KW_INTEGER e.I) e.Tokens t.Errs
    = <SimpleType () <TypeIdentifier () (KW_INTEGER e.I) e.Tokens t.Errs>>;
  () (KW_BOOLEAN e.B) e.Tokens t.Errs
    = <SimpleType () <TypeIdentifier () (KW_BOOLEAN e.B) e.Tokens t.Errs>>;
  () (KW_REAL e.R) e.Tokens t.Errs
    = <SimpleType () <TypeIdentifier () (KW_REAL e.R) e.Tokens t.Errs>>;
  () (KW_CHAR e.C) e.Tokens t.Errs
    = <SimpleType () <TypeIdentifier () (KW_CHAR e.C) e.Tokens t.Errs>>;
  () (KW_TEXT e.T) e.Tokens t.Errs
    = <SimpleType () <TypeIdentifier () (KW_TEXT e.T) e.Tokens t.Errs>>;
  () (IDENTIFIER e.I) e.Tokens t.Errs

```

```

    = <SimpleType () <TypeIdentifier () (IDENTIFIER e.I) e.Tokens t.Errs>>;

((TypeIdentifier e.T)) e.Tokens t.Errs
    = (SimpleType (TypeIdentifier) (TypeIdentifier e.T)) e.Tokens t.Errs;

/* SimpleType -> '(' IdentifierList ')' */
() ('(' e.B) e.Tokens t.Errs
    = <SimpleType (('(' e.B)) e.Tokens t.Errs>;

(('(' e.B)) (IdentifierList e.I) e.Tokens t.Errs
    = <SimpleType (('(' e.B) (IdentifierList e.I)) e.Tokens t.Errs>;
(('(' e.B)) e.Tokens t.Errs
    = <SimpleType (('(' e.B)) <IdentifierList () e.Tokens t.Errs>>;

(('(' e.B) t.I) (')' e.BC) e.Tokens t.Errs
    = <SimpleType (('(' e.B) t.I (')' e.BC)) e.Tokens t.Errs>;

(('(' e.B) t.I t.BC) e.Tokens t.Errs
    = (SimpleType ('(' IdentifierList ')') ('(' e.B) t.I t.BC) e.Tokens t.Errs;

/* SimpleType -> Constant '.' '.' Constant */
() (Constant e.C1) e.Tokens t.Errs
    = <SimpleType ((Constant e.C1)) e.Tokens t.Errs>;
() e.Tokens t.Errs
    = <SimpleType () <Constant () e.Tokens t.Errs>>;

((Constant e.C1)) ('.' e.D1) e.Tokens t.Errs
    = <SimpleType ((Constant e.C1) ('.' e.D1)) e.Tokens t.Errs>;
((Constant e.C1)) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
    = <SimpleType ((Constant e.C1))
        ('.' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
        e.Tokens (e.Errs (t.Start SimpleType '.'
            Unexpected t.Type '.'
            Expected '[' '.' ''].')
            Inserted '.'))>;
((Constant e.C1)) '$' (e.Errs)
    = <SimpleType ((Constant e.C1))
        ('.' ((0 0) (0 0))) '$'
        (e.Errs ((EOF) SimpleType '.'
            Unexpected End Of File '.'
            Expected '[' '.' ''].')
            Inserted '.'))>;

((Constant e.C1) t.D1) ('.' e.D2) e.Tokens t.Errs
    = <SimpleType ((Constant e.C1) t.D1 ('.' e.D2)) e.Tokens t.Errs>;
((Constant e.C1) t.D1) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)

```

```

    = <SimpleType ((Constant e.C1) t.D1)
      ('.' (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
      e.Tokens (e.Errs (t.Start SimpleType '.'
        Unexpected t.Type '.'
        Expected '[' ' '.' '].'
        Inserted '.)>;
    ((Constant e.C1) t.D1) '$' (e.Errs)
    = <SimpleType ((Constant e.C1) t.D1)
      ('.' ((0 0) (0 0))) '$'
      (e.Errs ((EOF) SimpleType '.'
        Unexpected End Of File '.'
        Expected '[' ' '.' '].'
        Inserted '.)>;

    ((Constant e.C1) t.D1 t.D2) (Constant e.C2) e.Tokens t.Errs
    = <SimpleType ((Constant e.C1) t.D1 t.D2 (Constant e.C2)) e.Tokens t.Errs>;
    ((Constant e.C1) t.D1 t.D2) e.Tokens t.Errs
    = <SimpleType ((Constant e.C1) t.D1 t.D2) <Constant () e.Tokens t.Errs>>;

    ((Constant e.C1) t.D1 t.D2 t.C2) e.Tokens t.Errs
    = (SimpleType (Constant '.' '.' Constant) t.D1 t.D2 t.C2) e.Tokens t.Errs;
}

```

#### **Parser/SimpleType/TypeIdentifier.ref**

```

*$FROM Parser/SimpleType/CommonTypeIdentifier
$EXTERN CommonTypeIdentifier;

$ENTRY TypeIdentifier {
  /* TypeIdentifier -> IDENTIFIER */
  () (IDENTIFIER e.I) e.Tokens t.Errs
    = <TypeIdentifier ((IDENTIFIER e.I)) e.Tokens t.Errs>;

  ((IDENTIFIER e.I)) e.Tokens t.Errs
    = (TypeIdentifier (IDENTIFIER) (IDENTIFIER e.I)) e.Tokens t.Errs;

  /* TypeIdentifier -> CommonTypeIdentifier */
  () (CommonTypeIdentifier e.C) e.Tokens t.Errs
    = <TypeIdentifier ((CommonTypeIdentifier e.C)) e.Tokens t.Errs>;
  () e.Tokens t.Errs
    = <TypeIdentifier () <CommonTypeIdentifier () e.Tokens t.Errs>>;

  ((CommonTypeIdentifier e.C)) e.Tokens t.Errs
    = (TypeIdentifier (CommonTypeIdentifier) (CommonTypeIdentifier e.C)) e.Tokens t.Errs;
}

```



### Parser/Type/SimpleTypeList.ref

```
*$FROM Parser/SimpleType/SimpleType
$EXTERN SimpleType;

$ENTRY SimpleTypeList {
  /* SimpleTypeList -> SimpleType ',' SimpleTypeList */
  () (SimpleType e.S) e.Tokens t.Errs
    = <SimpleTypeList ((SimpleType e.S)) e.Tokens t.Errs>;
  () e.Tokens t.Errs
    = <SimpleTypeList () <SimpleType () e.Tokens t.Errs>>;

  (t.S) (',' e.C) e.Tokens t.Errs
    = <SimpleTypeList (t.S (',' e.C)) e.Tokens t.Errs>;

  (t.S t.C) (SimpleTypeList e.ST) e.Tokens t.Errs
    = <SimpleTypeList (t.S t.C (SimpleTypeList e.ST)) e.Tokens t.Errs>;
  (t.S t.C) e.Tokens t.Errs
    = <SimpleTypeList (t.S t.C) <SimpleTypeList () e.Tokens t.Errs>>;

  (t.S t.C t.ST) e.Tokens t.Errs
    = (SimpleTypeList (SimpleType ',' SimpleTypeList) t.S t.C t.ST) e.Tokens t.Errs;

  /* SimpleTypeList -> SimpleType */
  (t.S) e.Tokens t.Errs
    = (SimpleTypeList (SimpleType) t.S) e.Tokens t.Errs;
}
```

### Parser/Type/Type.ref

```
*$FROM Parser/SimpleType/TypeIdentifier
*$FROM Parser/Type/TypeAfterPacked
*$FROM Parser/SimpleType/SimpleType
$EXTERN TypeIdentifier, TypeAfterPacked, SimpleType;

$ENTRY Type_ {
  /* Type -> '^' TypeIdentifier */
  () ('^' e.U) e.Tokens t.Errs
    = <Type_ (('^' e.U)) e.Tokens t.Errs>;

  (('^' e.U)) (TypeIdentifier e.T) e.Tokens t.Errs
    = <Type_ (('^' e.U) (TypeIdentifier e.T)) e.Tokens t.Errs>;
  (('^' e.U)) e.Tokens t.Errs
    = <Type_ (('^' e.U)) <TypeIdentifier () e.Tokens t.Errs>>;

  (('^' e.U) t.T) e.Tokens t.Errs
```

```

        = (Type ('^' TypeIdentifier) ('^' e.U) t.T) e.Tokens t.Errs;

/* Type -> KW_PACKED TypeAfterPacked */
() (KW_PACKED e.P) e.Tokens t.Errs
    = <Type_ ((KW_PACKED e.P)) e.Tokens t.Errs>;

((KW_PACKED e.P)) (TypeAfterPacked e.T) e.Tokens t.Errs
    = <Type_ ((KW_PACKED e.P) (TypeAfterPacked e.T)) e.Tokens t.Errs>;
((KW_PACKED e.P)) e.Tokens t.Errs
    = <Type_ (KW_PACKED e.P) <TypeAfterPacked () e.Tokens t.Errs>>;

((KW_PACKED) t.T) e.Tokens t.Errs
    = (Type (KW_PACKED TypeAfterPacked) (KW_PACKED) t.T) e.Tokens t.Errs;

/* Type -> TypeAfterPacked */
() (TypeAfterPacked e.T) e.Tokens t.Errs
    = <Type_ ((TypeAfterPacked e.T)) e.Tokens t.Errs>;
() (s.TypeKW e.K) e.Tokens t.Errs
    , KW_ARRAY KW_FILE KW_SET KW_RECORD : e.1 s.TypeKW e.2
    = <Type_ () <TypeAfterPacked () (s.TypeKW e.K) e.Tokens t.Errs>>;

((TypeAfterPacked e.T)) e.Tokens t.Errs
    = (Type (TypeAfterPacked) (TypeAfterPacked e.T)) e.Tokens t.Errs;

/* Type -> SimpleType */
() (SimpleType e.S) e.Tokens t.Errs
    = <Type_ ((SimpleType e.S)) e.Tokens t.Errs>;
() e.Tokens t.Errs
    = <Type_ () <SimpleType () e.Tokens t.Errs>>;

((SimpleType e.S)) e.Tokens t.Errs
    = (Type (SimpleType) (SimpleType e.S)) e.Tokens t.Errs;
}

```

#### **Parser/Type/TypeAfterPacked.ref**

```

*$FROM Parser/Type/SimpleTypeList
*$FROM Parser/Type/Type
*$FROM Parser/SimpleType/SimpleType
*$FROM Parser/FieldList/FieldList
$EXTERN SimpleTypeList, Type_, SimpleType, FieldList;

$ENTRY TypeAfterPacked {
    /* TypeAfterPacked -> KW_ARRAY SimpleTypeList KW_OF Type */
    () (KW_ARRAY e.A) e.Tokens t.Errs
        = <TypeAfterPacked ((KW_ARRAY e.A)) e.Tokens t.Errs>;
}

```

```

((KW_ARRAY e.A)) (SimpleTypeList e.S) e.Tokens t.Errs
= <TypeAfterPacked ((KW_ARRAY e.A) (SimpleTypeList e.S)) e.Tokens t.Errs>;
((KW_ARRAY e.A)) e.Tokens t.Errs
= <TypeAfterPacked ((KW_ARRAY e.A)) <SimpleTypeList () e.Tokens t.Errs>>;

((KW_ARRAY e.A) t.S) (KW_OF e.O) e.Tokens t.Errs
= <TypeAfterPacked ((KW_ARRAY e.A) t.S (KW_OF e.O)) e.Tokens t.Errs>;
((KW_ARRAY e.A) t.S) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
= <TypeAfterPacked ((KW_ARRAY e.A) t.S)
  (KW_OF (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
  e.Tokens (e.Errs (t.Start TypeAfterPacked '.'
    Unexpected t.Type '.'
    Expected '[' KW_OF '].'
    Inserted '.'))>;
((KW_ARRAY e.A) t.S) '$' (e.Errs)
= <TypeAfterPacked ((KW_ARRAY e.A) t.S)
  (KW_OF ((0 0) (0 0))) '$'
  (e.Errs ((EOF) TypeAfterPacked '.'
    Unexpected End Of File '.'
    Expected '[' KW_OF '].'
    Inserted '.'))>;

((KW_ARRAY e.A) t.S t.O) (Type e.T) e.Tokens t.Errs
= <TypeAfterPacked ((KW_ARRAY e.A) t.S t.O (Type e.T)) e.Tokens t.Errs>;
((KW_ARRAY e.A) t.S t.O) e.Tokens t.Errs
= <TypeAfterPacked ((KW_ARRAY e.A) t.S t.O) <Type_ () e.Tokens t.Errs>>;

((KW_ARRAY e.A) t.S t.O t.T) e.Tokens t.Errs
= (TypeAfterPacked (KW_ARRAY SimpleTypeList KW_OF Type) (KW_ARRAY e.A) t.S t.O t.T) e.Tokens t.Errs

/* TypeAfterPacked -> KW_FILE KW_OF Type */
() (KW_FILE e.F) e.Tokens t.Errs
= <TypeAfterPacked ((KW_FILE e.F) e.Tokens t.Errs)>;

((KW_FILE e.F)) (KW_OF e.O) e.Tokens t.Errs
= <TypeAfterPacked ((KW_FILE e.F) (KW_OF e.O)) e.Tokens t.Errs>;
((KW_FILE e.F)) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
= <TypeAfterPacked ((KW_FILE e.F))
  (KW_OF (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
  e.Tokens (e.Errs (t.Start TypeAfterPacked '.'
    Unexpected t.Type '.'
    Expected '[' KW_OF '].'
    Inserted '.'))>;
((KW_FILE e.F)) '$' (e.Errs)
= <TypeAfterPacked ((KW_FILE e.F))

```

```

        (KW_OF ((0 0) (0 0))) '$'
        (e.Errs ((EOF) TypeAfterPacked '.'
                Unexpected End Of File '.'
                Expected '[' KW_OF '].'
                Inserted '.)'))>;

((KW_FILE e.F) t.0) (Type e.T) e.Tokens t.Errs
= <TypeAfterPacked ((KW_FILE e.F) t.0 (Type e.T)) e.Tokens t.Errs>;
((KW_FILE e.F) t.0) e.Tokens t.Errs
= <TypeAfterPacked ((KW_FILE e.F) t.0) <Type_ () e.Tokens t.Errs>>;

((KW_FILE e.F) t.0 t.T) e.Tokens t.Errs
= (TypeAfterPacked (KW_FILE KW_OF Type) (KW_FILE e.F) t.0 t.T) e.Tokens t.Errs;

/* TypeAfterPacked -> KW_SET KW_OF SimpleType */
() (KW_SET e.S) e.Tokens t.Errs
= <TypeAfterPacked ((KW_SET e.S)) e.Tokens t.Errs>;

((KW_SET e.S)) (KW_OF e.0) e.Tokens t.Errs
= <TypeAfterPacked ((KW_SET e.S) (KW_OF e.0)) e.Tokens t.Errs>;
((KW_SET e.S)) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
= <TypeAfterPacked ((KW_SET e.S))
    (KW_OF (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
    e.Tokens (e.Errs (t.Start TypeAfterPacked '.'
        Unexpected t.Type '.'
        Expected '[' KW_OF '].'
        Inserted '.)'))>;
((KW_SET e.S)) '$' (e.Errs)
= <TypeAfterPacked ((KW_SET e.S))
    (KW_OF ((0 0) (0 0))) '$'
    (e.Errs ((EOF) TypeAfterPacked '.'
        Unexpected End Of File '.'
        Expected '[' KW_OF '].'
        Inserted '.)'))>;

((KW_SET e.S) t.0) (SimpleType e.T) e.Tokens t.Errs
= <TypeAfterPacked ((KW_SET e.S) t.0 (SimpleType e.T)) e.Tokens t.Errs>;
((KW_SET e.S) t.0) e.Tokens t.Errs
= <TypeAfterPacked ((KW_SET e.S) t.0) <SimpleType () e.Tokens t.Errs>>;

((KW_SET e.S) t.0 t.T) e.Tokens t.Errs
= (TypeAfterPacked (KW_SET KW_OF SimpleType) (KW_SET e.S) t.0 t.T) e.Tokens t.Errs;

/* TypeAfterPacked -> KW_RECORD FieldList KW_END */
() (KW_RECORD e.R) e.Tokens t.Errs
= <TypeAfterPacked ((KW_RECORD e.R)) e.Tokens t.Errs>;

```

```

() (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <TypeAfterPacked ()
    e.Tokens (e.Errs (t.Start TypeAfterPacked '.'
      Unexpected t.Type '.'
      Expected '[' KW_ARRAY or KW_FILE or KW_SET or KW_RECORD '].'
      Skipped '.'))>;
() '$' (e.Errs)
  = (TypeAfterPacked (EOF))
    '$'
    (e.Errs ((EOF) TypeAfterPacked '.'
      Unexpected End Of File '.'
      Expected '[' KW_ARRAY or KW_FILE or KW_SET or KW_RECORD '].'
      Terminated '.'));

((KW_RECORD e.R)) (FieldList e.F) e.Tokens t.Errs
  = <TypeAfterPacked ((KW_RECORD e.R) (FieldList e.F)) e.Tokens t.Errs>;
((KW_RECORD e.R)) e.Tokens t.Errs
  = <TypeAfterPacked ((KW_RECORD e.R)) <FieldList () e.Tokens t.Errs>>;

((KW_RECORD e.R) t.F) (KW_END e.E) e.Tokens t.Errs
  = <TypeAfterPacked ((KW_RECORD e.R) t.F (KW_END e.E)) e.Tokens t.Errs>;
((KW_RECORD e.R) t.F) (t.Type (t.Start t.End) e.Attrs) e.Tokens (e.Errs)
  = <TypeAfterPacked ((KW_RECORD e.R) t.F)
    (KW_END (t.Start t.Start)) (t.Type (t.Start t.End) e.Attrs)
    e.Tokens (e.Errs (t.Start TypeAfterPacked '.'
      Unexpected t.Type '.'
      Expected '[' KW_END '].'
      Inserted '.'))>;
((KW_RECORD e.R) t.F) '$' (e.Errs)
  = <TypeAfterPacked ((KW_RECORD e.R) t.F)
    (KW_END ((0 0) (0 0))) '$'
    (e.Errs ((EOF) TypeAfterPacked '.'
      Unexpected End Of File '.'
      Expected '[' KW_END '].'
      Inserted '.'))>;

((KW_RECORD e.R) t.F t.E) e.Tokens t.Errs
  = (TypeAfterPacked (KW_RECORD FieldList KW_END) (KW_RECORD e.R) t.F t.E) e.Tokens t.Errs;
}

```

### Parser/Parser.ref

```

*$FROM Parser/Program/Program
$EXTERN Program;

/*

```

```

    <Parse t.Token*> == t.Errors t.TreeNode
    t.Errors ::= (t.Error*)
    t.Error ::= s.Char*
    t.TreeNode ::= (s.Nterm (s.Token*) t.TreeNode*)
*/
$ENTRY Parse {
    e.Tokens
    , <Program () e.Tokens '$' ()> : {
        t.ParseTree '$' t.Errors = t.ParseTree t.Errors;
        t.ParseTree (t.Type (t.Start t.End) e.Attr) e._ (e.Errs)
            = t.ParseTree (e.Errs (t.Start Parser '.'
                Token t.Type and all next didnt recognized '.'
                Expected End Of File '.'));
    };
}

```

### Lexer.ref

```

*$FROM LibraryEx
$EXTERN Inc, Dec, Map;

/*
    e.Lines ::= t.Line*
    t.Line ::= (s.Sym*)
    t.Token ::=
    t.Fragment ::= (t.StartPos t.EndPos)
    t.StartPos ::= t.Pos
    t.EndPos ::= t.Pos
    t.Pos ::= (s.Line s.Col)
    t.Lexem ::= (s.Char+)

    s.Bool ::= TRUE | FALSE
*/

/* <Lexem-Pos e.Lines> == t.Token* */
$ENTRY Lexer {
    e.Lines = <Lexer-Pos (1 1) e.Lines>;
}

/* <Count e.Element*> ::= s.Count */
Count {
    /* нусто */ = 0;
    t._ e.Elements = <Inc <Count e.Elements>>;
}

/* <Join (e.Sep) e.Lines> ::= e.Sym* */

```

```

Join {
    (e.Sep) = /* пусто */;
    (e.Sep) t.Line = t.Line;
    (e.Sep) (e.Line) e.Lines = e.Line e.Sep <Join (e.Sep) e.Lines>
}

/* <Or s.Bool*> ::= s.Bool */
Or {
    e._ TRUE e._ = TRUE;
    e._ = FALSE;
}

/* <And s.Bool*> ::= s.Bool */
And {
    e._ FALSE e._ = FALSE;
    e._ = TRUE;
}

/* <CharEQ s.Sym s.Sym> ::= s.Bool */
CharEQ {
    s.Left s.Right
    , <Compare <Ord s.Left> <Ord s.Right>> : {
        '+' = FALSE;
        '0' = TRUE;
        '-' = FALSE;
    };
}

/* <CharLE s.Sym s.Sym> ::= s.Bool */
CharLE {
    s.Left s.Right
    , <Compare <Ord s.Left> <Ord s.Right>> : {
        '+' = FALSE;
        '0' = TRUE;
        '-' = TRUE;
    };
}

/* <CharGE s.Sym s.Sym> ::= s.Bool */
CharGE {
    s.Left s.Right
    , <Compare <Ord s.Left> <Ord s.Right>> : {
        '+' = TRUE;
        '0' = TRUE;
        '-' = FALSE;
    };
}

```

```

}

/* <IsDigit s.Sym> ::= s.Bool */
IsDigit {
    s.Sym = <And <CharGE s.Sym '0'> <CharLE s.Sym '9'>>;
}

/* <IsAlpha s.Sym> ::= TRUE | FALSE */
IsAlpha {
    s.LwSym
    , <Upper s.LwSym> : s.Sym
    = <And <CharGE s.Sym 'A'> <CharLE s.Sym 'Z'>>;
}

/* <Lexem-Pos (s.Line s.Col) e.Lines> == t.Token* */
Lexer-Pos {
    (s.Line s.Col) = /* пусто */;

    /* Space ::= \s */
    (s.Line s.Col) (' ' e.Syms) e.Lines = <Lexer-Pos (s.Line <Inc s.Col>) (e.Syms) e.Lines>;
    (s.Line s.Col) ('\r' e.Syms) e.Lines = <Lexer-Pos (s.Line <Inc s.Col>) (e.Syms) e.Lines>;
    (s.Line s.Col) ('\t' e.Syms) e.Lines = <Lexer-Pos (s.Line <Inc s.Col>) (e.Syms) e.Lines>;
    (s.Line s.Col) () e.Lines = <Lexer-Pos (<Inc s.Line> 1) e.Lines>;

    /* Comment ::= {.*} */
    (s.Line s.Col) ('{' e.Inf '}' e.Postf) e.Lines
    = <Lexer-Pos (s.Line <Add <Count e.Inf> 3>) (e.Postf) e.Lines>;
    (s.Line s.Col) ('{' e.Postf) e.Inf (e.Pref '}') e.Postf2) e.Lines
    = <Lexer-Pos (<Add s.Line <Add <Count e.Inf> 1>> <Add <Count e.Pref> 2>)
    (e.Postf2) e.Lines>;

    /* Comment ::= (*.**) */
    (s.Line s.Col) ('(' e.Inf '*' e.Postf) e.Lines
    = <Lexer-Pos (s.Line <Add <Count e.Inf> 5>) (e.Postf) e.Lines>;
    (s.Line s.Col) ('(' e.Postf) e.Inf (e.Pref '*') e.Postf2) e.Lines
    = <Lexer-Pos (<Add s.Line <Add <Count e.Inf> 1>> <Add <Count e.Pref> 3>)
    (e.Postf2) e.Lines>;

    /* UNAR_SIGN ::= [+ -] */
    (s.Line s.Col) ('+' e.Syms) e.Lines =
    (UNAR_SIGN ((s.Line s.Col) (s.Line <Inc s.Col>)) '+')
    <Lexer-Pos (s.Line <Inc s.Col>) (e.Syms) e.Lines>;
    (s.Line s.Col) ('-' e.Syms) e.Lines =
    ('-' ((s.Line s.Col) (s.Line <Inc s.Col>)) '-')
    <Lexer-Pos (s.Line <Inc s.Col>) (e.Syms) e.Lines>;

```



```

/* CHAR_SEQUENCE ::= (?<='\')[^\\']+(?='\') */
(s.Line s.Col) ('\\' e.Postf) e.Inf (e.Pref '\\' e.Postf2) e.Lines
, <Add s.Line <Add <Count e.Inf> 1>> <Add <Count e.Pref> 1> : s.Line_ s.Col_
= ('\\' ((s.Line s.Col) (s.Line <Inc s.Col>)))
  (CHAR_SEQUENCE
    ((s.Line <Inc s.Col>) (s.Line_ s.Col_))
    (<Join ('\\n') (e.Postf) e.Inf (e.Pref)>))
    ('\\' ((s.Line_ s.Col_) (s.Line_ <Inc s.Col_>)))
    <Lexer-Pos (s.Line_ <Inc s.Col_>) (e.Postf2) e.Lines>;
(s.Line s.Col) ('\\' e.Inf '\\' e.Postf) e.Lines
, <Add s.Col <Add <Count e.Inf> 1>> : s.Col_
= ('\\' ((s.Line s.Col) (s.Line <Inc s.Col>)))
  (CHAR_SEQUENCE
    ((s.Line <Inc s.Col>) (s.Line s.Col_))
    (e.Inf))
    ('\\' ((s.Line s.Col_) (s.Line <Inc s.Col_>)))
    <Lexer-Pos (s.Line <Inc s.Col_>) (e.Postf) e.Lines>;

/*
  UNSIGNED_NUMBER ::= [0-9]+(\\. [0-9]+)?(E[+-]?[0-9]+)?
  IDENTIFIER ::= [a-zA-Z][a-zA-Z0-9]*
  CHAR ::= .
*/
(s.Line s.Col) (s.LwSym e.LwSyms) e.Lines
, <Upper s.LwSym> : s.Sym
, <Map Upper e.LwSyms> : e.Syms
, <IsDigit s.Sym> : {
TRUE, <ReadNum (s.Col) s.Sym e.Syms> : e.Lexem_ (s.Col_) e.Syms_
= UNSIGNED_NUMBER ((e.Lexem_) (s.Col_) e.Syms_);
FALSE, <IsAlpha s.Sym> : {
TRUE, <ReadIdent (s.Col) s.Sym e.Syms> : e.Lexem_ (s.Col_) e.Syms_
, e.Lexem_ : {
  'INTEGER' = Kw_INTEGER;
  'BOOLEAN' = Kw_BOOLEAN;
  'REAL' = Kw_REAL;
  'CHAR' = Kw_CHAR;
  'TEXT' = Kw_TEXT;
  'PACKED' = Kw_PACKED;
  'ARRAY' = Kw_ARRAY;
  'OF' = Kw_OF;
  'FILE' = Kw_FILE;
  'SET' = Kw_SET;
  'RECORD' = Kw_RECORD;
  'END' = Kw_END;
  'CASE' = Kw_CASE;
  'CONST' = Kw_CONST;

```

```

        'TYPE' = KW_TYPE;
        e._ = IDENTIFIER (e.Lexem_);
    } : t.LexemType_ e.Lexem__
        = t.LexemType_ (e.Lexem__) (s.Col_) e.Syms_;
    FALSE = s.Sym () (<Inc s.Col>) e.Syms;
};
} : s.LexemType (e.Lexem) (s.Col__) e.Syms__
= (s.LexemType ((s.Line s.Col) (s.Line s.Col__)) e.Lexem)
  <Lexer-Pos (s.Line s.Col__) (e.Syms__) e.Lines>;
}

/* <ReadNum (s.Col) e.Syms> == e.Lexem (s.Col) e.Syms */
ReadNum {
    (s.Col) e.Syms
    , <ReadDigits (s.Col) e.Syms> : e.Int (s.Col_) e.Syms_
    , <ReadNumDot (s.Col_) e.Syms_> : e.Dot (s.Col__) e.Syms__
    = e.Int e.Dot <ReadNumExp (s.Col__) e.Syms__>;
}
ReadDigits {
    (s.Col) = (s.Col);
    (s.Col) s.Sym e.Syms
    , <IsDigit s.Sym> : {
        TRUE = s.Sym <ReadDigits (<Inc s.Col>) e.Syms>;
        FALSE = (s.Col) s.Sym e.Syms;
    }
}
ReadNumDot {
    (s.Col) '.' s.Sym e.Syms
    , <IsDigit s.Sym> : {
        TRUE = '.' <ReadDigits (<Inc s.Col>) s.Sym e.Syms>;
        FALSE = (s.Col) '.' s.Sym e.Syms;
    };
    (s.Col) e.Syms = (s.Col) e.Syms;
}
ReadNumSign {
    (s.Col) '+' e.Syms = '+' (<Inc s.Col>) e.Syms;
    (s.Col) '-' e.Syms = '-' (<Inc s.Col>) e.Syms;
    (s.Col) e.Syms = (s.Col) e.Syms;
}
ReadNumExp {
    (s.Col) 'E' s.Sym e.Syms
    , <ReadNumSign (<Inc s.Col>) s.Sym e.Syms> : {
        e.Sign (s.Col_) s.Sym_ e.Syms_
        , <IsDigit s.Sym_> : {
            TRUE = 'E' e.Sign <ReadDigits (s.Col_) s.Sym_ e.Syms_>;
            FALSE = (s.Col) 'E' e.Sign s.Sym_ e.Syms_;
        }
    }
}

```

```

    };
    e.Sign (s.Col_) = (s.Col) 'E' e.Sign;
  };
  (s.Col) e.Syms = (s.Col) e.Syms;
}

/* <ReadIdent (s.Col) e.Syms> == e.Lexem (s.Col) e.Syms */
ReadIdent {
  (s.Col) = (s.Col);
  (s.Col) s.Sym e.Syms
    , <Or <IsAlpha s.Sym> <IsDigit s.Sym>> : {
      TRUE = s.Sym <ReadIdent (<Inc s.Col>) e.Syms>;
      FALSE = (s.Col) s.Sym e.Syms;
    }
}

```

### Main.ref

```

*$FROM LibraryEx
*$FROM Lexer
*$FROM Parser/Parser
$EXTERN ArgList, LoadFile, Map, Lexer, Parse;

$ENTRY Go {
  /* нycto */ = <Main <ArgList>>
}

Main {
  (e.ProgName) (e.InputFile)
    /** /, <Lexer <LoadFile e.InputFile>> : e.Tokens
    = <Map Prout e.Tokens>/**/
    , <Lexer <LoadFile e.InputFile>> : e.Tokens
    , <Parse e.Tokens> : t.ParseTree (e.Errors)
    = <Print-ParseTree () t.ParseTree>
    <Prout "\nERRORS:">
    <Map {(e.Err) = <Prout 'Error: ' e.Err>;} e.Errors>;/**/
}

Print-ParseTree {
  (e.Indent) () = /* нycto */;
  (e.Indent) (s.Nterm (t.Start t.End))
    = <Prout e.Indent '\\' s.Nterm '\\' -> ' t.Start '-' t.End>;
  (e.Indent) (s.Nterm (t.Start t.End) (e.Value))
    = <Prout e.Indent '\\' s.Nterm '\\' -> ' t.Start '-'
    ' t.End ' "' e.Value "'>;
  (e.Indent) (s.Nterm ())

```

```

        = <Prout e.Indent s.Nterm ' ->  $\epsilon$ '>;
    (e.Indent) (s.Nterm (e.Tokens) e.TreeNodes)
    = <Prout e.Indent s.Nterm ' -> ' e.Tokens>
      <Map {
        t.TreeNode = <Print-ParseTree (e.Indent ' ') t.TreeNode>;
      } e.TreeNodes>;
  }

```

## Тестирование

Входные данные

```

Type
  Coords = Record x, y: INTEGER end;
Const
  MaxPoints = 100;
type
  CoordsVector = array 1..MaxPoints of Coords;

const
  Heigh = 480;
  Width = 640;
  Lines = 24;
  Columns = 80;
type
  BaseColor = (red, green, blue, highlited);
  Color = set of BaseColor;
  GraphicScreen = array 1..Heigh of array 1..Width of Color;
  TextScreen = array 1..Lines of array 1..Columns of
    record
      Symbol : CHAR;
      SymColor : Color;
      BackColor : Color
    end;

(* определения токенов *)
{ определения токенов *}
(* определения токенов *)
{ определения токенов *}
{ определения токенов *}
(* определения токенов *}
TYPE
  Domain = (Ident, IntNumber, RealNumber);
  Token = record
    fragment : record

```

```

        start, following : record
            row, col : INTEGER
        end
    end;
end;
case tokType : Domain of
    Ident : (
        name : array 1..32 of CHAR
    );
    IntNumber : (
        intval : INTEGER
    );
    RealNumber : (
        realval : REAL
    );
end;

Year = 1900..2050;

List = record
    value : Token;
    next : ^List
end

```

Вывод на stdout

```

*Compiling Main.ref:
+Linking C:\...\refal-5-lambda\lib\references\Library.ras1
+Linking C:\...\refal-5-lambda\lib\slim\exe\LibraryEx.ras1
*Compiling Lexer.ref:
*Compiling Parser/Parser.ref:
*Compiling Parser/Program/Program.ref:
*Compiling Parser/Block/Block.ref:
*Compiling Parser/Block/BlockConstSequence.ref:
*Compiling Parser/Block/BlockConst.ref:
*Compiling Parser/Constant/Constant.ref:
*Compiling Parser/Constant/UnarSign.ref:
*Compiling Parser/Constant/ConstantIdentifier.ref:
*Compiling Parser/Block/BlockTypeSequence.ref:
*Compiling Parser/Block/BlockType.ref:
*Compiling Parser/Type/Type.ref:
*Compiling Parser/SimpleType/TypeIdentifier.ref:
*Compiling Parser/SimpleType/CommonTypeIdentifier.ref:
*Compiling Parser/Type/TypeAfterPacked.ref:
*Compiling Parser/Type/SimpleTypeList.ref:
*Compiling Parser/SimpleType/SimpleType.ref:
*Compiling Parser/SimpleType/IdentifierList.ref:
*Compiling Parser/FieldList/FieldList.ref:

```

```

*Compiling Parser/FieldList/IdentifierWithTypeList.ref:
*Compiling Parser/FieldList/IdentifierWithType.ref:
*Compiling Parser/FieldList/CaseBlock.ref:
*Compiling Parser/FieldList/CaseVariantSequence.ref:
*Compiling Parser/FieldList/CaseVariant.ref:
*Compiling Parser/FieldList/ConstantList.ref:
** Compilation succeeded **
Program -> Block
Block -> KW_TYPE BlockTypeSequence Block
'KW_TYPE ' -> (1 1 )-(1 5 )
BlockTypeSequence -> BlockType
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (2 3 )-(2 9 ) "COORDS"
'=' -> (2 10 )-(2 11 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (2 12 )-(2 18 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -> IdentifierWithType
IdentifierWithType -> IdentifierList :Type
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (2 19 )-(2 20 ) "X"
',' -> (2 20 )-(2 21 )
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (2 22 )-(2 23 ) "Y"
':' -> (2 23 )-(2 24 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -> CommonTypeIdentifier
CommonTypeIdentifier -> KW_INTEGER
'KW_INTEGER ' -> (2 25 )-(2 32 )
'KW_END ' -> (2 33 )-(2 36 )
';' -> (2 36 )-(2 37 )
Block -> KW_CONST BlockConstSequence Block
'KW_CONST ' -> (3 1 )-(3 6 )
BlockConstSequence -> BlockConst
BlockConst -> IDENTIFIER =Constant ;
'IDENTIFIER ' -> (4 3 )-(4 12 ) "MAXPOINTS"
'=' -> (4 13 )-(4 14 )
Constant -> UNSIGNED_NUMBER
'UNSIGNED_NUMBER ' -> (4 15 )-(4 18 ) "100"
';' -> (4 18 )-(4 19 )
Block -> KW_TYPE BlockTypeSequence Block
'KW_TYPE ' -> (5 1 )-(5 5 )
BlockTypeSequence -> BlockType
BlockType -> IDENTIFIER =Type ;

```

```

'IDENTIFIER ' -> (6 3 )-(6 15 ) "COORDSVECTOR"
'=' -> (6 16 )-(6 17 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_ARRAY SimpleTypeList KW_OF Type
'KW_ARRAY ' -> (6 18 )-(6 23 )
SimpleTypeList -> SimpleType
SimpleType -> Constant ..Constant
'.' -> (6 25 )-(6 26 )
'.' -> (6 26 )-(6 27 )
Constant -> ConstantIdentifier
ConstantIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (6 27 )-(6 36 ) "MAXPOINTS"
'KW_OF ' -> (6 37 )-(6 39 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (6 40 )-(6 46 ) "COORDS"
';' -> (6 46 )-(6 47 )
Block -> KW_CONST BlockConstSequence Block
'KW_CONST ' -> (8 1 )-(8 6 )
BlockConstSequence -> BlockConst BlockConstSequence
BlockConst -> IDENTIFIER =Constant ;
'IDENTIFIER ' -> (9 3 )-(9 8 ) "HEIGH"
'=' -> (9 9 )-(9 10 )
Constant -> UNSIGNED_NUMBER
'UNSIGNED_NUMBER ' -> (9 11 )-(9 14 ) "480"
';' -> (9 14 )-(9 15 )
BlockConstSequence -> BlockConst BlockConstSequence
BlockConst -> IDENTIFIER =Constant ;
'IDENTIFIER ' -> (10 3 )-(10 8 ) "WIDTH"
'=' -> (10 9 )-(10 10 )
Constant -> UNSIGNED_NUMBER
'UNSIGNED_NUMBER ' -> (10 11 )-(10 14 ) "640"
';' -> (10 14 )-(10 15 )
BlockConstSequence -> BlockConst BlockConstSequence
BlockConst -> IDENTIFIER =Constant ;
'IDENTIFIER ' -> (11 3 )-(11 8 ) "LINES"
'=' -> (11 9 )-(11 10 )
Constant -> UNSIGNED_NUMBER
'UNSIGNED_NUMBER ' -> (11 11 )-(11 13 ) "24"
';' -> (11 13 )-(11 14 )
BlockConstSequence -> BlockConst
BlockConst -> IDENTIFIER =Constant ;
'IDENTIFIER ' -> (12 3 )-(12 10 ) "COLUMNS"
'=' -> (12 11 )-(12 12 )
Constant -> UNSIGNED_NUMBER

```

```

        'UNSIGNED_NUMBER ' -> (12 13 )-(12 15 ) "80"
        ';' -> (12 15 )-(12 16 )
Block -> KW_TYPE BlockTypeSequence Block
'KW_TYPE ' -> (13 1 )-(13 5 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (14 3 )-(14 12 ) "BASECOLOR"
'=' -> (14 13 )-(14 14 )
Type -> SimpleType
SimpleType -> (IdentifierList )
'(' -> (14 15 )-(14 16 )
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (14 16 )-(14 19 ) "RED"
',' -> (14 19 )-(14 20 )
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (14 21 )-(14 26 ) "GREEN"
',' -> (14 26 )-(14 27 )
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (14 28 )-(14 32 ) "BLUE"
',' -> (14 32 )-(14 33 )
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (14 34 )-(14 43 ) "HIGHLIGHTED"
')' -> (14 43 )-(14 44 )
';' -> (14 44 )-(14 45 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (15 3 )-(15 8 ) "COLOR"
'=' -> (15 9 )-(15 10 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_SET KW_OF SimpleType
'KW_SET ' -> (15 11 )-(15 14 )
'KW_OF ' -> (15 15 )-(15 17 )
SimpleType -> TypeIdentifier
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (15 18 )-(15 27 ) "BASECOLOR"
';' -> (15 27 )-(15 28 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (16 3 )-(16 16 ) "GRAPHICSCREEN"
'=' -> (16 17 )-(16 18 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_ARRAY SimpleTypeList KW_OF Type
'KW_ARRAY ' -> (16 19 )-(16 24 )
SimpleTypeList -> SimpleType
SimpleType -> Constant ..Constant
'.' -> (16 26 )-(16 27 )

```



```

        '.' -> (16 27 )-(16 28 )
        Constant -> ConstantIdentifier
        ConstantIdentifier -> IDENTIFIER
        'IDENTIFIER ' -> (16 28 )-(16 33 ) "HEIGHT"
        'KW_OF ' -> (16 34 )-(16 36 )
        Type -> TypeAfterPacked
                                TypeAfterPacked -
> KW_ARRAY SimpleTypeList KW_OF Type
        'KW_ARRAY ' -> (16 37 )-(16 42 )
        SimpleTypeList -> SimpleType
        SimpleType -> Constant ..Constant
        '.' -> (16 44 )-(16 45 )
        '.' -> (16 45 )-(16 46 )
        Constant -> ConstantIdentifier
        ConstantIdentifier -> IDENTIFIER
        'IDENTIFIER ' -> (16 46 )-(16 51 ) "WIDTH"
        'KW_OF ' -> (16 52 )-(16 54 )
        Type -> SimpleType
        SimpleType -> TypeIdentifier
        TypeIdentifier -> IDENTIFIER
        'IDENTIFIER ' -> (16 55 )-(16 60 ) "COLOR"
        ';' -> (16 60 )-(16 61 )
        BlockTypeSequence -> BlockType
        BlockType -> IDENTIFIER =Type ;
        'IDENTIFIER ' -> (17 3 )-(17 13 ) "TEXTSCREEN"
        '=' -> (17 14 )-(17 15 )
        Type -> TypeAfterPacked
        TypeAfterPacked -> KW_ARRAY SimpleTypeList KW_OF Type
        'KW_ARRAY ' -> (17 16 )-(17 21 )
        SimpleTypeList -> SimpleType
        SimpleType -> Constant ..Constant
        '.' -> (17 23 )-(17 24 )
        '.' -> (17 24 )-(17 25 )
        Constant -> ConstantIdentifier
        ConstantIdentifier -> IDENTIFIER
        'IDENTIFIER ' -> (17 25 )-(17 30 ) "LINES"
        'KW_OF ' -> (17 31 )-(17 33 )
        Type -> TypeAfterPacked
                                TypeAfterPacked -
> KW_ARRAY SimpleTypeList KW_OF Type
        'KW_ARRAY ' -> (17 34 )-(17 39 )
        SimpleTypeList -> SimpleType
        SimpleType -> Constant ..Constant
        '.' -> (17 41 )-(17 42 )
        '.' -> (17 42 )-(17 43 )
        Constant -> ConstantIdentifier

```

```

ConstantIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (17 43 )-
(17 50 ) "COLUMNS"
'KW_OF ' -> (17 51 )-(17 53 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (18 5 )-(18 11 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -
> IdentifierWithType ;IdentifierWithTypeList
IdentifierWithType -
> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (19 7 )-
(19 13 ) "SYMBOL"
':' -> (19 14 )-(19 15 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -
> CommonTypeIdentifier
CommonTypeIdentifier -> KW_CHAR
'KW_CHAR ' -> (19 16 )-(19 20 )
';' -> (19 20 )-(19 21 )
IdentifierWithTypeList -
> IdentifierWithType ;IdentifierWithTypeList
IdentifierWithType -
> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (20 7 )-
(20 15 ) "SYMCOLOR"
':' -> (20 16 )-(20 17 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -
> (20 18 )-(20 23 ) "COLOR"
';' -> (20 23 )-(20 24 )
IdentifierWithTypeList -
> IdentifierWithType
IdentifierWithType -
> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -
> (21 7 )-(21 16 ) "BACKCOLOR"
':' -> (21 17 )-(21 18 )
Type -> SimpleType

```

```

SimpleType -> TypeIdentifier
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -
> (21 19 )-(21 24 ) "COLOR"
'KW_END ' -> (22 5 )-(22 8 )
';' -> (22 8 )-(22 9 )
Block -> KW_TYPE BlockTypeSequence Block
'KW_TYPE ' -> (30 1 )-(30 5 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (31 3 )-(31 9 ) "DOMAIN"
'=' -> (31 10 )-(31 11 )
Type -> SimpleType
SimpleType -> (IdentifierList )
'(' -> (31 12 )-(31 13 )
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (31 13 )-(31 18 ) "IDENT"
',' -> (31 18 )-(31 19 )
IdentifierList -> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (31 20 )-(31 29 ) "INTNUMBER"
',' -> (31 29 )-(31 30 )
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (31 31 )-(31 41 ) "REALNUMBER"
')' -> (31 41 )-(31 42 )
';' -> (31 42 )-(31 43 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (32 3 )-(32 8 ) "TOKEN"
'=' -> (32 9 )-(32 10 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (32 11 )-(32 17 )
FieldList -> IdentifierWithTypeList ;CaseBlock
IdentifierWithTypeList -> IdentifierWithType
IdentifierWithType -> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (33 5 )-(33 13 ) "FRAGMENT"
':' -> (33 14 )-(33 15 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (33 16 )-(33 22 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -
> IdentifierWithType
IdentifierWithType -
> IdentifierList :Type

```

```

IdentifierList -
> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -> (34 7 )-
(34 12 ) "START"
', ' -> (34 12 )-(34 13 )
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (34 14 )-
(34 23 ) "FOLLOWING"
': ' -> (34 24 )-(34 25 )
Type -> TypeAfterPacked
TypeAfterPacked -
> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (34 26 )-(34 32 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -
> IdentifierWithType
IdentifierWithType -
> IdentifierList :Type
IdentifierList -
> IDENTIFIER ,IdentifierList
'IDENTIFIER ' -
> (35 9 )-(35 12 ) "ROW"
', ' -> (35 12 )-(35 13 )
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -
> (35 14 )-(35 17 ) "COL"
': ' -> (35 18 )-(35 19 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -
> CommonTypeIdentifier
CommonTypeIdentifier -
> KW_INTEGER
'KW_INTEGER ' -
> (35 20 )-(35 27 )
'KW_END ' -> (36 7 )-(36 10 )
'KW_END ' -> (37 5 )-(37 8 )
';' -> (37 8 )-(37 9 )
CaseBlock -> KW_CASE IDENTIFIER :TypeIdentifier KW_OF CaseVariantSequence
'KW_CASE ' -> (38 5 )-(38 9 )
'IDENTIFIER ' -> (38 10 )-(38 17 ) "TOKTYPE"
': ' -> (38 18 )-(38 19 )
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (38 20 )-(38 26 ) "DOMAIN"
'KW_OF ' -> (38 27 )-(38 29 )
CaseVariantSequence -

```

```

> CaseVariant ;CaseVariantSequence
    CaseVariant -> ConstantList :(FieldList )
        ConstantList -> Constant
            Constant -> ConstantIdentifier
            ConstantIdentifier -> IDENTIFIER
            'IDENTIFIER ' -> (39 7 )-(39 12 ) "IDENT"
                ':' -> (39 13 )-(39 14 )
                '(' -> (39 15 )-(39 16 )
            FieldList -> IdentifierWithTypeList
                IdentifierWithTypeList -

> IdentifierWithType
    IdentifierWithType -

> IdentifierList :Type
    IdentifierList -> IDENTIFIER
    'IDENTIFIER ' -> (40 9 )-(40 13 ) "NAME"
        ':' -> (40 14 )-(40 15 )
        Type -> TypeAfterPacked
            TypeAfterPacked -

> KW_ARRAY SimpleTypeList KW_OF Type
    'KW_ARRAY ' -> (40 16 )-(40 21 )
        SimpleTypeList -> SimpleType
        SimpleType -> Constant ..Constant
            '.' -> (40 23 )-(40 24 )
            '.' -> (40 24 )-(40 25 )
            Constant -> UNSIGNED_NUMBER
                'UNSIGNED_NUMBER ' -

> (40 25 )-(40 27 ) "32"
    'KW_OF ' -> (40 28 )-(40 30 )
        Type -> SimpleType
        SimpleType -> TypeIdentifier
            TypeIdentifier -

> CommonTypeIdentifier
    CommonTypeIdentifier -> KW_CHAR
    'KW_CHAR ' -> (40 31 )-(40 35 )
        ')' -> (41 7 )-(41 8 )
        ';' -> (41 8 )-(41 9 )
        CaseVariantSequence -

> CaseVariant ;CaseVariantSequence
    CaseVariant -> ConstantList :(FieldList )
        ConstantList -> Constant
            Constant -> ConstantIdentifier
            ConstantIdentifier -> IDENTIFIER
            'IDENTIFIER ' -> (42 7 )-(
(42 16 ) "INTNUMBER"
                ':' -> (42 17 )-(42 18 )
                '(' -> (42 19 )-(42 20 )

```

```

FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -
> IdentifierWithType
IdentifierWithType -
> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (43 9 )-
(43 15 ) "INTVAL"
':' -> (43 16 )-(43 17 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -
> CommonTypeIdentifier
CommonTypeIdentifier -> KW_INTEGER
'KW_INTEGER ' -> (43 18 )-(43 25 )
')' -> (44 7 )-(44 8 )
';' -> (44 8 )-(44 9 )
CaseVariantSequence -> CaseVariant
CaseVariant -> ConstantList :(FieldList )
ConstantList -> Constant
Constant -> ConstantIdentifier
ConstantIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (45 7 )-
(45 17 ) "REALNUMBER"
':' -> (45 18 )-(45 19 )
'(' -> (45 20 )-(45 21 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList -
> IdentifierWithType
IdentifierWithType -
> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (46 9 )-
(46 16 ) "REALVAL"
':' -> (46 17 )-(46 18 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -
> CommonTypeIdentifier
CommonTypeIdentifier -> KW_REAL
'KW_REAL ' -> (46 19 )-(46 23 )
')' -> (48 3 )-(48 3 )
'KW_END ' -> (48 3 )-(48 6 )
';' -> (48 6 )-(48 7 )
BlockTypeSequence -> BlockType BlockTypeSequence
BlockType -> IDENTIFIER =Type ;

```

```

'IDENTIFIER ' -> (50 3 )-(50 7 ) "YEAR"
'=' -> (50 8 )-(50 9 )
Type -> SimpleType
SimpleType -> Constant ..Constant
'.' -> (50 14 )-(50 15 )
'.' -> (50 15 )-(50 16 )
Constant -> UNSIGNED_NUMBER
'UNSIGNED_NUMBER ' -> (50 16 )-(50 20 ) "2050"
';' -> (50 20 )-(50 21 )
BlockTypeSequence -> BlockType
BlockType -> IDENTIFIER =Type ;
'IDENTIFIER ' -> (52 3 )-(52 7 ) "LIST"
'=' -> (52 8 )-(52 9 )
Type -> TypeAfterPacked
TypeAfterPacked -> KW_RECORD FieldList KW_END
'KW_RECORD ' -> (52 10 )-(52 16 )
FieldList -> IdentifierWithTypeList
IdentifierWithTypeList ->
> IdentifierWithType ;IdentifierWithTypeList
IdentifierWithType -> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (53 5 )-(53 10 ) "VALUE"
':' -> (53 11 )-(53 12 )
Type -> SimpleType
SimpleType -> TypeIdentifier
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (53 13 )-(
(53 18 ) "TOKEN"
';' -> (53 18 )-(53 19 )
IdentifierWithTypeList -> IdentifierWithType
IdentifierWithType -> IdentifierList :Type
IdentifierList -> IDENTIFIER
'IDENTIFIER ' -> (54 5 )-(54 9 ) "NEXT"
':' -> (54 10 )-(54 11 )
Type -> ^TypeIdentifier
'^' -> (54 12 )-(54 13 )
TypeIdentifier -> IDENTIFIER
'IDENTIFIER ' -> (54 13 )-(
(54 17 ) "LIST"
'KW_END ' -> (55 3 )-(55 6 )
';' -> (0 0 )-(0 0 )
Block -> ε

```

ERRORS:

Error: (48 3 )CaseVariant .Unexpected KW\_END .Expected [)].Inserted .  
Error: (EOF )BlockType .Unexpected End Of File .Expected [;].Inserted .

## **Вывод**

В результате выполнения данной работы были изучены алгоритмов построения парсеров методом рекурсивного спуска.