

Basic Data Manipulation

Bui Dinh Ngoc

June 30, 2016

Read an NIfTI file

This is example to read some NIfTI files and execute some basic data manipulation, by using this example code you must be install package `oro.nifti`, `fslr`, `AnalyzeFMRI` first.

Download a NIfTI file from Neurohacking_data repository

```
library(oro.nifti)

url <- "https://raw.githubusercontent.com/muschellij2/Neurohacking/master/Basic_Data_Manipulations/Kirby"
destfile <- "SUBJ0001-01-MPRAGE.nii.gz"
fname <- file.path(getwd(), destfile)
download.file(url, destfile, mode="wb") # NIfTI is binaryfile format

maskurl <- "https://raw.githubusercontent.com/muschellij2/Neurohacking/master/Basic_Data_Manipulations/"
maskdestfile <- "SUBJ0001_mask.nii.gz"
maskfname <- file.path(getwd(), maskdestfile)
download.file(maskurl, maskdestfile, mode="wb") # NIfTI is binaryfile format

T1 <- readNIfTI(fname, reorient=FALSE)

mask <- readNIfTI(maskfname, reorient=FALSE)
```

Show meta data from MPRAGE file

```
print (T1)

## NIfTI-1 format
##   Type           : nifti
##   Data Type      : 16 (FLOAT32)
##   Bits per Pixel  : 32
##   Slice Code     : 0 (Unknown)
##   Intent Code    : 0 (None)
##   Qform Code     : 1 (Scanner_Anat)
##   Sform Code     : 0 (Unknown)
##   Dimension      : 170 x 256 x 256
##   Pixel Dimension : 1.2 x 1 x 1
##   Voxel Units    : mm
##   Time Units     : sec
```

As you see the Dimension is : 170 x 256 x 256

Show meta data from MPRAGE file


```
print (mask)
```

```
## NIfTI-1 format
##   Type           : nifti
##   Data Type      : 4 (INT16)
##   Bits per Pixel  : 16
##   Slice Code     : 0 (Unknown)
##   Intent Code    : 0 (None)
##   Qform Code     : 1 (Scanner_Anat)
##   Sform Code     : 1 (Scanner_Anat)
##   Dimension      : 170 x 256 x 256
##   Pixel Dimension : 1.2 x 1 x 1
##   Voxel Units    : mm
##   Time Units     : sec
```

As you see the of mask is same dimension (170 x 256 x 256).


Visualizing orthographic T1

```
orthographic(T1)
```



Visualizing orthographic mask

```
orthographic(mask)
```




Visualizing orthographic T1*mask

```
library(fslr) # you may need install fslr
```

```
masked.T1 <- niftiarr(T1, T1*mask)
```

```
orthographic(masked.T1)
```




Visualizing orthographic subtract

```
library(fslr) # you may need install fslr

followurl <- "https://raw.githubusercontent.com/muschellij2/Neurohacking/master/Basic_Data_Manipulation"
followdestfile <- "SUBJ0001-02-MPRAGE.nii.gz"
followfname <- file.path(getwd(), followdestfile)
download.file(followurl, followdestfile, mode="wb")

T1.follow <- readNIfTI(followfname, reorient=FALSE)

subtract.T1 <- niftiarr(T1, T1.follow - T1)
orthographic(subtract.T1)
```



Visualizing orthographic subtract process


```
library(fslr) # you may need install fslr

baseurl <- "https://raw.githubusercontent.com/muschellij2/Neurohacking/master/Basic_Data_Manipulations/"
basefile <- "SUBJ0001-01-MPRAGE_N3.nii.gz"
basefname <- file.path(getwd(), basefile)
download.file(baseurl, basefile, mode="wb")

followurl <- "https://raw.githubusercontent.com/muschellij2/Neurohacking/master/Basic_Data_Manipulations/"
followfile <- "SUBJ0001-02-MPRAGE_N3_REG.nii.gz"
followfname <- file.path(getwd(), followfile)
download.file(followurl, followfile, mode="wb")

T1.base.process <- readNifti(basefname, reorient=FALSE)
T1.follow.process <- readNifti(followfname, reorient=FALSE)

subtract.T1.process <- niftiarr(T1, T1.follow.process - T1.base.process)
orthographic(subtract.T1.process)
```



Full generated page can be found here <http://rpubs.com/ngocbd/Basic-Data-Manipulation>