

Name: Borja, Angelo Louis C.
Section: CPE22S3
Performed on: 03/11/2024
Submitted on: 03/20/2024
Submitted to:Engr . Roman M. Richard

✓ **Handling duplicate, missing, or invalid data**

```
from google.colab import drive
drive.mount('/content/drive')

Mounted at /content/drive

import pandas as pd
df = pd.read_csv('/content/drive/MyDrive/dirty_data.csv')
```

Finding problematic data

```
df.head()
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	inclemen
0	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	

```
df.describe()
```

/usr/local/lib/python3.10/dist-packages/numpy/lib/function_base.py:4655: RuntimeWarning
diff_b_a = subtract(b, a)

	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	
count	765.000000	577.000000	577.0	765.000000	765.000000	398.000000	11.000000	
mean	5.360392	4.202773	NaN	2649.175294	-15.914379	8.632161	16.290909	
std	10.002138	25.086077	NaN	2744.156281	24.242849	9.815054	9.489832	
min	0.000000	0.000000	-inf	-11.700000	-40.000000	-16.100000	1.800000	
25%	0.000000	0.000000	NaN	13.300000	-40.000000	0.150000	8.600000	
50%	0.000000	0.000000	NaN	32.800000	-11.100000	8.300000	19.300000	
75%	5.800000	0.000000	NaN	5505.000000	6.700000	18.300000	24.900000	
max	61.700000	229.000000	inf	5505.000000	23.900000	26.100000	28.700000	

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 765 entries, 0 to 764
Data columns (total 10 columns):
#   Column              Non-Null Count  Dtype
---  -
0   date                 765 non-null   object
1   station              765 non-null   object
2   PRCP                 765 non-null   float64
3   SNOW                 577 non-null   float64
4   SNWD                 577 non-null   float64
5   TMAX                 765 non-null   float64
6   TMIN                 765 non-null   float64
7   TOBS                 398 non-null   float64
8   WESF                 11 non-null    float64
9   inclement_weather  408 non-null   object
```

```
dtypes: float64(7), object(3)
memory usage: 59.9+ KB
```

```
# creates a new dataframe where the it contains entries from df
# that have null or NaN values in their 'TOBS' or 'WESF' columns
contain_nulls = df[
    df.SNOW.isnull() | df.SNWD.isna()\
    | pd.isnull(df.TOBS) | pd.isna(df.WESF)\
    | df.inclement_weather.isna()
]
contain_nulls.shape[0]
```

```
765
```

```
contain_nulls.head(10)
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	incleme
0	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
3	2018-01-02T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-8.3	-16.1	-12.2	NaN	
4	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	
5	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	

```
# NaN is not a string so it doesn't work
df[df.inclement_weather == 'NaN'].shape[0]
```

```
0
```

```
# this will also not work
import numpy as np
df[df.inclement_weather == np.nan].shape[0]
```

```
0
```

```
# to check if a column of an entry have missing values
# use isna() method
df[df.inclement_weather.isna()].shape[0]
```

```
357
```

```
# to check for inf and -inf values in their column entries
# use isin() method
df[df.SNWD.isin([-np.inf, np.inf])].shape[0]
```

```
577
```

```
# creates a dictionary where it counts the number of inf and -inf
# values for each column
import numpy as np
def get_inf_count(df):
    """Find the number of inf/-inf values per column in the dataframe"""
    return {
        col : df[df[col].isin([np.inf, -np.inf])].shape[0] for col in df.columns
    }
get_inf_count(df)
```

```
{'date': 0,
 'station': 0,
 'PRCP': 0,
 'SNOW': 0,
 'SNWD': 577,
 'TMAX': 0,
 'TMIN': 0,
 'TOBS': 0,
 'WESF': 0,
 'inclement_weather': 0}

# inspect by finding the statistical summary of both entries that have
# an inf or -inf in their 'SNWD'
pd.DataFrame({
    'np.inf Snow Depth': df[df.SNWD == np.inf].SNOW.describe(),
    '-np.inf Snow Depth': df[df.SNWD == -np.inf].SNOW.describe()
}).T
```

	count	mean	std	min	25%	50%	75%	max
np.inf Snow Depth	24.0	101.041667	74.498018	13.0	25.0	120.5	152.0	229.0
-np.inf Snow Depth	553.0	0.000000	0.000000	0.0	0.0	0.0	0.0	0.0

```
df.describe(include='object')
```

	date	station	inclement_weather
count	765	765	408
unique	324	2	2
top	2018-07-05T00:00:00	GHCND:USC00280907	False
freq	8	398	384

```
df[df.duplicated()].shape[0]
```

284

```
df[df.duplicated(keep=False)].shape[0]
```

482

```
df[df.duplicated(['date', 'station'])].shape[0]
```

284

```
df[df.duplicated()].head()
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	incleme
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
5	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	

✓ Mitigating Issues

Handling duplicated data

```
df[df.WESF.notna()].station.unique()

array(['?'], dtype=object)

# save this information for later
station_qm_wesf = df[df.station == '?'].WESF
# sort ? to the bottom
df.sort_values('station', ascending=False, inplace=True)
# drop duplicates based on the date column keeping the first occurrence
# which will be the valid station if it has data
df_deduped = df.drop_duplicates('date').drop(
    # remove the station column because we are done with it
    # and WESF because we need to replace it later
    columns=['station', 'WESF']

).sort_values('date').assign( # sort by the date
    # add back the WESF column which will be properly matched because of the index
    WESF=station_qm_wesf
)
df_deduped.shape

(324, 9)

df_deduped.head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF	
0	2018-01-01T00:00:00	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	NaN	
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	NaN	
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	NaN	
~	2018-01-	00.0	000.0	-inf	5505.0	-40.0	NaN	NaN	NaN	

Dealing with nulls

```
df_deduped.dropna().shape

(0, 9)

df_deduped.dropna(how='all').shape

(324, 9)

df_deduped.dropna(
    how='all', subset=['inclement_weather', 'SNOW', 'SNWD']
).shape

(293, 9)

df_deduped.dropna(axis='columns', thresh=df_deduped.shape[0]*.75).columns

Index(['date', 'PRCP', 'SNOW', 'SNWD', 'TMAX', 'TMIN', 'TOBS',
       'inclement_weather'],
      dtype='object')

df_deduped.loc[:, 'WESF'].fillna(0, inplace=True)
df_deduped.head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	0.0

```
df_deduped.assign(
    TMAX=lambda x: x.TMAX.replace(5505, np.nan).fillna(method='ffill'),
    TMIN=lambda x: x.TMIN.replace(-40, np.nan).fillna(method='ffill')
).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	NaN	NaN	NaN	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0

```
df_deduped.assign(
    SNWD=lambda x: np.nan_to_num(x.SNWD)
).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-1.797693e+308	5505.0	-40.0	NaN	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-1.797693e+308	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-1.797693e+308	-4.4	-13.9	-13.3	False	0.0

```
df_deduped.assign(
    TMAX=lambda x: x.TMAX.replace(5505, np.nan).fillna(x.TMAX.median()),
    TMIN=lambda x: x.TMIN.replace(-40, np.nan).fillna(x.TMIN.median()),
    # average of TMAX and TMIN
    TOBS=lambda x: x.TOBS.fillna((x.TMAX + x.TMIN) / 2)
).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	22.8	0.0	11.4	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	0.0	0.0	-inf	22.8	0.0	11.4	NaN	0.0

```
df_deduped.assign(
    # make TMAX and TMIN NaN where appropriate
    TMAX=lambda x: x.TMAX.replace(5505, np.nan),
    TMIN=lambda x: x.TMIN.replace(-40, np.nan)
).set_index('date').apply(
    # rolling calculations will be covered in chapter 4, this is a rolling 7 day median
    # we set min_periods (# of periods required for calculation) to 0 so we always get a result
    lambda x: x.fillna(x.rolling(7, min_periods=0).median())
).head(10)
```

	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF	
date									
2018-01-01T00:00:00	0.0	0.0	-inf	NaN	NaN	NaN		NaN	0.0
2018-01-02T00:00:00	0.0	0.0	-inf	-8.30	-16.1	-12.20		False	0.0
2018-01-03T00:00:00	0.0	0.0	-inf	-4.40	-13.9	-13.30		False	0.0
2018-01-04T00:00:00	20.6	229.0	inf	-6.35	-15.0	-12.75		True	19.3
2018-01-05T00:00:00	14.2	127.0	inf	-4.40	-13.9	-13.90		True	0.0
2018-01-06T00:00:00	0.0	0.0	-inf	-10.00	-15.6	-15.00		False	0.0
2018-01-07T00:00:00	0.0	0.0	-inf	-11.70	-17.2	-16.10		False	0.0
2018-01-08T00:00:00	0.0	0.0	-inf	-7.80	-16.7	-8.30		False	0.0
2018-01-10T00:00:00	0.0	0.0	-inf	5.00	-7.8	-7.80		False	0.0
2018-01-11T00:00:00	0.0	0.0	-inf	4.40	-7.8	1.10		False	0.0

```
df_deduped.assign(
    # make TMAX and TMIN NaN where appropriate
    TMAX=lambda x: x.TMAX.replace(5505, np.nan),
    TMIN=lambda x: x.TMIN.replace(-40, np.nan),
    date=lambda x: pd.to_datetime(x.date)
).set_index('date').reindex(
    pd.date_range('2018-01-01', '2018-12-31', freq='D')
).apply(
    lambda x: x.interpolate()
).head(10)
```

	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF	
2018-01-01	0.0	0.0	-inf	NaN	NaN	NaN		NaN	0.0
2018-01-02	0.0	0.0	-inf	-8.3	-16.10	-12.20		False	0.0
2018-01-03	0.0	0.0	-inf	-4.4	-13.90	-13.30		False	0.0
2018-01-04	20.6	229.0	inf	-4.4	-13.90	-13.60		True	19.3
2018-01-05	14.2	127.0	inf	-4.4	-13.90	-13.90		True	0.0
2018-01-06	0.0	0.0	-inf	-10.0	-15.60	-15.00		False	0.0
2018-01-07	0.0	0.0	-inf	-11.7	-17.20	-16.10		False	0.0
2018-01-08	0.0	0.0	-inf	-7.8	-16.70	-8.30		False	0.0
2018-01-09	0.0	0.0	-inf	-1.4	-12.25	-8.05		NaN	0.0
2018-01-10	0.0	0.0	-inf	5.0	-7.80	-7.80		False	0.0