

# SICP Notes 02

<https://mitpress.mit.edu/sicp/>

<http://www.aduni.org/courses/sicp/index.php>

Geoffrey Matthews

Department of Computer Science  
Western Washington University

March 31, 2015

# Mantra Review

- ▶ Every expression has a value (exceptions: errors, infinite loops and define)
- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest
- ▶ The value of a lambda expression is a procedure

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

(+ 2 3)

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

(+ 2 3)

(+ 2 3)

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

(+ 2 3)

(+ 2 3)

(+ 2 3)

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

(+ 2 3)

(+ 2 3)

(+ 2 3)

(+ 2 3)

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

(+ 2 3)

(+ 2 3)

(+ 2 3)

(+ 2 3)

5

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$



# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ \boxed{(- \ 8 \ 2)} \ \boxed{5})$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ \boxed{(- \ 8 \ 2)} \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ \boxed{6} \ \boxed{5})$

# Values of combinations

- ▶ To find the value of a combination,
  - ▶ Find the values of all of the subexpressions, in any order
  - ▶ Apply the value of the first to the values of the rest

$(+ \ 3 \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ (+ \ 2 \ 3))$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{(+ \ 2 \ 3)})$

$(+ \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ (- \ 8 \ 2) \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ \boxed{(- \ 8 \ 2)} \ \boxed{5})$

$(\boxed{+} \ \boxed{3} \ \boxed{6} \ \boxed{5})$

14

# Compound procedures

- ▶ `(lambda (x) (* x x))`
- ▶ What is/are the parameters?



# Compound procedures

- ▶ `(lambda (x) (* x x))`
- ▶ What is/are the parameters?
- ▶ `x` is the only parameter in the parameter list `(x)`

# Compound procedures

- ▶ `(lambda (x) (* x x))`
- ▶ What is/are the parameters?
- ▶ `x` is the only parameter in the parameter list `(x)`
- ▶ What is the body?

# Compound procedures

- ▶ `(lambda (x) (* x x))`
- ▶ What is/are the parameters?
- ▶ `x` is the only parameter in the parameter list `(x)`
- ▶ What is the body?
- ▶ `(* x x)` is the body of the lambda expression.

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```



## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```

```
(if (< -5 0) (- -5) -5)
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if (< -5 0) (- -5) -5)
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if #t (- -5) -5)
```

## Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if #t (- -5) -5)
```

```
(- -5)
```

# Substitution Model

To apply a compound procedure to arguments, evaluate the body of the procedure with each formal parameter replaced by the corresponding argument.

```
(define absolute-value (lambda (n) (if (< n 0) (- n) n)))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value (+ 3 -8))
```

```
(absolute-value -5)
```

```
(absolute-value -5)
```

```
((lambda (n) (if (< n 0) (- n) n)) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if (< -5 0) (- -5) -5)
```

```
(if #t (- -5) -5)
```

```
(- -5)
```

5

## Computing the Euclidean distance between two points

```
(define square  
  (lambda (x) (* x x)))
```

```
(define sum-squares  
  (lambda (x y) (+ (square x) (square y))))
```

```
(define dist-between-pts  
  (lambda (x1 y1 x2 y2)  
    (sqrt (sum-squares (- x1 x2) (- y1 y2)))))
```

Use the substitution model to evaluate (dist-between-pts 1 1 4 5):

# Applicative and Normal Order

- ▶ **Applicative Order:** Evaluate the arguments and then apply the value of the first to the value of the rest.
  - ▶ Everything is evaluated, whether or not we use it.
  - ▶ This is the method Scheme uses and is the reason that we need special forms.
- ▶ **Normal Order:** Fully expand, then reduce. Don't evaluate operands until they are needed.

## Applicative and normal order

```
(define square  
  (lambda (x) (* x x)))
```

```
(define sum-squares  
  (lambda (x y) (+ (square x) (square y))))
```

```
(define dist-between-pts  
  (lambda (x1 y1 x2 y2)  
    (sqrt (sum-squares (- x1 x2) (- y1 y2)))))
```

```
(sum-squares (+ 5 1) (* 6 2))
```



## Applicative and normal order

```
(define square  
  (lambda (x) (* x x)))
```

```
(define sum-squares  
  (lambda (x y) (+ (square x) (square y))))
```

```
(define dist-between-pts  
  (lambda (x1 y1 x2 y2)  
    (sqrt (sum-squares (- x1 x2) (- y1 y2)))))
```

```
(sum-squares (+ 5 1) (* 6 2))
```

- ▶ Normal order is not as efficient as applicative order. We needed to evaluate  $(+ 5 1)$  and  $(* 6 2)$  twice each using normal order, instead of once each with applicative order.

## Applicative and normal order

```
(define square  
  (lambda (x) (* x x)))
```

```
(define sum-squares  
  (lambda (x y) (+ (square x) (square y))))
```

```
(define dist-between-pts  
  (lambda (x1 y1 x2 y2)  
    (sqrt (sum-squares (- x1 x2) (- y1 y2)))))
```

```
(sum-squares (+ 5 1) (* 6 2))
```

- ▶ Normal order is not as efficient as applicative order. We needed to evaluate  $(+ 5 1)$  and  $(* 6 2)$  twice each using normal order, instead of once each with applicative order.
- ▶ How can we test if Scheme is applicative or normal order?

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?
- ▶ It calls itself repeatedly, causing an infinite loop.

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?
- ▶ It calls itself repeatedly, causing an infinite loop.

```
(define test  
  (lambda (x y)  
    (if (= x 0)  
        0  
        y)))
```

```
(test 0 (p))
```

- ▶ What happens with applicative order?

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?
- ▶ It calls itself repeatedly, causing an infinite loop.

```
(define test  
  (lambda (x y)  
    (if (= x 0)  
        0  
        y)))
```

```
(test 0 (p))
```

- ▶ What happens with applicative order?
- ▶ We get an infinite loop.

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?
- ▶ It calls itself repeatedly, causing an infinite loop.

```
(define test  
  (lambda (x y)  
    (if (= x 0)  
        0  
        y)))
```

```
(test 0 (p))
```

- ▶ What happens with applicative order?
- ▶ We get an infinite loop.
- ▶ What happens with normal order?

## Applicative and normal order

```
(define p (lambda () (p)))
```

- ▶ What does this function do?
- ▶ It calls itself repeatedly, causing an infinite loop.

```
(define test  
  (lambda (x y)  
    (if (= x 0)  
        0  
        y)))
```

```
(test 0 (p))
```

- ▶ What happens with applicative order?
- ▶ We get an infinite loop.
- ▶ What happens with normal order?
- ▶ It returns 0.



## Writing our own if

What if if were not a special form?

```
(define new-if
  (lambda (predicate consequent alternative)
    (cond (predicate consequent)
          (else alternative)))))
```

What happens when we evaluate (new-if (> 3 2) 0 2)?

```
(new-if (> 3 2) 0 2)
(new-if (> 3 2) 0 2)
(new-if (> 3 2) 0 2)
(new-if (> 3 2) 0 2)
(new-if #t 0 2)
(cond (#t 0) (else 2))
0
```

No real problems so far.

## Writing our own if

```
(define fact
  (lambda (n)
    (if (= n 0)
        1
        (* n (fact (- n 1))))))
```

- What if we use new-if instead of the special form if?

## Writing our own if

```
(define fact
  (lambda (n)
    (if (= n 0)
        1
        (* n (fact (- n 1))))))
```

- ▶ What if we use new-if instead of the special form if?
- ▶ We'll get an infinite loop, since `(* n (fact (- n 1)))` will be evaluated every time, even if we have hit the base case.