

Generalization Error

ML Instruction Team, Fall 2022

CE Department
Sharif University of Technology

ML Cycle

- In every ML project:
 - ▷ You study the data.
 - ▷ You select a model.
 - ▷ You train it on the training data (i.e., it searches for model parameters that minimize a cost function).
 - ▷ As a final step, you apply the model to predict new cases, which is called inference, and you expect the model to generalize well.
- In addition to predicting the training examples correctly, the model should also be capable of generalizing to new cases.
 - ▷ It is only through the application of a model to new cases that we can determine how well it will generalize.
 - ▷ Putting your model into production and monitoring how well it performs is one way to do that.
 - ▷ The more suitable strategy would be to divide your data into two sets: a Training set and a Test set.

Measuring Generalization

- **Training Set:** which is used to train the model.
- **Validation Set:** which is used to tune the hyperparameters of the model.
- **Test Set:** which is used to measure the generalization performance.
- The losses on these subsets are called **training** , **validation** , and **test** loss, respectively.
- **Cost Function:** the average loss over the **training set** :

$$\frac{1}{N} \sum_{i=1}^N \mathcal{L}(y_i, \hat{y}_i)$$

- What is the purpose of the **hyperparameter tuning** in ML projects?

Bias + Variance

■ What are Bias and Variance:

- ▷ **Bias**: is commonly defined as the difference between the expected value of the estimator and the parameter that we want to estimate.
- ▷ **Variance**: is defined as the difference between the expected value of the squared estimator minus the squared expectation of the estimator.

$$\text{Bias}(\hat{\theta}) = \mathbb{E}[\hat{\theta}] - \theta, \quad \text{Var}(\hat{\theta}) = \mathbb{E}[(\mathbb{E}[\hat{\theta}] - \hat{\theta})^2].$$

■ Bias-Variance Decomposition:

$$\begin{aligned} \text{MSE} &:= \mathbb{E}[(y - \hat{y})^2] \\ &= \mathbb{E}[y^2 + \hat{y}^2 - 2y\hat{y}] = \mathbb{E}[y^2] + \mathbb{E}[\hat{y}^2] - \mathbb{E}[y\hat{y}] \\ &= \text{Var}(y) + \mathbb{E}[y]^2 + \text{Var}[\hat{y}] + \mathbb{E}[\hat{y}]^2 - 2y\mathbb{E}[\hat{y}] \\ &= \text{Var}(y) + \text{Var}(\hat{y}) + (y^2 - 2y\mathbb{E}[\hat{y}] + \mathbb{E}[\hat{y}]^2) \\ &= \text{Var}(y) + \text{Var}(\hat{y}) + (y - \mathbb{E}[\hat{y}])^2 \\ &= \varepsilon^2 + \text{Var}[\hat{y}] + \text{Bias}[\hat{y}]^2 \end{aligned}$$

Overfitting

- **Overfitting** means the model works well on training data, but it doesn't generalize well.
- Overfitting occurs when there is too much complexity in the model in comparison to the amount and noise in the training data.




Figure: High Variance, [Source](#)

- How to fix this problem?
 - ▷ Simplify the model by selecting one with fewer parameters, reducing the number of attributes in the training data, or constraining the model.
 - ▷ Gather more training data.
 - ▷ Reduce the noise in the training data.

Underfitting

- **Underfitting** is the opposite of overfitting: it occurs when your model is too simple to learn the underlying structure of the data.




Figure: High Variance, Source

- The main options to fix this problem:
 - ▷ Selecting a more powerful model, with more parameters
 - ▷ Feeding better features to the learning algorithm (feature engineering)
 - ▷ Reducing the constraints on the model (e.g., reducing the regularization hyperparameter)

Overview




Figure: Overfitting vs Underfitting, [Source](#)

Overview




Figure: Overfitting vs Underfitting, [Source](#)

Thank You!

Any Question?