

D. Misha and Permutations Summation

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Let's define the sum of two permutations p and q of numbers $0, 1, \dots, (n - 1)$ as permutation $Perm((Ord(p) + Ord(q)) \bmod n!)$, where $Perm(x)$ is the x -th lexicographically permutation of numbers $0, 1, \dots, (n - 1)$ (counting from zero), and $Ord(p)$ is the number of permutation p in the lexicographical order.

For example, $Perm(0) = (0, 1, \dots, n - 2, n - 1)$, $Perm(n! - 1) = (n - 1, n - 2, \dots, 1, 0)$

Misha has two permutations, p and q . Your task is to find their sum.

Permutation $a = (a_0, a_1, \dots, a_{n-1})$ is called to be lexicographically smaller than permutation $b = (b_0, b_1, \dots, b_{n-1})$, if for some k following conditions hold:
 $a_0 = b_0, a_1 = b_1, \dots, a_{k-1} = b_{k-1}, a_k < b_k$.

Input

The first line contains an integer n ($1 \leq n \leq 200\,000$).

The second line contains n distinct integers from 0 to $n - 1$, separated by a space, forming permutation p .

The third line contains n distinct integers from 0 to $n - 1$, separated by spaces, forming permutation q .

Output

Print n distinct integers from 0 to $n - 1$, forming the sum of the given permutations. Separate the numbers by spaces.

Examples

input	Copy
2 0 1 0 1	
output	Copy
0 1	
input	Copy
2 0 1 1 0	
output	Copy
1 0	

Codeforces Round #285 (Div. 2)

Finished

→ Practice?

Want to solve the contest problems after the official contest ends? Just register for practice and you will be able to submit solutions.

[Register for practice](#)

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Problem tags

[data structures](#) [*2000](#)

No tag edit access

→ Contest materials

- Announcement [×](#)
- Tutorial #1 (ru) [×](#)
- Tutorial #2 (en) [×](#)

input	Copy
<pre>3 1 2 0 2 1 0</pre>	
output	Copy
<pre>1 0 2</pre>	

Note

Permutations of numbers from 0 to 1 in the lexicographical order: (0, 1), (1, 0).

In the first sample $Ord(p) = 0$ and $Ord(q) = 0$, so the answer is
 $Perm((0 + 0) \bmod 2) = Perm(0) = (0, 1)$.

In the second sample $Ord(p) = 0$ and $Ord(q) = 1$, so the answer is
 $Perm((0 + 1) \bmod 2) = Perm(1) = (1, 0)$.

Permutations of numbers from 0 to 2 in the lexicographical order:
(0, 1, 2), (0, 2, 1), (1, 0, 2), (1, 2, 0), (2, 0, 1), (2, 1, 0).

In the third sample $Ord(p) = 3$ and $Ord(q) = 5$, so the answer is
 $Perm((3 + 5) \bmod 6) = Perm(2) = (1, 0, 2)$.

[Codeforces](#) (c) Copyright 2010-2020 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Jun/01/2020 12:55:28^{UTC-4} (i1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#)

Supported by



ITMO UNIVERSITY