

D. Subway

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

A subway scheme, classic for all Berland cities is represented by a set of n stations connected by n passages, each of which connects exactly two stations and does not pass through any others. Besides, in the classic scheme one can get from any station to any other one along the passages. The passages can be used to move in both directions. Between each pair of stations there is no more than one passage.

Berland mathematicians have recently proved a theorem that states that any classic scheme has a ringroad. There can be only one ringroad. In other words, in any classic scheme one can find the only scheme consisting of stations (where any two neighbouring ones are linked by a passage) and this cycle doesn't contain any station more than once.

This invention had a powerful social impact as now the stations could be compared according to their distance from the ringroad. For example, a citizen could say "I live in three passages from the ringroad" and another one could reply "you loser, I live in one passage from the ringroad". The Internet soon got filled with applications that promised to count the distance from the station to the ringroad (send a text message to a short number...).

The Berland government decided to put an end to these disturbances and start to control the situation. You are requested to write a program that can determine the remoteness from the ringroad for each station by the city subway scheme.

Input

The first line contains an integer n ($3 \leq n \leq 3000$), n is the number of stations (and trains at the same time) in the subway scheme. Then n lines contain descriptions of the trains, one per line. Each line contains a pair of integers x_i, y_i ($1 \leq x_i, y_i \leq n$) and represents the presence of a passage from station x_i to station y_i . The stations are numbered from 1 to n in an arbitrary order. It is guaranteed that $x_i \neq y_i$ and that no pair of stations contain more than one passage. The passages can be used to travel both ways. It is guaranteed that the given description represents a classic subway scheme.

Output

Print n numbers. Separate the numbers by spaces, the i -th one should be equal to the distance of the i -th station from the ringroad. For the ringroad stations print number 0.

Examples

input	Copy
<pre>4 1 3 4 3 4 2 1 2</pre>	
output	Copy

→ Attention

Package for this problem was not updated by the problem writer or Codeforces administration after we've upgraded the judging servers. To adjust the time limit constraint, solution execution time will be multiplied by 2. For example, if your solution works for 400 ms on judging servers, then value 800 ms will be displayed and used to determine the verdict.

Codeforces Beta Round #95 (Div. 2)

Finished

→ Virtual participation



Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Problem tags

dfs and similar graphs *1600
No tag edit access

→ Contest materials

- Announcement 
- Tutorial #1 (en) 
- Tutorial #2 (ru) 
- Tutorial #3 (ru) 

```
0 0 0 0
```

input**Copy**

```
6
1 2
3 4
6 4
2 3
1 3
3 5
```

output**Copy**

```
0 0 0 1 1 2
```

[Codeforces](#) (c) Copyright 2010-2020 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: May/12/2020 21:10:18^{UTC-4} (h3).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#)

Supported by



ITMO UNIVERSITY