



Please, try [EDU on Codeforces](#)! New educational section with videos, subtitles, texts, and problems.

[PROBLEMS](#) [SUBMIT](#) [STATUS](#) [STANDINGS](#) [CUSTOM TEST](#)

F1. Flying Sort (Easy Version)

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

This is an easy version of the problem. In this version, all numbers in the given array are distinct and the constraints on n are less than in the hard version of the problem.

You are given an array a of n integers (**there are no equals elements in the array**). You can perform the following operations on array elements:

- choose any index i ($1 \leq i \leq n$) and move the element $a[i]$ to the **begin** of the array;
- choose any index i ($1 \leq i \leq n$) and move the element $a[i]$ to the **end** of the array.

For example, if $n = 5$, $a = [4, 7, 2, 3, 9]$, then the following sequence of operations can be performed:

- after performing the operation of the first type to the second element, the array a will become $[7, 4, 2, 3, 9]$;
- after performing the operation of the second type to the second element, the array a will become $[7, 2, 3, 9, 4]$.

You can perform operations of any type any number of times in any order.

Find the minimum total number of operations of the first and second type that will make the a array sorted in non-decreasing order. In other words, what is the minimum number of operations that must be performed so the array satisfies the inequalities $a[1] \leq a[2] \leq \dots \leq a[n]$.

Input

The first line contains a single integer t ($1 \leq t \leq 100$) — the number of test cases in the test. Then t test cases follow.

Each test case starts with a line containing an integer n ($1 \leq n \leq 3000$) — length of the array a .

Then follow n integers a_1, a_2, \dots, a_n ($0 \leq a_i \leq 10^9$) — an array that needs to be sorted by the given operations. **All numbers in the given array are distinct.**

The sum of n for all test cases in one test does not exceed 3000.

Output

For each test case output one integer — the minimum total number of operations of the first and second type, which will make the array sorted in non-decreasing order.

Codeforces Round #650 (Div. 3)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Problem tags

[dp](#) [greedy](#) [two pointers](#) [*2100](#)

No tag edit access

→ Contest materials

- Announcement
- Tutorial

Example

input	Copy
4 5 4 7 2 3 9 5 3 5 8 1 7 5 1 4 5 7 12 4 0 2 1 3	
output	Copy
2 2 0 2	

Note

In the first test case, you first need to move 3, and then 2 to the beginning of the array.

Therefore, the desired sequence of operations:

$[4, 7, 2, 3, 9] \rightarrow [3, 4, 7, 2, 9] \rightarrow [2, 3, 4, 7, 9]$.

In the second test case, you need to move the 1 to the beginning of the array, and the 8 — to the end. Therefore, the desired sequence of operations:

$[3, 5, 8, 1, 7] \rightarrow [1, 3, 5, 8, 7] \rightarrow [1, 3, 5, 7, 8]$.

In the third test case, the array is already sorted.

[Codeforces](#) (c) Copyright 2010-2020 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Jul/01/2020 08:08:43^{UTC-4} (i1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#)

Supported by



ITMO UNIVERSITY