

# An algorithmic reasoning approach to GNNs

A project for the *Deep Learning* course

---

Angela Carraro, Matteo Scoria

DSSC + IN20 - UNITS



**Graph Neural Networks** can have a lot of meanings, there isn't just one architecture that can be recognized as "GNN". We will try to understand the general, abstract structure of a GNN that is presented in the book [3] (which also includes [2]) and to shed light about the relational inductive bias and combinatorial generalization of a GNN.

Our motivation is to better understand the extent to which graph neural networks are capable of **precise and logical reasoning**.

Graphs are a widespread data structure and a universal language for describing and modelling complex systems. In the most general view, a graph is simply a collection of objects (i.e., nodes), along with a set of interactions (i.e., edges) between pairs of these objects.

Graphs are an important building block since they can naturally encode an **entity-relationship structure**, as well as an **invariance to permutations** (of both nodes and edges) and awareness of **input sparsity**.




Figure 1: A graph.

### Definition

A **graph** is a tuple  $G = (V, E)$  where  $V$  is the set of nodes and  $E$  is the set of edges between these nodes. We denote an edge going from node  $u \in V$  to node  $v \in V$  as  $(u, v) \in E$ , so  $E \subseteq V \times V$ . The graph is **undirected** if  $(u, v) \in E \iff (v, u) \in E$ , otherwise it is **directed**.


A convenient way to represent graphs is through an **adjacency matrix**  $A \in \mathbb{R}^{|V| \times |V|}$ , with  $A[u, v] = 1$  if  $(u, v) \in E$  and  $A[u, v] = 0$  otherwise. If the graph is undirected the matrix is *symmetric*. If the graph has weighted edges we have that  $A[u, v] \in \mathbb{R}$ .

We also have **attribute** or **feature** information associated with a graph. Most often these are *node-level attributes* that we represent using a real-valued matrix  $\mathbf{X} \in \mathbb{R}^{d \times |V|}$ , where we assume that the ordering of the nodes is consistent with the ordering in the adjacency matrix. In some cases we even associate real-valued *features with entire graphs*.

GNNs are used for one of three tasks:





- *node classification*: predict the label of a given node  
→ E.g., predicting whether a user is a bot in a social network
- *edge prediction*: infer the edges between nodes in a graph  
→ E.g., content recommendation in online platforms, predicting drug side-effects, or inferring new facts in a relational databases
- *graph classification*: make independent predictions specific to each graph  
→ E.g., property prediction based on molecular graph structures

Thank you for your attention!



# References

---

-  Miltos Allamanis. *An Introduction to Graph Neural Networks: Models and Applications*. Youtube. 2020. URL: [https://www.youtube.com/watch?v=zCEYiCxrL\\_0](https://www.youtube.com/watch?v=zCEYiCxrL_0).
-  Peter W. Battaglia et al. “Relational inductive biases, deep learning, and graph networks”. In: CoRR abs/1806.01261 (2018). arXiv: [1806.01261](https://arxiv.org/abs/1806.01261). URL: <http://arxiv.org/abs/1806.01261>.
-  William L. Hamilton. *Graph Representation Learning*. Vol. 14. 3. Morgan and Claypool, 2020, pp. 1–159. URL: [https://www.cs.mcgill.ca/~wlh/grl\\_book/](https://www.cs.mcgill.ca/~wlh/grl_book/).
-  William L. Hamilton. *Graph Representation Learning*. Youtube. 2021. URL: <https://www.youtube.com/watch?v=fbRDfhNrCwo>.

-  William L. Hamilton, Rex Ying, and Jure Leskovec. “Representation Learning on Graphs: Methods and Applications”. In: CoRR abs/1709.05584 (2017). arXiv: [1709.05584](http://arxiv.org/abs/1709.05584). URL: <http://arxiv.org/abs/1709.05584>.
-  Petar Veličković. *Graph Representation Learning for Algorithmic Reasoning*. Youtube. 2020. URL: <https://www.youtube.com/watch?v=IPQ6CPoLuok>.
-  Petar Veličković. *Theoretical Foundations of Graph Neural Networks*. Youtube. 2021. URL: <https://www.youtube.com/watch?v=uF53xsT7mjc>.
-  Yujun Yan et al. “Neural Execution Engines: Learning to Execute Subroutines”. In: CoRR abs/2006.08084 (2020). arXiv: [2006.08084](https://arxiv.org/abs/2006.08084). URL: <https://arxiv.org/abs/2006.08084>.