

Project report

M Ahsan Al Mahir

The report should be considered to be a technical document designed to be readable by a computer scientist who is not a specialist in the topic, say one of your colleagues. The sort of structure that would suit many programming projects is as follows:

- (i) Abstract: a brief description of what you did; about 200 words.
- (ii) Contents.
- (iii) Chapters 1, 2, etc. Areas to cover: Introduction, Explanation of the Problem or Context, Description of the Method, Account of the Work (several chapters, the main body of the dissertation), Conclusions.
- (iv) A bibliography and list of reference

§1 The Apollo Guidance Computer (AGC)

The Apollo Guidance Computer (AGC) was a pioneering digital computer developed in the early 1960s to navigate and control the Apollo spacecraft during their missions to the Moon. Installed aboard both the Command Module and the Lunar Module, the AGC was integral to the success of the Apollo program, providing real-time guidance, navigation, and control capabilities.

Designed by the MIT Instrumentation Laboratory under the leadership of Charles Stark Draper, the AGC featured a 16-bit word length, with 15 data bits and one parity bit, and operated at a frequency of 2.048 MHz. The computer's memory was divided into 2,048 words of erasable magnetic-core memory (RAM) and 36,864 words of fixed core rope memory (ROM), which stored the software and mission data.

Astronauts interacted with the AGC through the Display and Keyboard (DSKY) interface, a 21-digit display and 19-button keyboard that allowed them to input commands and receive information. This interface was crucial for manual adjustments and monitoring during the missions.

The AGC's software was written in AGC assembly language and stored on rope memory. The bulk of the software was on read-only rope memory and thus could not be changed in operation, but some key parts of the software were stored in standard read-write magnetic-core memory and could be overwritten by the astronauts using the DSKY interface, as was done on Apollo 14.

1.1 Operating System

The Apollo Guidance Computer (AGC) utilized a specialized operating system to manage its resources and execute the software required for the Apollo missions. The operating system, known as AGC software, was designed to perform real-time control and navigation tasks with extreme reliability and efficiency. Unlike modern operating systems, which handle general-purpose tasks for a wide variety of applications, the AGC's operating system was dedicated exclusively to the guidance, navigation, and control of the Apollo spacecraft.

One of the key innovations of the AGC operating system was its use of a “*priority scheduling*” system. This system ensured that higher-priority tasks, such as navigation corrections or abort sequences, were processed before lower-priority tasks, allowing the AGC to respond dynamically to changing conditions during the mission. The operating system also utilized memory efficiently, with the available 2,048 words of RAM and 36,864 words of ROM being carefully allocated to critical software routines.

The AGC operating system also incorporated error-checking mechanisms to maintain reliability in the face of potential hardware malfunctions. Given the harsh and unpredictable environment of space, the system was designed to operate autonomously, with minimal input from the astronauts, while still allowing for manual intervention when necessary. The operating system's software was written in AGC assembly language and was stored in the AGC's rope memory, providing a highly optimized and space-efficient solution for spacecraft operations.

This operating system consisted of two parts: the **Executive**, a batch job-scheduler that used priority based cooperative multi-tasking to manage longer running jobs, and the **Waitlist**, a timer interrupt-driven pre-emptive scheduler that managed real-time tasks running on tight timing constraints. By design, waitlist tasks were run in an interrupt-inhibited mode, ensuring uninterrupted processing. This greatly limited how much computation these tasks are able to do, limiting each task to about 150-200 instructions. As a result, a waitlist task requiring extensive calculation would have to schedule other waitlist tasks, or a longer running executive job. On the other hand, to meet the deadlines on critical tasks, executive jobs must schedule waitlist tasks to be run within a certain deadline.

The operating system also consisted of a robust recovery mechanism, that offered different levels of restart protection for various tasks and jobs.

elaborate

The success of the AGC operating system relied on the cooperation between the executive jobs and waitlist tasks and its robust recovery system.

§2 The Executive

The **Executive** in the Apollo Guidance Computer is a multiprocessing preemptive real-time operating system. It has a few features that set it apart from modern RTOS's, and made it such a visionary piece of technology of its time.

In this section, we'll give a brief overview of the features of the Executive.

- Cooperative and preemptive
- Process construction:
- What we'd call process descriptors, were called Core Set.

- Could ask for dynamic storage at the point of process creation.
- Priority based scheduling
- Context switching: using the NEWJOB register
- Process sleep and wakeup
- Waitlist to do most of the real time operations
- Restart and recovery

§3 Reinventing the wheels

The current implementation differs from the original design of the Executive in quite a few ways.

- Processes are allocated dynamically
- Dynamic memory management
-

§4 Scratch

4.1 Progress

- waitlist
- process switching
- timer interrupts
- debug mechanism

4.2 Log

- Currently, working on designing the restart mechanism.

4.3 To-Do

- Abstract out the setup functions, so that different applications can be written independently.
- Write a few examples to demonstrate.