COMPS 203 F

QUZZI 2021.3.25 Name: Jiawei Wang ID: 512395870

```
(a)
          class GUI extends J Frame {
  public
           private Jlabel label = new Jlabel ("5");
           Private JTextField textField = new JTextField (8);
           Private J Button button = new J Button ("+3");
          public Jlabel getlabel() freturn label; }
          public JToxt Field get Toxt Field () freturn text Field; }
          public J Button get Button() { return button; }
         Public GUI {
                set Layout (new Flow Layout ());
                add (label); add (text Field); add (button);
               Set Default Close Operation (EXIT_ON_CLOSE);
               Pack();
         3
(b)
         Private JMenuBar menuBar = new TMenuBar();
         private 7 Menu
                                     new TMenu ("Action");
                            menu =
         Private JMenuItem MenuItem = new JMenuItem ("No nowels");
                 · set MenuBar (menuBar);
                  menuBor. add (menu); menu. add (menuItem);
```

1

KOKUYD

```
(C) import javax swing. *; import java.ant. prent. *; import java.ant. *;
           public class GUI extends J Frame implements Action Listener {
                    button adol Action Listemer (this );
                    Public Void action Performed (Action Event event) {
                         Object source = event get Source();
                         if (source == button) {
int t = Integer parke Int (label. get Text());
                               t = t+3;
                               label. setText (t);
                   Pack();
import jara.util. Arraylist.
                   menuItem.add Action Listener (this);
                   else if (source == menuItem) {
                          String S = text Field. got Text ();
                         Arraylist < char > ch = new Arraylist < char > ();
                         ch.adol('a'); ch.adol('e'); ch.adol('i'); ch.adol('0'); ch.adol('u');
                         for (char c: 5) {
                              if (ch.contains(c)) {
              private J Button Button 2 = new J Button ('Multiply');
      (e)
                addcbatton2);
                button 2. add A otion Listener (this);
                else if (source == button2) f
```

```
int num1 = Integer. paseInt (text Field getText1);
    int nam = Integer . Parse Int (label . get Text());
    label. setText ( num1 * num 2 + "");
                                                        Har I Day Ton Hall
                                                      i(f) rolling policy
                                                    West & become not define med wing
Campus
```