CIVICTWIN: AI-ENABLED DIGITAL TWIN FOR PREDICTIVE URBAN INFRASTRUCTURE RESILIENCE

PAMCA698J - Dissertation-1 / Internship-1

Submitted in partial fulfillment of the requirements for the degree of

Master of Computer Applications

in

Department of Computer Applications

by

ADRIJA BISWAS
(25MCA0212)

Under the guidance of

Dr. Parimala M.
Professor Grade I



School of Computer Science Engineering and Information Systems
Vellore Institute of Technology, Vellore

November, 2026

CIVICTWIN: AI-ENABLED DIGITAL TWIN FOR PREDICTIVE URBAN INFRASTRUCTURE RESILIENCE

PAMCA698J - Dissertation-1 / Internship-1

Submitted in partial fulfillment of the requirements for the degree of

Master of Computer Applications

in

Department of Computer Applications

by

ADRIJA BISWAS
(25MCA0212)

Under the guidance of

Dr. Parimala M.
Professor Grade I



School of Computer Science Engineering and Information Systems
Vellore Institute of Technology, Vellore

November, 2026

DECLARATION

I hereby declare that the PAMCA698J - Dissertation-1 entitled "CivicTwin: AI-Enabled Digital Twin for Predictive Urban Infrastructure Resilience" submitted by me, for the award of the degree of Master of Computer Applications in Department of Computer Applications, School of Computer Science Engineering and Information Systems to VIT is a record of bonafide work carried out by me under the supervision of Dr Parimala.M., Professor Grade I, SCORE, VIT, Vellore.

I further declare that the work reported in this dissertation has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Place: Vellore

Date: 28th October, 2026

Signature of the Candidate

(Adrija Biswas, 25MCA0212)

CERTIFICATE

This is to certify that the PAMCA698J - Dissertation-1 entitled "CivicTwin: AI-Enabled Digital Twin for Predictive Urban Infrastructure Resilience" submitted by Adrija Biswas (25MCA0212), SCORE, VIT, for the award of the degree of Master of Computer Applications in Department of Computer Applications, is a record of bonafide work carried out by him / her under my supervision during the period, 06.07.2026 to 03.11.2026, as per the VIT code of academic and research ethics.

The contents of this report have not been submitted and will not be submitted either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university. The dissertation fulfills the requirements and regulations of the University and in my opinion meets the necessary standards for submission.

Place: Vellore

Date: 28th October, 2026

Signature of the VIT-SCORE - Guide

Dr. Parimala M.

Professor Grade I, SCORE, VIT, Vellore

Internal Examiner

External Examiner

Head of the Department

Department of Computer Applications

ACKNOWLEDGEMENT

It is my pleasure to express with a deep sense of gratitude to my Dissertation-1 guide Dr. Parimala M., Professor Grade I, School of Computer Science Engineering and Information Systems, Vellore Institute of Technology, Vellore for her constant guidance and continual encouragement throughout my endeavor. My association with her has not been confined to academics alone; it has been a profound opportunity to work with an intellectual and expert in the field of Urban Hydroinformatics, Cyber-Physical Systems, and Digital Twins for Urban Infrastructure Resilience.

I would like to express my heartfelt gratitude to Honorable Chancellor Dr. G. Viswanathan; respected Vice Presidents Dr. Sankar Viswanathan and Dr. Sekar Viswanathan; Vice Chancellor Dr. V. S. Kanchana Bhaaskaran; Pro-Vice Chancellor Dr. Partha Sharathi Mallick; and Registrar Dr. Jayabarathi T. for providing world-class infrastructure and an inspiring research environment.

My whole-hearted thanks to Dean Dr. Daphne Lopez, School of Computer Science Engineering and Information Systems; Head of the Department of Computer Applications Dr. Senthilkumar N; MCA Project Coordinator Dr. Krishnamoorthy N; and SCORE School Project Coordinator Dr. Karthikeyan P, alongside all faculty and staff members of the university for their continuous academic counsel and administrative support throughout my course of study.

It is indeed a pleasure to thank my parents and friends who consistently supported and encouraged me to take up and complete my dissertation successfully. Last, but not least, I express my sincere appreciation to everyone who helped me directly or indirectly towards the successful completion of this dissertation.

Place: Vellore — Adrija Biswas

Date: 28th October, 2026 — (Reg. No: 25MCA0212)

EXECUTIVE SUMMARY

Rapid, unplanned urbanization and recurrent high-intensity monsoon precipitation severely overwhelm aging stormwater drainage infrastructures across tier-two Indian municipalities, culminating in systemic waterlogging, structural asset degradation, and public paralysis. Conventional municipal public works operate reactively, deploying desilting crews primarily in response to localized citizen grievances or visible surface overflow while neglecting topological connectivity and backwater surcharge dynamics.

This dissertation presents CivicTwin, an AI-enabled cyber-physical digital twin developed for predictive urban drainage management and proactive flood resilience in Vellore Municipal Corporation (CMC). CivicTwin formulates 13,998 drain conduits across 60 spatial zones into a Directed Acyclic Graph (DAG) comprising 22,737 hydraulic edges. Integrating the rational runoff method, an ensemble Random Forest blockage surrogate, and a bitset-accelerated reachability engine, CivicTwin introduces a multi-criteria cascade-aware dispatch strategy. Across simulated rainfall intensities from 80 to 160 mm/hr, the proposed cascade-aware method resolves between 3.1× and 4.4× more at-risk and backwater-threatened conduits than traditional severity-only desilting under identical municipal clearing budgets. Implemented as an interactive web GIS command dashboard connecting FastAPI, React-Leaflet, and PostgreSQL/PostGIS, CivicTwin provides municipal administrators with real-time hydraulic bottleneck foresight, maximizing labor productivity and transforming municipal disaster response into predictive urban resilience.

CONTENTS

Acknowledgement v

Executive Summary vi

Table of Contents vii

List of Figures x

List of Tables xi

Abbreviations xii

Symbols and Notations xiii

1 INTRODUCTION 1
- 1.1 Background and Context 1
  - 1.1.1 Hydro-Meteorological Context and Topographic setting of Vellore 2
  - 1.1.2 Hydrological Challenges in Tier-Two Indian Agglomerations 2
  - 1.1.3 Infrastructural Heterogeneity of the Vellore Drainage Network 3
- 1.2 Problem Statement 3
- 1.3 Research Questions 4
- 1.4 Project Objectives 4
- 1.5 Motivation and Societal Impact 5
  - 1.5.1 Socio-Economic and Infrastructure Degradation Hazards . 6
- 1.6 Summary of Novel Contributions 6
- 1.7 Scope and Delimitations 7
- 1.8 Dissertation Organization 7

2 LITERATURE REVIEW 9
- 2.1 Urban Stormwater Infrastructure and Hydraulic Modeling 9
  - 2.1.1 Governing Saint-Venant Shallow Water Equations 9
  - 2.1.2 Hydraulic Friction Models and Roughness Parameterization 10
- 2.2 Digital Twins in Civil and Municipal Engineering 11
  - 2.2.1 Cyber-Physical System (CPS) Control Loop Architecture . 12
- 2.3 Machine Learning and Surrogate Modeling in Flood Risk Assessment 12

2.3.1 Comparative Analysis: Ensemble Methods vs. Deep Graph Architectures . . . 13
2.4 Complex Network Theory and Cascading Failures in Urban Utilities 14
2.5 Critical Analysis and Research Gaps . . . 15

3 TECHNICAL SPECIFICATIONS AND ARCHITECTURE 17
3.1 System Requirements and Specifications . . . 17
3.2 High-Level System Architecture . . . 17
3.3 Spatial Data Modeling and PostGIS Database Schema . . . 19
3.3.1 Relational Schema Design and Constraints . . . 19
3.3.2 GiST Index Mechanics and Viewport Query Optimization 20
3.4 RESTful API Architecture and Integration . . . 20
3.5 Concurrency Control and Audit Trail Logging . . . 21

4 HYDRODYNAMIC MODELING AND GRAPH CASCADE ENGINE 23
4.1 Hydrological Formulation and Catchment Inversion . . . 23
4.1.1 Hydraulic Continuity and Sub-Catchment Inflow Aggregation 23
4.1.2 Derivation of Open-Channel Flow and Manning's Equation 24
4.1.3 Geometry-Specific Capacity Formulations . . . 24
4.2 Effective Capacity and Utilisation Formulation . . . 25
4.3 Directed Acyclic Graph Construction and Cycle Elimination . . . 26
4.3.1 Matrix Representation of the Drainage Network . . . 26
4.3.2 Theorem: Acyclicity of Elevation-Enforced Flow Graphs . 26
4.4 Bitset-Accelerated Ancestor Reachability . . . 27
4.4.1 Bitwise Parallelism and Hardware Acceleration . . . 28
4.5 Systemic Network Risk Exposure Metric . . . 28
4.5.1 Dynamic Programming Traversal over Reverse Topological Order . . . 29

5 PREDICTIVE MODELING AND SURROGATE RISK ESTIMATION 30
5.1 Dataset Profiling and Preprocessing . . . 30
5.2 Feature Engineering and Hydromorphometric Indices . . . 31
5.3 Spatial Clustering and Ward Demarcation . . . 32
5.3.1 K-Means Optimization and Centroid Convergence . . . 32
5.4 Random Forest Surrogate Formulation . . . 32
5.4.1 Decision Tree Split Criteria and Impurity Metrics . . . 33
5.5 Model Evaluation and Feature Importance . . . 34

6 DISPATCH OPTIMIZATION STRATEGIES AND SIMULATION EXPERIMENTS 36

6.1 The Municipal Resource Allocation Dilemma 36
6.1.1 Formal Combinatorial Optimization Problem Formulation 36
6.2 Proposed Cascade-Aware Dispatch Strategy 37
6.2.1 Lexicographical Sorting Mechanics and Computational Complexity 38
6.3 Comparative Baseline Strategies and Ablation Formulations . . . 38
6.3.1 Local Severity-Only (Standard Municipal Baseline) 38
6.3.2 Cascade-Only (Ablation Baseline) 39
6.3.3 Random Dispatch (Stochastic Baseline) 39
6.4 Closed-Loop Simulation Lifecycle and Feedback Dynamics 39
6.4.1 State Transition Algebraic Formulation 40
6.5 Simulation Experimental Design 40
6.5.1 Monte Carlo Statistical Reliability Protocols 41

7 RESULTS AND DISCUSSION 42
7.1 Quantitative Performance Benchmarking 42
7.2 Analysis of At-Risk and Backwater Flood Resolution 43
7.2.1 Mechanisms of Hydraulic Cascade Relief 43
7.3 Spatial Zone Sensitivity and Ward-Level Efficacy 44
7.4 Network Risk Exposure Trajectories 44
7.5 Reachability Impact and Upstream Relief 46
7.6 Computational Latency and Scalability 46
7.7 Statistical Significance and Hypothesis Testing 47

8 SUMMARY, CONCLUSION AND FUTURE WORK 48
8.1 Summary of Research Contributions 48
8.2 Practical Implications for Municipal Public Works 49
8.3 Limitations of the Current Study 49
8.4 Future Research Directions 50

9 REFERENCES 51

APPENDIX A: SYSTEM USER INTERFACE DEMONSTRATION 53

APPENDIX B: CORE MATHEMATICAL ALGORITHMS 58

APPENDIX C: DATABASE DDL AND API SPECIFICATIONS 60

LIST OF FIGURES

3.1 CivicTwin Multi-Tier System Architecture and Data Pipelines . . 18

5.1 Gini Feature Importance of Top Predictors for Drainage Blockage Vulnerability 35

6.1 Conduit Operational State Lifecycle in CivicTwin 39

7.1 Comparative Resolution of At-Risk Conduits Across Storm Intensities 43
7.2 Network Risk Exposure Reduction (%) Across Cleaning Interventions 44
7.3 Distinct Upstream Conduits Relieved Across Cleaning Interventions 46

8.1 Full CivicTwin Operations Center Interface Showing GIS Map and Live KPI Counters 53
8.2 Priority Drains Table Showing Surcharge Ratios, Upstream Cascade Reachability, and Dispatch Actions 55
8.3 Activity Audit Log and Administrative Metric Interpretation Guidelines 56

LIST OF TABLES

2.1 Comparative Analysis of Urban Drainage Management Paradigms 15

3.1 System Hardware and Software Specifications 17

5.1 Dataset Feature Profiles for CMC Drainage Conduits ($N = 13,998$) 30
5.2 5-Fold Stratified Cross-Validation Performance Metrics for Blockage Surrogate Classifier 34
5.3 Aggregated Multi-Class Confusion Matrix for Random Forest Surrogate Classifier 34

7.1 Comparative Dispatch Strategy Performance Across Storm Regimes 42
7.2 Spatial Resolution Efficacy Across Vellore Municipal Zones ($K = 100, i = 120$ mm/hr) 45
7.3 Analytical Engine Algorithmic Runtime Profiles ($N = 13,998$) . . 46

8.1 UI Component Architecture and Backend API Mapping 54
8.2 Operational Audit Trail Data Fields and Administrative Utility . 57

LIST OF ABBREVIATIONS

Abbreviation	Expansion
AI	Artificial Intelligence
API	Application Programming Interface
CMC	City Municipal Corporation (Vellore Corporation)
CPS	Cyber-Physical System
DAG	Directed Acyclic Graph
DEM	Digital Elevation Model
EPA	Environmental Protection Agency
EPSG	European Petroleum Survey Group
GIS	Geographic Information System
IoT	Internet of Things
JSON	JavaScript Object Notation
KPI	Key Performance Indicator
ML	Machine Learning
MSL	Mean Sea Level
OSM	OpenStreetMap
PostGIS	PostgreSQL Spatial Object Extension
REST	Representational State Transfer
RF	Random Forest
SRTM	Shuttle Radar Topography Mission
SWMM	Storm Water Management Model
TWI	Topographic Wetness Index
UI	User Interface
WGS84	World Geodetic System 1984

SYMBOLS AND NOTATIONS

Symbol	Description	Unit
Q	Peak stormwater runoff discharge rate	m^3/s
C	Catchment surface runoff coefficient	Dimensionless
i	Rainfall storm precipitation intensity	mm/hr
A	Tributary catchment contributing area	m^2
Q_{design}	Unobstructed design conveyance capacity	m^3/s
S	Silt and solid waste sediment blockage	%
Q_{avail}	Effective hydraulic capacity post-silt reduction	m^3/s
U	Hydraulic capacity utilisation ratio (Q/Q_{avail})	Dimensionless
$G = (V, E)$	Directed Acyclic Graph of drainage network	—
V	Vertex set of drainage conduit segments (n = 13,998)	—
E	Directed edge set of downhill gravity flow links (m = 22,737)	—
$\text{pred}(v)$	Immediate upstream hydraulic predecessors of node v	—
$\text{succ}(v)$	Immediate downstream hydraulic successors of node v	—
$\text{anc}(v)$	Set of all transitive upstream ancestor conduits of node v	—
$\text{desc}(v)$	Set of all transitive downstream descendant conduits of node v	—
$C_{\text{saved}}(v)$	Cascade reachability relief count ($\lvert\text{anc}(v)\rvert$)	Conduits
E_{net}	Systemic network risk exposure summation	%
$T(v)$	Categorical threat tier (0 = Low, 1 = High, 2 = Critical)	Discrete
K	Municipal maintenance clearing budget	Conduits
z	Terrain invert elevation above MSL	m

Chapter 1

INTRODUCTION

1.1 Background and Context

Urban stormwater drainage systems represent critical subterranean lifeline infrastructures engineered to evacuate excess surface precipitation, safeguard municipal assets, and prevent localized hydraulic inundation[cite: 80]. In rapidly developing urban agglomerations across the Global South, particularly tier-two Indian municipalities such as Vellore, Tamil Nadu, infrastructural expansion has struggled to keep pace with rapid surface imperviousness and urbanization[cite: 80]. The expansion of asphalt roadways, dense concrete residential layouts, and commercial corridors has drastically compromised natural hydrological infiltration basins, multiplying urban runoff coefficients from pre-development estimates of 0.20–0.30 to values exceeding 0.75–0.85[cite: 80].

Simultaneously, changing climatic patterns have intensified convective precipitation events[cite: 80]. Modern monsoon seasons are increasingly punctuated by short-duration, high-intensity cloudburst phenomena wherein precipitation rates regularly exceed 80 to 120 mm/hr[cite: 80]. When these acute volumetric downpours strike municipal drainage networks choked with unsegregated municipal solid waste, construction debris, and heavy silt deposition, the effective hydraulic conveyance cross-section of drainage conduits contracts drastically[cite: 80]. Water levels rapidly breach curb-inlet thresholds, resulting in widespread flash waterlogging, road surface destruction, economic paralysis, and acute vector-borne public health hazards[cite: 80].

The Vellore City Municipal Corporation (CMC), comprising 60 administrative wards covering diverse topography ranging from the slopes of the Eastern Ghats down toward the Palar river basin, faces chronic inundation during the Northeast and Southwest monsoon seasons[cite: 80]. The municipal drainage network consists of heterogeneous open roadside channels, covered masonry channels, and buried pipe culverts built incrementally over several decades[cite: 80]. Managing such a sprawling, subterranean network under severe municipal budget and labor constraints remains one of the most pressing civic governance challenges in urban engineering[cite: 80].

1.1.1 Hydro-Meteorological Context and Topographic setting of Vellore

Vellore is situated at an mean elevation of approximately 216 meters above Mean Sea Level (MSL), bounded by rugged granitic terrain characteristics of the Eastern Ghats[cite: 80]. The geographical positioning exposes the urban agglomeration to bimodal precipitation patterns:

1. Southwest Monsoon (June to September): Characterized by localized convective thunder-showers and high-intensity short-duration cloudbursts[cite: 80].

2. Northeast Monsoon (October to December): Generates sustained regional depressions that drop substantial cumulative volumetric rainfall across the Palar river catchment basin[cite: 80].

Due to steep elevation gradients descending from hill-slope peripheral wards (e.g., Ward 1 to Ward 12) down into central valley markets (e.g., CMC Hospital zone, Long Bazaar, and Katpadi road junction), surface runoff accelerates rapidly along upper tributaries[cite: 80]. However, as flow reaches flatter central commercial corridors where bed slopes flatten below 0.10%, hydraulic conveyance velocities collapse[cite: 80, 85]. This sudden hydraulic drop promotes rapid gravitational settling of suspended urban silt, creating chronic structural bottlenecks that trigger extensive upstream backwater surcharges[cite: 80, 88].

1.1.2 Hydrological Challenges in Tier-Two Indian Agglomerations

Tier-two Indian cities experience unique hydro-dynamic pressures due to high urban density coupled with legacy stormwater networks[cite: 80]. Unlike planned metropolitan centers with dedicated subterranean storm trunks, municipal corporations in tier-two regions rely predominantly on roadside open drains designed for low-intensity continuous rainfall[cite: 80]. Over past decades, commercial encroachment and informal building expansion have converted permeable soil surfaces into continuous impervious slabs[cite: 80].

During monsoon depressions, peak discharge (Q) arriving at roadside channels spikes within minutes of precipitation onset[cite: 80, 85]. Because time-of-concentration (t_c) across small urban sub-catchments is short (often under 10 to 15 minutes), drainage channels receive immediate, unattenuated peak flows[cite: 80, 85]. When these channels are partially clogged by urban silt or solid waste, local hydraulic conveyance capacity falls below peak incoming runoff, initiating immediate surface surcharging[cite: 80, 85].

1.1.3 Infrastructural Heterogeneity of the Vellore Drainage Network

The stormwater network of Vellore Municipal Corporation reflects decades of unsystematic infrastructural additions[cite: 80]. The network encompasses four primary structural classifications[cite: 80]:

1. Open Concrete Channels: Standard roadside U-shaped drains engineered for surface runoff collection along arterial and secondary roads[cite: 80].
2. Covered Masonry Drains: Brick or concrete block channels covered with removable slab covers, prevalent in dense commercial markets such as CMC Hospital Zone and Long Bazaar[cite: 80].
3. Buried Concrete Pipe Culverts: Circular cross-section pipes conveying flow beneath road intersections and major transit corridors[cite: 80].
4. Natural Earthen Channels: Unlined ditches serving peripheral wards and primary outfalls discharging toward the Palar river basin[cite: 80].

Each structural classification exhibits distinct Manning roughness coefficients ($n \in [0.013, 0.035]$), cross-sectional geometries, and sediment deposition dynamics[cite: 80, 85]. Modeling such a heterogeneous network requires unifying diverse geometric parameters into a standardized hydraulic framework[cite: 80].

1.2 Problem Statement

Current municipal flood management practices in municipal corporations operate predominantly in a reactive and localized operational paradigm[cite: 80]:

- Reactive Desilting Deployment: Desilting machinery, suction tankers, and manual public works crews are conventionally mobilized only after citizen complaints are filed via grievance portals or following visible surface inundation on arterial transit corridors[cite: 80, 81].
- Topological Blindness in Prioritization: When municipal supervisors do attempt proactive desilting, prioritization is guided almost exclusively by isolated channel blockage ratios (e.g., clearing whatever conduit appears visually most silted)[cite: 81]. This heuristic fundamentally ignores the directed network topology of the drainage graph[cite: 81]. A severely silted conduit situated near a high-elevation headwater with no upstream tributaries causes strictly localized overflow; conversely, a moderately silted conduit serving as a primary downstream bottleneck can trigger severe backwater surcharge and hydraulic failure across dozens or hundreds of interconnected upstream channels[cite: 81].

- Absence of Predictive Hydro-Informatics Tools: Municipal public works departments lack accessible, real-time computational decision-support systems that couple hydrological rainfall-runoff calculations with spatial network topology to evaluate dynamic failure cascades before a storm arrives[cite: 81]. Full-scale hydrodynamic software packages (such as US-EPA SWMM) demand extensive boundary parameter calibration and take hours or days to execute over thousands of conduits, rendering them impractical for live emergency dispatch decisions[cite: 81, 85].

Without an integrated cyber-physical digital twin capable of mapping subterranean flow connectivity, predicting blockage-induced surcharge, and ranking interventions by systemic network impact, municipal interventions remain inefficient, treating localized symptoms rather than hydraulic root causes[cite: 81].

1.3 Research Questions

To address these administrative and technical challenges, this dissertation investigates four fundamental research questions:

- **RQ_1**: How can heterogeneous municipal vector data and terrain Digital Elevation Models (DEMs) be synthesized into an elevation-enforced Directed Acyclic Graph (DAG) that accurately enforces physical gravity flow while eliminating topological cycles[cite: 81, 95, 96]?
- **RQ_2**: Can bitset-accelerated transitive closure over topological sort orders compress all-pairs reachability computations to sub-30 millisecond latencies for real-time web decision support[cite: 82, 97, 98]?
- **RQ_3**: How accurately can an ensemble machine learning surrogate predict structural blockage vulnerability and hydraulic surcharge risk across continuous continuous morphological feature spaces[cite: 82, 101, 102]?
- **RQ_4**: To what degree does a multi-criteria cascade-aware dispatch optimization strategy outperform standard municipal severity-only heuristics under strictly constrained municipal maintenance budgets[cite: 82, 104, 105]?

1.4 Project Objectives

The primary objective of this dissertation is to design, implement, and validate CivicTwin, an AI-enabled, cyber-physical digital twin that unifies geospatial topology, hydrodynamic modeling, and machine learning surrogates into a real-time predictive decision-support system for municipal drainage management[cite: 81]. The specific technical objectives are:

1. Topological Graph Modeling of Municipal Drainage: To extract, clean, and vectorize the multi-modal stormwater conduit network of the Vellore City Municipal Corporation from geospatial data sources into a rigorous Directed Acyclic Graph (DAG) enforced by elevation gradients and shared vertex topology[cite: 81, 95].

2. Hydrologic-Hydraulic Capacity Formulation: To formulate an efficient rational runoff and capacity utilisation model that computes hydrodynamic discharge and structural capacity consumption across all conduits under user-specified precipitation regimes ranging from 20 to 200 mm/hr[cite: 82, 94].

3. Bitset Reachability Cascade Metric: To develop a bitset-accelerated transitive closure algorithm that calculates the exact count of upstream tributary conduits vulnerable to backwater inundation (C_{saved}) for every individual drainage segment[cite: 82, 97].

4. Machine Learning Blockage Surrogate: To train and deploy an ensemble Random Forest classifier capable of estimating conduit blockage and structural flood vulnerability from morphometric, spatial, and meteorological covariates[cite: 82, 101].

5. Multi-Criteria Cascade-Aware Dispatch Optimization: To formulate a multi-objective ranking algorithm that prioritizes desilting interventions by threat tier, upstream cascade reachability, and local capacity exhaustion, comparing its performance against standard municipal baselines[cite: 82, 104].

6. Interactive Web GIS Operations Center: To implement a production-ready, full-stack spatial command interface that allows municipal engineers to simulate storm scenarios, inspect network exposure, and manage field clearing work orders in real time[cite: 82, 112].

1.5 Motivation and Societal Impact

Urban drainage resilience directly intersects citizen safety, public health, and municipal economics[cite: 82]. Flooded arterial roads paralyze public transportation, strand emergency services, and inflict substantial structural damage upon road pavements and foundation soils, necessitating recurring multi-crore road resurfacing expenditures[cite: 82]. Furthermore, stagnant stormwater mixed with overflowing drainage promotes the breeding of disease vectors (such as Aedes aegypti and Anopheles mosquitoes), escalating dengue, chikungunya, and malaria outbreaks in high-density urban wards[cite: 82].

1.5.1 Socio-Economic and Infrastructure Degradation Hazards

The impact of localized urban inundation in tier-two municipalities manifests across three distinct socio-economic dimensions[cite: 80, 82]:

- Economic Distruption: Surcharged roadside drains inundate local ground-floor commercial storefronts and informal vendor markets, resulting in structural inventory loss and municipal business paralysis[cite: 80, 82].
- Transportation and Road Asset Degradation: Prolonged sub-base saturation beneath asphalt pavements accelerates stripping, pothole formation, and structural foundation collapse[cite: 80, 82]. Subgrade soils in low-lying zones lose shear strength when fully saturated, leading to multi-crore recurring maintenance costs for municipal public works[cite: 80, 82].
- Public Health Hazards: Floodwaters mixed with choked drainage silt create widespread standing pools, dramatically accelerating vector breeding cycles during monsoon months[cite: 80, 82].

From an administrative perspective, municipal corporations possess strictly finite maintenance budgets[cite: 82]. A typical municipal zone may employ only two to four desilting crews capable of addressing 5 to 15 major drain segments per operational shift[cite: 82]. In a sprawling city containing nearly 14,000 conduit segments, deciding exactly which 50 or 100 segments to excavate prior to a forecasted monsoon depression determines whether an entire district remains functional or collapses into gridlock[cite: 80, 82, 83]. CivicTwin provides municipal administrators with an empirical, scientifically grounded roadmap that maximizes the marginal flood-reduction yield per rupee of municipal maintenance expenditure[cite: 81, 83].

1.6 Summary of Novel Contributions

This research introduces several major scientific and applied contributions to the fields of urban hydro-informatics, cyber-physical systems, and municipal infrastructure management[cite: 80, 81, 82]:

1. Elevation-Enforced DAG Formalization: A robust graph construction methodology that enforces physical downhill gravity flow across 13,998 segments while eliminating topological cycles[cite: 81, 95].
2. Bitset Transitive Closure Acceleration: A bitset algorithm achieving sub-20 millisecond runtime for calculating global upstream reachability (C_{saved}) over a 14,000-node municipal graph[cite: 82, 97, 98].

3. Explainable Machine Learning Surrogate: An ensemble Random Forest model achieving 89.4% classification accuracy for structural blockage risk estimation[cite: 82, 101, 102].

4. Cascade-Aware Prioritization Metric: A multi-criteria lexicographical sort strategy that achieves 3.1× to 4.4× greater flood resolution yield than conventional severity-only heuristics under identical operational budgets[cite: 82, 104, 108].

5. Production-Grade Full-Stack Digital Twin Platform: A microservices web architecture connecting FastAPI, Node.js, PostGIS, and React-Leaflet with real-time audit logging and viewport culling[cite: 82, 90, 112].

1.7 Scope and Delimitations

The operational scope and technical boundaries of this dissertation are defined as follows[cite: 83]:

- Geographic Scope: The study encompasses the municipal territory of the Vellore City Municipal Corporation (CMC), comprising 13,998 surveyed and extracted drain conduit segments partitioned across 60 localized spatial clusters representing municipal wards[cite: 83].

- Topological Scope: Conduits are structured as a Directed Acyclic Graph containing 22,737 directed hydraulic edges[cite: 83]. Conduits without valid spatial coordinates (37 segments out of 13,998) or located exterior to corporation limits are retained in the global database but excluded from dispatch ranking[cite: 83].

- Hydrological Delimitations: Runoff discharge is modeled using the rational method calibrated through catchment inversion[cite: 83]. The model operates under steady-state peak intensity assumptions suitable for real-time dispatch rather than full dynamic Saint-Venant 1D/2D unsteady wave routing[cite: 83, 85].

- Sediment and Silt Model: Baseline silt accumulation values reflect municipal pre-monsoon survey data; following a simulated field intervention, cleared conduits reset to an empirical post-cleaning residual silt threshold of 5.0%[cite: 83].

1.8 Dissertation Organization

The remainder of this dissertation is organized as follows[cite: 83, 84]:

- Chapter 2 surveys related literature across urban drainage modeling, digital twin architectures, machine learning hydrodynamic surrogates, and complex network cascade dynamics, highlighting the research gap addressed by CivicTwin[cite: 83, 85].

- Chapter 3 establishes the technical system specifications, full-stack software architecture, PostgreSQL/PostGIS database design, and RESTful API endpoints[cite: 83, 90].

- Chapter 4 details the mathematical foundation of CivicTwin, encompassing rational method runoff formulations, DAG construction from OpenStreetMap geometry, bitset reachability algorithms, and the systemic network risk exposure metric[cite: 84, 94].

- Chapter 5 discusses the dataset profiling of 13,998 Vellore conduits, spatial k-means clustering, and the training and validation of the Random Forest blockage surrogate classifier[cite: 84, 99].

- Chapter 6 formalizes the dispatch optimization problem, detailing the proposed cascade-aware ranking strategy, baseline algorithms, and the closed-loop simulation experimental framework[cite: 84, 104].

- Chapter 7 presents comprehensive empirical results across 80, 120, and 160 mm/hr storm regimes, demonstrating quantitative advantages in network exposure reduction, at-risk conduit resolution, and statistical stability[cite: 84, 108].

- Chapter 8 provides a thorough walkthrough and UI demonstration of the CivicTwin Operations Center, detailing map interactivity, dynamic storm sliders, and work-order state management[cite: 84, 112].

- Chapter 9 summarizes key findings, discusses municipal deployment implications, outlines study limitations, and proposes future directions including IoT telemetry integration[cite: 84, 118].

Chapter 2

LITERATURE REVIEW

2.1 Urban Stormwater Infrastructure and Hydraulic Modeling

Urban stormwater drainage design has historically relied on empirical and numerical physics-based hydrodynamic formulations[cite: 101]. The foundational formulation for surface runoff estimation remains the rational method, popularized by Kuichling and formalized by Chow et al.[cite: 101]:

$$Q = \frac{C \cdot i \cdot A}{3.6 \times 10^6} \tag{2.1}$$

where Q denotes peak discharge in m^3/s, C represents the dimensionless runoff coefficient, i is rainfall intensity in mm/hr, and A is the catchment surface area in m^2[cite: 101]. The rational method assumes that peak runoff occurs when the entire tributary area contributes flow simultaneously, corresponding to a rainfall event whose duration equals or exceeds the time of concentration of the basin[cite: 101].

To model in-channel conduit hydraulics, classic civil engineering relies on the Manning equation for open-channel gravity flow[cite: 101]:

$$V = \frac{1}{n} R_h^{2/3} S_0^{1/2} \tag{2.2}$$

where V is the cross-sectional mean velocity (m/s), n is Manning's roughness coefficient (typically 0.013–0.017 for concrete and smooth masonry, and 0.025–0.035 for unlined or silted earthen channels), R_h is the hydraulic radius (A_c/P_w, the cross-sectional flow area divided by the wetted perimeter), and S_0 is the hydraulic bed slope[cite: 101].

2.1.1 Governing Saint-Venant Shallow Water Equations

Computational modeling packages such as the United States Environmental Protection Agency Storm Water Management Model (US-EPA SWMM) solve the one-dimensional Saint-Venant equations for unsteady open-channel flow[cite: 101]:

$$\frac{\partial A_c}{\partial t} + \frac{\partial Q}{\partial x} = 0 \quad \text{(Continuity Equation)} \tag{2.3}$$

$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial x}\left(\frac{Q^2}{A_c}\right) + gA_c\frac{\partial H}{\partial x} + gA_c S_f = 0 \quad \text{(Momentum Equation)} \tag{2.4}$$

where A_c is cross-sectional flow area (m^2), Q is volumetric flow rate (m^3/s), H is piezometric head (m), g is gravitational acceleration (m/s^2), x is longitudinal channel distance (m), t is time (s), and S_f is friction slope derived from Manning's roughness[cite: 101].

Depending on which momentum terms are preserved, hydrodynamic routing models are broadly categorized into three distinct wave approximations[cite: 101, 102]:

1. Kinematic Wave Routing: Assumes bed slope equals friction slope ($S_0 = S_f$), neglecting inertial and pressure gradient terms[cite: 101]. While computationally lightweight, it cannot simulate backwater effects, reverse flow, or pressurized pipe surcharging[cite: 101, 102].

2. Diffusion Wave Routing: Retains the pressure gradient term ($\partial H/\partial x$) alongside friction slope, allowing the model to simulate dynamic backwater attenuation and water surface profiles across mild bed slopes[cite: 101, 102].

3. Full Dynamic Wave Routing: Solves the complete momentum equation (Eqn. 2.4), fully capturing backwater surcharging, inertial momentum, pressurized pipe flow, and entrance/exit headlosses[cite: 101, 102].

While SWMM dynamic wave routing provides high hydraulic fidelity, simulating dynamic wave routing across municipal networks containing tens of thousands of links requires substantial computational overhead[cite: 101, 102]. Execution times can range from several minutes to hours, requiring fine-grained cross-sectional surveys, junction invert levels, and headloss coefficient calibration[cite: 101, 102]. Consequently, physics-based numerical packages are ideally suited for offline master-plan infrastructure sizing, but are ill-suited for real-time operational emergency dispatch where municipal decision-makers must evaluate alternative maintenance actions within seconds during imminent cloudburst threats[cite: 102].

2.1.2 Hydraulic Friction Models and Roughness Parameterization

Energy losses in open drainage channels stem from bed friction, sidewall shear, cross-sectional geometry transitions, and vegetative or debris obstructions[cite: 101]. The Darcy-Weisbach equation provides a foundational representation of friction headloss h_f[cite: 101]:

$$h_f = f \cdot \frac{L}{D_h} \cdot \frac{V^2}{2g} \tag{2.5}$$

where f is the dimensionless Darcy friction factor, L is conduit length, D_h is hydraulic diameter ($4R_h$), V is flow velocity, and g is acceleration due to gravity[cite:

101]. For turbulent flow in rough conduit segments, f is governed by the implicit Colebrook-White formulation[cite: 101]:

$$\frac{1}{\sqrt{f}} = -2.0 \log_{10} \left(\frac{\epsilon}{3.7 D_h} + \frac{2.51}{\mathrm{Re}\sqrt{f}} \right) \tag{2.6}$$

where ϵ denotes absolute equivalent sand roughness height (meters) and $\mathrm{Re} = VD_h/\nu$ represents the Reynolds number[cite: 101]. Explicit approximations, such as the Swamee-Jain equation, circumvent numerical iterations during high-throughput channel calculations[cite: 101]:

$$f = \frac{0.25}{\left[\log_{10} \left(\frac{\epsilon}{3.7 D_h} + \frac{5.74}{\mathrm{Re}^{0.9}} \right) \right]^2} \tag{2.7}$$

In municipal engineering applications, f is related to Manning's n through the conversion[cite: 101]:

$$f = \frac{8 g n^2}{R_h^{1/3}} \tag{2.8}$$

When heavy sediment, plastic accumulation, or urban waste deposits settle along channel bedlines, n increases dramatically from clean concrete values ($n \approx 0.013$) up to clogged earthen channel levels ($n \geq 0.035$)[cite: 101]. This doubling of effective roughness reduces flow velocity by over 60%, drastically reducing the conduit's flow carrying capacity[cite: 101].

2.2 Digital Twins in Civil and Municipal Engineering

The paradigm of the Digital Twin (DT), originally conceived in aerospace and advanced manufacturing by Grieves and Vickers, has rapidly expanded into civil infrastructure and smart city operations[cite: 102]. A digital twin constitutes a dynamic virtual counterpart of a physical asset or municipal system that maintains continuous bi-directional synchronization through data ingestion, computational analytics, and actionable operational feedback[cite: 102].

Fuller et al. categorize digital twins across three distinct evolutionary tiers[cite: 102]:

1. Digital Models: Static digital representations with manual data flow in both directions (e.g., standard CAD/BIM repositories and static GIS maps)[cite: 102].

2. Digital Shadows: Systems wherein data flows automatically from the physical asset to the digital model via sensing devices or automated field surveys, but operational interventions remain manual[cite: 102].

3. Digital Twins: Closed-loop cyber-physical systems wherein real-time sensory or survey data updates the computational twin, and the twin generates predictive interventions that directly drive physical actions (e.g., automated control or prioritized field work orders)[cite: 102].

2.2.1 Cyber-Physical System (CPS) Control Loop Architecture

In an operational urban digital twin, the physical domain and virtual analytics engine interact via a closed feedback loop:

$$\mathcal{L}_{\text{CPS}} = \langle \mathcal{P}_{\text{physical}}, \mathcal{S}_{\text{sensing}}, \mathcal{M}_{\text{twin}}, \mathcal{O}_{\text{optimization}}, \mathcal{A}_{\text{actuation}} \rangle \tag{2.9}$$

where $\mathcal{P}_{\text{physical}}$ represents the physical urban sub-catchments and drainage conduits, $\mathcal{S}_{\text{sensing}}$ encompasses survey logs and telemetry streams, $\mathcal{M}_{\text{twin}}$ is the graph-theoretic hydrodynamic model, $\mathcal{O}_{\text{optimization}}$ executes dispatch strategy ranking, and $\mathcal{A}_{\text{actuation}}$ represents field crew desilting operations.

In the water sector, digital twins have been predominantly deployed in pressurized drinking water distribution networks to detect pipe bursts and optimize pumping schedules[cite: 102]. However, adapting the digital twin framework to gravity-driven urban stormwater drainage systems poses unique obstacles: networks are largely unpressurized, open to municipal solid waste infiltration, and lack pervasive subterranean sensor instrumentation[cite: 102]. CivicTwin addresses this paradigm by establishing a digital twin of the Vellore stormwater system that couples geospatial network models, surveyed sediment states, and dynamic storm simulations to guide physical municipal desilting operations[cite: 102].

2.3 Machine Learning and Surrogate Modeling in Flood Risk Assessment

Given the prohibitive computational runtime of numerical 1D/2D hydrodynamic models, researchers have turned to Machine Learning (ML) surrogate models to achieve rapid flood risk estimation[cite: 103]. Surrogate models approximate the input-output behavior of complex hydrodynamic simulations or empirical failure records using data-driven statistical learners[cite: 103].

Kabir et al. demonstrated that deep neural architectures and ensemble decision trees can predict urban inundation extents orders of magnitude faster than full 2D shallow water solvers while preserving adequate accuracy[cite: 103]. Bermúdez et al. utilized support vector machines and random forests trained on pre-calculated hydraulic simulations to forecast localized water depths across river reaches in real time[cite: 103].

2.3.1 Comparative Analysis: Ensemble Methods vs. Deep Graph Architectures

In recent years, Graph Neural Networks (GNNs) — including Graph Convolutional Networks (GCNs) and Message Passing Neural Networks (MPNNs) — have emerged as promising architectures for spatial network modeling[cite: 103]. GNNs operate directly on graph adjacency structures, passing node features across directed edges[cite: 103]:

$$h_v^{(l+1)} = \sigma\left(W^{(l)} \cdot \text{AGGREGATE}\left(\{h_u^{(l)} \mid u \in \mathcal{N}(v)\}\right)\right) \tag{2.10}$$

where $h_v^{(l)}$ denotes the feature representation of node v at layer l, $\mathcal{N}(v)$ represents the neighbor set, $W^{(l)}$ is a learnable weight matrix, and σ is a non-linear activation function[cite: 103].

However, deep neural graph architectures present substantial operational hurdles in municipal production environments[cite: 103]:

- They require massive GPU hardware infrastructure for inference across 14,000 nodes[cite: 103].
- They function as black-box estimators, lacking clear feature-attribution metrics that municipal public works engineers can easily interpret[cite: 103].
- They suffer from over-smoothing in deep directed graphs, obscuring local bottleneck signals across long flow paths[cite: 103, 104].

Among classical machine learning classifiers, the Random Forest (RF) algorithm proposed by Breiman possesses attributes that make it exceptionally well suited for municipal drainage assessment[cite: 103]:

- It builds an ensemble of decorrelated decision trees using bootstrap aggregating (bagging) and random feature selection, mitigating overfitting on tabular municipal engineering datasets[cite: 103].
- It effectively handles non-linear relationships, multi-collinearity, and heterogeneous continuous/categorical feature spaces (e.g., conduit dimensions, elevation, slope, and structural materials)[cite: 103].
- It provides native Gini impurity and permutation feature importance metrics, granting transparency and explainability to municipal engineers[cite: 103].

In CivicTwin, a Random Forest classifier serves as a surrogate vulnerability estimator, predicting structural conduit blockage and surcharge susceptibility from physical terrain and structural attributes[cite: 103].

2.4 Complex Network Theory and Cascading Failures in Urban Utilities

Stormwater drainage conduits do not function in isolation; they form complex interconnected directed networks governed by gravitational topography[cite: 103]. Complex network analysis provides powerful mathematical tools for modeling structural vulnerability and cascading failure across networked infrastructure[cite: 103].

A directed drainage graph $G = (V, E)$ can be represented algebraically by its non-symmetric adjacency matrix $A \in \{0, 1\}^{|V|\times|V|}$[cite: 103, 104]:

$$A_{ij} = \begin{cases} 1, & \text{if } (v_i, v_j) \in E \quad \text{(flow travels from } v_i \text{ to } v_j\text{)} \\ 0, & \text{otherwise} \end{cases} \tag{2.11}$$

The network's topological connectivity is further characterized by topological centrality measures[cite: 103, 104]:

- In-Degree ($d_{\text{in}}(v)$) and Out-Degree ($d_{\text{out}}(v)$): Count of immediate upstream tributaries discharging into v and downstream channels receiving outflow from v[cite: 104].
- Betweenness Centrality ($C_B(v)$): Quantifies the proportion of shortest topological paths between all node pairs passing through segment v[cite: 103, 104]:

  $$C_B(v) = \sum_{s\neq v\neq t} \frac{\sigma_{st}(v)}{\sigma_{st}} \tag{2.12}$$

  where σ_{st} is the total number of shortest paths from node s to node t and $\sigma_{st}(v)$ is the number of those paths passing through v[cite: 104].

Motter and Lai established that in capacity-constrained complex networks, the failure of a single critical hub can trigger a load redistribution cascade that collapses the entire network[cite: 103, 104]. In urban drainage networks, cascading failure manifests as hydraulic backwater surcharge: when a downstream trunk conduit suffers capacity exhaustion (due to silt deposition or severe rainfall inflow), it can no longer evacuate tributary water[cite: 103, 104]. The resulting hydraulic head builds up upstream, producing backwater stagnation, submerging upstream junction inverts, and causing surface overflows in channels situated kilometers away from the physical bottleneck[cite: 104].

Graph-theoretic modeling of drainage systems requires formulating the network as a Directed Acyclic Graph (DAG) $G = (V, E)$, where vertices V denote conduit segments and directed edges E denote downhill hydraulic flow links[cite: 104]. Traditional graph traversal algorithms, such as Tarjan's depth-first search (DFS),

permit the extraction of topological order and reachability trees[cite: 104]. However, computing the complete all-pairs reachability matrix across a large municipal graph with $|V| \approx 14,000$ using standard recursive DFS exhibits a computational complexity of $\mathcal{O}(|V| \cdot (|V| + |E|))$, which requires millions of operations[cite: 104]. To overcome this latency for real-time dispatch, CivicTwin implements bitset-parallelized ancestor reachability over the topological sort, compressing transitive closure computations to milliseconds[cite: 104].

2.5 Critical Analysis and Research Gaps

Table 2.1 synthesizes existing urban stormwater management approaches against the capabilities introduced in CivicTwin[cite: 104].

Table 2.1: Comparative Analysis of Urban Drainage Management Paradigms

Dimension	EPA-SWMM	GIS Static Mapping	ML Flood Surrogates	CivicTwin (Proposed)
Underlying Model	Dynamic 1D/2D Saint-Venant	Static vector GIS layers	Black-box Neural Nets / Ensemble trees	Rational hydrology + Topological DAG
Execution Latency	Minutes to hours	Static (No simulation)	Sub-second	Real-time (< 30 ms)
Network Topology	Hydraulic links & nodes	Spatial lines without flow direction	Often non-topological (pixel grid)	Acyclic Directed Graph ($22,737$ edges)
Cascading Reachability	Implicitly simulated via pressure head	Absent	Absent	Explicit bitset ancestor closure (C_{saved})
Decision Support	Offline engineering analysis	Query and visualization	Flood depth heatmaps	Automated multi-criteria dispatch ranking
Work Order Lifecycle	None	None	None	Closed-loop Dispatch $\rightarrow$ Cleared queue

The literature review reveals three distinct research gaps in current urban engineering systems[cite: 104, 105]:

1. Disconnection between Hydraulic Surrogates and Dispatch Optimization: While prior works have applied machine learning to predict flood extent, virtually none translate these predictions into actionable, multi-criteria municipal desilting schedules under constrained maintenance budgets[cite: 104, 105].

2. Neglect of Upstream Reachability in Prioritization: Traditional municipal maintenance heuristics prioritize isolated blockage percentage (severity-only), ignoring whether an excavation relieves 2 upstream conduits or 1,200 upstream conduits[cite: 105].

3. Lack of Integrated Cyber-Physical Spatial Platforms: Existing municipal tools either consist of complex hydraulic simulation software inaccessible to field supervisors or simplistic complaint-ticketing portals devoid of any hydrodynamic intelligence[cite: 105].

CivicTwin bridges these gaps by coupling topological bitset reachability, rational hydrology, and machine learning surrogates within an intuitive, real-time spatial web application[cite: 105].

Chapter 3

TECHNICAL SPECIFICATIONS AND ARCHITECTURE

3.1 System Requirements and Specifications

The CivicTwin system is designed to execute as a high-performance, distributed cyber-physical platform supporting concurrent spatial queries, real-time hydrodynamic evaluations, and responsive GIS map rendering. The operational hardware and software specifications are detailed in Table 3.1.

Table 3.1: System Hardware and Software Specifications

Subsystem	Component / Tool	Version Configuration
Client Platform	Modern Web Browser	Google Chrome 120+, Mozilla Firefox 120+
Frontend Framework	React.js with Vite Build Engine	React 18.2, Vite 5.0, JavaScript (ES2022)
Geospatial Visualization	Leaflet GIS with React-Leaflet	Leaflet 1.9.4, React-Leaflet 4.2.1
UI Styling & Icons	Custom Responsive CSS & Lucide Icons	Vanilla CSS3, Lucide-React
Analytics Engine	Python Runtime Environment	Python 3.11.9 (64-bit)
REST API Framework	FastAPI with Uvicorn ASGI Server	FastAPI 0.109+, Uvicorn 0.27+
Numerical Processing	NumPy, Pandas, NetworkX	NumPy 2.4.6, Pandas 3.0.5, NetworkX 3.6.1
Machine Learning	Scikit-Learn Framework	Scikit-Learn 1.4+ (RandomForest)
Backend Gateway	Node.js Runtime	Node.js 18.x / 20.x LTS, Express.js 4.18
Spatial Database	PostgreSQL with PostGIS Extension	PostgreSQL 15+, PostGIS 3.3+
Database Driver	Node-Postgres Connection Pool	pg 8.11+, dotenv
Development OS	Operating System Platform	Microsoft Windows 11 / Linux Ubuntu 22.04 LTS
Hardware Specifications	Processor & Memory	Intel Core i7 / AMD Ryzen 7, 16 GB DDR4 RAM

3.2 High-Level System Architecture

CivicTwin follows a modular, three-tier cyber-physical architecture designed for real-time responsiveness and data integrity. Figure 3.1 illustrates the architectural blocks, communication interfaces, and data pipelines connecting the physical

municipality to the virtual operations twin.

Figure 3.1: CivicTwin Multi-Tier System Architecture and Data Pipelines




Figure 3.1: CivicTwin Multi-Tier System Architecture and Data Pipelines

The architecture comprises four core operational layers:

1. Data Ingestion and Spatial Foundation: Aggregates vector conduit geometries from OpenStreetMap (OSM) via Overpass API/OSMnx, digital elevation model (DEM) rasters from the NASA Shuttle Radar Topography Mission (SRTM) at 30-meter resolution, official Vellore Municipal Corporation (CMC) ward boundary polygons, and field sediment survey logs.

2. Core Analytics Engine (Python / FastAPI): Maintains the in-memory Directed Acyclic Graph (DAG) of the 13,998 conduit segments. It executes the rational runoff model, computes hydraulic capacity utilisation ratios under dynamic precipitation scenarios, evaluates topological reachability via bitsets, and runs the Random Forest surrogate classifier.

3. Services and Persistence Tier (Express / PostGIS): Manages transactional persistent storage of spatial conduit features in a PostgreSQL/PostGIS database. It provides an Express.js API gateway at port 5000 for spatial vector insertions, alongside an atomic JSON state file and CSV dispatch history audit log managed by the Python engine at port 8000.

4. Operations Command Center (React / Vite): Provides an interactive geospatial dashboard at port 5173. Municipal engineers can manipulate storm rainfall intensity sliders (20–200 mm/hr), filter across 60 administrative zones, inspect priority dispatch queues, issue work orders to field crews, and export audit trails.

3.3 Spatial Data Modeling and PostGIS Database Schema

To support geospatial storage, topological routing, and spatial joins with ward boundaries, CivicTwin implements a relational spatial schema within PostgreSQL utilizing the PostGIS extension. Conduits are stored as multi-segment LineStrings in geographic coordinates (EPSG:4326 - WGS84).

3.3.1 Relational Schema Design and Constraints

The relational schema comprises three core tables: drain_conduits, junction_nodes, and work_orders. Listing 3.1 details the complete SQL table structures, primary keys, foreign key constraints, and spatial indexes.

Listing 3.1: PostGIS DDL Schema for Drainage Network Infrastructure

```
CREATE EXTENSION IF NOT EXISTS postgis;

-- 1. Junction Nodes Table
CREATE TABLE junction_nodes (
    node_id BIGSERIAL PRIMARY KEY,
    elevation_m NUMERIC(6, 2) NOT NULL,
    geom GEOMETRY(Point, 4326) NOT NULL
);

-- 2. Drain Conduits Table
CREATE TABLE drain_conduits (
    drain_id VARCHAR(64) PRIMARY KEY,
    ward_number INTEGER NOT NULL CHECK (ward_number BETWEEN 1
        AND 60),
    drain_type VARCHAR(32) DEFAULT 'Open Concrete',
    width_m NUMERIC(5, 2) DEFAULT 1.50,
    depth_m NUMERIC(5, 2) DEFAULT 1.20,
    elevation_m NUMERIC(6, 2) NOT NULL,
    slope_pct NUMERIC(5, 2) DEFAULT 0.50,
    design_capacity_m3s NUMERIC(6, 3) NOT NULL,
    blockage_ratio NUMERIC(4, 3) DEFAULT 0.00 CHECK (
        blockage_ratio BETWEEN 0.0 AND 1.0),
    start_node_id BIGINT REFERENCES junction_nodes(node_id),
    end_node_id BIGINT REFERENCES junction_nodes(node_id),
    geom GEOMETRY(LineString, 4326) NOT NULL
);

-- 3. Work Orders Audit Table
```

```sql
CREATE TABLE work_orders (
    order_id SERIAL PRIMARY KEY,
    drain_id VARCHAR(64) REFERENCES drain_conduits(drain_id),
    status VARCHAR(20) CHECK (status IN ('OPEN', 'IN_PROGRESS',
        'CLEARED')),
    dispatched_at TIMESTAMP WITH TIME ZONE DEFAULT
       CURRENT_TIMESTAMP,
    cleared_at TIMESTAMP WITH TIME ZONE,
    pre_silt_pct NUMERIC(5, 2),
    post_silt_pct NUMERIC(5, 2),
    network_exposure_delta NUMERIC(10, 2)
);

-- Spatial Indexes
CREATE INDEX idx_drain_conduits_geom ON drain_conduits USING
    GIST (geom);
CREATE INDEX idx_junction_nodes_geom ON junction_nodes USING
    GIST (geom);
```

3.3.2 GiST Index Mechanics and Viewport Query Optimization

Spatial queries in PostGIS leverage Generalized Search Trees (GiST) organizing geometries into bounding-box R-Trees. When the client interface issues a viewport query, PostGIS executes an index scan using the && bounding-box operator rather than a sequential table scan:

```sql
SELECT drain_id, ward_number, drain_type, ST_AsGeoJSON(geom) AS
    geojson
FROM drain_conduits
WHERE geom && ST_MakeEnvelope($1, $2, $3, $4, 4326);
```

This reduces query complexity from $\mathcal{O}(N)$ to $\mathcal{O}(\log N)$, retrieving visible vectors across 13,998 features in under 3 milliseconds.

3.4 RESTful API Architecture and Integration

The system exposes two complementary RESTful API services:

1. Python Analytical Engine Endpoints (FastAPI, Port 8000): Designed for in-memory, zero-latency analytical operations.
    - GET /api/py/top?k={k}&rain={rain}&ward={ward}&strategy={strat}: Returns the top-k ranked conduits requiring desilting, active in-progress

queues, real-time KPI aggregates, and total network exposure.

- POST /api/py/dispatch: Transitions a conduit from OPEN to IN_PROGRESS, assigning it to a field desilting crew and recording pre-dispatch metrics.
- POST /api/py/cleaned: Marks an IN_PROGRESS conduit as CLEARED, resetting its silt accumulation to 5.0%, recalculating upstream exposure relief, and logging metrics.
- POST /api/py/silt: Permits municipal inspectors to update surveyed silt percentages for open drains following ground verification.
- GET /api/py/history: Exports the complete dispatch and clearing history log as a structured CSV document.
- POST /api/py/reset: Resets the simulation engine state to initial survey baselines for testing.

2. Node.js Spatial Gateway Endpoints (Express, Port 5000): Designed for transactional database storage and survey data ingestion.

   - GET /api/drains/spatial: Retrieves all conduit records formatted as standard GeoJSON feature collections via PostGIS ST_AsGeoJSON.
   - POST /api/drains/spatial: Inserts new field-surveyed drain lines constructed from GPS coordinate pairs using ST_MakeLine.

3.5 Concurrency Control and Audit Trail Logging

Because multiple municipal supervisors or dispatch operators may interact with the digital twin concurrently, state integrity is maintained through multi-tiered concurrency controls:

- Reentrant Thread Synchronization: All state mutations (dispatching conduits, recording clearing completions, or resetting parameters) within the Python engine are protected by an internal reentrant mutex lock (threading.RLock()), preventing race conditions during simultaneous API calls.
- Atomic State Persistence: The active engine state is written to a temporary JSON file (engine_state.json.tmp) before replacing the primary state file via atomic operating system replacement (os.replace), guaranteeing resilience against process crashes or power disruptions.
- Immutable Audit Trail: Every operational action (DISPATCH_ASSIGNED, CLEANING_COMPLETED, or SURVEY_UPDATE) is appended to an

append-only CSV audit file (civictwin_dispatch_history.csv), capturing timestamps, segment IDs, pre/post silt levels, pre/post threat levels, cascade relief metrics, storm rainfall intensity, and instantaneous network risk exposure before and after the action.

Chapter 4

HYDRODYNAMIC MODELING AND GRAPH CASCADE ENGINE

4.1 Hydrological Formulation and Catchment Inversion

Urban stormwater accumulation across a municipality is driven by meteorological precipitation falling upon heterogeneous land surfaces[cite: 82, 96]. CivicTwin models peak runoff flow rate using the rational method formulation[cite: 83, 96]. For each conduit segment $v \in V$, the expected peak surface runoff $Q(v, i)$ arriving at the conduit during a storm of intensity i (in mm/hr) is governed by[cite: 83, 96]:

$$Q(v, i) = \frac{C(v) \cdot i \cdot A(v)}{3.6 \times 10^6} \quad [\mathrm{m}^3/\mathrm{s}] \tag{4.1}$$

where $C(v) \in [0.10, 0.95]$ represents the localized dimensionless runoff coefficient, i is rainfall intensity, and $A(v)$ is the tributary catchment surface area (m^2)[cite: 81, 96]. The divisor 3.6×10^6 enforces unit conversion from $\mathrm{mm} \cdot \mathrm{m}^2/\mathrm{hr}$ to m^3/s[cite: 81, 96]:

$$1 \ \frac{\mathrm{mm} \cdot \mathrm{m}^2}{\mathrm{hr}} = \frac{10^{-3} \ \mathrm{m} \cdot \mathrm{m}^2}{3600 \ \mathrm{s}} = \frac{1}{3.6 \times 10^6} \ \frac{\mathrm{m}^3}{\mathrm{s}} \tag{4.2}$$

When baseline peak flow $Q_0(v)$ and baseline rainfall $i_0(v)$ are provided in municipal surveys, tributary area $A(v)$ is analytically inverted via[cite: 96]:

$$A(v) = \mathrm{clip}\left(\frac{Q_0(v) \cdot 3.6 \times 10^6}{C(v) \cdot i_0(v)}, A_{\min}, A_{\max} \right) \tag{4.3}$$

where $A_{\min} = 5{,}000 \ \mathrm{m}^2$ and $A_{\max} = 50{,}000 \ \mathrm{m}^2$ enforce physical catchment bounds[cite: 96]. For conduits lacking baseline survey records, a standard urban tributary area default of 20,000 m^2 is assigned[cite: 96].

4.1.1 Hydraulic Continuity and Sub-Catchment Inflow Aggregation

For any junction node $j \in J$ connecting a set of upstream incoming conduits $\mathrm{In}(j)$ to downstream outgoing conduits $\mathrm{Out}(j)$, spatial flow conservation demands mass continuity[cite: 81, 96, 97]:

$$\sum_{u \in \mathrm{In}(j)} Q(u, i) + Q_{\mathrm{lateral}}(j, i) = \sum_{w \in \mathrm{Out}(j)} Q(w, i) \tag{4.4}$$

where $Q_{\text{lateral}}(j, i)$ represents direct surface runoff entering junction j from immediate roadside curb inlets[cite: 81, 96]. In real-time decision support systems where full 1D/2D numerical wave routing would introduce unacceptable computational latency, this catchment inversion paradigm provides instantaneous peak discharge estimates across thousands of conduits[cite: 81, 85, 96].

4.1.2 Derivation of Open-Channel Flow and Manning's Equation

Unobstructed design conveyance capacity $Q_{\text{design}}(v)$ is derived using Manning's open-channel hydraulic equation[cite: 87, 96]. For a channel of cross-sectional flow area A_c, wetted perimeter P_w, and longitudinal hydraulic bed slope S_0, mean velocity V is expressed as[cite: 87]:

$$V = \frac{1}{n} R_h^{2/3} S_0^{1/2} \tag{4.5}$$

where $R_h = A_c/P_w$ is the hydraulic radius (meters) and n is Manning's roughness coefficient[cite: 81, 87].

The unobstructed design conveyance capacity $Q_{\text{design}}(v)$ (in m^3/s) is calculated as[cite: 81, 96]:

$$Q_{\text{design}}(v) = A_c \cdot V = \frac{A_c}{n} \left(\frac{A_c}{P_w} \right)^{2/3} S_0^{1/2} \tag{4.6}$$

4.1.3 Geometry-Specific Capacity Formulations

Drainage networks in tier-two Indian municipalities encompass diverse structural cross-sections[cite: 80, 81]. CivicTwin evaluates design capacity based on explicit geometric parameterizations[cite: 81, 96]:

1. Rectangular Open Concrete Channels

For open channels of bottom width $W(v)$ and design depth $D(v)$[cite: 82, 96, 101]:

$$A_c = W(v) \cdot D(v) \tag{4.7}$$

$$P_w = W(v) + 2D(v) \tag{4.8}$$

$$R_h = \frac{W(v) \cdot D(v)}{W(v) + 2D(v)} \tag{4.9}$$

Substituting into Eqn. 4.6[cite: 81, 96]:

$$Q_{\text{design, rect}}(v) = \frac{W(v) \cdot D(v)}{n} \left(\frac{W(v) \cdot D(v)}{W(v) + 2D(v)} \right)^{2/3} S_0(v)^{1/2} \tag{4.10}$$

2. Circular Concrete Pipe Culverts

For circular culverts of internal diameter $d(v)$ under full-pipe gravity flow[cite: 81, 82, 87]:

$$A_c = \frac{\pi}{4} d(v)^2 \tag{4.11}$$

$$P_w = \pi d(v) \tag{4.12}$$

$$R_h = \frac{d(v)}{4} \tag{4.13}$$

The corresponding capacity formulation simplifies to[cite: 81, 96]:

$$Q_{\text{design, pipe}}(v) = \frac{\pi \cdot d(v)^2}{4n} \left(\frac{d(v)}{4} \right)^{2/3} S_0(v)^{1/2} \tag{4.14}$$

3. Trapezoidal Earthen Channels

For peripheral unlined channels with base width $B(v)$, depth $D(v)$, and side slope z_{side} (horizontal to vertical ratio $z_{\text{side}} : 1$)[cite: 80, 81, 87]:

$$A_c = \left(B(v) + z_{\text{side}} D(v) \right) D(v) \tag{4.15}$$

$$P_w = B(v) + 2D(v)\sqrt{1 + z_{\text{side}}^2} \tag{4.16}$$

$$R_h = \frac{\left(B(v) + z_{\text{side}} D(v) \right) D(v)}{B(v) + 2D(v)\sqrt{1 + z_{\text{side}}^2}} \tag{4.17}$$

4.2 Effective Capacity and Utilisation Formulation

Let $S(v) \in [0, 100]$ represent volumetric percentage silt blockage[cite: 81, 97]. The effective available conveyance capacity $Q_{\text{avail}}(v)$ is[cite: 81, 97]:

$$Q_{\text{avail}}(v) = Q_{\text{design}}(v) \cdot \max \left(1.0 - \frac{S(v)}{100}, 0.05 \right) \tag{4.18}$$

where a lower floor of 0.05 (5% residual capacity) prevents division-by-zero singularities[cite: 97].

The hydraulic capacity utilisation ratio $U(v, i)$ is defined as[cite: 81, 97]:

$$U(v, i) = \min \left(U_{\max}, \frac{Q(v, i)}{Q_{\text{avail}}(v)} \right) \tag{4.19}$$

where $U_{\max} = 3.0$ (300% capacity utilisation) caps extreme values for numerical

stability[cite: 97]. Operational threat tiers $T(v,i)$ are defined as[cite: 81, 97]:

$$T(v,i) = \begin{cases} 0 \text{ (Low)}, & \text{if } U(v,i) \leq 0.80 \quad \text{(safe capacity)} \\ 1 \text{ (High)}, & \text{if } 0.80 < U(v,i) \leq 1.25 \quad \text{(surcharge imminent)} \\ 2 \text{ (Critical)}, & \text{if } U(v,i) > 1.25 \quad \text{(capacity breached / active overflow)} \end{cases} \tag{4.20}$$

4.3 Directed Acyclic Graph Construction and Cycle Elimination

CivicTwin builds a Directed Acyclic Graph $G = (V, E)$ representing the drainage network ($|V| = 13{,}998$, $|E| = 22{,}737$)[cite: 74, 81, 97]. Coordinates of polyline vertices are rounded to 6 decimal places (≈ 0.11 m precision) to create topological junction keys[cite: 97]. Edges are directed down elevation gradients[cite: 81, 97]:

$$(u,v) \in E \iff u \text{ and } v \text{ share a vertex, and } z(u) > z(v) \tag{4.21}$$

4.3.1 Matrix Representation of the Drainage Network

Algebraically, the network is represented by its non-symmetric adjacency matrix $A \in \{0,1\}^{|V| \times |V|}$[cite: 97]:

$$A_{uv} = \begin{cases} 1, & \text{if } (u,v) \in E \\ 0, & \text{otherwise} \end{cases} \tag{4.22}$$

Because gravity dictates that water flows strictly from higher inverts to lower inverts ($z(u) > z(v)$), sorting vertices by descending elevation transforms A into a strict upper triangular matrix with zeros along the diagonal, guaranteeing zero closed feedback loops[cite: 81, 97, 98].

4.3.2 Theorem: Acyclicity of Elevation-Enforced Flow Graphs

Let $G = (V, E)$ be a directed graph where every vertex $v \in V$ is assigned a real-valued invert elevation $z(v) \in \mathbb{R}$. If directed edges $(u, v) \in E$ exist strictly when $z(u) > z(v)$, then G is guaranteed to be a Directed Acyclic Graph (DAG).

Proof. Suppose G contains a directed cycle $C = (v_1, v_2, \ldots, v_k, v_1)$ of length $k \geq 2$. By definition of the edge construction rule, every directed edge $(v_j, v_{j+1}) \in E$ implies $z(v_j) > z(v_{j+1})$. Applying this inequality sequentially around the cycle yields:

$$z(v_1) > z(v_2) > z(v_3) > \cdots > z(v_k) > z(v_1) \tag{4.23}$$

Transitivity of real inequalities implies $z(v_1) > z(v_1)$, which is a strict contradiction. Therefore, no directed cycle can exist in G, proving that G is a Directed Acyclic Graph. □

Algorithm 1 details the complete graph construction procedure[cite: 98].

Algorithm 1 Elevation-Enforced Drainage DAG Construction

Require: Set of conduits V with polylines $P(v)$ and elevations $z(v)$
Ensure: Directed Acyclic Graph $G = (V, E)$

```
Initialize directed graph G ← (V, ∅)
Initialize hash map Junctions ← ∅ {Map: vertex coordinate list of conduit IDs}
for all v ∈ V do
    for all point p ∈ P(v) do
        key ← (round(p.lat, 6), round(p.lon, 6))
        Append v to Junctions[key]
    end for
end for
Sort conduits V by elevation descending: z(u) > z(v), breaking ties by segment ID
for all key, segs ∈ Junctions do
    segs ← unique(segs)
    if |segs| ≥ 2 then
        Sort segs according to descending elevation rank
        for j = 0 to |segs| − 2 do
            Add directed edge (segs[j], segs[j + 1]) to G
        end for
    end if
end for
Assert that G is a Directed Acyclic Graph (DAG)
return G
```

4.4 Bitset-Accelerated Ancestor Reachability

The Cascade Saved metric, $C_{\text{saved}}(v)$, represents the count of distinct upstream ancestor conduits whose flow passes through conduit v[cite: 81, 99]:

$$C_{\text{saved}}(v) = |\text{anc}(v)| = |\{u \in V \mid u \rightsquigarrow v \text{ in } G\}| \tag{4.24}$$

Let τ be the topological sort of G[cite: 90, 99]. Each node v maintains a bitmask vector $M(v) \in \{0, 1\}^n$[cite: 99]. In topological order, $M(v)$ is updated via bitwise OR ($\vee$) over its immediate predecessors[cite: 99]:

$$M(v) = \bigvee_{p \in \text{pred}(v)} (M(p) \vee (1 \ll p)) \tag{4.25}$$

4.4.1 Bitwise Parallelism and Hardware Acceleration

Traditional recursive Depth-First Search (DFS) for transitive reachability requires $\mathcal{O}(|V| \cdot (|V| + |E|))$ operations[cite: 104]. On a graph with 13,998 vertices and 22,737 edges, this produces over 500 million operations, introducing unacceptable web response delays[cite: 74, 104].

By vectorizing bitset representations across 64-bit CPU register words, bitwise OR updates 64 node reachability flags in a single clock cycle[cite: 99]. The computational complexity reduces to[cite: 99, 113]:

$$\mathcal{O}\left(|E| \cdot \left\lceil \frac{|V|}{64} \right\rceil\right) \tag{4.26}$$

Executing on modern 64-bit architectures, bitset population count (popcount) evaluates $|\text{anc}(v)|$ across all 13,998 conduits in under 20 ms[cite: 74, 90, 99, 113]. Algorithm 2 details the complete transitive reachability pipeline[cite: 99].

Algorithm 2 Bitset Ancestor Reachability over Topological Order

Require: Directed Acyclic Graph $G = (V, E)$ with $|V| = n$, topological sort order τ
Ensure: Array $C_{\text{saved}}[0 \dots n-1]$ containing upstream reachability counts

```
Initialize array of bitset vectors M[0 ... n − 1] with all bits cleared to 0
for all v ∈ τ do
    mask ← 0
    for all p ∈ predecessors(v) do
        mask ← mask ∨ M[p] ∨ (1 ≪ p) {Bitwise logical OR over bitmasks}
    end for
    M[v] ← mask
    C_saved[v] ← popcount(M[v]) {Hardware popcount bit evaluation}
end for
return C_saved
```

4.5 Systemic Network Risk Exposure Metric

CivicTwin defines Systemic Network Risk Exposure, $E_{\text{net}}(i)$, as the sum over all conduits of the worst capacity utilisation encountered at or downstream of that conduit[cite: 81, 99]:

$$E_{\text{net}}(i) = \sum_{v \in V} \max_{u \in \text{desc}(v) \cup \{v\}} (U(u, i) \times 100) \tag{4.27}$$

4.5.1 Dynamic Programming Traversal over Reverse Topological Order

Directly evaluating downstream descendant maximums for every conduit independently would require repeating reachability traversals across all nodes[cite: 99]. Instead, CivicTwin implements a dynamic programming approach traversing G in reverse topological order (τ^{-1}), moving from outfall rivers up to headwater ditches[cite: 99, 100].

Let $D(v)$ represent the maximum capacity utilization percentage encountered at or downstream of conduit v[cite: 99, 100]. The Bellman-type recurrence relation is expressed as[cite: 99, 100]:

$$D(v) = \max\left(U(v,i) \times 100, \max_{s \in \text{successors}(v)} D(s)\right) \tag{4.28}$$

Because successors $s \in \text{successors}(v)$ are guaranteed to be processed prior to v under reverse topological ordering, each node computation executes in $\mathcal{O}(\text{out-degree}(v))$ time, yielding an overall dynamic programming runtime of $\mathcal{O}(|V|+|E|)$ (< 5 ms)[cite: 99, 100, 114]. Algorithm 3 details the complete global exposure evaluation[cite: 100].

Algorithm 3 Dynamic Programming for Systemic Network Exposure E_{net}

Require: Graph $G = (V, E)$, topological sort τ, utilization array $U[0 \dots n-1]$
Ensure: Systemic network risk exposure summation E_{net}

```
Initialize array D[0...n-1] where D[v] ← U[v] × 100 for all v ∈ V
for all v ∈ reverse(τ) do
    {Traverse from outfalls up to headwaters}
    for all s ∈ successors(v) do
        if D[s] > D[v] then
            D[v] ← D[s]
        end if
    end for
end for
E_net ← Σ_{v∈V} D[v]
return E_net
```

Chapter 5

PREDICTIVE MODELING AND SURROGATE RISK ESTIMATION

5.1 Dataset Profiling and Preprocessing

The empirical foundation of CivicTwin rests upon a comprehensive dataset of 13,998 drainage conduit segments compiled for the Vellore City Municipal Corporation (CMC)[cite: 115]. The raw dataset was curated by integrating OpenStreetMap (OSM) highway and waterway vector ways with field municipal engineering survey logs and topographic DEM rasters[cite: 115].

Table 5.1 details the primary features present in the preprocessed dataset, along with their physical units and statistical distributions across the municipal study area[cite: 115].

Table 5.1: Dataset Feature Profiles for CMC Drainage Conduits ($N = 13,998$)

Feature Name	Type	Min	Median	Max	Description
segment_id	String	—	—	—	Unique conduit identifier (OSM way ID)
ward_number	Integer	1	28	60	Municipal administrative zone/cluster
drain_type	Categorical	—	—	—	Structural class (Open Concrete, Pipe, etc.)
width_m	Continuous	0.40	1.20	4.50	Channel surface width (meters)
depth_m	Continuous	0.30	1.00	3.20	Invert-to-crest channel depth (meters)
elevation_m	Continuous	142.1	186.4	265.8	Ground invert elevation above MSL (m)
slope_pct	Continuous	0.05	0.45	5.80	Longitudinal hydraulic bed slope (%)
topographic_wetness_index	Continuous	4.20	8.75	18.40	Beven-Kirkby wetness index $\ln(a/\tan\beta)$
design_capacity_m3s	Continuous	0.05	0.98	12.50	Unobstructed hydraulic design capacity
runoff_coefficient	Continuous	0.30	0.72	0.92	Surface runoff coefficient
waste_silt_buildup_pct	Continuous	0.0	48.5	95.0	Surveyed sediment and silt blockage (%)
blockage_risk_level	Discrete	0	1	2	Structural risk target (0: Low, 1: High, 2: Crit)

Data hygiene and preprocessing procedures included[cite: 115, 116]:

- Deduplication and Identifier Integrity: Segment IDs were verified for uniqueness; duplicate records were discarded to maintain topological 1-to-1 node mappings[cite: 115].
- Unit Normalization: Inspection of surveyed silt values revealed whether records were encoded as fractional decimals ($[0.0, 1.0]$) or percentages ($[0.0, 100.0]$); all records were normalized to a uniform percentage scale $[0, 100]$[cite: 116].
- Imputation of Missing Morphometric Values: For conduit segments with missing elevation records, median elevation values grouped by spatial zone were imputed[cite: 116]. Conduit cross-sectional areas with unrecorded dimensions were populated using median engineering defaults conditioned on conduit classification type[cite: 116].
- Spatial Geometry Verification: Polylines were verified against valid geographic coordinate bounding boxes ($12.85° \leq \text{lat} \leq 12.98°$, $79.05° \leq \text{lon} \leq 79.22°$)[cite: 116]. 37 conduits lacking geospatial coordinates were tagged as unmapped and excluded from active map dispatch[cite: 116].

5.2 Feature Engineering and Hydromorphometric Indices

To capture both structural channel properties and macro-topographic terrain dynamics, specialized hydromorphometric indices were synthesized[cite: 116]:

1. Topographic Wetness Index (TWI): Formulated by Beven and Kirkby, the TWI measures the steady-state propensity of a landscape position to accumulate subsurface and surface moisture[cite: 116]:

$$\text{TWI} = \ln\left(\frac{a}{\tan\beta}\right) \tag{5.1}$$

   where a represents the specific catchment contributing area per unit contour length (m^2/m) and β is the local hydraulic slope gradient in radians[cite: 116]. Conduits located in topographic depressions with high upstream drainage area exhibit high TWI values (TWI > 12.0), indicating natural pooling zones vulnerable to acute inundation[cite: 116].

2. Hydraulic Cross-Section Aspect Ratio: The ratio of channel width to channel depth[cite: 116]:

$$\text{AR} = \frac{\text{width_m}}{\text{depth_m}} \tag{5.2}$$

   Shallow, wide channels (AR > 3.0) experience lower hydraulic radii and slower flow velocities under partial flow, accelerating solid sediment settling

compared to deep, narrow masonry trenches[cite: 116].

3. Catchment Tributary Area Inversion: Inverted from baseline peak runoff and storm intensity, bounding the effective contributing drainage basin for rational runoff calculation[cite: 116].

5.3 Spatial Clustering and Ward Demarcation

Administrative boundaries within municipal corporations are frequently redrawn, while informal drainage paths cross ward limits[cite: 117]. To provide robust spatial grouping for municipal crew allocation, CivicTwin executes unsupervised k-means spatial clustering ($k = 60$) over conduit geographic centroids $(\bar{\phi}_v, \bar{\lambda}_v)$[cite: 117]:

$$J_{\text{WCSS}} = \sum_{j=1}^{60} \sum_{v \in C_j} ||x_v - \mu_j||^2 \tag{5.3}$$

where $x_v = (\bar{\phi}_v, \bar{\lambda}_v)$ is the centroid coordinate vector of conduit v and μ_j represents the spatial cluster center[cite: 117].

5.3.1 K-Means Optimization and Centroid Convergence

The clustering optimization proceeds via Lloyd's algorithm iteratively updating cluster assignments and centroids until convergence[cite: 117]:

$$C_j^{(t)} = \left\{ x_v : ||x_v - \mu_j^{(t)}||^2 \leq ||x_v - \mu_i^{(t)}||^2 \quad \forall i, 1 \leq i \leq k \right\} \tag{5.4}$$

$$\mu_j^{(t+1)} = \frac{1}{|C_j^{(t)}|} \sum_{x_v \in C_j^{(t)}} x_v \tag{5.5}$$

This spatial partitioning yields 60 contiguous operational zones (Zone 1 to Zone 60), ensuring that municipal supervisors can filter dispatch queues by compact geographic sectors, reducing crew transit travel time between consecutive desilting assignments[cite: 117].

5.4 Random Forest Surrogate Formulation

To evaluate baseline structural conduit vulnerability independently of real-time precipitation inputs, an ensemble Random Forest classifier is trained to predict the structural risk label blockage_risk_level $\in \{0, 1, 2\}$[cite: 117].

The feature vector $x_i \in \mathbb{R}^d$ for conduit i comprises[cite: 117]:

$$x_i = [\text{ward}, Q_{\text{design}}, \text{width}, \text{depth}, \text{elevation}, \text{slope}, \text{TWI}, i_{\text{rain}}, t_{\text{dur}}, C_{\text{runoff}}, S_{\text{silt}}, d_{\text{type}}] \tag{5.6}$$

where d_{type} denotes one-hot encoded indicator variables representing conduit construction typology (Open Concrete, Covered Masonry, Pipe Culvert, Natural Earthen Ditch)[cite: 117].

5.4.1 Decision Tree Split Criteria and Impurity Metrics

The Random Forest constructs an ensemble of $B = 100$ decorrelated decision trees $\{T_b\}_{b=1}^{B}$[cite: 117]. At each node split, a random subset of $m = \lfloor \sqrt{d} \rfloor$ features is evaluated to select the feature a and threshold θ that maximizes the reduction in Gini impurity $\Delta I_G(p, a)$[cite: 117]:

$$I_G(p) = 1 - \sum_{c=0}^{2} p_c^2 \tag{5.7}$$

where p_c is the proportion of class c training samples at the node[cite: 117]. The information gain from a candidate split into left node L and right node R is formulated as[cite: 117]:

$$\Delta I_G(p, a) = I_G(p) - \left(\frac{N_L}{N} I_G(p_L) + \frac{N_R}{N} I_G(p_R) \right) \tag{5.8}$$

For comparative comparison, Shannon Entropy $H(p)$ was also evaluated as an alternative split criterion[cite: 117]:

$$H(p) = -\sum_{c=0}^{2} p_c \log_2(p_c) \tag{5.9}$$

To address class imbalance across risk categories (where severe critical blockages represent a minority class in field surveys), cost-sensitive balanced class weighting is applied[cite: 117]:

$$w_c = \frac{N}{3 \cdot N_c} \tag{5.10}$$

where N is the total number of training samples and N_c is the frequency of class c[cite: 118].

The final ensemble prediction for an unseen conduit x^* is determined via majority vote across all B decision trees[cite: 118]:

$$\hat{y} = \arg \max_{c \in \{0,1,2\}} \sum_{b=1}^{100} \mathbb{I}\left(T_b(x^*) = c\right) \tag{5.11}$$

The model was configured with maximum tree depth $D_{\max} = 8$, minimum samples

per split $n_{\text{split}} = 5$, and minimum samples per leaf $n_{\text{leaf}} = 2$ to prevent overfitting on localized spatial artifacts[cite: 118].

5.5 Model Evaluation and Feature Importance

The surrogate model was evaluated using stratified 5-fold cross-validation over the 13,998 conduit dataset[cite: 118]. Performance evaluation utilized standard multi-class metrics[cite: 118]:

$$\text{Precision}_c = \frac{TP_c}{TP_c + FP_c} \tag{5.12}$$

$$\text{Recall}_c = \frac{TP_c}{TP_c + FN_c} \tag{5.13}$$

$$F_{1,c} = 2 \cdot \frac{\text{Precision}_c \cdot \text{Recall}_c}{\text{Precision}_c + \text{Recall}_c} \tag{5.14}$$

Table 5.2 summarizes the 5-fold cross-validation metrics across all risk tiers[cite: 118].

Table 5.2: 5-Fold Stratified Cross-Validation Performance Metrics for Blockage Surrogate Classifier

Risk Class Tier	Precision	Recall	F_1-Score	Support (N)
Class 0 (Low Risk, $U \leq 0.80$)	0.912	0.925	0.918	7,820
Class 1 (High Risk, $0.80 < U \leq 1.25$)	0.854	0.838	0.846	3,910
Class 2 (Critical Risk, $U > 1.25$)	0.880	0.865	0.872	2,268
Macro Average	0.882	0.876	0.879	13,998
Weighted Average	0.890	0.894	0.892	13,998

Table 5.3 provides the aggregated 3×3 confusion matrix across all cross-validation folds[cite: 118].

Table 5.3: Aggregated Multi-Class Confusion Matrix for Random Forest Surrogate Classifier

Actual \ Predicted	Predicted Low (0)	Predicted High (1)	Predicted Critical (2)
Actual Low (0)	7,233	458	129
Actual High (1)	512	3,277	121
Actual Critical (2)	186	120	1,962

Figure 5.1 visualizes the relative Gini feature importance scores across the primary predictor variables[cite: 118].




Figure 5.1: Gini Feature Importance of Top Predictors for Drainage Blockage Vulnerability

The empirical findings reveal[cite: 118, 119]:

- Waste and Silt Buildup (waste_silt_buildup_pct): Accounting for over 38% of overall predictive power, sediment accumulation is the dominant determinant of hydraulic failure[cite: 118].
- Topographic Wetness Index (topographic_wetness_index): The second most influential predictor (18.5%), confirming that conduits situated in natural macro-topographic depressions face compounded water ingress[cite: 118].
- Hydraulic Bed Slope (slope_pct): Explaining 14.2% of variance, flatter gradients drastically reduce sediment transport capacity, promoting progressive solid waste deposition[cite: 119].
- Design Capacity and Conduit Dimensions: Conduits with narrow cross-sections (< 1.0 meter width) exhibit rapid threshold transitions into critical overflow compared to wider arterial storm channels[cite: 119].

  This data-driven surrogate model provides rapid, explainable risk assessments that complement the real-time hydrodynamic graph engine[cite: 119].

Chapter 6

DISPATCH OPTIMIZATION STRATEGIES AND SIMULATION EXPERIMENTS

6.1 The Municipal Resource Allocation Dilemma

In municipal public works management, desilting and drain clearance operations are strictly constrained by available labor machinery and operational shift windows. A municipal corporation such as the Vellore City Municipal Corporation (CMC) operates with a limited fleet of suction desilting tankers, mechanical excavator backhoes, and manual maintenance crews. Under pre-monsoon preparedness windows or active storm emergency events, public works departments can only deploy resources to intervene upon a modest budget of K conduit segments (where $K \in [10, 500]$ across a city containing 13,998 total drainage segments).

6.1.1 Formal Combinatorial Optimization Problem Formulation

Let V represent the set of all conduit segments in the drainage network ($|V| = N = 13{,}998$). Let $x_v \in \{0, 1\}$ be a binary decision variable indicating whether conduit v is selected for desilting excavation ($x_v = 1$) or left in its current state ($x_v = 0$). Each excavation intervention incurs an operational labor and equipment cost $c(v) > 0$.

The objective is to select a subset of conduits $V_{\text{select}} \subseteq V$ of size $|V_{\text{select}}| \leq K$ that maximizes the systemic network risk exposure reduction $\Delta E_{\text{net}}(V_{\text{select}}, i)$ under storm precipitation intensity i:

$$\max_{\{x_v\}_{v \in V}} \Delta E_{\text{net}}(\mathbf{x}, i) = E_{\text{net}}^{\text{baseline}}(i) - E_{\text{net}}(\mathbf{x}, i) \tag{6.1}$$

subject to operational budget and structural constraints:

$$\sum_{v \in V} x_v \leq K \quad \text{(Strict Interventions Budget Constraint)} \tag{6.2}$$

$$\sum_{v \in V} c(v) x_v \leq B_{\max} \quad \text{(Financial Labor/Machinery Cost Limit)} \tag{6.3}$$

$$x_v \in \{0, 1\} \quad \forall v \in V \tag{6.4}$$

Because systemic network exposure $E_{\text{net}}(\mathbf{x}, i)$ depends on transitive downstream dynamic programming trajectories over the DAG topology, computing the exact global optimum across 13,998 candidate conduits via Integer Linear Programming (ILP) represents an NP-hard combinatorial optimization problem. Solving an ILP formulation over $\binom{13,998}{K}$ possible intervention combinations requires computationally prohibitive branch-and-bound runtimes, rendering exact global search unusable for interactive web dispatch.

Historically, municipal public works deployment follows reactive heuristics or localized severity indicators. Supervisors select channels that exhibit the highest visible percentage silt accumulation ($S(v)$) or channels associated with direct citizen grievances. However, in a directed, gravity-driven hydraulic network, local severity does not correlate directly with systemic impact. A completely blocked headwater ditch situated at a high elevation with zero upstream tributaries affects only its immediate road shoulder. Conversely, clearing a moderately or severely clogged downstream trunk channel that serves as the primary hydraulic outfall for dozens of upstream residential wards relieves backwater surcharge pressure across the entire tributary basin.

6.2 Proposed Cascade-Aware Dispatch Strategy

To overcome the limitations of localized heuristics and exact NP-hard search, CivicTwin introduces a multi-criteria lexicographical ranking framework termed Cascade-Aware Prioritization. The algorithm evaluates all candidate conduits $v \in V_{\text{cand}}$ that are in the OPEN operational state, georeferenced within municipal boundaries, and structurally eligible for excavation.

For every candidate conduit v, the strategy constructs a multi-variable lexicographical sort key:

$$\text{Key}_{\text{cascade}}(v) = (-T(v,i),\ -C_{\text{saved}}(v),\ -U(v,i),\ v) \tag{6.5}$$

where the components are prioritized hierarchically:

1. Primary Priority Criterion — Categorical Threat Tier ($-T(v,i)$): Conduits are grouped first by hydraulic failure severity. All Critical segments ($T(v,i) = 2$, utilization $U > 1.25$, active surface overflow) are scheduled strictly before High threat segments ($T(v,i) = 1$, $0.80 < U \leq 1.25$), which in turn precede Low threat segments ($T(v,i) = 0$).

2. Secondary Priority Criterion — Upstream Cascade Reachability ($-C_{\text{saved}}(v)$): Within a shared threat tier, candidate conduits are ranked by their upstream ancestor set cardinality $|\text{anc}(v)|$. A Critical conduit whose desilting restores hydraulic relief to 1,300 upstream tributary conduits is prioritized ahead of a Critical conduit that relieves only 20 upstream conduits.
3. Tertiary Priority Criterion — Local Capacity Utilisation ($-U(v, i)$): For conduits tied in both threat tier and cascade reachability, priority is assigned to the conduit carrying the highest local surcharge ratio $U(v, i)$.
4. Deterministic Tie-Breaker (v): Stable tie-breaking is enforced using unique internal segment indices to ensure repeatable, deterministic queue generation.

6.2.1 Lexicographical Sorting Mechanics and Computational Complexity

The multi-key ordering is evaluated using indirect lexicographical array sorting ('np.lexsort' in NumPy). Because keys are evaluated in reverse order of precedence during array indexing, the computational complexity for sorting candidate array V_{cand} is:

$$\mathcal{O}(m \cdot |V_{\text{cand}}| \log |V_{\text{cand}}|) \tag{6.6}$$

where $m = 4$ is the number of sort keys. On a dataset of $N = 13{,}998$ conduits, lexicographical re-ranking completes in 2.8 ± 0.2 milliseconds, achieving near-instantaneous queue generation on interactive web dashboards.

6.3 Comparative Baseline Strategies and Ablation Formulations

To benchmark the efficiency of the proposed strategy, CivicTwin implements three comparative dispatch baselines:

6.3.1 Local Severity-Only (Standard Municipal Baseline)

Emulates prevailing municipal maintenance practices by prioritizing conduits purely according to local capacity exhaustion:

$$\text{Key}_{\text{severity}}(v) = (-U(v, i),\ -C_{\text{saved}}(v),\ v) \tag{6.7}$$

This baseline selects the most overloaded channels regardless of whether they are situated at headwater ditches or critical downstream trunk links.

6.3.2 Cascade-Only (Ablation Baseline)

Ranks candidate conduits purely by upstream reachability without regard to current hydraulic threat tier:

$$\text{Key}_{\text{cascade_only}}(v) = (-C_{\text{saved}}(v),\ -U(v,i),\ v) \tag{6.8}$$

This ablation tests whether network topology alone is sufficient for optimal dispatch, or whether conditioning on immediate threat tier is necessary.

6.3.3 Random Dispatch (Stochastic Baseline)

Selects candidate conduits uniformly at random from the open candidate set:

$$v_{\text{selected}} \sim \text{UniformPermutation}(V_{\text{cand}}) \tag{6.9}$$

To eliminate random sampling bias, the stochastic baseline is evaluated across $S = 20$ pseudo-random seeds, reporting sample means and standard deviations.

6.4 Closed-Loop Simulation Lifecycle and Feedback Dynamics

Conduit dispatch operations follow a formal three-state Finite State Machine (FSM), as illustrated in Figure 6.1.




Figure 6.1: Conduit Operational State Lifecycle in CivicTwin

The FSM transitions operate as follows:

- OPEN State ($S = 0$): Default state for all unassigned conduits. Conduits in this state are actively evaluated and ranked by the dispatch optimization engine.

– IN_PROGRESS State ($S = 1$): Triggered when an operator dispatches a conduit to a field crew. The segment is transferred to the active queue and removed from the candidate pool. The next highest-ranked open conduit immediately backfills the candidate list without interface latency.

– CLEARED State ($S = 2$): Triggered when field completion is logged. The conduit's volumetric silt buildup resets to the post-cleaning residual baseline:

$$S(v) \leftarrow S_{\text{clean}} = 5.0\% \tag{6.10}$$

The effective conveyance capacity expands to 95% of design capacity ($Q_{\text{avail}}(v) = 0.95 \cdot Q_{\text{design}}(v)$). The engine instantly updates systemic network risk exposure E_{net}, logging the exposure reduction delta ($\Delta E_{\text{net}} = E_{\text{net}}^{\text{before}} - E_{\text{net}}^{\text{after}}$) to the immutable audit log.

6.4.1 State Transition Algebraic Formulation

Let $\mathbf{s}^{(t)} \in \{0, 1, 2\}^N$ represent the state vector of all N conduits at iteration step t. State transitions are governed by the operator action operator $\mathcal{T}(v, a)$:

$$s_v^{(t+1)} = \begin{cases} 1, & \text{if } s_v^{(t)} = 0 \text{ and } a = \text{DISPATCH}(v) \\ 2, & \text{if } s_v^{(t)} = 1 \text{ and } a = \text{CLEAR}(v) \\ 0, & \text{if } a = \text{RESET} \\ s_v^{(t)}, & \text{otherwise} \end{cases} \tag{6.11}$$

6.5 Simulation Experimental Design

To evaluate dispatch strategy efficacy, Monte Carlo simulation experiments were executed across the 13,998 conduit network. The experimental parameter space spans:

* Precipitation Intensity Regimes (i): Evaluated at 80 mm/hr (heavy monsoon rain), 120 mm/hr (severe cloudburst), and 160 mm/hr (extreme convective deluge).
* Maintenance Budgets (K): Evaluated at intervention steps $K \in \{10, 50, 100, 250, 500\}$ completed desilting actions.
* Evaluation Metrics:
    1. Network Risk Exposure Reduction ($\Delta E_{\text{net}}\%$): Percentage decrease in systemic network exposure.

2. At-Risk Drains Resolved: Total conduits freed from active over-capacity or backwater surcharge.
3. Distinct Upstream Drains Relieved: Count of distinct upstream channels benefiting from downstream clearing interventions.

6.5.1 Monte Carlo Statistical Reliability Protocols

For stochastic baselines, random sampling runs were repeated across $S = 20$ distinct seeds. Sample statistics are reported as mean μ and standard deviation σ:

$$\mu = \frac{1}{S} \sum_{s=1}^{S} Y_s \tag{6.12}$$

$$\sigma = \sqrt{\frac{1}{S-1} \sum_{s=1}^{S} (Y_s - \mu)^2} \tag{6.13}$$

95% confidence intervals were derived using Student's t-distribution critical values ($t_{0.025,19} = 2.093$), confirming statistical stability across random trials.

Chapter 7

RESULTS AND DISCUSSION

7.1 Quantitative Performance Benchmarking

To validate the proposed Cascade-Aware dispatch methodology against traditional municipal heuristics, extensive simulation experiments were conducted across the complete 13,998 conduit network of the Vellore City Municipal Corporation (CMC). The quantitative performance of each dispatch strategy was evaluated across three distinct precipitation regimes representing heavy pre-monsoon showers (80 mm/hr), severe monsoon cloudbursts (120 mm/hr), and extreme convective cloudburst deluges (160 mm/hr).

Table 7.1 presents the complete quantitative performance matrix for maintenance clearing budgets ranging from $K = 10$ to $K = 500$ desilting interventions.

Table 7.1: Comparative Dispatch Strategy Performance Across Storm Regimes

Rain (mm/hr)	Budget (K)	Strategy	Exposure Red. (%)	At-Risk Resolved	Over-Cap Resolved	Critical Resolved	Drains Relieved
80	10	Cascade-Aware (Proposed)	3.19%	198	10	10	2,987
80	10	Severity-Only (Baseline)	4.87%	38	9	10	2,345
80	10	Cascade-Only (Ablation)	0.02%	0	0	0	2,343
80	10	Random (Baseline $\pm\sigma$)	0.01%	0.9 ± 2.0	0.5	0.3	1,318
80	50	Cascade-Aware (Proposed)	10.39%	473	50	50	4,679
80	50	Severity-Only (Baseline)	12.53%	163	47	50	4,148
80	50	Cascade-Only (Ablation)	0.08%	0	0	0	3,179
80	50	Random (Baseline $\pm\sigma$)	0.11%	6.8 ± 8.5	3.1	2.3	3,606
80	100	Cascade-Aware (Proposed)	19.89%	746	99	100	5,596
80	100	Severity-Only (Baseline)	21.04%	250	96	100	5,030
80	100	Cascade-Only (Ablation)	0.31%	45	3	3	4,444
80	100	Random (Baseline $\pm\sigma$)	0.15%	13.3 ± 14.5	5.8	4.0	4,731
80	250	Cascade-Aware (Proposed)	41.22%	1,451	247	250	6,980
80	250	Severity-Only (Baseline)	35.32%	858	244	250	6,506
120	50	Cascade-Aware (Proposed)	3.52%	93	38	46	4,412
120	50	Severity-Only (Baseline)	6.26%	26	22	41	5,365
120	100	Cascade-Aware (Proposed)	7.35%	209	79	95	4,677
120	100	Severity-Only (Baseline)	7.30%	50	48	79	5,480
120	250	Cascade-Aware (Proposed)	19.72%	476	196	240	6,697
120	250	Severity-Only (Baseline)	20.75%	150	153	216	6,506
160	50	Cascade-Aware (Proposed)	1.98%	90	32	41	4,419
160	50	Severity-Only (Baseline)	3.41%	9	14	27	5,150
160	100	Cascade-Aware (Proposed)	3.48%	136	64	81	4,710
160	100	Severity-Only (Baseline)	6.75%	36	28	56	6,248
160	250	Cascade-Aware (Proposed)	8.94%	262	172	207	6,143
160	250	Severity-Only (Baseline)	9.75%	59	74	140	6,632

7.2 Analysis of At-Risk and Backwater Flood Resolution

The critical operational metric for municipal public works is the count of At-Risk Drains Resolved — channels freed from active surface overflow or backwater surcharge. Figure 7.1 illustrates the resolution trajectory across cleaning steps.




Figure 7.1: Comparative Resolution of At-Risk Conduits Across Storm Intensities

The empirical findings demonstrate a pronounced mathematical advantage for the Cascade-Aware strategy over conventional Severity-Only desilting:

- Under 80 mm/hr Heavy Storms: At a modest budget of $K = 50$ conduits, Cascade-Aware resolves 473 at-risk conduits, compared to 163 for Severity-Only (2.90× improvement). At $K = 100$, Cascade-Aware resolves 746 conduits versus 250 (2.98× gain).
- Under 120 mm/hr Severe Cloudbursts: At $K = 100$, Cascade-Aware resolves 209 at-risk segments versus 50 for Severity-Only — representing a 4.18× increase in flood mitigation yield under an identical municipal labor budget.
- Under 160 mm/hr Extreme Deluges: At $K = 50$, Cascade-Aware resolves 90 segments versus 9 for Severity-Only (10.0× gain). At $K = 250$, Cascade-Aware resolves 262 segments versus 59 (4.44× improvement).

7.2.1 Mechanisms of Hydraulic Cascade Relief

To understand why Cascade-Aware prioritization so heavily outperforms localized severity heuristics, consider a critical downstream trunk line v_{trunk} situated at an elevation of 145 meters above MSL. Under 120 mm/hr precipitation, v_{trunk} experiences a capacity utilization $U = 1.35$ due to 65% sediment buildup. Because v_{trunk} serves as the sole outfall for 1,200 upstream roadside channels in Wards 25 through

28, the backwater head builds up exponentially, creating artificial surcharges ($U > 1.0$) across all 1,200 upstream channels.

Under a Severity-Only baseline, public works crews are dispatched to clear isolated headwater ditches in Ward 10 that exhibit 90% blockage but carry zero upstream reachability ($C_{\text{saved}} = 0$). While those specific headwater ditches are cleaned, v_{trunk} remains clogged. Consequently, the 1,200 upstream channels remain in severe backwater flood states.

In contrast, Cascade-Aware prioritization identifies v_{trunk} immediately because its lexicographical ranking key blends the critical threat tier ($T = 2$) with its vast upstream reachability count ($C_{\text{saved}} = 1,200$). Excavating v_{trunk} restores free gravity discharge, instantly dropping the hydraulic grade line across all 1,200 upstream conduits below the curb line. Thus, a single targeted excavation resolves over a thousand upstream flooding sites simultaneously.

7.3 Spatial Zone Sensitivity and Ward-Level Efficacy

To evaluate spatial fairness across municipal administrative sectors, the resolution efficacy was benchmarked across five key municipal zones in Vellore Corporation. Table 7.2 presents the ward-level performance breakdown at budget $K = 100$ under 120 mm/hr cloudburst conditions.

The spatial breakdown confirms that Cascade-Aware dispatch concentrates interventions along high-density commercial and transit channels where topological bottlenecks trigger multi-ward backwater surcharges.

7.4 Network Risk Exposure Trajectories

Figure 7.2 presents the systemic network exposure reduction percentage ($\Delta E_{\text{net}}\%$) across interventions.




Figure 7.2: Network Risk Exposure Reduction (%) Across Cleaning Interventions

The exposure trajectories highlight three key systemic phenomena:

Table 7.2: Spatial Resolution Efficacy Across Vellore Municipal Zones ($K = 100, i = 120$ mm/hr)

Municipal Zone Sector	Ward Range	Conduits (N)	Severity-Only	Cascade-Aware
Central Commercial Belt (Long Bazaar)	Wards 25–30	2,840	14 resolved	78 resolved
Katpadi Transit Corridor	Wards 35–40	3,120	11 resolved	52 resolved
Sathuvachari Residential Sector	Wards 41–48	2,910	9 resolved	39 resolved
Thorapadi Southern Outfalls	Wards 49–55	2,650	10 resolved	26 resolved
Western Hill Slope Tributaries	Wards 1–12	2,478	6 resolved	14 resolved
Total Corporation Summary	Wards 1–60	13,998	50 resolved	209 resolved

1. Stochastic Inefficacy of Random Maintenance: Uniform random desilting yields under 0.8% total exposure reduction even after 500 interventions. This confirms that unguided, arbitrary municipal public works assignments fail to improve urban flood resilience.
2. Failure of Non-Hydraulic Topological Heuristics: The Cascade-Only ablation strategy fails because it targets primary downstream outfall canals that possess massive tributary counts ($C_{\text{saved}} > 2,000$) but are currently flowing safely within design parameters ($U < 0.5$). Thus, coupling network topology with hydrodynamic capacity utilization is mathematically essential.
3. Convergence at Deep Maintenance Budgets: As K approaches 500 completed interventions, Severity-Only and Cascade-Aware exposure reductions begin to converge ($\approx 45.6\%$ at 80 mm/hr) as both strategies eventually exhaust the pool of critical bottlenecks. However, in real-world municipal operations where budgets are strictly constrained ($K \leq 100$), Cascade-Aware delivers up to four-fold higher operational yield.

7.5 Reachability Impact and Upstream Relief

Figure 7.3 illustrates the total count of distinct upstream conduit segments relieved ($|\bigcup_{k=1}^{K} \text{anc}(v_k)|$) across intervention steps.




Figure 7.3: Distinct Upstream Conduits Relieved Across Cleaning Interventions

Within just 50 targeted clearing actions, Cascade-Aware directly relieves between 4,412 and 4,679 distinct upstream channels across Vellore Corporation, expanding to 7,943 channels at $K = 500$ (representing 56.8% of the entire municipal drainage network).

7.6 Computational Latency and Scalability

Table 7.3 profiles the execution latency of each core algorithm within the Python analytical engine.

Table 7.3: Analytical Engine Algorithmic Runtime Profiles ($N = 13,998$)

Computational Operation	Algorithm / Mechanism	Latency
Full Network Graph Construction	DAG Topology + Elevation Chaining	142.0 ± 8.2 ms
Transitive Ancestor Reachability	Topological Sort + Bitset Popcount	18.4 ± 1.1 ms
Rational Runoff Flow Evaluation	Vectorized NumPy Array Math	1.2 ± 0.1 ms
Downstream Exposure Dynamic Program	Reverse Topological Traversal	4.6 ± 0.3 ms
Full Strategy Re-Ranking	Lexicographical Sort (np.lexsort)	2.8 ± 0.2 ms
Single Conduit State Transition	Mutex Lock + Incremental Update	0.4 ± 0.05 ms
Total Interactive Request Latency	End-to-End FastAPI /api/py/top	$\mathbf{28.2 \pm 2.4}$ ms

Because the complete analytical cycle executes in under 30 ms, municipal engineers experience zero UI lag when adjusting rainfall sliders or issuing dispatches on the live command dashboard.

7.7 Statistical Significance and Hypothesis Testing

To mathematically confirm that the superior performance of Cascade-Aware dispatch over standard Severity-Only desilting is statistically significant and not an artifact of spatial clustering, two-tailed paired Wilcoxon signed-rank tests were performed across all simulation runs. Let $d_k = \text{Resolved}_{\text{cascade}}(k) - \text{Resolved}_{\text{severity}}(k)$ represent the paired difference in at-risk drains resolved at budget step k. The null hypothesis (H_0) asserts that the median difference between the two strategy distributions is zero ($\mu_d = 0$), versus the alternative hypothesis (H_1) that Cascade-Aware yields a statistically greater median resolution ($\mu_d > 0$). Across 150 paired evaluation points spanning all three storm regimes (80, 120, and 160 mm/hr), the test yielded a test statistic $W = 11{,}245.5$ with a p-value $p < 0.0001$ ($p = 2.41 \times 10^{-14}$). Because $p \ll 0.05$, the null hypothesis is rejected at the 99.9% confidence level, confirming that Cascade-Aware prioritization provides a statistically significant, non-random improvement in municipal flood hazard mitigation.

Chapter 8

SUMMARY, CONCLUSION AND FUTURE WORK

8.1 Summary of Research Contributions

This dissertation has presented the design, implementation, and empirical validation of CivicTwin, an AI-enabled cyber-physical digital twin engineered to optimize predictive stormwater drainage resilience for the Vellore City Municipal Corporation (CMC)[cite: 74, 119]. By synthesizing geospatial information systems, hydraulic principles, complex network graph theory, and machine learning, CivicTwin addresses the systemic inefficiencies of traditional reactive municipal desilting operations[cite: 74, 83, 89, 119].

The key contributions of this research are[cite: 119]:

1. Urban Scale Drainage DAG Modeling: Successfully extracted and structured 13,998 multi-modal stormwater conduit segments from OpenStreetMap and elevation rasters into a topological Directed Acyclic Graph (DAG) comprising 22,737 directed downhill edges across 60 administrative zones[cite: 74, 83, 97, 119].
2. Bitset Reachability Engine: Developed a bitset-accelerated transitive closure algorithm over topological order that evaluates upstream ancestor reachability (C_{saved}) in under 20 milliseconds, providing real-time visibility into backwater surcharge propagation[cite: 74, 99, 113, 119].
3. Machine Learning Blockage Surrogate: Formulated and evaluated an ensemble Random Forest classifier achieving 89.4% cross-validated accuracy in predicting structural blockage vulnerability from morphometric, spatial, and topographic features[cite: 74, 104, 119].
4. Cascade-Aware Prioritization Algorithm: Formulated a multi-criteria lexicographical ranking strategy that prioritizes conduits by threat tier, upstream reachability, and local capacity utilization[cite: 74, 106, 119]. Simulation experiments across 80, 120, and 160 mm/hr storm regimes demonstrated that the proposed method resolves between 3.1x and 4.4x more over-capacity and backwater-affected conduits than conventional severity-only municipal desilting under identical maintenance budgets[cite: 74, 110, 119].

5. Full-Stack Operations Command Center: Built and deployed a production-grade web GIS command application integrating FastAPI, Node.js/Express, PostGIS, and React-Leaflet, providing civic authorities with real-time storm scenario sliders, viewport culling, and closed-loop work order audit logging[cite: 74, 92, 115, 119].

8.2 Practical Implications for Municipal Public Works

The findings of this study offer direct, actionable implications for municipal administration and urban disaster resilience[cite: 120]:

* Maximizing Return on Municipal Maintenance Budgets: Municipalities operate under stringent labor and machinery constraints[cite: 82, 106, 120]. By shifting desilting schedules from isolated blockage percentages to cascade-aware bottleneck interventions, public works departments can multiply their effective flood mitigation yield up to four-fold without increasing capital expenditures[cite: 74, 110, 120].
* Objective, Transparent Resource Allocation: Desilting crew deployment is frequently influenced by political lobbying or subjective citizen complaints[cite: 82, 120]. CivicTwin provides an empirical, data-driven prioritization framework that justifies intervention schedules through quantifiable metrics of upstream flood relief and network risk reduction[cite: 74, 120].
* Pre-Monsoon Preparedness Drills: CivicTwin enables municipal commissioners to conduct realistic virtual storm simulations weeks in advance of forecasted monsoons, identifying chronically vulnerable trunk lines and directing proactive excavation before seasonal rains commence[cite: 83, 118, 120].

8.3 Limitations of the Current Study

Notwithstanding the promising empirical results, several limitations must be acknowledged[cite: 120]:

* Hydrological Steady-State Assumption: Runoff is computed using the rational method, which assumes a steady-state peak runoff rate corresponding to a storm duration equal to the basin concentration time[cite: 87, 96, 120]. While ideal for rapid operational ranking, it does not simulate unsteady dynamic hydrograph propagation or overland 2D surface inundation depths[cite: 87, 120].

* Survey Baseline Data Granularity: Conduit silt levels outside survey zones rely on baseline dataset estimates[cite: 85, 101, 120]. Although field inspectors can override these via the administrative survey endpoint, continuous physical ground-truth monitoring across 14,000 conduits remains challenging[cite: 95, 120].
* Manual Work Order Closure: Field crew clearing completion is currently confirmed via operator input rather than automated IoT telemetry or GPS geofenced machinery tracking[cite: 120].

8.4 Future Research Directions

Future extensions of the CivicTwin platform will explore the following enhancements[cite: 121]:

1. IoT Ultrasonic Water-Level Telemetry: Integrating low-cost ultrasonic distance sensors and LoRaWAN gateways at key topological junction nodes to stream continuous water-level readings into the digital twin, replacing estimated silt baselines with live physical telemetry[cite: 121].
2. Doppler Weather Radar Integration: Connecting the simulation engine directly to India Meteorological Department (IMD) Doppler radar rainfall APIs to drive automated, spatially varied precipitation inputs across individual municipal wards rather than uniform city-wide assumptions[cite: 121].
3. Multi-Crew Vehicle Routing Optimization (VRP): Coupling the cascade-aware priority ranking with vehicle routing problem solvers (such as Google OR-Tools) to generate turn-by-turn driving routes for desilting machinery fleets, minimizing transit time between prioritized excavation sites[cite: 121].
4. Automated Drone and CCTV Sediment Inspection: Utilizing computer vision models (such as YOLOv8) deployed on municipal surveillance cameras and quadcopter drones to estimate channel sediment accumulation from visual surface imagery[cite: 121].

CHAPTER 9
REFERENCES

Ardebili Pour, M., Ghiasi, M. B., & Karkehabadi, A. (2024). Applying machine learning tools for urban resilience against floods (arXiv:2412.06205). arXiv. https://doi.org/10.48550/arXiv.2412.06205

Brucherseifer, E., Winter, H., Mentges, A., Mühlhäuser, M., & Hellmann, M. (2021). Digital Twin conceptual framework for improving critical infrastructure resilience. Automatisierungstechnik, 69(12), 1062–1080. https://doi.org/10.1515/auto-2021-0104

Colwell, M., & Abolghasemi, M. (2024). Digital twins for forecasting and decision optimisation with machine learning: Applications in wastewater treatment (arXiv:2404.14635). arXiv. https://doi.org/10.48550/arXiv.24

Dai, W., Tang, Y., Liao, N., Zou, S., & Cai, Z. (2024). Urban flood prediction using ensemble artificial neural network: An investigation on improving model uncertainty. Applied Water Science, 14, Article 144. https://doi.org/10.1007/s13201-024-02198-4

Ge, C., & Qin, S. (2025). Urban flooding digital twin system framework. Systems Science & Control Engineering, 13(1), Article 2460432. https://doi.org/10.1080/21642583.2025.2460432

Hlal, M., Al-Fuqaha, A., Ghannam, R., Qadir, J., & Erbad, A. (2025). Digital Twin technology for urban flood risk management: A systematic review of remote sensing applications and early warning systems. Remote Sensing, 17(17), Article 3104. https://doi.org/10.3390/rs17173104

Mandal, D., Zou, L., Wadhwa, A., Wilkho, R. S., Cai, Z., Zhou, B., Ye, X., Newman, G., Gharaibeh, N., & Güneralp, B. (2025). FlowsDT: A geospatial digital twin for navigating urban flood dynamics (arXiv:2507.08850). arXiv. https://doi.org/10.48550/arXiv.2507.08850

Omrany, H., Mehdipour, A., Oteng, D., & Sharifi, A. (2025). The uptake of urban digital twins in the built environment: A pathway to resilient and sustainable cities. Computational Urban Science, 5, Article 20. https://doi.org/10.1007/s43762-025-00162-8

Roudbari, N. S., Punekar, S. R., Patterson, Z., Eicker, U., & Poullis, C. (2024). From data to action in flood forecasting leveraging graph

neural networks and digital twin visualization. Scientific Reports, 14, Article 18571. https://doi.org/10.1038/s41598-024-69211-1

Temple, L., Viale Pereira, G., & Klausner, L. D. (2024). Unravelling the use of digital twins to assist decision- and policy-making in smart cities (arXiv:2405.20916). arXiv. https://doi.org/10.48550/arXiv.2405.20916

Water Research. (2025). Efficient urban flood control and drainage management framework based on digital twin technology and optimization scheduling algorithm. Water Research, 282, Article 123711. https://doi.org/10.1016/j.watres.2025.123711

Weil, C., Bibri, S. E., Longchamp, R., Golay, F., & Alahi, A. (2023). Urban Digital Twin challenges: A systematic review and perspectives for sustainable smart cities. Sustainable Cities and Society, 99, Article 104862. https://doi.org/10.1016/j.scs.2023.104862

Xu, H., Zhang, L., Wang, Y., Liu, Z., & Chen, X. (2024). Leveraging generative AI for urban digital twins: A scoping review on the autonomous generation of urban data, scenarios, designs, and 3D city models for smart city advancement. Urban Informatics, 3, Article 12. https://doi.org/10.1007/s44212-024-00060-w

Zhang, K., Deng, T., & Shen, M. (2021). A systematic review of the Digital Twin City: The new pattern of urban governance towards smart city. Journal of Management Science and Engineering, 6(4), 355–372. https://doi.org/10.1016/j.jmse.2021.09.006

Zhang, Z., Tian, W., Lu, C., Liao, Z., & Yuan, Z. (2024). Graph neural network-based surrogate modelling for real-time hydraulic prediction of urban drainage networks. Water Research, 263, Article 122142. https://doi.org/10.1016/j.watres.2024.122142

APPENDIX A: SYSTEM USER INTERFACE DEMONSTRATION

A.1 Interactive Operations Center Command View

The CivicTwin Operations Center user interface provides a single-pane spatial command view designed for municipal disaster management directors and public works supervisors. Figure 8.1 presents the primary interface layout displaying real-time synchronization between executive KPI counters, simulation controls, and the vector GIS map.




Figure 8.1: Full CivicTwin Operations Center Interface Showing GIS Map and Live KPI Counters

The primary command viewport integrates three synchronized layout modules designed for municipal decision-makers during high-stress cloudburst emergencies:

1. Top Executive KPI Banner: Computes instantaneous macro-level network indicators across all 13,998 conduit segments. The banner tracks the total count of conduits exceeding design capacity ($U > 100\%$), the count of critical surcharge segments ($U > 125\%$), active field dispatch crew counts (IN_PROGRESS vs. CLEARED), and the aggregate systemic risk exposure metric (E_{net}).
2. Left Control Sidebar: Provides real-time scenario simulation controls. Municipal supervisors can drag the storm rainfall intensity

slider between 20 and 200 mm/hr, filter dispatch priorities by 60 administrative ward clusters, switch between dispatch optimization strategies (Cascade-Aware vs. Severity-Only), and inspect active field crew assignments.

3. Central Geospatial Map Viewport: Built on top of Leaflet GIS and React 18 canvas rendering, this viewport displays vector geometries of the Vellore drainage network. Conduits are color-coded dynamically by operational threat tier (Green: Safe, Orange: High Surcharge, Red: Critical Overflow, Slate Blue: In-Progress Dispatch, Light Grey: Cleared Conduit).

A.2 Detailed Control Panel and Component Architecture

To guarantee sub-30 millisecond interface updates when municipal operators adjust simulation parameters, the user interface relies on an optimized React component hierarchy coupled with client-side canvas memory caching. Table 8.1 provides a structural breakdown of the frontend components, internal state hooks, and corresponding backend API integrations.

Table 8.1: UI Component Architecture and Backend API Mapping

UI Subsystem Module	React Component File	Internal State & Context Hooks	Backend REST API Endpoint
Executive KPI Banner	KPIHeader.jsx	useContext(EngineContext)	GET /api/py/top
Simulation Control Sidebar	SidebarControls.jsx	useState(rain), useState(ward)	GET /api/py/top?rain={i}
Geospatial Map Canvas	DrainMapCanvas.jsx	useMemo(vectorTiles), useCallback()	GET /api/drains/spatial
Priority Dispatch Table	PriorityTable.jsx	useState(topK), useOptimistic()	POST /api/py/dispatch
Active Work Order Queue	DispatchQueue.jsx	useReducer(workOrders)	POST /api/py/cleaned
Activity Audit Log	AuditLogTable.jsx	useEffect(fetchHistory)	GET /api/py/history

When an operator interacts with the precipitation slider, the client executes an asynchronous fetch request with optimistic UI updates. The slider event triggers a debounced handler (150 ms window) to prevent API flooding during continuous drag events. A parameterized request is dispatched to /api/py/top, updating the global store, KPI cards, vector tile styles, and top-k dispatch recommendations simultaneously.

A.3 Priority Dispatch Queue and Structural Overload Metrics

Figure 8.2 shows the priority dispatch queue where municipal operators inspect conduit IDs, physical structures, surveyed silt levels, and intuitive capacity utilization bars with diagonal striped overflow patterns.




Figure 8.2: Priority Drains Table Showing Surcharge Ratios, Upstream Cascade Reachability, and Dispatch Actions

To bridge complex hydrodynamic calculations with practical field deployment, the Priority Drains Table translates mathematical outputs into intuitive visual cues:

* Capacity Utilization Bar: Rather than displaying abstract volumetric flow numbers (m^3/s), the table renders a dynamic percentage bar. For conduits exceeding 100% capacity, a diagonal striped warning pattern visually represents excess surface surcharge (e.g., "218% — 118% more water than channel capacity").
* Cascade Saved Metric (C_{saved}): Displays the exact count of upstream tributary channels that benefit from desilting the selected conduit (e.g., "1,320 upstream drains relieved"), providing immediate, transparent justification for why a specific channel is prioritized over others.
* One-Click Action Button: Clicking Dispatch immediately locks the conduit, assigns it to a field maintenance crew, and automatically backfills the table with the next highest-priority open bottleneck from the network.

A.4 Operational Activity Audit Trail and Interpretation Guidelines

Figure 8.3 illustrates the recent activity audit logging panel, showing immutable records of field dispatches, cleaning completions, upstream cascade reliefs, and quantitative network risk deltas.




Figure 8.3: Activity Audit Log and Administrative Metric Interpretation Guidelines

The lower dashboard panel maintains a closed-loop transaction ledger recording every operational state change executed during the active management session. Table 8.2 details the data fields recorded in the immutable audit trail (civictwin_dispatch_history.csv), which can be exported via the Download History CSV interface button for municipal administrative review and contractor invoicing.

This closed-loop logging framework ensures complete transparency, preventing fraudulent work order reporting while providing quantitative verification of municipal flood mitigation progress.

Table 8.2: Operational Audit Trail Data Fields and Administrative Utility

Data Field Name	Data Type	Operational Administrative Purpose
timestamp	ISO-8601 String	Precise execution timestamp for contractor shift verification.
drain_id	String ID	Unique OpenStreetMap conduit way identifier.
action_type	Categorical	Action status (DISPATCHED, CLEARED, SURVEY_UPDATE).
ward_number	Integer (1–60)	Administrative zone identification for municipal ward reporting.
pre_silt_pct	Float (%)	Baseline surveyed sediment blockage prior to excavation.
post_silt_pct	Float (%)	Post-intervention residual sediment blockage (reset to 5.0%).
cascade_relieved	Integer	Upstream tributary channels freed from backwater surcharge.
net_risk_before	Float	Systemic network exposure score (E_{net}) prior to action.
net_risk_after	Float	Systemic network exposure score (E_{net}) post-action.
risk_delta	Float	Absolute quantitative systemic risk reduction achieved (ΔE_{net}).

APPENDIX B: CORE MATHEMATICAL ALGORITHMS

Algorithm 4 Bitset Ancestor Reachability over Topological Order

Require: Directed Acyclic Graph $G = (V, E)$, $|V| = n$
Ensure: Array $C_{\text{saved}}[0 \dots n-1]$ containing count of upstream ancestors

Compute topological sort order $\tau = (\tau_1, \tau_2, \dots, \tau_n)$ of G using Kahn's algorithm or DFS
Initialize array of bitsets $M[0 \dots n-1]$ with all bits set to 0
for all $v \in \tau$ do
    $mask \leftarrow 0$
    for all $p \in$ predecessors(v) do
        $mask \leftarrow mask \vee M[p] \vee (1 \ll p)$ {Bitwise OR operation}
    end for
    $M[v] \leftarrow mask$
    $C_{\text{saved}}[v] \leftarrow$ popcount$(M[v])$ {Count number of 1-bits}
end for
return C_{saved}

Algorithm 5 Dynamic Programming for Systemic Network Risk Exposure

Require: Directed Acyclic Graph $G = (V, E)$, topological order τ, capacity utilisation array $U[0 \dots n-1]$
Ensure: Total systemic network risk exposure E_{net}

Initialize array $D[0 \dots n-1]$ where $D[v] \leftarrow U[v] \times 100$ for all $v \in V$
for all v in reverse of τ do
    {Traverse from outfalls up to headwaters}
    for all $s \in$ successors(v) do
        if $D[s] > D[v]$ then
            $D[v] \leftarrow D[s]$
        end if
    end for
end for
$E_{\text{net}} \leftarrow \sum_{v \in V} D[v]$
return E_{net}

Algorithm 6 Cascade-Aware Priority Dispatch and Queue Management

Require: Conduits V, status array S, rain i, ward filter w, budget K
Ensure: Top-K ranked conduits for dispatch

Compute rational runoff flow $Q[v] = C[v] \cdot i \cdot A[v]/3.6 \times 10^{6}$ for all $v \in V$
Compute available capacity $Q_{\text{avail}}[v] = Q_{\text{design}}[v] \cdot \max(1 - \text{silt}[v]/100, 0.05)$
Compute utilization $U[v] = \min(3.0, Q[v]/Q_{\text{avail}}[v])$
Classify threat tier $T[v] \leftarrow 2$ if $U[v] > 1.25$ else (1 if $U[v] > 0.80$ else 0)
Filter candidates: $Cand \leftarrow \{v \in V \mid S[v] == \text{OPEN}$ and v is rankable$\}$
if w is not NULL then
    $Cand \leftarrow \{v \in Cand \mid \text{ward}[v] == w\}$
end if
Sort $Cand$ lexicographically by: $(-T[v], -C_{\text{saved}}[v], -U[v], v)$
return First K elements of $Cand$

APPENDIX C: DATABASE DDL AND API SPECIFICATIONS

C.1 Complete PostgreSQL / PostGIS Spatial Database DDL

The CivicTwin spatial persistence tier utilizes PostgreSQL 15 with the PostGIS 3.3 geospatial extension. Listing C.1 details the schema definition, spatial GiST indexing, and attribute constraints.

Listing 8.1: PostgreSQL 15 / PostGIS 3.3 DDL Schema for Drainage Network Infrastructure

```
-- Enable PostGIS Extension
CREATE EXTENSION IF NOT EXISTS postgis;

-- 1. Primary Drain Conduits Table
CREATE TABLE IF NOT EXISTS drain_conduits (
    drain_id VARCHAR(64) PRIMARY KEY,
    ward_number INTEGER NOT NULL CHECK (ward_number
        BETWEEN 1 AND 60),
    drain_type VARCHAR(32) NOT NULL DEFAULT 'Open
        Concrete',
    width_m NUMERIC(5, 2) NOT NULL DEFAULT 1.50,
    depth_m NUMERIC(5, 2) NOT NULL DEFAULT 1.20,
    elevation_m NUMERIC(6, 2) NOT NULL,
    slope_pct NUMERIC(5, 2) NOT NULL DEFAULT 0.50,
    topographic_wetness_index NUMERIC(5, 2) DEFAULT
        8.00,
    design_capacity_m3s NUMERIC(6, 3) NOT NULL DEFAULT
         1.000,
    runoff_coefficient NUMERIC(4, 2) NOT NULL DEFAULT
        0.70,
    blockage_ratio NUMERIC(4, 3) NOT NULL DEFAULT
        0.000 CHECK (blockage_ratio BETWEEN 0.0 AND
        1.0),
    start_node_id BIGINT,
    end_node_id BIGINT,
    geom GEOMETRY(LineString, 4326) NOT NULL
);
```

```
21
22 -- Spatial GiST Index for Bounding-Box Viewport
       Filtering
23 CREATE INDEX IF NOT EXISTS idx_drain_conduits_geom
24     ON drain_conduits USING GIST (geom);
25
26 -- B-Tree Attribute Indexes for Zone Filtering
27 CREATE INDEX IF NOT EXISTS idx_drain_conduits_ward
28     ON drain_conduits (ward_number);
29
30 -- 2. Field Desilting Audit Trail Log Table
31 CREATE TABLE IF NOT EXISTS audit_dispatch_log (
32     log_id BIGSERIAL PRIMARY KEY,
33     timestamp TIMESTAMP WITH TIME ZONE DEFAULT
           CURRENT_TIMESTAMP,
34     drain_id VARCHAR(64) REFERENCES drain_conduits(
           drain_id),
35     action_type VARCHAR(32) NOT NULL,
36     ward_number INTEGER NOT NULL,
37     pre_silt_pct NUMERIC(5,2) NOT NULL,
38     post_silt_pct NUMERIC(5,2) NOT NULL,
39     cascade_relieved INTEGER NOT NULL,
40     net_risk_before NUMERIC(12,2) NOT NULL,
41     net_risk_after NUMERIC(12,2) NOT NULL,
42     risk_delta NUMERIC(10,2) NOT NULL
43 );
```

C.2 Core FastAPI Analytical Engine Endpoint Schemas

Listing C.2 presents the Pydantic data validation schemas managing JSON serialization across backend API routes.

Listing 8.2: Pydantic Data Models for API Serialization

```
1 from pydantic import BaseModel, Field
2 from typing import List, Optional
3
4 class DrainItemResponse(BaseModel):
5     segment_id: str = Field(..., description="Unique
          OpenStreetMap conduit way ID")
6     rank: Optional[int] = Field(None, description="
          Ordinal priority rank in dispatch queue")
```

```
    ward_number: int = Field(..., ge=1, le=60,
        description="Municipal administrative zone")
    drain_type: str = Field(..., description="
        Structural classification typology")
    silt_pct: float = Field(..., ge=0.0, le=100.0,
        description="Surveyed silt percentage")
    util_pct: int = Field(..., description="Capacity
        utilization percentage at current rainfall")
    threat: int = Field(..., description="Categorical
        threat tier (0: Low, 1: High, 2: Critical)")
    cascade_saved: int = Field(..., description="
        Upstream ancestor channel count relieved")
    status: str = Field(..., description="Operational
        state: OPEN, IN_PROGRESS, or CLEARED")
    path: List[List[float]] = Field(..., description="
        LineString coordinate polyline array")
    center: Optional[List[float]] = Field(None,
        description="Centroid geographic coordinates")
    has_geometry: bool = Field(True, description="
        Geospatial geometry validity flag")

class SimulationKPIs(BaseModel):
    blocked_ge_50: int = Field(..., description="Count
         of conduits with >= 50% silt blockage")
    over_capacity: int = Field(..., description="Count
         of conduits with utilization > 100%")
    critical: int = Field(..., description="Count of
        conduits with utilization > 125%")
    open: int = Field(..., description="Count of
        unassigned open conduits")
    in_progress: int = Field(..., description="Count
        of conduits currently dispatched")
    cleared: int = Field(..., description="Count of
        completed desilting interventions")

class TopDrainsResponse(BaseModel):
    items: List[DrainItemResponse] = Field(...,
        description="Top-k recommended dispatch list")
    queue: List[DrainItemResponse] = Field(...,
        description="Active in-progress dispatch queue"
        )
```

```
29      remaining_open: int = Field(..., description="
            Count of open candidate conduits")
30      kpis: SimulationKPIs = Field(..., description="
            Macro network health indicator metrics")
31      network_risk: float = Field(..., description="
            Aggregate systemic network risk exposure score"
            )
32      rainfall_mmhr: float = Field(..., description="
            Active precipitation intensity scenario")
33      ward: Optional[int] = Field(None, description="
            Filtered administrative zone cluster")
34      strategy: str = Field(..., description="Active
            prioritization ranking strategy")
35      run_id: str = Field(..., description="Unique
            session execution identifier")
```