SELECT track AS "Номер", CASE WHEN finished THEN 2 WHEN cancelled THEN -1 WHEN "inDelivery" THEN 1 ELSE 0 END AS "Статус" FROM "Orders";

```
Elena@LAPTOP-864MBMMO ~
$ ssh f42005da-8df1-4f83-97ca-06fc318c1dbf@serverhub.praktikum-services.ru -p 4554
morty@3635b127acbe:~$ psql -U morty -d scooter_rent
Password for user morty:
psql (11.18 (Debian 11.18-0+deb10u1))
Type "help" for help.

scooter_rent=# SELECT track AS "Номер", CASE WHEN finished THEN 2 WHEN cancelled THEN -1 WHEN
 "inDelivery" THEN 1 ELSE 0 END AS "Статус" FROM "Orders";
 Номер  | Статус
--------+--------
  26091 |      0
 136412 |      0
 532819 |      0
 135640 |      0
 246808 |     -1
 545847 |      1
 161413 |      1
 161413 |      1
 377440 |      1
 377440 |      1
 991470 |      1
 991470 |      1
 949677 |      1
 949677 |      1
 545847 |      2
 639311 |     -1
 138081 |      1
 197777 |     -1
 978295 |      1
 937605 |      1
 937605 |      1
 138081 |      2
 978295 |      2
 117831 |     -1
(24 rows)

scooter_rent=#
```