ROCmSMI

Generated by Doxygen 1.8.13

Contents

1 ROCm System Management Interface (ROCm SMI) Library **1**

2 Module Index **5**

2.1 Modules 5

3 Data Structure Index **7**

3.1 Data Structures 7

4 File Index **9**

4.1 File List 9

5 Module Documentation **11**

5.1 Initialization and Shutdown 11

5.1.1 Detailed Description 11

5.1.2 Function Documentation 11

5.1.2.1 rsmi_init() 11

5.1.2.2 rsmi_shut_down() 12

5.2 Identifier Queries 13

5.2.1 Detailed Description 13

5.2.2 Function Documentation 13

5.2.2.1 rsmi_num_monitor_devices() 13

5.2.2.2 rsmi_dev_id_get() 14

5.2.2.3 rsmi_dev_vendor_id_get() 14

5.2.2.4 rsmi_dev_name_get() 15

5.2.2.5 rsmi_dev_vendor_name_get() 15

5.2.2.6 rsmi_dev_subsystem_id_get() . . . 16
5.2.2.7 rsmi_dev_subsystem_name_get() . . . 16
5.2.2.8 rsmi_dev_subsystem_vendor_id_get() . . . 17
5.2.2.9 rsmi_dev_unique_id_get() . . . 17
5.3 PCIe Queries . . . 18
5.3.1 Detailed Description . . . 18
5.3.2 Function Documentation . . . 18
5.3.2.1 rsmi_dev_pci_bandwidth_get() . . . 18
5.3.2.2 rsmi_dev_pci_id_get() . . . 19
5.3.2.3 rsmi_dev_pci_throughput_get() . . . 19
5.3.2.4 rsmi_dev_pci_replay_counter_get() . . . 20
5.4 PCIe Control . . . 21
5.4.1 Detailed Description . . . 21
5.4.2 Function Documentation . . . 21
5.4.2.1 rsmi_dev_pci_bandwidth_set() . . . 21
5.5 Power Queries . . . 22
5.5.1 Detailed Description . . . 22
5.5.2 Function Documentation . . . 22
5.5.2.1 rsmi_dev_power_ave_get() . . . 22
5.5.2.2 rsmi_dev_power_cap_get() . . . 23
5.5.2.3 rsmi_dev_power_cap_range_get() . . . 23
5.6 Power Control . . . 24
5.6.1 Detailed Description . . . 24
5.6.2 Function Documentation . . . 24
5.6.2.1 rsmi_dev_power_cap_set() . . . 24
5.6.2.2 rsmi_dev_power_profile_set() . . . 24
5.7 Memory Queries . . . 26
5.7.1 Detailed Description . . . 26
5.7.2 Function Documentation . . . 26
5.7.2.1 rsmi_dev_memory_total_get() . . . 26

5.7.2.2 rsmi_dev_memory_usage_get() . . . 26
5.8 Physical State Queries . . . 28
5.8.1 Detailed Description . . . 28
5.8.2 Function Documentation . . . 28
5.8.2.1 rsmi_dev_fan_rpms_get() . . . 28
5.8.2.2 rsmi_dev_fan_speed_get() . . . 29
5.8.2.3 rsmi_dev_fan_speed_max_get() . . . 29
5.8.2.4 rsmi_dev_temp_metric_get() . . . 30
5.9 Physical State Control . . . 31
5.9.1 Detailed Description . . . 31
5.9.2 Function Documentation . . . 31
5.9.2.1 rsmi_dev_fan_reset() . . . 31
5.9.2.2 rsmi_dev_fan_speed_set() . . . 31
5.10 Clock, Power and Performance Queries . . . 33
5.10.1 Detailed Description . . . 33
5.10.2 Function Documentation . . . 33
5.10.2.1 rsmi_dev_busy_percent_get() . . . 33
5.10.2.2 rsmi_dev_perf_level_get() . . . 34
5.10.2.3 rsmi_dev_overdrive_level_get() . . . 34
5.10.2.4 rsmi_dev_gpu_clk_freq_get() . . . 35
5.10.2.5 rsmi_dev_od_volt_info_get() . . . 35
5.10.2.6 rsmi_dev_od_volt_curve_regions_get() . . . 36
5.10.2.7 rsmi_dev_power_profile_presets_get() . . . 36
5.11 Clock, Power and Performance Control . . . 38
5.11.1 Detailed Description . . . 38
5.11.2 Function Documentation . . . 38
5.11.2.1 rsmi_dev_perf_level_set() . . . 38
5.11.2.2 rsmi_dev_overdrive_level_set() . . . 39
5.11.2.3 rsmi_dev_gpu_clk_freq_set() . . . 39
5.11.2.4 rsmi_dev_od_freq_range_set() . . . 40
5.12 Version Queries . . . 41
5.12.1 Detailed Description . . . 41
5.12.2 Function Documentation . . . 41
5.12.2.1 rsmi_version_get() . . . 41
5.12.2.2 rsmi_version_str_get() . . . 41
5.12.2.3 rsmi_dev_vbios_version_get() . . . 42
5.13 Error Queries . . . 43
5.13.1 Detailed Description . . . 43
5.13.2 Function Documentation . . . 43
5.13.2.1 rsmi_dev_ecc_count_get() . . . 43
5.13.2.2 rsmi_dev_ecc_enabled_get() . . . 44
5.13.2.3 rsmi_dev_ecc_status_get() . . . 44
5.13.2.4 rsmi_status_string() . . . 45

6 Data Structure Documentation **47**

6.1 rsmi_error_count_t Struct Reference . . . 47
6.1.1 Detailed Description . . . 47
6.2 rsmi_freq_volt_region_t Struct Reference . . . 47
6.2.1 Detailed Description . . . 48
6.3 rsmi_frequencies_t Struct Reference . . . 48
6.3.1 Detailed Description . . . 48
6.3.2 Field Documentation . . . 48
6.3.2.1 num_supported . . . 48
6.3.2.2 current . . . 49
6.3.2.3 frequency . . . 49
6.4 rsmi_od_vddc_point_t Struct Reference . . . 49
6.4.1 Detailed Description . . . 49
6.5 rsmi_od_volt_curve_t Struct Reference . . . 49
6.5.1 Detailed Description . . . 50
6.5.2 Field Documentation . . . 50
6.5.2.1 vc_points . . . 50
6.6 rsmi_od_volt_freq_data_t Struct Reference . . . 50
6.6.1 Detailed Description . . . 50
6.6.2 Field Documentation . . . 51
6.6.2.1 curr_mclk_range . . . 51
6.7 rsmi_pcie_bandwidth_t Struct Reference . . . 51
6.7.1 Detailed Description . . . 51
6.7.2 Field Documentation . . . 51
6.7.2.1 transfer_rate . . . 51
6.7.2.2 lanes . . . 52
6.8 rsmi_power_profile_status_t Struct Reference . . . 52
6.8.1 Detailed Description . . . 52
6.8.2 Field Documentation . . . 52
6.8.2.1 available_profiles . . . 52
6.8.2.2 current . . . 52
6.8.2.3 num_profiles . . . 53
6.9 rsmi_range_t Struct Reference . . . 53
6.9.1 Detailed Description . . . 53
6.10 rsmi_version_t Struct Reference . . . 53
6.10.1 Detailed Description . . . 53

7 File Documentation **55**

7.1 rocm_smi.h File Reference 55

7.1.1 Detailed Description 59

7.1.2 Macro Definition Documentation 60

7.1.2.1 RSMI_MAX_FAN_SPEED 60

7.1.3 Enumeration Type Documentation 60

7.1.3.1 rsmi_status_t 60

7.1.3.2 rsmi_init_flags_t 60

7.1.3.3 rsmi_dev_perf_level_t 61

7.1.3.4 rsmi_sw_component_t 61

7.1.3.5 rsmi_clk_type_t 62

7.1.3.6 rsmi_temperature_metric_t 62

7.1.3.7 rsmi_temperature_type_t 63

7.1.3.8 rsmi_power_profile_preset_masks_t 63

7.1.3.9 rsmi_gpu_block_t 63

7.1.3.10 rsmi_ras_err_state_t 64

7.1.3.11 rsmi_memory_type_t 64

7.1.3.12 rsmi_freq_ind_t 64

Index **65**

Chapter 1

ROCm System Management Interface (ROCm SMI) Library

The ROCm System Management Interface Library, or ROCm SMI library, is part of the Radeon Open Compute ROCm software stack . It is a C library for Linux that provides a user space interface for applications to monitor and control GPU applications.

Important note about Versioning and Backward Compatibility

The ROCm SMI library is currently under development, and therefore subject to change either at the ABI or API level. The intention is to keep the API as stable as possible even while in development, but in some cases we may need to break backwards compatibility in order to ensure future stability and usability. Following Semantic Versioning rules, while the ROCm SMI library is in high state of change, the major version will remain 0, and backward compatibility is not ensured.

Once new development has leveled off, the major version will become greater than 0, and backward compatibility will be enforced between major versions.

Building ROCm SMI

Additional Required software for building

In order to build the ROCm SMI library, the following components are required. Note that the software versions listed are what was used in development. Earlier versions are not guaranteed to work:

- CMake (v3.5.0)
- g++ (5.4.0)

In order to build the latest documentation, the following are required:

- DOxygen (1.8.11)
- latex (pdfTeX 3.14159265-2.6-1.40.16)

The source code for ROCm SMI is available on Github.

After the the ROCm SMI library git repository has been cloned to a local Linux machine, building the library is achieved by following the typical CMake build sequence. Specifically,

```
$ mk -p build

$ cd build

$ cmake <location of root of ROCm SMI library CMakeLists.txt>

$ make
```

The built library will appear in the `build` folder.

Building the Documentation

The documentation PDF file can be built with the following steps (continued from the steps above):

```
$ make doc

$ cd latex

$ make
```

The reference manual, `refman.pdf` will be in the `latex` directory upon a successful build.

Building the Tests

In order to verify the build and capability of ROCm SMI on your system and to see an example of how ROCm SMI can be used, you may build and run the tests that are available in the repo. To build the tests, follow these steps:

```
# Set environment variables used in CMakeLists.txt file

$ ROCM_DIR=<location of ROCm SMI library>

$ mkdir <location for test build>

$ cd <location for test build>

$ cmake -DROCM_DIR=<location of ROCM SMI library .so> <ROCm SMI source root>/tests/rocm
_smi_test
```

To run the test, execute the program `rsmitst` that is built from the steps above. Make sure ROCm SMI library is in your library search path when executing the test program.

Usage Basics

Device Indices

Many of the functions in the library take a "device index". The device index is a number greater than or equal to 0, and less than the number of devices detected, as determined by `rsmi_num_monitor_devices()`. The index is used to distinguish the detected devices from one another. It is important to note that a device may end up with a different index after a reboot, so an index should not be relied upon to be constant over reboots.

Hello ROCm SMI

The only required ROCm-SMI call for any program that wants to use ROCm-SMI is the `rsmi_init()` call. This call initializes some internal data structures that will be used by subsequent ROCm-SMI calls.

When ROCm-SMI is no longer being used, `rsmi_shut_down()` should be called. This provides a way to do any releasing of resources that ROCm-SMI may have held. In many cases, this may have no effect, but may be necessary in future versions of the library.

A simple "Hello World" type program that displays the device ID of detected devices would look like this:

```
#include <stdint.h>
#include "rocm_smi/rocm_smi.h"
int main() {
  rsmi_status_t ret;
  uint32_t num_devices;
  uint64_t dev_id;

  // We will skip return code checks for this example, but it
  // is recommended to always check this as some calls may not
  // apply for some devices or ROCm releases

  ret = rsmi_init(0);
  ret = rsmi_num_monitor_devices(&num_devices);

  for (int i=0; i < num_devices; ++i) {
    ret = rsmi_dev_id_get(i, &dev_id);
    // dev_id holds the device ID of device i, upon a
    // successful call
  }
  ret = rsmi_shut_down();
  return 0;
}
```

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Initialization and Shutdown 11
Identifier Queries 13
PCIe Queries 18
PCIe Control 21
Power Queries 22
Power Control 24
Memory Queries 26
Physical State Queries 28
Physical State Control 31
Clock, Power and Performance Queries 33
Clock, Power and Performance Control 38
Version Queries 41
Error Queries 43

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

rsmi_error_count_t
: This structure holds error counts . . . 47

rsmi_freq_volt_region_t
: This structure holds 2 rsmi_range_t's, one for frequency and one for voltage. These 2 ranges indicate the range of possible values for the corresponding rsmi_od_vddc_point_t . . . 47

rsmi_frequencies_t
: This structure holds information about clock frequencies . . . 48

rsmi_od_vddc_point_t
: This structure represents a point on the frequency-voltage plane . . . 49

rsmi_od_volt_curve_t . . . 49

rsmi_od_volt_freq_data_t
: This structure holds the frequency-voltage values for a device . . . 50

rsmi_pcie_bandwidth_t
: This structure holds information about the possible PCIe bandwidths. Specifically, the possible transfer rates and their associated numbers of lanes are stored here . . . 51

rsmi_power_profile_status_t
: This structure contains information about which power profiles are supported by the system for a given device, and which power profile is currently active . . . 52

rsmi_range_t
: This structure represents a range (e.g., frequencies or voltages) . . . 53

rsmi_version_t
: This structure holds version information . . . 53

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

rocm_smi.h
The rocm_smi library api is new, and therefore subject to change either at the ABI or API level. Instead of marking every function prototype as "unstable", we are instead saying the API is unstable (i.e., changes are possible) while the major version remains 0. This means that if the API/ABI changes, we will not increment the major version to 1. Once the ABI stabilizes, we will increment the major version to 1, and thereafter increment it on all ABI breaks 55

Chapter 5

Module Documentation

5.1 Initialization and Shutdown

Functions

- rsmi_status_t rsmi_init (uint64_t init_flags)

  Initialize ROCm SMI.
- rsmi_status_t rsmi_shut_down (void)

  Shutdown ROCm SMI.

5.1.1 Detailed Description

These functions are used for initialization of ROCm SMI and clean up when done.

5.1.2 Function Documentation

5.1.2.1 rsmi_init()

```
rsmi_status_t rsmi_init (
            uint64_t init_flags )
```

Initialize ROCm SMI.

When called, this initializes internal data structures, including those corresponding to sources of information that SMI provides.

Parameters

in	*init_flags*	Bit flags that tell SMI how to initialze. Values of rsmi_init_flags_t may be OR'd together and passed through `init_flags` to modify how RSMI initializes.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.1.2.2 rsmi_shut_down()

```
rsmi_status_t rsmi_shut_down (
            void  )
```

Shutdown ROCm SMI.

Do any necessary clean up.

5.2 Identifier Queries

Functions

- rsmi_status_t rsmi_num_monitor_devices (uint32_t *num_devices)
  Get the number of devices that have monitor information.
- rsmi_status_t rsmi_dev_id_get (uint32_t dv_ind, uint16_t *id)
  Get the device id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_vendor_id_get (uint32_t dv_ind, uint16_t *id)
  Get the device vendor id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_name_get (uint32_t dv_ind, char *name, size_t len)
  Get the name string of a gpu device.
- rsmi_status_t rsmi_dev_vendor_name_get (uint32_t id, char *name, size_t len)
  Get the name string for a give vendor ID.
- rsmi_status_t rsmi_dev_subsystem_id_get (uint32_t dv_ind, uint16_t *id)
  Get the subsystem device id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_subsystem_name_get (uint32_t dv_ind, char *name, size_t len)
  Get the name string for the device subsytem.
- rsmi_status_t rsmi_dev_subsystem_vendor_id_get (uint32_t dv_ind, uint16_t *id)
  Get the device subsystem vendor id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_unique_id_get (uint32_t dv_ind, uint64_t *id)
  Get Unique ID.

5.2.1 Detailed Description

These functions provide identification information.

5.2.2 Function Documentation

5.2.2.1 rsmi_num_monitor_devices()

```
rsmi_status_t rsmi_num_monitor_devices (
            uint32_t * num_devices )
```

Get the number of devices that have monitor information.

The number of devices which have monitors is returned. Monitors are referenced by the index which can be between 0 and `num_devices` - 1.

Parameters

`in,out`	*num_devices*	Caller provided pointer to uint32_t. Upon successful call, the value num_devices will contain the number of monitor devices.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.2.2.2 rsmi_dev_id_get()

```
rsmi_status_t rsmi_dev_id_get (
            uint32_t dv_ind,
            uint16_t * id )
```

Get the device id associated with the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `id`, this function will write the device id value to the uint64_t pointed to by `id`. This ID is an identification of the type of device, so calling this function for different devices will give the same value if they are kind of device. Consequently, this function should not be used to distinguish one device from another. rsmi_dev_pci_id_get() should be used to get a unique identifier.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*id*	a pointer to uint64_t to which the device id will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.2.2.3 rsmi_dev_vendor_id_get()

```
rsmi_status_t rsmi_dev_vendor_id_get (
            uint32_t dv_ind,
            uint16_t * id )
```

Get the device vendor id associated with the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `id`, this function will write the device vendor id value to the uint64_t pointed to by `id`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*id*	a pointer to uint64_t to which the device vendor id will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.2.2.4 rsmi_dev_name_get()

```
rsmi_status_t rsmi_dev_name_get (
            uint32_t dv_ind,
            char * name,
            size_t len )
```

Get the name string of a gpu device.

Given a device index `dv_ind`, a pointer to a caller provided char buffer `name`, and a length of this buffer `len`, this function will write the name of the device (up to `len` characters) to the buffer `name`.

If the integer ID associated with the device is not found in one of the system files containing device name information (e.g. /usr/share/misc/pci.ids), then this function will return the hex device ID as a string. Updating the system name files can be accompplished with "sudo update-pciids".

Parameters

`in`	*dv_ind*	a device index
`in,out`	*name*	a pointer to a caller provided char buffer to which the name will be written
`in`	*len*	the length of the caller provided buffer `name`.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.
RSMI_STATUS_INSUFFICIENT_SIZE	is returned if `len` bytes is not large enough to hold the entire name. In this case, only `len` bytes will be written.

5.2.2.5 rsmi_dev_vendor_name_get()

```
rsmi_status_t rsmi_dev_vendor_name_get (
            uint32_t id,
            char * name,
            size_t len )
```

Get the name string for a give vendor ID.

Given vendor ID `id`, a pointer to a caller provided char buffer `name`, and a length of this buffer `len`, this function will write the name of the vendor (up to `len` characters) buffer `name`. The `id` may be a device vendor or subsystem vendor ID.

If the integer ID associated with the vendor is not found in one of the system files containing device name information (e.g. /usr/share/misc/pci.ids), then this function will return the hex vendor ID as a string. Updating the system name files can be accompplished with "sudo update-pciids".

Parameters

`in`	*id*	a vendor ID
`in,out`	*name*	a pointer to a caller provided char buffer to which the name will be written
`in`	*len*	the length of the caller provided buffer `name`.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.
RSMI_STATUS_INSUFFICIENT_SIZE	is returned if `len` bytes is not large enough to hold the entire name. In this case, only `len` bytes will be written.

5.2.2.6 rsmi_dev_subsystem_id_get()

```
rsmi_status_t rsmi_dev_subsystem_id_get (
            uint32_t dv_ind,
            uint16_t * id )
```

Get the subsystem device id associated with the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `id`, this function will write the subsystem device id value to the uint64_t pointed to by `id`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*id*	a pointer to uint64_t to which the subsystem device id will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.2.2.7 rsmi_dev_subsystem_name_get()

```
rsmi_status_t rsmi_dev_subsystem_name_get (
            uint32_t dv_ind,
            char * name,
            size_t len )
```

Get the name string for the device subsytem.

Given a device index `dv_ind`, a pointer to a caller provided char buffer `name`, and a length of this buffer `len`, this function will write the name of the device subsystem (up to `len` characters) to the buffer `name`.

If the integer ID associated with the sub-system is not found in one of the system files containing device name information (e.g. /usr/share/misc/pci.ids), then this function will return the hex sub-system ID as a string. Updating the system name files can be accompplished with "sudo update-pciids".

Parameters

`in`	*dv_ind*	a device index
`in,out`	*name*	a pointer to a caller provided char buffer to which the name will be written
`in`	*len*	the length of the caller provided buffer `name`.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.
RSMI_STATUS_INSUFFICIENT_SIZE	is returned if `len` bytes is not large enough to hold the entire name. In this case, only `len` bytes will be written.

5.2.2.8 rsmi_dev_subsystem_vendor_id_get()

```
rsmi_status_t rsmi_dev_subsystem_vendor_id_get (
            uint32_t dv_ind,
            uint16_t * id )
```

Get the device subsystem vendor id associated with the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `id`, this function will write the device subsystem vendor id value to the uint64_t pointed to by `id`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*id*	a pointer to uint64_t to which the device subsystem vendor id will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.2.2.9 rsmi_dev_unique_id_get()

```
rsmi_status_t rsmi_dev_unique_id_get (
            uint32_t dv_ind,
            uint64_t * id )
```

Get Unique ID.

Given a device index `dv_ind` and a pointer to a uint64_t `id`, this function will write the unique ID of the GPU pointed to `id`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*id*	a pointer to uint64_t to which the unique ID of the GPU is written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.3 PCIe Queries

Functions

- rsmi_status_t rsmi_dev_pci_bandwidth_get (uint32_t dv_ind, rsmi_pcie_bandwidth_t *bandwidth)

  Get the list of possible PCIe bandwidths that are available.
- rsmi_status_t rsmi_dev_pci_id_get (uint32_t dv_ind, uint64_t *bdfid)

  Get the unique PCI device identifier associated for a device.
- rsmi_status_t rsmi_dev_pci_throughput_get (uint32_t dv_ind, uint64_t *sent, uint64_t *received, uint64_t *max_pkt_sz)

  Get PCIe traffic information.
- rsmi_status_t rsmi_dev_pci_replay_counter_get (uint32_t dv_ind, uint64_t *counter)

  Get PCIe replay counter.

5.3.1 Detailed Description

These functions provide information about PCIe.

5.3.2 Function Documentation

5.3.2.1 rsmi_dev_pci_bandwidth_get()

```
rsmi_status_t rsmi_dev_pci_bandwidth_get (
            uint32_t dv_ind,
            rsmi_pcie_bandwidth_t * bandwidth )
```

Get the list of possible PCIe bandwidths that are available.

Given a device index `dv_ind` and a pointer to a to an rsmi_pcie_bandwidth_t structure `bandwidth`, this function will fill in `bandwidth` with the possible T/s values and associated number of lanes, and indication of the current selection.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*bandwidth*	a pointer to a caller provided rsmi_pcie_bandwidth_t structure to which the frequency information will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.3.2.2 rsmi_dev_pci_id_get()

```
rsmi_status_t rsmi_dev_pci_id_get (
              uint32_t dv_ind,
              uint64_t * bdfid )
```

Get the unique PCI device identifier associated for a device.

Give a device index `dv_ind` and a pointer to a uint64_t `bdfid`, this function will write the Bus/Device/Function PCI identifier (BDFID) associated with device `dv_ind` to the value pointed to by `bdfid`.

Parameters

in	*dv_ind*	a device index
in,out	*bdfid*	a pointer to uint64_t to which the device bdfid value will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.3.2.3 rsmi_dev_pci_throughput_get()

```
rsmi_status_t rsmi_dev_pci_throughput_get (
              uint32_t dv_ind,
              uint64_t * sent,
              uint64_t * received,
              uint64_t * max_pkt_sz )
```

Get PCIe traffic information.

Give a device index `dv_ind` and pointers to a uint64_t's, `sent`, `received` and `max_pkt_sz`, this function will write the number of bytes sent and received in 1 second to `sent` and `received`, respectively. The maximum possible packet size will be written to `max_pkt_sz`.

Parameters

in	*dv_ind*	a device index
in,out	*sent*	a pointer to uint64_t to which the number of bytes sent will be written in 1 second. If pointer is NULL, it will be ignored.
in,out	*received*	a pointer to uint64_t to which the number of bytes received will be written. If pointer is NULL, it will be ignored.
in,out	*max_pkt_sz*	a pointer to uint64_t to which the maximum packet size will be written. If pointer is NULL, it will be ignored.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.3.2.4 rsmi_dev_pci_replay_counter_get()

```
rsmi_status_t rsmi_dev_pci_replay_counter_get (
            uint32_t dv_ind,
            uint64_t * counter )
```

Get PCIe replay counter.

Given a device index `dv_ind` and a pointer to a uint64_t `counter`, this function will write the sum of the number of NAK's received by the GPU and the NAK's generated by the GPU to memory pointed to by `counter`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*counter*	a pointer to uint64_t to which the sum of the NAK's received and generated by the GPU is written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.4 PCIe Control

Functions

- rsmi_status_t rsmi_dev_pci_bandwidth_set (uint32_t dv_ind, uint64_t bw_bitmask)

  Control the set of allowed PCIe bandwidths that can be used.

5.4.1 Detailed Description

These functions provide some control over PCIe.

5.4.2 Function Documentation

5.4.2.1 rsmi_dev_pci_bandwidth_set()

```
rsmi_status_t rsmi_dev_pci_bandwidth_set (
            uint32_t dv_ind,
            uint64_t bw_bitmask )
```

Control the set of allowed PCIe bandwidths that can be used.

Given a device index `dv_ind` and a 64 bit bitmask `bw_bitmask`, this function will limit the set of allowable bandwidths. If a bit in `bw_bitmask` has a value of 1, then the frequency (as ordered in an rsmi_frequencies_t returned by rsmi_dev_gpu_clk_freq_get()) corresponding to that bit index will be allowed.

This function will change the performance level to RSMI_DEV_PERF_LEVEL_MANUAL in order to modify the set of allowable band_widths. Caller will need to set to RSMI_DEV_PERF_LEVEL_AUTO in order to get back to default state.

All bits with indices greater than or equal to the value of the rsmi_frequencies_t::num_supported field of rsmi_pcie_bandwidth_t will be ignored.

Parameters

in	*dv_ind*	a device index
in	*bw_bitmask*	A bitmask indicating the indices of the bandwidths that are to be enabled (1) and disabled (0). Only the lowest rsmi_frequencies_t::num_supported (of rsmi_pcie_bandwidth_t) bits of this mask are relevant.

5.5 Power Queries

Functions

- rsmi_status_t rsmi_dev_power_ave_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *power)

  Get the average power consumption of the device with provided device index.
- rsmi_status_t rsmi_dev_power_cap_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *cap)

  Get the cap on power which, when reached, causes the system to take action to reduce power.
- rsmi_status_t rsmi_dev_power_cap_range_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *max, uint64_t *min)

  Get the range of valid values for the power cap.

5.5.1 Detailed Description

These functions provide information about power usage.

5.5.2 Function Documentation

5.5.2.1 rsmi_dev_power_ave_get()

```
rsmi_status_t rsmi_dev_power_ave_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t * power )
```

Get the average power consumption of the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint64_t `power`, this function will write the current average power consumption to the uint64_t in microwatts pointed to by `power`. This function requires root privilege.

Parameters

`in`	*dv_ind*	a device index
`in`	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
`in,out`	*power*	a pointer to uint64_t to which the average power consumption will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.5.2.2 rsmi_dev_power_cap_get()

```
rsmi_status_t rsmi_dev_power_cap_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t * cap )
```

Get the cap on power which, when reached, causes the system to take action to reduce power.

When power use rises above the value `power`, the system will take action to reduce power use. The power level returned through `power` will be in microWatts.

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in,out	*cap*	a pointer to a uint64_t that indicates the power cap, in microwatts

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.5.2.3 rsmi_dev_power_cap_range_get()

```
rsmi_status_t rsmi_dev_power_cap_range_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t * max,
            uint64_t * min )
```

Get the range of valid values for the power cap.

This function will return the maximum possible valid power cap `max` and the minimum possible valid power cap `min`

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in,out	*max*	a pointer to a uint64_t that indicates the maximum possible power cap, in microwatts
in,out	*min*	a pointer to a uint64_t that indicates the minimum possible power cap, in microwatts

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.6 Power Control

Functions

- rsmi_status_t rsmi_dev_power_cap_set (uint32_t dv_ind, uint32_t sensor_ind, uint64_t cap)

  Set the power cap value.
- rsmi_status_t rsmi_dev_power_profile_set (uint32_t dv_ind, uint32_t sensor_ind, rsmi_power_profile_preset_masks_t profile)

  Set the power profile.

5.6.1 Detailed Description

These functions provide ways to control power usage.

5.6.2 Function Documentation

5.6.2.1 rsmi_dev_power_cap_set()

```
rsmi_status_t rsmi_dev_power_cap_set (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t cap )
```

Set the power cap value.

This function will set the power cap to the provided value `cap`. `cap` must be between the minimum and maximum power cap values set by the system, which can be obtained from rsmi_dev_power_cap_range_get.

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in,out	*cap*	a uint64_t that indicates the desired power cap, in microwatts

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.6.2.2 rsmi_dev_power_profile_set()

```
rsmi_status_t rsmi_dev_power_profile_set (
            uint32_t dv_ind,
```

```
        uint32_t sensor_ind,
        rsmi_power_profile_preset_masks_t profile )
```

Set the power profile.

Given a device index dv_ind, a sensor index sensor_ind, and a profile, this function will attempt to set the current profile to the provided profile. The provided profile must be one of the currently supported profiles, as indicated by a call to rsmi_dev_power_profile_presets_get()

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in	*profile*	a rsmi_power_profile_preset_masks_t that hold the mask of the desired new power profile

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.7 Memory Queries

Functions

- rsmi_status_t rsmi_dev_memory_total_get (uint32_t dv_ind, rsmi_memory_type_t mem_type, uint64_t *total)

  Get the total amount of memory that exists.
- rsmi_status_t rsmi_dev_memory_usage_get (uint32_t dv_ind, rsmi_memory_type_t mem_type, uint64_t *used)

  Get the current memory usage.

5.7.1 Detailed Description

These functions provide information about memory systems.

5.7.2 Function Documentation

5.7.2.1 rsmi_dev_memory_total_get()

```
rsmi_status_t rsmi_dev_memory_total_get (
            uint32_t dv_ind,
            rsmi_memory_type_t mem_type,
            uint64_t * total )
```

Get the total amount of memory that exists.

Given a device index `dv_ind`, a type of memory `mem_type`, and a pointer to a uint64_t `total`, this function will write the total amount of `mem_type` memory that exists to the location pointed to by `total`.

Parameters

`in`	*dv_ind*	a device index
`in`	*mem_type*	The type of memory for which the total amount will be found
`in,out`	*total*	a pointer to uint64_t to which the total amount of memory will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.7.2.2 rsmi_dev_memory_usage_get()

```
rsmi_status_t rsmi_dev_memory_usage_get (
            uint32_t dv_ind,
```

```
rsmi_memory_type_t mem_type,
uint64_t * used )
```

Get the current memory usage.

Given a device index `dv_ind`, a type of memory `mem_type`, and a pointer to a uint64_t `usage`, this function will write the amount of `mem_type` memory that that is currently being used to the location pointed to by `total`.

Parameters

`in`	*dv_ind*	a device index
`in`	*mem_type*	The type of memory for which the amount being used will be found
`in,out`	*used*	a pointer to uint64_t to which the amount of memory currently being used will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.8 Physical State Queries

Functions

- rsmi_status_t rsmi_dev_fan_rpms_get (uint32_t dv_ind, uint32_t sensor_ind, int64_t *speed)

  Get the fan speed in RPMs of the device with the specified device index and 0-based sensor index.
- rsmi_status_t rsmi_dev_fan_speed_get (uint32_t dv_ind, uint32_t sensor_ind, int64_t *speed)

  Get the fan speed for the specified device in RPMs.
- rsmi_status_t rsmi_dev_fan_speed_max_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *max_speed)

  Get the max. fan speed of the device with provided device index.
- rsmi_status_t rsmi_dev_temp_metric_get (uint32_t dv_ind, uint32_t sensor_type, rsmi_temperature_metric_t metric, int64_t *temperature)

  Get the temperature metric value for the specified metric, from the specified temperature sensor on the specified device.

5.8.1 Detailed Description

These functions provide information about the physical characteristics of the device.

5.8.2 Function Documentation

5.8.2.1 rsmi_dev_fan_rpms_get()

```
rsmi_status_t rsmi_dev_fan_rpms_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            int64_t * speed )
```

Get the fan speed in RPMs of the device with the specified device index and 0-based sensor index.

Given a device index `dv_ind` and a pointer to a uint32_t `speed`, this function will write the current fan speed in RPMs to the uint32_t pointed to by `speed`

Parameters

`in`	*dv_ind*	a device index
`in`	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
`in,out`	*speed*	a pointer to uint32_t to which the speed will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.8.2.2 rsmi_dev_fan_speed_get()

```
rsmi_status_t rsmi_dev_fan_speed_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            int64_t * speed )
```

Get the fan speed for the specified device in RPMs.

Given a device index `dv_ind` this function will get the fan speed.

Parameters

in	*dv_ind*	a device index

Given a device index `dv_ind` and a pointer to a uint32_t `speed`, this function will write the current fan speed (a value between 0 and 255) to the uint32_t pointed to by `speed`

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in,out	*speed*	a pointer to uint32_t to which the speed will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.8.2.3 rsmi_dev_fan_speed_max_get()

```
rsmi_status_t rsmi_dev_fan_speed_max_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t * max_speed )
```

Get the max. fan speed of the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `max_speed`, this function will write the maximum fan speed possible to the uint32_t pointed to by `max_speed`

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
in,out	*max_speed*	a pointer to uint32_t to which the maximum speed will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.8.2.4 rsmi_dev_temp_metric_get()

```
rsmi_status_t rsmi_dev_temp_metric_get (
            uint32_t dv_ind,
            uint32_t sensor_type,
            rsmi_temperature_metric_t metric,
            int64_t * temperature )
```

Get the temperature metric value for the specified metric, from the specified temperature sensor on the specified device.

Given a device index `dv_ind`, a sensor type `sensor_type`, a rsmi_temperature_metric_t `metric` and a pointer to an int64_t `temperature`, this function will write the value of the metric indicated by `metric` and `sensor_type` to the memory location `temperature`.

Parameters

`in`	*dv_ind*	a device index
`in`	*sensor_type*	part of device from which temperature should be obtained. This should come from the enum rsmi_temperature_type_t
`in`	*metric*	enum indicated which temperature value should be retrieved
`in,out`	*temperature*	a pointer to int64_t to which the temperature will be written, in millidegrees Celcius.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.9 Physical State Control

Functions

- rsmi_status_t rsmi_dev_fan_reset (uint32_t dv_ind, uint32_t sensor_ind)

  Reset the fan to automatic driver control.
- rsmi_status_t rsmi_dev_fan_speed_set (uint32_t dv_ind, uint32_t sensor_ind, uint64_t speed)

  Set the fan speed for the specified device with the provided speed, in RPMs.

5.9.1 Detailed Description

These functions provide control over the physical state of a device.

5.9.2 Function Documentation

5.9.2.1 rsmi_dev_fan_reset()

```
rsmi_status_t rsmi_dev_fan_reset (
            uint32_t dv_ind,
            uint32_t sensor_ind )
```

Reset the fan to automatic driver control.

This function returns control of the fan to the system

Parameters

in	*dv_ind*	a device index
in	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.9.2.2 rsmi_dev_fan_speed_set()

```
rsmi_status_t rsmi_dev_fan_speed_set (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            uint64_t speed )
```

Set the fan speed for the specified device with the provided speed, in RPMs.

Given a device index `dv_ind` and a integer value indicating speed `speed`, this function will attempt to set the fan speed to `speed`. An error will be returned if the specified speed is outside the allowable range for the device. The maximum value is 255 and the minimum is 0.

Parameters

`in`	*dv_ind*	a device index
`in`	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
`in`	*speed*	the speed to which the function will attempt to set the fan

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10 Clock, Power and Performance Queries

Functions

- rsmi_status_t rsmi_dev_busy_percent_get (uint32_t dv_ind, uint32_t *busy_percent)

  Get percentage of time device is busy doing any processing.
- rsmi_status_t rsmi_dev_perf_level_get (uint32_t dv_ind, rsmi_dev_perf_level_t *perf)

  Get the performance level of the device with provided device index.
- rsmi_status_t rsmi_dev_overdrive_level_get (uint32_t dv_ind, uint32_t *od)

  Get the overdrive percent associated with the device with provided device index.
- rsmi_status_t rsmi_dev_gpu_clk_freq_get (uint32_t dv_ind, rsmi_clk_type_t clk_type, rsmi_frequencies_t *f)

  Get the list of possible system clock speeds of device for a specified clock type.
- rsmi_status_t rsmi_dev_od_volt_info_get (uint32_t dv_ind, rsmi_od_volt_freq_data_t *odv)

  This function retrieves the voltage/frequency curve information.
- rsmi_status_t rsmi_dev_od_volt_curve_regions_get (uint32_t dv_ind, uint32_t *num_regions, rsmi_freq_volt_region_t *buffer)

  This function will retrieve the current valid regions in the frequency/voltage space.
- rsmi_status_t rsmi_dev_power_profile_presets_get (uint32_t dv_ind, uint32_t sensor_ind, rsmi_power_profile_status_t *status)

  Get the list of available preset power profiles and an indication of which profile is currently active.

5.10.1 Detailed Description

These functions provide information about clock frequencies and performance.

5.10.2 Function Documentation

5.10.2.1 rsmi_dev_busy_percent_get()

```
rsmi_status_t rsmi_dev_busy_percent_get (
            uint32_t dv_ind,
            uint32_t * busy_percent )
```

Get percentage of time device is busy doing any processing.

Given a device index `dv_ind`, this function returns the percentage of time that the specified device is busy. The device is considered busy if any one or more of its sub-blocks are working, and idle if none of the sub-blocks are working.

Parameters

in	*dv_ind*	a device index
in,out	*busy_percent*	a pointer to the uint32_t to which the busy percent will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call

5.10.2.2 rsmi_dev_perf_level_get()

```
rsmi_status_t rsmi_dev_perf_level_get (
            uint32_t dv_ind,
            rsmi_dev_perf_level_t * perf )
```

Get the performance level of the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `perf`, this function will write the rsmi_dev_perf_level_t to the uint32_t pointed to by `perf`

Parameters

`in`	*dv_ind*	a device index
`in,out`	*perf*	a pointer to rsmi_dev_perf_level_t to which the performance level will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10.2.3 rsmi_dev_overdrive_level_get()

```
rsmi_status_t rsmi_dev_overdrive_level_get (
            uint32_t dv_ind,
            uint32_t * od )
```

Get the overdrive percent associated with the device with provided device index.

Given a device index `dv_ind` and a pointer to a uint32_t `od`, this function will write the overdrive percentage to the uint32_t pointed to by `od`

Parameters

`in`	*dv_ind*	a device index
`in,out`	*od*	a pointer to uint32_t to which the overdrive percentage will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10.2.4 rsmi_dev_gpu_clk_freq_get()

```
rsmi_status_t rsmi_dev_gpu_clk_freq_get (
            uint32_t dv_ind,
            rsmi_clk_type_t clk_type,
            rsmi_frequencies_t * f )
```

Get the list of possible system clock speeds of device for a specified clock type.

Given a device index `dv_ind`, a clock type `clk_type`, and a pointer to a to an rsmi_frequencies_t structure `f`, this function will fill in `f` with the possible clock speeds, and indication of the current clock speed selection.

Parameters

in	*dv_ind*	a device index
in	*clk_type*	the type of clock for which the frequency is desired
in,out	*f*	a pointer to a caller provided rsmi_frequencies_t structure to which the frequency information will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10.2.5 rsmi_dev_od_volt_info_get()

```
rsmi_status_t rsmi_dev_od_volt_info_get (
            uint32_t dv_ind,
            rsmi_od_volt_freq_data_t * odv )
```

This function retrieves the voltage/frequency curve information.

Given a device index `dv_ind` and a pointer to a rsmi_od_volt_freq_data_t structure `odv`, this function will populate `odv`. See rsmi_od_volt_freq_data_t for more details.

Parameters

in	*dv_ind*	a device index
in	*odv*	a pointer to an rsmi_od_volt_freq_data_t structure

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10.2.6 rsmi_dev_od_volt_curve_regions_get()

```
rsmi_status_t rsmi_dev_od_volt_curve_regions_get (
            uint32_t dv_ind,
            uint32_t * num_regions,
            rsmi_freq_volt_region_t * buffer )
```

This function will retrieve the current valid regions in the frequency/voltage space.

Given a device index `dv_ind`, a pointer to an unsigned integer `num_regions` and a buffer of rsmi_freq_volt_region_t structures, `buffer`, this function will populate `buffer` with the current frequency-volt space regions. The caller should assign `buffer` to memory that can be written to by this function. The caller should also indicate the number of rsmi_freq_volt_region_t structures that can safely be written to `buffer` in `num_regions`.

The number of regions to expect this function provide (`num_regions`) can be obtained by calling rsmi_dev_od_volt_info_get().

Parameters

`in`	*dv_ind*	a device index
`in,out`	*num_regions*	As input, this is the number of rsmi_freq_volt_region_t structures that can be written to `buffer`. As output, this is the number of rsmi_freq_volt_region_t structures that were actually written.
`in,out`	*buffer*	a caller provided buffer to which rsmi_freq_volt_region_t structures will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.10.2.7 rsmi_dev_power_profile_presets_get()

```
rsmi_status_t rsmi_dev_power_profile_presets_get (
            uint32_t dv_ind,
            uint32_t sensor_ind,
            rsmi_power_profile_status_t * status )
```

Get the list of available preset power profiles and an indication of which profile is currently active.

Given a device index `dv_ind` and a pointer to a rsmi_power_profile_status_t `status`, this function will set the bits of the rsmi_power_profile_status_t.available_profiles bit field of `status` to 1 if the profile corresponding to the respective rsmi_power_profile_preset_masks_t profiles are enabled. For example, if both the VIDEO and VR power profiles are available selections, then RSMI_PWR_PROF_PRST_VIDEO_MASK AND'ed with rsmi_power_profile_status_t.available_profiles will be non-zero as will RSMI_PWR_PROF_PRST_VR_MASK AND'ed with rsmi_power_profile_status_t.available_profiles. Additionally, rsmi_power_profile_status_t.current will be set to the rsmi_power_profile_preset_masks_t of the profile that is currently active.

Parameters

`in`	*dv_ind*	a device index
`in`	*sensor_ind*	a 0-based sensor index. Normally, this will be 0. If a device has more than one sensor, it could be greater than 0.
`in,out`	*status*	a pointer to rsmi_power_profile_status_t that will be populated by a call to this function

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.11 Clock, Power and Performance Control

Functions

- rsmi_status_t rsmi_dev_perf_level_set (int32_t dv_ind, rsmi_dev_perf_level_t perf_lvl)

  Set the PowerPlay performance level associated with the device with provided device index with the provided value.
- rsmi_status_t rsmi_dev_overdrive_level_set (int32_t dv_ind, uint32_t od)

  Set the overdrive percent associated with the device with provided device index with the provided value. See details for WARNING.
- rsmi_status_t rsmi_dev_gpu_clk_freq_set (uint32_t dv_ind, rsmi_clk_type_t clk_type, uint64_t freq_bitmask)

  Control the set of allowed frequencies that can be used for the specified clock.
- rsmi_status_t rsmi_dev_od_freq_range_set (uint32_t dv_ind, rsmi_clk_type_t clk, rsmi_range_t *range)

  Set the frequency limits for the specified clock.

5.11.1 Detailed Description

These functions provide control over clock frequencies, power and performance.

5.11.2 Function Documentation

5.11.2.1 rsmi_dev_perf_level_set()

```
rsmi_status_t rsmi_dev_perf_level_set (
            int32_t dv_ind,
            rsmi_dev_perf_level_t perf_lvl )
```

Set the PowerPlay performance level associated with the device with provided device index with the provided value.

Given a device index `dv_ind` and an rsmi_dev_perf_level_t `perf_level`, this function will set the PowerPlay performance level for the device to the value `perf_lvl`.

Parameters

in	*dv_ind*	a device index
in	*perf_lvl*	the value to which the performance level should be set

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.11.2.2 rsmi_dev_overdrive_level_set()

```
rsmi_status_t rsmi_dev_overdrive_level_set (
              int32_t dv_ind,
              uint32_t od )
```

Set the overdrive percent associated with the device with provided device index with the provided value. See details for WARNING.

Given a device index `dv_ind` and an overdrive level `od`, this function will set the overdrive level for the device to the value `od`. The overdrive level is an integer value between 0 and 20, inclusive, which represents the overdrive percentage; e.g., a value of 5 specifies an overclocking of 5%.

The overdrive level is specific to the gpu system clock.

The overdrive level is the percentage above the maximum Performance Level to which overclocking will be limited. The overclocking percentage does not apply to clock speeds other than the maximum. This percentage is limited to 20%.

******WARNING****** Operating your AMD GPU outside of official AMD specifications or outside of factory settings, including but not limited to the conducting of overclocking (including use of this overclocking software, even if such software has been directly or indirectly provided by AMD or otherwise affiliated in any way with AMD), may cause damage to your AMD GPU, system components and/or result in system failure, as well as cause other problems. DAMAGES CAUSED BY USE OF YOUR AMD GPU OUTSIDE OF OFFICIAL AMD SPECIFICATIONS OR OUTSIDE OF FACTORY SETTINGS ARE NOT COVERED UNDER ANY AMD PRODUCT WARRANTY A↩ ND MAY NOT BE COVERED BY YOUR BOARD OR SYSTEM MANUFACTURER'S WARRANTY. Please use this utility with caution.

Parameters

`in`	*dv_ind*	a device index
`in`	*od*	the value to which the overdrive level should be set

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.11.2.3 rsmi_dev_gpu_clk_freq_set()

```
rsmi_status_t rsmi_dev_gpu_clk_freq_set (
              uint32_t dv_ind,
              rsmi_clk_type_t clk_type,
              uint64_t freq_bitmask )
```

Control the set of allowed frequencies that can be used for the specified clock.

Given a device index `dv_ind`, a clock type `clk_type`, and a 64 bit bitmask `freq_bitmask`, this function will limit the set of allowable frequencies. If a bit in `freq_bitmask` has a value of 1, then the frequency (as ordered in an rsmi_frequencies_t returned by rsmi_dev_gpu_clk_freq_get()) corresponding to that bit index will be allowed.

This function will change the performance level to RSMI_DEV_PERF_LEVEL_MANUAL in order to modify the set of allowable frequencies. Caller will need to set to RSMI_DEV_PERF_LEVEL_AUTO in order to get back to default state.

All bits with indices greater than or equal to rsmi_frequencies_t::num_supported will be ignored.

Parameters

in	*dv_ind*	a device index
in	*clk_type*	the type of clock for which the set of frequencies will be modified
in	*freq_bitmask*	A bitmask indicating the indices of the frequencies that are to be enabled (1) and disabled (0). Only the lowest rsmi_frequencies_t.num_supported bits of this mask are relevant.

5.11.2.4 rsmi_dev_od_freq_range_set()

```
rsmi_status_t rsmi_dev_od_freq_range_set (
            uint32_t dv_ind,
            rsmi_clk_type_t clk,
            rsmi_range_t * range )
```

Set the frequency limits for the specified clock.

Given a device index `dv_ind`, a clock type (rsmi_clk_type_t) `clk`, and a pointer to a rsmi_range_t `range` containing the desired upper and lower frequency limits, this function will attempt to set the frequency limits to those specified in `range`.

Parameters

in	*dv_ind*	a device index
in	*clk*	The clock type for which the limits should be imposed.
in	*range*	A pointer to the rsmi_range_t containing the desired limits

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.12 Version Queries

Functions

- rsmi_status_t rsmi_version_get (rsmi_version_t *version)
  Get the build version information for the currently running build of RSMI.
- rsmi_status_t rsmi_version_str_get (rsmi_sw_component_t component, char *ver_str, uint32_t len)
  Get the driver version string for the current system.
- rsmi_status_t rsmi_dev_vbios_version_get (uint32_t dv_ind, char *vbios, uint32_t len)
  Get the VBIOS identifer string.

5.12.1 Detailed Description

These functions provide version information about various subsystems.

5.12.2 Function Documentation

5.12.2.1 rsmi_version_get()

```
rsmi_status_t rsmi_version_get (
            rsmi_version_t * version )
```

Get the build version information for the currently running build of RSMI.

Get the major, minor, patch and build string for RSMI build currently in use through `version`

Parameters

`in,out`	*version*	A pointer to an rsmi_version_t structure that will be updated with the version information upon return.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call

5.12.2.2 rsmi_version_str_get()

```
rsmi_status_t rsmi_version_str_get (
            rsmi_sw_component_t component,
            char * ver_str,
            uint32_t len )
```

Get the driver version string for the current system.

Given a software component `component`, a pointer to a char buffer, `ver_str`, this function will write the driver version string (up to `len` characters) for the current system to `ver_str`. The caller must ensure that it is safe to write at least `len` characters to `ver_str`.

Parameters

`in`	*component*	The component for which the version string is being requested
`in,out`	*ver_str*	A pointer to a buffer of char's to which the VBIOS name will be written
`in`	*len*	The number of char's pointed to by `ver_str` which can safely be written to by this function.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.12.2.3 rsmi_dev_vbios_version_get()

```
rsmi_status_t rsmi_dev_vbios_version_get (
            uint32_t dv_ind,
            char * vbios,
            uint32_t len )
```

Get the VBIOS identifer string.

Given a device ID `dv_ind`, and a pointer to a char buffer, `vbios`, this function will write the VBIOS string (up to `len` characters) for device `dv_ind` to `vbios`. The caller must ensure that it is safe to write at least `len` characters to `vbios`.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*vbios*	A pointer to a buffer of char's to which the VBIOS name will be written
`in`	*len*	The number of char's pointed to by `vbios` which can safely be written to by this function.

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.13 Error Queries

Functions

- rsmi_status_t rsmi_dev_ecc_count_get (uint32_t dv_ind, rsmi_gpu_block_t block, rsmi_error_count_t *ec)

  Retrieve the error counts for a GPU block.
- rsmi_status_t rsmi_dev_ecc_enabled_get (uint32_t dv_ind, uint64_t *enabled_mask)

  Retrieve the enabled ECC bit-mask.
- rsmi_status_t rsmi_dev_ecc_status_get (uint32_t dv_ind, rsmi_gpu_block_t block, rsmi_ras_err_state_t *state)

  Retrieve the ECC status for a GPU block.
- rsmi_status_t rsmi_status_string (rsmi_status_t status, const char **status_string)

  Get a description of a provided RSMI error status.

5.13.1 Detailed Description

These functions provide error information about RSMI calls as well as device errors.

5.13.2 Function Documentation

5.13.2.1 rsmi_dev_ecc_count_get()

```
rsmi_status_t rsmi_dev_ecc_count_get (
            uint32_t dv_ind,
            rsmi_gpu_block_t block,
            rsmi_error_count_t * ec )
```

Retrieve the error counts for a GPU block.

Given a device index `dv_ind`, an rsmi_gpu_block_t `block` and a pointer to an rsmi_error_count_t `ec`, this function will write the error count values for the GPU block indicated by `block` to memory pointed to by `ec`.

Parameters

`in`	*dv_ind*	a device index
`in`	*block*	The block for which error counts should be retrieved
`in,out`	*ec*	A pointer to an rsmi_error_count_t to which the error counts should be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.13.2.2 rsmi_dev_ecc_enabled_get()

```
rsmi_status_t rsmi_dev_ecc_enabled_get (
            uint32_t dv_ind,
            uint64_t * enabled_mask )
```

Retrieve the enabled ECC bit-mask.

Given a device index `dv_ind`, and a pointer to a uint64_t `enabled_mask`, this function will write a bit_mask to memory pointed to by `enabled_mask`. Upon a successful call, the bitmask can then be AND'd with elements of the rsmi_gpu_block_t ennumeration to determine if the corresponding block has ECC enabled. Note that the bits above RSMI_GPU_BLOCK_LAST correspond to blocks that do not yet have ECC support.

Parameters

`in`	*dv_ind*	a device index
`in,out`	*enabled_mask*	A pointer to a uint64_t to which the enabled mask will be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.13.2.3 rsmi_dev_ecc_status_get()

```
rsmi_status_t rsmi_dev_ecc_status_get (
            uint32_t dv_ind,
            rsmi_gpu_block_t block,
            rsmi_ras_err_state_t * state )
```

Retrieve the ECC status for a GPU block.

Given a device index `dv_ind`, an rsmi_gpu_block_t `block` and a pointer to an rsmi_ras_err_state_t `state`, this function will write the current state for the GPU block indicated by `block` to memory pointed to by `state`.

Parameters

`in`	*dv_ind*	a device index
`in`	*block*	The block for which error counts should be retrieved
`in,out`	*state*	A pointer to an rsmi_ras_err_state_t to which the ECC state should be written

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call.

5.13.2.4 rsmi_status_string()

```
rsmi_status_t rsmi_status_string (
             rsmi_status_t status,
             const char ** status_string )
```

Get a description of a provided RSMI error status.

Set the provided pointer to a const char *, `status_string`, to a string containing a description of the provided error code `status`.

Parameters

`in`	*status*	The error status for which a description is desired
`in,out`	*status_string*	A pointer to a const char * which will be made to point to a description of the provided error code

Return values

RSMI_STATUS_SUCCESS	is returned upon successful call

Chapter 6

Data Structure Documentation

6.1 rsmi_error_count_t Struct Reference

This structure holds error counts.

`#include <rocm_smi.h>`

Data Fields

- uint64_t correctable_err

  Accumulated correctable errors.
- uint64_t uncorrectable_err

  Accumulated uncorrectable errors.

6.1.1 Detailed Description

This structure holds error counts.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.2 rsmi_freq_volt_region_t Struct Reference

This structure holds 2 rsmi_range_t's, one for frequency and one for voltage. These 2 ranges indicate the range of possible values for the corresponding rsmi_od_vddc_point_t.

`#include <rocm_smi.h>`

Data Fields

- rsmi_range_t freq_range

  The frequency range for this VDDC Curve point.
- rsmi_range_t volt_range

  The voltage range for this VDDC Curve point.

6.2.1 Detailed Description

This structure holds 2 rsmi_range_t's, one for frequency and one for voltage. These 2 ranges indicate the range of possible values for the corresponding rsmi_od_vddc_point_t.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.3 rsmi_frequencies_t Struct Reference

This structure holds information about clock frequencies.

```
#include <rocm_smi.h>
```

Data Fields

- uint32_t num_supported
- uint32_t current
- uint64_t frequency [RSMI_MAX_NUM_FREQUENCIES]

6.3.1 Detailed Description

This structure holds information about clock frequencies.

6.3.2 Field Documentation

6.3.2.1 num_supported

```
uint32_t rsmi_frequencies_t::num_supported
```

The number of supported frequencies

6.3.2.2 current

```
uint32_t rsmi_frequencies_t::current
```

The current frequency index

6.3.2.3 frequency

```
uint64_t rsmi_frequencies_t::frequency[RSMI_MAX_NUM_FREQUENCIES]
```

List of frequencies. Only the first num_supported frequencies are valid.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.4 rsmi_od_vddc_point_t Struct Reference

This structure represents a point on the frequency-voltage plane.

```
#include <rocm_smi.h>
```

Data Fields

- uint64_t frequency
  Frequency coordinate (in Hz)
- uint64_t voltage
  Voltage coordinate (in mV)

6.4.1 Detailed Description

This structure represents a point on the frequency-voltage plane.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.5 rsmi_od_volt_curve_t Struct Reference

```
#include <rocm_smi.h>
```

Data Fields

- rsmi_od_vddc_point_t vc_points [RSMI_NUM_VOLTAGE_CURVE_POINTS]

6.5.1 Detailed Description

RSMI_NUM_VOLTAGE_CURVE_POINTS number of rsmi_od_vddc_point_t's

6.5.2 Field Documentation

6.5.2.1 vc_points

```
rsmi_od_vddc_point_t rsmi_od_volt_curve_t::vc_points[RSMI_NUM_VOLTAGE_CURVE_POINTS]
```

Array of RSMI_NUM_VOLTAGE_CURVE_POINTS rsmi_od_vddc_point_t's that make up the voltage frequency curve points.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.6 rsmi_od_volt_freq_data_t Struct Reference

This structure holds the frequency-voltage values for a device.

```
#include <rocm_smi.h>
```

Data Fields

- rsmi_range_t curr_sclk_range
  The current SCLK frequency range.
- rsmi_range_t curr_mclk_range
- rsmi_range_t sclk_freq_limits
  The range possible of SCLK values.
- rsmi_range_t mclk_freq_limits
  The range possible of MCLK values.
- rsmi_od_volt_curve_t curve
  The current voltage curve.
- uint32_t num_regions
  The number of voltage curve regions.

6.6.1 Detailed Description

This structure holds the frequency-voltage values for a device.

6.6.2 Field Documentation

6.6.2.1 curr_mclk_range

```
rsmi_range_t rsmi_od_volt_freq_data_t::curr_mclk_range
```

The current MCLK frequency range; (upper bound only)

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.7 rsmi_pcie_bandwidth_t Struct Reference

This structure holds information about the possible PCIe bandwidths. Specifically, the possible transfer rates and their associated numbers of lanes are stored here.

```
#include <rocm_smi.h>
```

Data Fields

- rsmi_frequencies_t transfer_rate
- uint32_t lanes [RSMI_MAX_NUM_FREQUENCIES]

6.7.1 Detailed Description

This structure holds information about the possible PCIe bandwidths. Specifically, the possible transfer rates and their associated numbers of lanes are stored here.

6.7.2 Field Documentation

6.7.2.1 transfer_rate

```
rsmi_frequencies_t rsmi_pcie_bandwidth_t::transfer_rate
```

Transfer rates (T/s) that are possible

6.7.2.2 lanes

```
uint32_t rsmi_pcie_bandwidth_t::lanes[RSMI_MAX_NUM_FREQUENCIES]
```

List of lanes for corresponding transfer rate. Only the first num_supported bandwidths are valid.

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.8 rsmi_power_profile_status_t Struct Reference

This structure contains information about which power profiles are supported by the system for a given device, and which power profile is currently active.

```
#include <rocm_smi.h>
```

Data Fields

- rsmi_bit_field_t available_profiles
- rsmi_power_profile_preset_masks_t current
- uint32_t num_profiles

6.8.1 Detailed Description

This structure contains information about which power profiles are supported by the system for a given device, and which power profile is currently active.

6.8.2 Field Documentation

6.8.2.1 available_profiles

```
rsmi_bit_field_t rsmi_power_profile_status_t::available_profiles
```

Which profiles are supported by this system

6.8.2.2 current

```
rsmi_power_profile_preset_masks_t rsmi_power_profile_status_t::current
```

Which power profile is currently active

6.8.2.3 num_profiles

`uint32_t rsmi_power_profile_status_t::num_profiles`

How many power profiles are available

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.9 rsmi_range_t Struct Reference

This structure represents a range (e.g., frequencies or voltages).

`#include <rocm_smi.h>`

Data Fields

- uint64_t lower_bound
  Lower bound of range.
- uint64_t upper_bound
  Upper bound of range.

6.9.1 Detailed Description

This structure represents a range (e.g., frequencies or voltages).

The documentation for this struct was generated from the following file:

- rocm_smi.h

6.10 rsmi_version_t Struct Reference

This structure holds version information.

`#include <rocm_smi.h>`

Data Fields

- uint32_t major
  Major version.
- uint32_t minor
  Minor version.
- uint32_t patch
  Patch, build or stepping version.
- const char * build
  Build string.

6.10.1 Detailed Description

This structure holds version information.

The documentation for this struct was generated from the following file:

- rocm_smi.h

Chapter 7

File Documentation

7.1 rocm_smi.h File Reference

The rocm_smi library api is new, and therefore subject to change either at the ABI or API level. Instead of marking every function prototype as "unstable", we are instead saying the API is unstable (i.e., changes are possible) while the major version remains 0. This means that if the API/ABI changes, we will not increment the major version to 1. Once the ABI stabilizes, we will increment the major version to 1, and thereafter increment it on all ABI breaks.

```
#include <stdint.h>
#include <stddef.h>
```

Data Structures

- struct rsmi_power_profile_status_t

  This structure contains information about which power profiles are supported by the system for a given device, and which power profile is currently active.
- struct rsmi_frequencies_t

  This structure holds information about clock frequencies.
- struct rsmi_pcie_bandwidth_t

  This structure holds information about the possible PCIe bandwidths. Specifically, the possible transfer rates and their associated numbers of lanes are stored here.
- struct rsmi_version_t

  This structure holds version information.
- struct rsmi_range_t

  This structure represents a range (e.g., frequencies or voltages).
- struct rsmi_od_vddc_point_t

  This structure represents a point on the frequency-voltage plane.
- struct rsmi_freq_volt_region_t

  This structure holds 2 rsmi_range_t's, one for frequency and one for voltage. These 2 ranges indicate the range of possible values for the corresponding rsmi_od_vddc_point_t.
- struct rsmi_od_volt_curve_t
- struct rsmi_od_volt_freq_data_t

  This structure holds the frequency-voltage values for a device.
- struct rsmi_error_count_t

  This structure holds error counts.

Macros

- #define RSMI_MAX_NUM_FREQUENCIES 32

  Guaranteed maximum possible number of supported frequencies.
- #define RSMI_MAX_FAN_SPEED 255
- #define RSMI_NUM_VOLTAGE_CURVE_POINTS 3

  The number of points that make up a voltage-frequency curve definition.
- #define RSMI_MAX_NUM_POWER_PROFILES (sizeof(rsmi_bit_field_t) * 8)

  Number of possible power profiles that a system could support.

Typedefs

- typedef uint64_t rsmi_bit_field_t

  Bitfield used in various RSMI calls.

Enumerations

- enum rsmi_status_t {
  RSMI_STATUS_SUCCESS = 0x0, RSMI_STATUS_INVALID_ARGS, RSMI_STATUS_NOT_SUPPORTED, RSMI_STATUS_FILE_ERROR,
  RSMI_STATUS_PERMISSION, RSMI_STATUS_OUT_OF_RESOURCES, RSMI_STATUS_INTERNAL_EXCEPTION, RSMI_STATUS_INPUT_OUT_OF_BOUNDS,
  RSMI_STATUS_INIT_ERROR, **RSMI_INITIALIZATION_ERROR** = RSMI_STATUS_INIT_ERROR, RSMI_STATUS_NOT_YET_IMPLEMENTED, RSMI_STATUS_NOT_FOUND,
  RSMI_STATUS_INSUFFICIENT_SIZE, RSMI_STATUS_UNKNOWN_ERROR = 0xFFFFFFFF }

  Error codes retured by rocm_smi_lib functions.
- enum rsmi_init_flags_t { RSMI_INIT_FLAG_ALL_GPUS = 0x1 }

  Initialization flags.
- enum rsmi_dev_perf_level_t {
  RSMI_DEV_PERF_LEVEL_AUTO = 0, **RSMI_DEV_PERF_LEVEL_FIRST** = RSMI_DEV_PERF_LEVEL_AUTO, RSMI_DEV_PERF_LEVEL_LOW, RSMI_DEV_PERF_LEVEL_HIGH,
  RSMI_DEV_PERF_LEVEL_MANUAL, RSMI_DEV_PERF_LEVEL_STABLE_STD, RSMI_DEV_PERF_LEVEL_STABLE_PEAK, RSMI_DEV_PERF_LEVEL_STABLE_MIN_MCLK,
  RSMI_DEV_PERF_LEVEL_STABLE_MIN_SCLK, **RSMI_DEV_PERF_LEVEL_LAST** = RSMI_DEV_PERF_LEVEL_STABLE_MIN_SCLK, RSMI_DEV_PERF_LEVEL_UNKNOWN = 0x100 }

  PowerPlay performance levels.
- enum rsmi_sw_component_t { **RSMI_SW_COMP_FIRST** = 0x0, RSMI_SW_COMP_DRIVER = RSMI_SW_COMP_FIRST, **RSMI_SW_COMP_LAST** = RSMI_SW_COMP_DRIVER }

  Available clock types.
- enum rsmi_clk_type_t {
  RSMI_CLK_TYPE_SYS = 0x0, **RSMI_CLK_TYPE_FIRST** = RSMI_CLK_TYPE_SYS, RSMI_CLK_TYPE_DF, RSMI_CLK_TYPE_DCEF,
  RSMI_CLK_TYPE_SOC, RSMI_CLK_TYPE_MEM, **RSMI_CLK_TYPE_LAST** = RSMI_CLK_TYPE_MEM, **RSMI_CLK_INVALID** = 0xFFFFFFFF }
- enum rsmi_temperature_metric_t {
  RSMI_TEMP_CURRENT = 0x0, **RSMI_TEMP_FIRST** = RSMI_TEMP_CURRENT, RSMI_TEMP_MAX, RSMI_TEMP_MIN,
  RSMI_TEMP_MAX_HYST, RSMI_TEMP_MIN_HYST, RSMI_TEMP_CRITICAL, RSMI_TEMP_CRITICAL_HYST,
  RSMI_TEMP_EMERGENCY, RSMI_TEMP_EMERGENCY_HYST, RSMI_TEMP_CRIT_MIN, RSMI_TEMP_CRIT_MIN_HYST,
  RSMI_TEMP_OFFSET, RSMI_TEMP_LOWEST, RSMI_TEMP_HIGHEST, **RSMI_TEMP_LAST** = RSMI_TEMP_HIGHEST }

Temperature Metrics. This enum is used to identify various temperature metrics. Corresponding values will be in millidegress Celcius.

- enum rsmi_temperature_type_t {
  RSMI_TEMP_TYPE_FIRST = 0, RSMI_TEMP_TYPE_EDGE = RSMI_TEMP_TYPE_FIRST, RSMI_TEMP↩
  _TYPE_JUNCTION, RSMI_TEMP_TYPE_MEMORY,
  RSMI_TEMP_TYPE_LAST = RSMI_TEMP_TYPE_MEMORY }

  This ennumeration is used to indicate from which part of the device a temperature reading should be obtained.
- enum rsmi_power_profile_preset_masks_t {
  RSMI_PWR_PROF_PRST_CUSTOM_MASK = 0x1, RSMI_PWR_PROF_PRST_VIDEO_MASK = 0x2, R↩
  SMI_PWR_PROF_PRST_POWER_SAVING_MASK = 0x4, RSMI_PWR_PROF_PRST_COMPUTE_MASK
  = 0x8,
  RSMI_PWR_PROF_PRST_VR_MASK = 0x10, **RSMI_PWR_PROF_PRST_3D_FULL_SCR_MASK** = 0x20,
  RSMI_PWR_PROF_PRST_BOOTUP_DEFAULT = 0x40, RSMI_PWR_PROF_PRST_LAST = RSMI_PW↩
  R_PROF_PRST_BOOTUP_DEFAULT,
  RSMI_PWR_PROF_PRST_INVALID = 0xFFFFFFFFFFFFFFFF }

  Pre-set Profile Selections. These bitmasks can be AND'd with the rsmi_power_profile_status_t.available_profiles returned from rsmi_dev_power_profile_presets_get() to determine which power profiles are supported by the system.
- enum rsmi_gpu_block_t {
  RSMI_GPU_BLOCK_INVALID = 0x0000000000000000, **RSMI_GPU_BLOCK_FIRST** = 0x0000000000000001,
  RSMI_GPU_BLOCK_UMC = RSMI_GPU_BLOCK_FIRST, RSMI_GPU_BLOCK_SDMA = 0x0000000000000002,
  RSMI_GPU_BLOCK_GFX = 0x0000000000000004, RSMI_GPU_BLOCK_LAST = RSMI_GPU_BLOCK_↩
  GFX, **RSMI_GPU_BLOCK_RESERVED** = 0x8000000000000000 }

  This enum is used to identify different GPU blocks.
- enum rsmi_ras_err_state_t {
  RSMI_RAS_ERR_STATE_NONE = 0, RSMI_RAS_ERR_STATE_DISABLED, RSMI_RAS_ERR_STATE↩
  _PARITY, RSMI_RAS_ERR_STATE_SING_C,
  RSMI_RAS_ERR_STATE_MULT_UC, RSMI_RAS_ERR_STATE_POISON, **RSMI_RAS_ERR_STATE_L↩**
  AST = RSMI_RAS_ERR_STATE_POISON, **RSMI_RAS_ERR_STATE_INVALID** = 0xFFFFFFFF }

  The current ECC state.
- enum rsmi_memory_type_t {
  RSMI_MEM_TYPE_FIRST = 0, RSMI_MEM_TYPE_VRAM = RSMI_MEM_TYPE_FIRST, RSMI_MEM_T↩
  YPE_VIS_VRAM, RSMI_MEM_TYPE_GTT,
  RSMI_MEM_TYPE_LAST = RSMI_MEM_TYPE_GTT }

  Types of memory.
- enum rsmi_freq_ind_t { RSMI_FREQ_IND_MIN = 0, RSMI_FREQ_IND_MAX = 1, RSMI_FREQ_IND_INV↩
  ALID = 0xFFFFFFFF }

  This values of this enum are used as frequency identifiers.

Functions

- rsmi_status_t rsmi_init (uint64_t init_flags)

  Initialize ROCm SMI.
- rsmi_status_t rsmi_shut_down (void)

  Shutdown ROCm SMI.
- rsmi_status_t rsmi_num_monitor_devices (uint32_t *num_devices)

  Get the number of devices that have monitor information.
- rsmi_status_t rsmi_dev_id_get (uint32_t dv_ind, uint16_t *id)

  Get the device id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_vendor_id_get (uint32_t dv_ind, uint16_t *id)

  Get the device vendor id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_name_get (uint32_t dv_ind, char *name, size_t len)

  Get the name string of a gpu device.
- rsmi_status_t rsmi_dev_vendor_name_get (uint32_t id, char *name, size_t len)

Get the name string for a give vendor ID.

- rsmi_status_t rsmi_dev_subsystem_id_get (uint32_t dv_ind, uint16_t *id)

  Get the subsystem device id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_subsystem_name_get (uint32_t dv_ind, char *name, size_t len)

  Get the name string for the device subsytem.
- rsmi_status_t rsmi_dev_subsystem_vendor_id_get (uint32_t dv_ind, uint16_t *id)

  Get the device subsystem vendor id associated with the device with provided device index.
- rsmi_status_t rsmi_dev_unique_id_get (uint32_t dv_ind, uint64_t *id)

  Get Unique ID.
- rsmi_status_t rsmi_dev_pci_bandwidth_get (uint32_t dv_ind, rsmi_pcie_bandwidth_t *bandwidth)

  Get the list of possible PCIe bandwidths that are available.
- rsmi_status_t rsmi_dev_pci_id_get (uint32_t dv_ind, uint64_t *bdfid)

  Get the unique PCI device identifier associated for a device.
- rsmi_status_t rsmi_dev_pci_throughput_get (uint32_t dv_ind, uint64_t *sent, uint64_t *received, uint64_t *max_pkt_sz)

  Get PCIe traffic information.
- rsmi_status_t rsmi_dev_pci_replay_counter_get (uint32_t dv_ind, uint64_t *counter)

  Get PCIe replay counter.
- rsmi_status_t rsmi_dev_pci_bandwidth_set (uint32_t dv_ind, uint64_t bw_bitmask)

  Control the set of allowed PCIe bandwidths that can be used.
- rsmi_status_t rsmi_dev_power_ave_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *power)

  Get the average power consumption of the device with provided device index.
- rsmi_status_t rsmi_dev_power_cap_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *cap)

  Get the cap on power which, when reached, causes the system to take action to reduce power.
- rsmi_status_t rsmi_dev_power_cap_range_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *max, uint64_t *min)

  Get the range of valid values for the power cap.
- rsmi_status_t rsmi_dev_power_cap_set (uint32_t dv_ind, uint32_t sensor_ind, uint64_t cap)

  Set the power cap value.
- rsmi_status_t rsmi_dev_power_profile_set (uint32_t dv_ind, uint32_t sensor_ind, rsmi_power_profile_preset_masks_t profile)

  Set the power profile.
- rsmi_status_t rsmi_dev_memory_total_get (uint32_t dv_ind, rsmi_memory_type_t mem_type, uint64_t *total)

  Get the total amount of memory that exists.
- rsmi_status_t rsmi_dev_memory_usage_get (uint32_t dv_ind, rsmi_memory_type_t mem_type, uint64_t *used)

  Get the current memory usage.
- rsmi_status_t rsmi_dev_fan_rpms_get (uint32_t dv_ind, uint32_t sensor_ind, int64_t *speed)

  Get the fan speed in RPMs of the device with the specified device index and 0-based sensor index.
- rsmi_status_t rsmi_dev_fan_speed_get (uint32_t dv_ind, uint32_t sensor_ind, int64_t *speed)

  Get the fan speed for the specified device in RPMs.
- rsmi_status_t rsmi_dev_fan_speed_max_get (uint32_t dv_ind, uint32_t sensor_ind, uint64_t *max_speed)

  Get the max. fan speed of the device with provided device index.
- rsmi_status_t rsmi_dev_temp_metric_get (uint32_t dv_ind, uint32_t sensor_type, rsmi_temperature_metric_t metric, int64_t *temperature)

  Get the temperature metric value for the specified metric, from the specified temperature sensor on the specified device.
- rsmi_status_t rsmi_dev_fan_reset (uint32_t dv_ind, uint32_t sensor_ind)

  Reset the fan to automatic driver control.
- rsmi_status_t rsmi_dev_fan_speed_set (uint32_t dv_ind, uint32_t sensor_ind, uint64_t speed)

  Set the fan speed for the specified device with the provided speed, in RPMs.

- rsmi_status_t rsmi_dev_busy_percent_get (uint32_t dv_ind, uint32_t *busy_percent)

  Get percentage of time device is busy doing any processing.
- rsmi_status_t rsmi_dev_perf_level_get (uint32_t dv_ind, rsmi_dev_perf_level_t *perf)

  Get the performance level of the device with provided device index.
- rsmi_status_t rsmi_dev_overdrive_level_get (uint32_t dv_ind, uint32_t *od)

  Get the overdrive percent associated with the device with provided device index.
- rsmi_status_t rsmi_dev_gpu_clk_freq_get (uint32_t dv_ind, rsmi_clk_type_t clk_type, rsmi_frequencies_t *f)

  Get the list of possible system clock speeds of device for a specified clock type.
- rsmi_status_t rsmi_dev_od_volt_info_get (uint32_t dv_ind, rsmi_od_volt_freq_data_t *odv)

  This function retrieves the voltage/frequency curve information.
- rsmi_status_t rsmi_dev_od_volt_curve_regions_get (uint32_t dv_ind, uint32_t *num_regions, rsmi_freq_volt_region_t *buffer)

  This function will retrieve the current valid regions in the frequency/voltage space.
- rsmi_status_t rsmi_dev_power_profile_presets_get (uint32_t dv_ind, uint32_t sensor_ind, rsmi_power_profile_status_t *status)

  Get the list of available preset power profiles and an indication of which profile is currently active.
- rsmi_status_t rsmi_dev_perf_level_set (int32_t dv_ind, rsmi_dev_perf_level_t perf_lvl)

  Set the PowerPlay performance level associated with the device with provided device index with the provided value.
- rsmi_status_t rsmi_dev_overdrive_level_set (int32_t dv_ind, uint32_t od)

  Set the overdrive percent associated with the device with provided device index with the provided value. See details for WARNING.
- rsmi_status_t rsmi_dev_gpu_clk_freq_set (uint32_t dv_ind, rsmi_clk_type_t clk_type, uint64_t freq_bitmask)

  Control the set of allowed frequencies that can be used for the specified clock.
- rsmi_status_t rsmi_dev_od_freq_range_set (uint32_t dv_ind, rsmi_clk_type_t clk, rsmi_range_t *range)

  Set the frequency limits for the specified clock.
- rsmi_status_t rsmi_version_get (rsmi_version_t *version)

  Get the build version information for the currently running build of RSMI.
- rsmi_status_t rsmi_version_str_get (rsmi_sw_component_t component, char *ver_str, uint32_t len)

  Get the driver version string for the current system.
- rsmi_status_t rsmi_dev_vbios_version_get (uint32_t dv_ind, char *vbios, uint32_t len)

  Get the VBIOS identifer string.
- rsmi_status_t rsmi_dev_ecc_count_get (uint32_t dv_ind, rsmi_gpu_block_t block, rsmi_error_count_t *ec)

  Retrieve the error counts for a GPU block.
- rsmi_status_t rsmi_dev_ecc_enabled_get (uint32_t dv_ind, uint64_t *enabled_mask)

  Retrieve the enabled ECC bit-mask.
- rsmi_status_t rsmi_dev_ecc_status_get (uint32_t dv_ind, rsmi_gpu_block_t block, rsmi_ras_err_state_t *state)

  Retrieve the ECC status for a GPU block.
- rsmi_status_t rsmi_status_string (rsmi_status_t status, const char **status_string)

  Get a description of a provided RSMI error status.

7.1.1 Detailed Description

The rocm_smi library api is new, and therefore subject to change either at the ABI or API level. Instead of marking every function prototype as "unstable", we are instead saying the API is unstable (i.e., changes are possible) while the major version remains 0. This means that if the API/ABI changes, we will not increment the major version to 1. Once the ABI stabilizes, we will increment the major version to 1, and thereafter increment it on all ABI breaks.

Main header file for the ROCm SMI library. All required function, structure, enum, etc. definitions should be defined in this file.

7.1.2 Macro Definition Documentation

7.1.2.1 RSMI_MAX_FAN_SPEED

```
#define RSMI_MAX_FAN_SPEED 255
```

Maximum possible value for fan speed. Should be used as the denominator when determining fan speed percentage.

7.1.3 Enumeration Type Documentation

7.1.3.1 rsmi_status_t

```
enum rsmi_status_t
```

Error codes retured by rocm_smi_lib functions.

Enumerator

RSMI_STATUS_SUCCESS	Operation was successful.
RSMI_STATUS_INVALID_ARGS	Passed in arguments are not valid.
RSMI_STATUS_NOT_SUPPORTED	The requested information or action is not available for the given input, on the given system
RSMI_STATUS_FILE_ERROR	Problem accessing a file. This may because the operation is not supported by the Linux kernel version running on the executing machine
RSMI_STATUS_PERMISSION	Permission denied/EACCESS file error. Many functions require root access to run.
RSMI_STATUS_OUT_OF_RESOURCES	Unable to acquire memory or other resource
RSMI_STATUS_INTERNAL_EXCEPTION	An internal exception was caught.
RSMI_STATUS_INPUT_OUT_OF_BOUNDS	The provided input is out of allowable or safe range
RSMI_STATUS_INIT_ERROR	An error occurred when rsmi initializing internal data structures
RSMI_STATUS_NOT_YET_IMPLEMENTED	The requested function has not yet been implemented in the current system for the current devices
RSMI_STATUS_NOT_FOUND	An item was searched for but not found
RSMI_STATUS_INSUFFICIENT_SIZE	Not enough resources were for the operation
RSMI_STATUS_UNKNOWN_ERROR	An unknown error occurred.

7.1.3.2 rsmi_init_flags_t

```
enum rsmi_init_flags_t
```

Initialization flags.

Initialization flags may be OR'd together and passed to rsmi_init().

Enumerator

RSMI_INIT_FLAG_ALL_GPUS	Attempt to add all GPUs found (including non-AMD) to the list of devices from which SMI information can be retrieved. By default, only AMD devices are ennumerated by RSMI.

7.1.3.3 rsmi_dev_perf_level_t

`enum rsmi_dev_perf_level_t`

PowerPlay performance levels.

Enumerator

RSMI_DEV_PERF_LEVEL_AUTO	Performance level is "auto".
RSMI_DEV_PERF_LEVEL_LOW	Keep PowerPlay levels "low", regardless of workload
RSMI_DEV_PERF_LEVEL_HIGH	Keep PowerPlay levels "high", regardless of workload
RSMI_DEV_PERF_LEVEL_MANUAL	Only use values defined by manually setting the RSMI_CLK_TYPE_SYS speed
RSMI_DEV_PERF_LEVEL_STABLE_STD	Stable power state with profiling clocks
RSMI_DEV_PERF_LEVEL_STABLE_PEAK	Stable power state with peak clocks.
RSMI_DEV_PERF_LEVEL_STABLE_MIN_MCLK	Stable power state with minimum memory clock
RSMI_DEV_PERF_LEVEL_STABLE_MIN_SCLK	Stable power state with minimum system clock
RSMI_DEV_PERF_LEVEL_UNKNOWN	Unknown performance level.

7.1.3.4 rsmi_sw_component_t

`enum rsmi_sw_component_t`

Available clock types.

Software components

Enumerator

RSMI_SW_COMP_DRIVER	Driver.

7.1.3.5 rsmi_clk_type_t

```
enum rsmi_clk_type_t
```

Clock types

Enumerator

RSMI_CLK_TYPE_SYS	System clock.
RSMI_CLK_TYPE_DF	Data Fabric clock (for ASICs running on a separate clock)
RSMI_CLK_TYPE_DCEF	Display Controller Engine clock.
RSMI_CLK_TYPE_SOC	SOC clock.
RSMI_CLK_TYPE_MEM	Memory clock.

7.1.3.6 rsmi_temperature_metric_t

```
enum rsmi_temperature_metric_t
```

Temperature Metrics. This enum is used to identify various temperature metrics. Corresponding values will be in millidegress Celcius.

Enumerator

RSMI_TEMP_CURRENT	Temperature current value.
RSMI_TEMP_MAX	Temperature max value.
RSMI_TEMP_MIN	Temperature min value.
RSMI_TEMP_MAX_HYST	Temperature hysteresis value for max limit. (This is an absolute temperature, not a delta).
RSMI_TEMP_MIN_HYST	Temperature hysteresis value for min limit. (This is an absolute temperature, not a delta).
RSMI_TEMP_CRITICAL	Temperature critical max value, typically greater than corresponding temp_max values.
RSMI_TEMP_CRITICAL_HYST	Temperature hysteresis value for critical limit. (This is an absolute temperature, not a delta).
RSMI_TEMP_EMERGENCY	Temperature emergency max value, for chips supporting more than two upper temperature limits. Must be equal or greater than corresponding temp_crit values.
RSMI_TEMP_EMERGENCY_HYST	Temperature hysteresis value for emergency limit. (This is an absolute temperature, not a delta).
RSMI_TEMP_CRIT_MIN	Temperature critical min value, typically lower than corresponding temperature minimum values.
RSMI_TEMP_CRIT_MIN_HYST	Temperature hysteresis value for critical minimum limit. (This is an absolute temperature, not a delta).
RSMI_TEMP_OFFSET	Temperature offset which is added to the temperature reading by the chip.
RSMI_TEMP_LOWEST	Historical minimum temperature.
RSMI_TEMP_HIGHEST	Historical maximum temperature.

7.1.3.7 rsmi_temperature_type_t

`enum rsmi_temperature_type_t`

This ennumeration is used to indicate from which part of the device a temperature reading should be obtained.

Enumerator

RSMI_TEMP_TYPE_EDGE	Edge GPU temperature.
RSMI_TEMP_TYPE_JUNCTION	Junction/hotspot temperature
RSMI_TEMP_TYPE_MEMORY	VRAM temperature.

7.1.3.8 rsmi_power_profile_preset_masks_t

`enum rsmi_power_profile_preset_masks_t`

Pre-set Profile Selections. These bitmasks can be AND'd with the rsmi_power_profile_status_t.available_profiles returned from rsmi_dev_power_profile_presets_get() to determine which power profiles are supported by the system.

Enumerator

RSMI_PWR_PROF_PRST_CUSTOM_MASK	Custom Power Profile.
RSMI_PWR_PROF_PRST_VIDEO_MASK	Video Power Profile.
RSMI_PWR_PROF_PRST_POWER_SAVING_MASK	Power Saving Profile.
RSMI_PWR_PROF_PRST_COMPUTE_MASK	Compute Saving Profile.
RSMI_PWR_PROF_PRST_VR_MASK	VR Power Profile. 3D Full Screen Power Profile
RSMI_PWR_PROF_PRST_BOOTUP_DEFAULT	Default Boot Up Profile.
RSMI_PWR_PROF_PRST_LAST	Invalid power profile.

7.1.3.9 rsmi_gpu_block_t

`enum rsmi_gpu_block_t`

This enum is used to identify different GPU blocks.

Enumerator

RSMI_GPU_BLOCK_INVALID	Used to indicate an invalid block
RSMI_GPU_BLOCK_UMC	UMC block.
RSMI_GPU_BLOCK_SDMA	SDMA block.
RSMI_GPU_BLOCK_GFX	GFX block.
RSMI_GPU_BLOCK_LAST	The highest bit position for supported blocks

7.1.3.10 rsmi_ras_err_state_t

`enum rsmi_ras_err_state_t`

The current ECC state.

Enumerator

RSMI_RAS_ERR_STATE_NONE	No current errors.
RSMI_RAS_ERR_STATE_DISABLED	ECC is disabled.
RSMI_RAS_ERR_STATE_PARITY	ECC errors present, but type unknown.
RSMI_RAS_ERR_STATE_SING_C	Single correctable error.
RSMI_RAS_ERR_STATE_MULT_UC	Multiple uncorrectable errors.
RSMI_RAS_ERR_STATE_POISON	Firmware detected error and isolated page. Treat as uncorrectable.

7.1.3.11 rsmi_memory_type_t

`enum rsmi_memory_type_t`

Types of memory.

Enumerator

RSMI_MEM_TYPE_VRAM	VRAM memory.
RSMI_MEM_TYPE_VIS_VRAM	VRAM memory that is visible.
RSMI_MEM_TYPE_GTT	GTT memory.

7.1.3.12 rsmi_freq_ind_t

`enum rsmi_freq_ind_t`

This values of this enum are used as frequency identifiers.

Enumerator

RSMI_FREQ_IND_MIN	Index used for the minimum frequency value.
RSMI_FREQ_IND_MAX	Index used for the maximum frequency value.
RSMI_FREQ_IND_INVALID	An invalid frequency index.

Index

available_profiles
    rsmi_power_profile_status_t, 52

Clock, Power and Performance Control, 38
    rsmi_dev_gpu_clk_freq_set, 39
    rsmi_dev_od_freq_range_set, 40
    rsmi_dev_overdrive_level_set, 38
    rsmi_dev_perf_level_set, 38
Clock, Power and Performance Queries, 33
    rsmi_dev_busy_percent_get, 33
    rsmi_dev_gpu_clk_freq_get, 35
    rsmi_dev_od_volt_curve_regions_get, 35
    rsmi_dev_od_volt_info_get, 35
    rsmi_dev_overdrive_level_get, 34
    rsmi_dev_perf_level_get, 34
    rsmi_dev_power_profile_presets_get, 36
curr_mclk_range
    rsmi_od_volt_freq_data_t, 51
current
    rsmi_frequencies_t, 48
    rsmi_power_profile_status_t, 52

Error Queries, 43
    rsmi_dev_ecc_count_get, 43
    rsmi_dev_ecc_enabled_get, 43
    rsmi_dev_ecc_status_get, 44
    rsmi_status_string, 44

frequency
    rsmi_frequencies_t, 49

Identifier Queries, 13
    rsmi_dev_id_get, 14
    rsmi_dev_name_get, 15
    rsmi_dev_subsystem_id_get, 16
    rsmi_dev_subsystem_name_get, 16
    rsmi_dev_subsystem_vendor_id_get, 17
    rsmi_dev_unique_id_get, 17
    rsmi_dev_vendor_id_get, 14
    rsmi_dev_vendor_name_get, 15
    rsmi_num_monitor_devices, 13
Initialization and Shutdown, 11
    rsmi_init, 11
    rsmi_shut_down, 12

lanes
    rsmi_pcie_bandwidth_t, 51

Memory Queries, 26
    rsmi_dev_memory_total_get, 26
    rsmi_dev_memory_usage_get, 26

num_profiles
    rsmi_power_profile_status_t, 52
num_supported
    rsmi_frequencies_t, 48

PCIe Control, 21
    rsmi_dev_pci_bandwidth_set, 21
PCIe Queries, 18
    rsmi_dev_pci_bandwidth_get, 18
    rsmi_dev_pci_id_get, 18
    rsmi_dev_pci_replay_counter_get, 20
    rsmi_dev_pci_throughput_get, 19
Physical State Control, 31
    rsmi_dev_fan_reset, 31
    rsmi_dev_fan_speed_set, 31
Physical State Queries, 28
    rsmi_dev_fan_rpms_get, 28
    rsmi_dev_fan_speed_get, 28
    rsmi_dev_fan_speed_max_get, 29
    rsmi_dev_temp_metric_get, 30
Power Control, 24
    rsmi_dev_power_cap_set, 24
    rsmi_dev_power_profile_set, 24
Power Queries, 22
    rsmi_dev_power_ave_get, 22
    rsmi_dev_power_cap_get, 22
    rsmi_dev_power_cap_range_get, 23

RSMI_MAX_FAN_SPEED
    rocm_smi.h, 60
rocm_smi.h, 55
    RSMI_MAX_FAN_SPEED, 60
    rsmi_clk_type_t, 61
    rsmi_dev_perf_level_t, 61
    rsmi_freq_ind_t, 64
    rsmi_gpu_block_t, 63
    rsmi_init_flags_t, 60
    rsmi_memory_type_t, 64
    rsmi_power_profile_preset_masks_t, 63
    rsmi_ras_err_state_t, 64
    rsmi_status_t, 60
    rsmi_sw_component_t, 61
    rsmi_temperature_metric_t, 62
    rsmi_temperature_type_t, 63
rsmi_clk_type_t
    rocm_smi.h, 61
rsmi_dev_busy_percent_get
    Clock, Power and Performance Queries, 33
rsmi_dev_ecc_count_get
    Error Queries, 43

rsmi_dev_ecc_enabled_get
Error Queries, 43
rsmi_dev_ecc_status_get
Error Queries, 44
rsmi_dev_fan_reset
Physical State Control, 31
rsmi_dev_fan_rpms_get
Physical State Queries, 28
rsmi_dev_fan_speed_get
Physical State Queries, 28
rsmi_dev_fan_speed_max_get
Physical State Queries, 29
rsmi_dev_fan_speed_set
Physical State Control, 31
rsmi_dev_gpu_clk_freq_get
Clock, Power and Performance Queries, 35
rsmi_dev_gpu_clk_freq_set
Clock, Power and Performance Control, 39
rsmi_dev_id_get
Identifier Queries, 14
rsmi_dev_memory_total_get
Memory Queries, 26
rsmi_dev_memory_usage_get
Memory Queries, 26
rsmi_dev_name_get
Identifier Queries, 15
rsmi_dev_od_freq_range_set
Clock, Power and Performance Control, 40
rsmi_dev_od_volt_curve_regions_get
Clock, Power and Performance Queries, 35
rsmi_dev_od_volt_info_get
Clock, Power and Performance Queries, 35
rsmi_dev_overdrive_level_get
Clock, Power and Performance Queries, 34
rsmi_dev_overdrive_level_set
Clock, Power and Performance Control, 38
rsmi_dev_pci_bandwidth_get
PCIe Queries, 18
rsmi_dev_pci_bandwidth_set
PCIe Control, 21
rsmi_dev_pci_id_get
PCIe Queries, 18
rsmi_dev_pci_replay_counter_get
PCIe Queries, 20
rsmi_dev_pci_throughput_get
PCIe Queries, 19
rsmi_dev_perf_level_get
Clock, Power and Performance Queries, 34
rsmi_dev_perf_level_set
Clock, Power and Performance Control, 38
rsmi_dev_perf_level_t
rocm_smi.h, 61
rsmi_dev_power_ave_get
Power Queries, 22
rsmi_dev_power_cap_get
Power Queries, 22
rsmi_dev_power_cap_range_get
Power Queries, 23
rsmi_dev_power_cap_set
Power Control, 24
rsmi_dev_power_profile_presets_get
Clock, Power and Performance Queries, 36
rsmi_dev_power_profile_set
Power Control, 24
rsmi_dev_subsystem_id_get
Identifier Queries, 16
rsmi_dev_subsystem_name_get
Identifier Queries, 16
rsmi_dev_subsystem_vendor_id_get
Identifier Queries, 17
rsmi_dev_temp_metric_get
Physical State Queries, 30
rsmi_dev_unique_id_get
Identifier Queries, 17
rsmi_dev_vbios_version_get
Version Queries, 42
rsmi_dev_vendor_id_get
Identifier Queries, 14
rsmi_dev_vendor_name_get
Identifier Queries, 15
rsmi_error_count_t, 47
rsmi_freq_ind_t
rocm_smi.h, 64
rsmi_freq_volt_region_t, 47
rsmi_frequencies_t, 48
current, 48
frequency, 49
num_supported, 48
rsmi_gpu_block_t
rocm_smi.h, 63
rsmi_init
Initialization and Shutdown, 11
rsmi_init_flags_t
rocm_smi.h, 60
rsmi_memory_type_t
rocm_smi.h, 64
rsmi_num_monitor_devices
Identifier Queries, 13
rsmi_od_vddc_point_t, 49
rsmi_od_volt_curve_t, 49
vc_points, 50
rsmi_od_volt_freq_data_t, 50
curr_mclk_range, 51
rsmi_pcie_bandwidth_t, 51
lanes, 51
transfer_rate, 51
rsmi_power_profile_preset_masks_t
rocm_smi.h, 63
rsmi_power_profile_status_t, 52
available_profiles, 52
current, 52
num_profiles, 52
rsmi_range_t, 53
rsmi_ras_err_state_t
rocm_smi.h, 64
rsmi_shut_down

Initialization and Shutdown, 12
rsmi_status_string
Error Queries, 44
rsmi_status_t
rocm_smi.h, 60
rsmi_sw_component_t
rocm_smi.h, 61
rsmi_temperature_metric_t
rocm_smi.h, 62
rsmi_temperature_type_t
rocm_smi.h, 63
rsmi_version_get
Version Queries, 41
rsmi_version_str_get
Version Queries, 41
rsmi_version_t, 53

transfer_rate
rsmi_pcie_bandwidth_t, 51

vc_points
rsmi_od_volt_curve_t, 50
Version Queries, 41
rsmi_dev_vbios_version_get, 42
rsmi_version_get, 41
rsmi_version_str_get, 41