

# Module sui::groth16

Represents an elliptic curve construction to be used in the verifier. Currently we support BLS12-381 and BN254. This should be given as the first parameter to [prepare\\_verifying\\_key](#) or [verify\\_groth16\\_proof](#).

A [PreparedVerifyingKey](#) consisting of four components in serialized form.

A [PublicProofInputs](#) wrapper around its serialized bytes.

A [ProofPoints](#) wrapper around the serialized form of three proof points.

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

Creates a [PreparedVerifyingKey](#) from bytes.

Returns bytes of the four components of the [PreparedVerifyingKey](#).

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

Creates a Groth16 [ProofPoints](#) from bytes.

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#). @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#).

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#).

## Struct

Represents an elliptic curve construction to be used in the verifier. Currently we support BLS12-381 and BN254. This should be given as the first parameter to [prepare\\_verifying\\_key](#) or [verify\\_groth16\\_proof](#).

```
```bash
```

```
...
```

A [PreparedVerifyingKey](#) consisting of four components in serialized form.

```
```bash
```

```
...
```

A [PublicProofInputs](#) wrapper around its serialized bytes.

```
```bash
```

```
...
```

A [ProofPoints](#) wrapper around the serialized form of three proof points.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Struct

A [PreparedVerifyingKey](#) consisting of four components in serialized form.

```
```bash
```

```
```
```

A [PublicProofInputs](#) wrapper around its serialized bytes.

```
```bash
```

```
```
```

A [ProofPoints](#) wrapper around the serialized form of three proof points.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [ElInvalidVerifyingKey](#) or [ElInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

## Struct

A [PublicProofInputs](#) wrapper around its serialized bytes.

```
```bash
```

```
```
```

A [ProofPoints](#) wrapper around the serialized form of three proof points.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

## Struct

A [ProofPoints](#) wrapper around the serialized form of three proof points.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
```bash
```



```
'''
```

```
'''bash
```

```
'''
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bs12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#).

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Constants

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
'''bash
```

```
'''
```

```
```bash
```

```
```
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
```bash
```

```
```
```

```
```bash
```

'''

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

'''bash

'''

'''bash

'''

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

'''bash

'''

'''bash

'''

## Function

Return the [Curve](#) value indicating that the BLS12-381 construction should be used in a given function.

'''bash

'''

'''bash

'''

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

'''bash

'''

'''bash

'''

Creates a [PreparedVerifyingKey](#) from bytes.

'''bash

'''

'''bash

'''

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

'''bash

'''

'''bash

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bbs12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bbs12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Return the [Curve](#) value indicating that the BN254 construction should be used in a given function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PreparedVerifyingKey](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Creates a [PreparedVerifyingKey](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```



## Function

Returns bytes of the four components of the [PreparedVerifyingKey](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Creates a [PublicProofInputs](#) wrapper from bytes. The bytes parameter should be a concatenation of a number of 32 bytes scalar field elements to be used as public inputs in little-endian format to a circuit.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bbs12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bbs12381](#) and [bn254](#) functions. @param prepared\_verifying\_key:

Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Creates a Groth16 [ProofPoints](#) from bytes.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#) . @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#).

```
```bash
```

```
```
```

```
```bash
```

```
```
```

## Function

@param curve: What elliptic curve construction to use. See [bls12381](#) and [bn254](#). @param verifying\_key: An Arkworks canonical compressed serialization of a verifying key.

Returns four vectors of bytes representing the four components of a prepared verifying key. This step computes one pairing  $e(P, Q)$ , and binds the verification to one particular proof statement. This can be used as inputs for the [verify\\_groth16\\_proof](#) function.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#).

```
```bash
```

```
```
```

```
```bash
```

```
```
```

@param curve: What elliptic curve construction to use. See the [bls12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#).

```
```bash
```

```
```
```

```
'''bash
```

```
'''
```

## Function

Native functions that flattens the inputs into an array and passes to the Rust native function. May abort with [EInvalidVerifyingKey](#) or [EInvalidCurve](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

@param curve: What elliptic curve construction to use. See the [bbs12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

@param curve: What elliptic curve construction to use. See the [bbs12381](#) and [bn254](#) functions. @param prepared\_verifying\_key: Consists of four vectors of bytes representing the four components of a prepared verifying key. @param public\_proof\_inputs: Represent inputs that are public. @param proof\_points: Represent three proof points.

Returns a boolean indicating whether the proof is valid.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
'''bash
```

```
'''
```

```
```bash
```

```
```
```

## Function

Native functions that flattens the inputs into arrays of vectors and passed to the Rust native function. May abort with [EInvalidCurve](#) or [ETooManyPublicInputs](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```