

Module sui::tx_context

Information about the transaction currently being executed. This cannot be constructed by a transaction--it is a privileged object created by the VM and passed in to the entrypoint of the transaction as & mut [TxContext](#).

Return the address of the user that signed the current transaction

Return the transaction digest (hash of transaction inputs). Please do not use as a source of randomness.

Return the current epoch

Return the epoch start time as a unix timestamp in milliseconds.

Return the address of the transaction sponsor or None if there was no sponsor.

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

Return the number of id's created by the current transaction. Hidden for now, but may expose later

Native function for deriving an ID via hash(tx_hash || ids_created)

Struct

Information about the transaction currently being executed. This cannot be constructed by a transaction--it is a privileged object created by the VM and passed in to the entrypoint of the transaction as & mut [TxContext](#).

```
```bash
```

```
...
```

Return the address of the user that signed the current transaction

```
```bash
```

```
...
```

```
```bash
```

```
...
```

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Return the transaction digest (hash of transaction inputs). Please do not use as a source of randomness.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Return the current epoch

```
```bash
```

```
...
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the epoch start time as a unix timestamp in milliseconds.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the address of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Return the address of the user that signed the current transaction

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
```bash
```

```
```
```

Return the transaction digest (hash of transaction inputs). Please do not use as a source of randomness.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the current epoch

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the epoch start time as a unix timestamp in milliseconds.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the adress of the transaction sponsor or None if there was no sponsor.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
```bash
```

```
```
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the transaction digest (hash of transaction inputs). Please do not use as a source of randomness.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the current epoch

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the epoch start time as a unix timestamp in milliseconds.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the adress of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

'''

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

Return the number of id's created by the current transaction. Hidden for now, but may expose later

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

'''bash

'''

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Return the transaction digest (hash of transaction inputs). Please do not use as a source of randomness.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the current epoch

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the epoch start time as a unix timestamp in milliseconds.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the address of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```



```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via `hash(tx_hash || ids_created)`

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Return the current epoch

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the epoch start time as a unix timestamp in milliseconds.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the adress of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the epoch start time as a unix timestamp in milliseconds.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the adress of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native function for deriving an ID via `hash(tx_hash || ids_created)`

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Function

Return the epoch start time as a unix timestamp in milliseconds.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the address of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via `hash(tx_hash || ids_created)`

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the adress of the transaction sponsor or None if there was no sponsor.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx\_hash || ids\_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Return the adress of the transaction sponsor or None if there was no sponsor.



```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx\_hash || ids\_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Create an address that has not been used. As it is an object address, it will never occur as the address for a user. In other words, the generated address is a globally unique object ID.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Native function for deriving an ID via `hash(tx_hash || ids_created)`

```
```bash
```

```
```
```

```
```bash
```

```
```
```

## Function

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via `hash(tx_hash || ids_created)`

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Return the number of id's created by the current transaction. Hidden for now, but may expose later

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Native function for deriving an ID via hash(tx_hash || ids_created)

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Function

Native function for deriving an ID via hash(tx_hash || ids_created)

```
```bash
```

```
```
```

```
```bash
```

```
```
```