

Module sui::zklogin_verified_issuer

Possession of a VerifiedIssuer proves that the user's address was created using zklogin and with the given issuer (identity provider).

Error if the proof consisting of the inputs provided to the verification function is invalid.

Error if the proof consisting of the inputs provided to the verification function is invalid.

Returns the address associated with the given VerifiedIssuer

Returns the issuer associated with the given VerifiedIssuer

Delete a VerifiedIssuer

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

Returns true if address was created using zklogin with the given issuer and address seed.

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

Struct

Possession of a VerifiedIssuer proves that the user's address was created using zklogin and with the given issuer (identity provider).

```
```bash
```

```
```
```

Error if the proof consisting of the inputs provided to the verification function is invalid.

```
```bash
```

```
```
```

Error if the proof consisting of the inputs provided to the verification function is invalid.

```
```bash
```

```
```
```

Returns the address associated with the given VerifiedIssuer

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns the issuer associated with the given VerifiedIssuer

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Delete a VerifiedIssuer

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if address was created using zklogin with the given issuer and address seed.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Constants

Error if the proof consisting of the inputs provided to the verification function is invalid.

```
```bash
```

```
```
```

Error if the proof consisting of the inputs provided to the verification function is invalid.

```
```bash
```

```
```
```

Returns the address associated with the given VerifiedIssuer

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Returns the issuer associated with the given VerifiedIssuer

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Delete a VerifiedIssuer

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Returns the address associated with the given VerifiedIssuer

```
'''bash
```

```
'''
```

```
'''bash
```

'''

Returns the issuer associated with the given VerifiedIssuer

'''bash

'''

'''bash

'''

Delete a VerifiedIssuer

'''bash

'''

'''bash

'''

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

'''bash

'''

'''bash

'''

Returns true if address was created using zklogin with the given issuer and address seed.

'''bash

'''

'''bash

'''

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

'''bash

'''

'''bash

'''

## Function

Returns the issuer associated with the given VerifiedIssuer

'''bash

'''

'''bash

'''

Delete a VerifiedIssuer

'''bash

'''

'''bash

'''

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

'''bash

'''

'''bash

'''

Returns true if address was created using zklogin with the given issuer and address seed.

'''bash

'''

'''bash

'''

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

'''bash

'''

'''bash

'''

## Function

Delete a VerifiedIssuer

'''bash

'''

'''bash

'''

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

'''bash

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Verify that the caller's address was created using zklogin with the given issuer. If so, a VerifiedIssuer object with the issuers id transferred to the caller.

Aborts with [EInvalidProof](#) if the verification fails.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Returns true if address was created using zklogin with the given issuer and address seed.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

## Function

Returns true if address was created using zklogin with the given issuer and address seed.

Aborts with [EInvalidInput](#) if the iss input is not a valid UTF-8 string.

```
```bash
```

```
```
```

```
```bash
```

```
```
```