

Module sui::dynamic_field

In addition to the fields declared in its type definition, a Sui object can have dynamic fields that can be added after the object has been constructed. Unlike ordinary field names (which are always statically declared identifiers) a dynamic field name can be any value with the copy, drop, and store abilities, e.g. an integer, a boolean, or a string. This gives Sui programmers the flexibility to extend objects on-the-fly, and it also serves as a building block for core collection types

Internal object used for storing the field and value

The object already has a dynamic field with this name (with the value and type specified)

Cannot load dynamic field. The object does not have a dynamic field with this name (with the value and type specified)

The object has a field with that name, but the value type does not match

Failed to serialize the field's name

The object added as a dynamic field was previously a shared object

Adds a dynamic field to the object [object](#) : & mut UID at field specified by name: Name. Aborts with [EFieldAlreadyExists](#) if the object already has that field with that name.

Immutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

May abort with [EBCSSerializationFailure](#) .

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

Struct

Internal object used for storing the field and value

```
```bash
```

```
```
```

The object already has a dynamic field with this name (with the value and type specified)

```
```bash
```

```
```
```

Cannot load dynamic field. The object does not have a dynamic field with this name (with the value and type specified)

```
```bash
```

```
```
```

The object has a field with that name, but the value type does not match

```
```bash
```

```
```
```

Failed to serialize the field's name

```
```bash
```

```
```
```

The object added as a dynamic field was previously a shared object

```
```bash
```

```
```
```

Adds a dynamic field to the object [object](#) : & mut UID at field specified by name: Name. Aborts with [EFieldAlreadyExists](#) if the object already has that field with that name.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Immutablely borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
bash (
bash (
bash (
bash (
```

Constants

The object already has a dynamic field with this name (with the value and type specified)

```
```bash
```
```

Cannot load dynamic field. The object does not have a dynamic field with this name (with the value and type specified)

```
```bash
```
```

The object has a field with that name, but the value type does not match

```
```bash
```
```

Failed to serialize the field's name

```
```bash
```
```

The object added as a dynamic field was previously a shared object

```
```bash
```
```

Adds a dynamic field to the object [object](#) : & mut UID at field specified by name: Name. Aborts with [EFieldAlreadyExists](#) if the object already has that field with that name.

```
```bash
```
```

```
```bash
```
```

Immutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```
```

```
```bash
```
```

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified

type.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

Function

Adds a dynamic field to the object [object](#) : & mut UID at field specified by name: Name. Aborts with [EFieldAlreadyExists](#) if the object already has that field with that name.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Immutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with

[EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
...
```

```
```bash
```

```
...
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

bash (

bash (

Function

Immutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.


```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

Function

Mutably borrows the [object](#) s dynamic field with the name specified by name: Name. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

'''

'''bash

'''

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

'''bash

'''

'''bash

'''

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

'''bash

'''

'''bash

'''

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

'''bash

'''

'''bash

'''

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

'''bash

'''

'''bash

'''

bash (

bash (

bash (

bash (

May abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and

may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

## Function

Removes the [object](#) s dynamic field with the name specified by name: Name and returns the bound value. Aborts with [EFieldDoesNotExist](#) if the object does not have a field with that name. Aborts with [EFieldTypeMismatch](#) if the field exists, but the value does not have the specified type.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

Function

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name but without specifying the Value type

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type

Value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

Function

Removes the dynamic field if it exists. Returns the some(Value) if it exists or none otherwise.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

## Function

Returns true if and only if the [object](#) has a dynamic field with the name specified by name: Name with an assigned value of type Value.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

```
bash (
```

```
bash (
```

```
bash (
```

```
bash (
```

May abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

bash (

bash (

## Function

bash (

bash (

bash (

bash (

May abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (  
bash (  
bash (  
bash (  
bash (

## Function

bash (  
bash (

May abort with [EBCSSerializationFailure](#) .

bash (  
bash (  
bash (  
bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (  
bash (  
bash (  
bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (  
bash (  
bash (  
bash (  
bash (  
bash (

## Function

May abort with [EBCSSerializationFailure](#) .

bash (  
bash (  
bash (  
bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (  
bash (  
bash (



bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

bash (

bash (

## Function

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (

bash (

bash (

## Function

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) we need two versions to return a reference or a mutable reference

bash (

bash (

bash (

bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (

bash (

bash (

bash (  
bash (  
bash (

## Function

bash (  
bash (

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (  
bash (  
bash (  
bash (  
bash (  
bash (

## Function

throws [EFieldDoesNotExist](#) if a child does not exist with that ID or throws [EFieldTypeMismatch](#) if the type does not match, and may also abort with [EBCSSerializationFailure](#) .

bash (  
bash (  
bash (  
bash (  
bash (  
bash (

## Function

bash (  
bash (  
bash (  
bash (

## Function

bash (  
bash (