




Research Notes

Problem framing, goal association, assumptions and associated research papers

PROJECT

Node v0

Document ID	NT-N-M-H-001	Revision	A
Status	Exploratory Draft	Date	2026-07-9
Stage	Preliminary Research	Owner	Robotics Systems Engineering
Author	NervTech Research	Class	INTERNAL

Research Question

Which motor housing architecture will fulfill NT-N-G1, NT-N-G2 and NT-N-G7?

Abstract

This document collates and analyses multiple research papers and notes for fulfilling Node v0 design goals. Its intended purpose is to isolate observations, assumptions, risks, and design direction before committing to a detailed technical design.

Keywords: integrated actuator, mechanical design, motor housing, robotics, research notes

CONTENTS

1	Research Snapshot	2
2	Problem Framing	2
3	Preliminary Direction	2
4	Assumptions	2
5	Frameless BLDC Architecture	3
6	Kollmorgen Mounting and Installation Guidelines	4
6.0.1	Bearings	4

1 RESEARCH SNAPSHOT

Research Snapshot

Problem	Build motor housing to maximise thermal and electromagnetic performance of the actuator, while reducing size and weight.
Key Finding	The highest leverage early decision is the actuator architecture, because it constrains torque density, controllability, thermal behaviour, and manufacturability.
Main Uncertainty	The true operating envelope is still uncertain: load profile, duty cycle, heat rejection, encoder resolution, and gearbox backlash all need validation.
Next Step	Prototype the smallest credible bench rig and measure torque, speed, temperature rise, backlash, and closed-loop response.

2 PROBLEM FRAMING

Research Question – System Direction

What outrunner BLDC motor housing architectures minimises thermal resistance ($^{\circ}\text{C}/\text{W}$), magnetic flux leakage and Air Gap instability ($\pm \text{mm}$)?

3 PRELIMINARY DIRECTION


This research document will collate results from multiple research papers and notes to inform the design of a motor housing for Node v0. The goal is to identify the most promising motor housing architecture that meets the specified design goals (NT-N-G1, NT-N-G2, NT-N-G7). A preliminary frameless outrunner BLDC motor has been selected, informed by cost and performance requirements.

4 ASSUMPTIONS

- The frameless outrunner BLDC architecture will provide the highest torque density and lowest thermal resistance for the Node v0 actuator.
- Aluminium provides the best balance of thermal conductivity, weight, and manufacturability for the motor housing.

5 FRAMELESS BLDC ARCHITECTURE

The selected frameless outrunner BLDC was the SteadyWin WK8115 model with the following specifications:



更新于2025. 7. 10

Figure 1: SteadyWin WK8115 Dimensions

The magnetic, thermal and electrical properties of the motor are taken from the manufacturer as follows:

规格型号	wk1105	wk2205	wk2806	wk3505	wk3510	wk4310	wk4315	wk5215	wk5225	wk6010	wk6025	wk8110	wk8115	wk10025
额定电压 (V)	12	12	12	12	12	16	16	24	24	24	36	24	48	72
额定电流 (A)	0.59	0.66	0.81	0.79	0.53	0.79	0.59	1.12	1.28	1.19	1.78	1.75	6.5	4
堵转电流 (A)	0.92	1	1.22	1.2	0.8	1.2	0.9	1.69	1.94	1.8	2.67	3	10	11.2
额定扭矩 (N.M)	0.01	0.04	0.06	0.07	0.11	0.21	0.28	0.76	1.26	0.73	1.77	1.6	2.16	6
堵转扭矩 (N.M)	0.02	0.07	0.1	0.12	0.19	0.32	0.42	1.24	1.92	1.21	2.83	2.68	5.83	8.9
额定转速 (rpm)	7000	5500	2060	1890	945	585	425	390	313	280	227	186	1800	190
最高转速 (rpm)	8700	7200	2570	2160	1250	875	608	565	455	410	315	312	2280	310
绕组匝数 (T)	50	65	60	40	160	160	160	50	80	50	30	30	30	20
相间电阻 (Ω)	12.5	8	5	6.5	8.8	10.9	15.2	14.8	11.8	11.9	10.1	3	0.4	2.5
相间电感 (mH)	1.15	1.45	1.51	2.35	3.95	4.74	6.56	7.8	11.31	13.03	10.07	31.5	0.2	66
转速常数 (rpm/V)	108	100	121	74	45	33	23	12	12	11	7	11	37	12
扭矩常数 (N.M/A)	0.01	0.06	0.07	0.09	0.2	0.27	0.47	0.68	0.98	0.61	1.63	1.13	0.58	0.76
转子惯量 (gcm ²)	15	42	51	56	81	202	268	667	933	748	1645	2860	1500	4656
极对数	6	7	7	11	11	14	14	11	11	14	14	21	21	21
工作温度范围 (℃)	-20~80													
最高退磁温度 (℃)	120													

Figure 2: SteadyWin WK8115 Specifications

Figure 1 shows that outrunner motor housing architectures must be examined. The interphase inductance and resistance will also inform the thermal characteristics of the housing.

6 KOLLMORGEN MOUNTING AND INSTALLATION GUIDELINES

Kollmorgen is a German engineering company that provides a range of motion control solutions. While the procured SteadyWin WK8115 is not a Kollmorgen product, the company provides a set of mounting and installation guidelines that can be applied to the Node v0 motor housing design.

6.0.1 Bearings

Bearings in the motor housing are critical for maintaining air gap stability and therefore electromagnetic performance [1]. Kollmorgen notes that concentricity requirements are noted on the motor datasheet, and should be considered when "sizing and selecting bearings for appropriate radial and preload forces to achieve desired motor running gap clearance and total runout".

REFERENCES

- [1] Kollmorgen Corporation (2020) *Mounting and Installation Guidelines for BLDC Motors*, Kollmorgen Technical Documentation.
- [2] Leslie Lamport (1994) *L^AT_EX: a document preparation system*, Addison Wesley, Massachusetts, 2nd ed.