


EEE511

Recurrent Neural Networks


Equations help provide great insight!



$$X_{t+1} = \varphi(WX_t + \Theta)$$

Hopfield network

Hopfield, John J. "Neurons with graded response have collective computational properties like those of two-state neurons." *Proceedings of the national academy of sciences* 81.10 (1984): 3088-3092.



$$Y_t = W_{hy}^T H_t$$


$$H_t = \tanh(W_{hh}^T H_{t-1} + W_{xh}^T X_t)$$

Elman network



J.L. Elman, Generalization, simple recurrent networks, and the emergence of structure, in: *Proceedings of the 20th Annual Conference of the Cognitive Science Society*, Mahway, NJ, 1998.

Sequence modeling and applications


- RNNs are well suited for sequence modeling (order matters...), such as natural language processing, music generation, image captioning, stock market predictions, DNA sequencing, and more
- Recurrence connections provide memory/store information
- (Truncated) backpropagation through time well suited to train RNN
- LSTM or GRU use gates to control information flow: forget not useful info and store useful info



Recurrent Neural Networks (RNN)



Elman network



Output vector:


$$y_t = W_{hy}^T h_t$$

Update hidden state:


$$h_t = \tanh(W_{hh}^T h_{t-1} + W_{xh}^T x_t)$$

Input vector: x_t


2 hidden layer RNN




Usually 2-3 hidden layers



RNN deals with sequential information
(examples as shown below)



RNN: Computational Graph: Many to Many




Example: Language modeling (determining the probability of a sequence of words)


Character-level language model


Vocab = [h e l o]

Training sample sequence: hello



Testing: sample characters one at a time
Input: one character
Output: prediction of the next character
...






Not quite successful...



A bird is perched
on a tree branch



A man in a
baseball uniform
throwing a ball



A woman standing
on a beach holding
a surfboard

Successful captioning



A cat sitting on a
suitcase on the floor



A cat is sitting on a
tree branch



A dog is running in the
grass with a frisbee




A white teddy bear
sitting in the grass

- Hochreiter, Sepp, and Jürgen Schmidhuber. "Long short-term memory." *Neural computation* 9, no. 8 (1997): 1735-1780.
- Bengio, Y., Simard, P., & Frasconi, P. (1994). Learning long-term dependencies with gradient descent is difficult. *IEEE transactions on neural networks*, 5(2), 157-166.
- Hochreiter, S., Bengio, Y., Frasconi, P., & Schmidhuber, J. (2001). Gradient flow in recurrent nets: the difficulty of learning long-term dependencies.

Backpropagation through time (BTT):

Forward through entire sequence to compute loss

Backward through entire sequence to compute gradient




Werbos, Paul J. "Backpropagation through time: what it does and how to do it." Proceedings of the IEEE 78, no. 10 (1990): 1550-1560.

Truncated backpropagation through time (Truncated BTT):

Carry hidden states forward in time

Only backpropagate for a chunk (~100) of the hidden states or smaller number of steps



Problems:

Exploding gradient (accumulation of large derivatives, unstable model, not effective learning – gradient clipping)

Vanishing gradient (accumulation of small gradients, model cannot learn, not updated effectively)

To see that... notice the equation below”

$$h_3 = (f \dots (f(f(h_0, x_0), x_1), x_2 \dots))$$

for example, $0.3^{10} \rightarrow 10^{-7}$, $1.7^{10} \rightarrow 201$

Solutions:

Ideas: introduce gated cells to control information flow

Long Short-Term Memory networks (LSTMs): track info flow through time

Gated Recurrent Units (GRUs)

Hochreiter, S., & Schmidhuber, J. (1997). Long short-term memory. Neural computation, 9(8), 1735-1780.

Introduce a new hidden (memory) cell: c_t

f gate (forget gate): erase or not?

i gate (input gate): write to cell or not?


g gate: info into cell

o gate (output gate): amount of info revealed

$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$

$$c_t = f \odot c_{t-1} + i \odot g$$


$$h_t = o \odot \tanh(c_t)$$



In 2015, Google reported cutting transcription errors in their speech recognition service by up to 49%, a huge increase after years of incremental progress.

Hochreiter, S., & Schmidhuber, J. (1997). Long short-term memory. Neural computation, 9(8), 1735-1780.

Controlled forward information flow
Uninterrupted gradient flow



$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$


$$c_t = f \odot c_{t-1} + i \odot g$$

$$h_t = o \odot \tanh(c_t)$$


Element-wise multiplication (not matrix multiplications) during error backpropagation
Recurrence on cell state, f gate $\sim(0,1)$ may have vanishing gradient (initialize to ~ 1)

Chung, J., Gulcehre, C., Cho, K., & Bengio, Y. (2014). Empirical evaluation of gated recurrent neural networks on sequence modeling. arXiv preprint arXiv:1412.3555.

GRU: Gated Recurrent Unit



(a) Long Short-Term Memory



(b) Gated Recurrent Unit

$$r_t = \sigma(W_{xr}x_t + W_{hr}h_{t-1} + b_r)$$

$$z_t = \sigma(W_{xz}x_t + W_{hz}h_{t-1} + b_z)$$

$$\tilde{h}_t = \tanh(W_{xh}x_t + W_{hh}(r_t \odot h_{t-1}) + b_h)$$

$$h_t = z_t \odot h_{t-1} + (1 - z_t) \odot \tilde{h}_t$$

Sequence modeling and applications

- RNNs are well suited for sequence modeling applications such as natural language processing, music generation, image captioning, etc...
- Recurrence connections provide memory/store information
- (Truncated) backpropagation through time well suited to train RNN
- LSTM or GRU use gates to control information flow: forget not useful info and store useful info