# Lab: Arrays

Problems for exercise and homework for the "JS Fundamentals" Course @ SoftUni. Submit your solutions in the SoftUni judge system at: <a href="https://judge.softuni.bg/Contests/1243">https://judge.softuni.bg/Contests/1243</a>

# 1. Sum First and Last Array Elements

Write a function that receives an array of strings and prints the sum of first and last element in that array.

## **Examples**

Input	Output
[20, 30, 40]	60
[10, 17, 22, 33]	43
[11, 58, 69]	80

#### Hints

You can access the **last element** in any array by subtracting 1 from **its length**:

```
function solve(input) {
    let first = input[0];
   let last = input[input.length - 1];
    console.log(first + last);
```

# 2. Day of Week

Write a program which receives a **number** and prints the corresponding **name** of the **day** of week.

If the number is **NOT** a valid day, print 'Invalid day!'.

## **Examples**

Input	Output
3	Wednesday
6	Saturday
11	Invalid day!











#### **Hints**

```
function dayOfWeek(day) {
    let days = [ "Monday", "Tuesday", "Wednesday",
        "Thursday", "Friday", "Saturday", "Sunday"];
    if (day >= 1 && day <= 7) {
        // TODO
    } else {
       // TODO
```

# 3. Reverse an Array of Numbers

Write a program which receives a number **n** and an **array** of elements. Your task is to **create** a new array with **n** numbers, reverse it and print its elements on a single line, space separated.

## **Examples**

Input	Output
3, [10, 20, 30, 40, 50]	30 20 10
4, [-1, 20, 99, 5]	5 99 20 -1
2, [66, 43, 75, 89, 47]	43 66

#### Hints

Use **push()** to add elements inside the new array

```
function reverse(n, inputArr) {
    let arr = [];
    for (let i = 0; i < n; i++) {
        // TODO
    }
```

Use **string interpolation** for the output

```
let output = '';
for (let i = arr.length - 1; i >= 0; i--) {
    // TODO
console.log(output);
```

# 4. Reverse an Array of Strings

Write a program which receives an array of strings (space separated values). Your task is to reverse it and print its elements. Swap elements.

# **Examples**

Input	Output	Comments
	5.00	













['a', 'b', 'c', 'd', 'e']	e d c b a	The first element should be <b>last</b> , and the last element should be <b>first</b> .
['abc', 'def', 'hig', 'klm', 'nop']	nop klm hig def abc	
['33', '123', '0', 'dd']	dd 0 123 33	

#### **Hints**

- Loop to the half-length of the array
- Create a function to swap two elements inside an array

```
function reverse(elements) {
    for (let i = 0; i < elements.length / 2; i++) {</pre>
        swapElements(elements, i, elements.length - 1 - i);
    console.log(elements.join(' '));
    function swapElements(arr, i, j) {
        // TODO
```

### 5. Sum Even Numbers

Write a program which receives an array of strings, parse them to numbers and sum only the even numbers.

## **Examples**

Input	Output
['1','2','3','4','5','6']	12
['3','5','7','9']	0
['2','4','6','8','10']	30

#### Hints

Parse each string to number

```
function sumEvenNumbers(arr) {
    for(let i = 0; i < arr.length; i++) {</pre>
        arr[i] = Number(arr[i]);
    }
```

Create a variable for the sum

```
let sum = 0;
```

- Iterate through all elements in the array with for-of loop
- Check if the number is even











```
for(let num of arr) {
    if (num % 2 === 0) {
        sum += num;
    }
```

Print the total sum

### 6. Even and Odd Subtraction

Write a program that calculates the difference between the sum of the even and the sum of the odd numbers in an array.

## **Examples**

Input	Output	Comments
[1,2,3,4,5,6]	3	2 + 4 + 6 = 12, 1 + 3 + 5 = 9, 12 - 9 = 3
[3,5,7,9]	-24	
[2,4,6,8,10]	30	

#### **Hints**

Parse each string to number

```
function sumEvenNumbers(arr) {
    for(let i = 0; i < arr.length; i++) {</pre>
        arr[i] = Number(arr[i]);
    }
```

Create two variables - for even and odd sum

```
let evenSum = 0;
let oddSum = 0;
```

Iterate through all elements in the array with for-of loop and check if the number is odd or even

```
for(let num of arr) {
    if(num % 2 === 0){
        evenSum += num;
    } else {
        // TODO
```

Print the difference

# 7. Equal Arrays

Write a program which receives two string arrays and print on the console whether they are identical or NOT.











Arrays are identical if their elements are equal. If the arrays are identical find the sum of the first one and print on the console following message:

```
'Arrays are identical. Sum: {sum}'
```

If the arrays are **NOT** identical find the first index where the arrays differ and print on the console following message:

'Arrays are not identical. Found difference at {index} index'.

## **Examples**

Input	Output
['10','20','30'], ['10','20','30']	Arrays are identical. Sum: 60
['1','2','3','4','5'], ['1','2','4','4','5']	Arrays are not identical. Found difference at 2 index
['1'], ['10']	Arrays are not identical. Found difference at 0 index

#### Hints

First, we receive **two** arrays of strings and parse them.

```
function equalArrays(arr1, arr2) {
    for(let i = 0; i < arr1.length; i++) {</pre>
        arr1[i] = Number(arr1[i]);
    }
    for(let i = 0; i < arr2.length; i++) {</pre>
        arr2[i] = Number(arr2[i]);
    }
```

Iterate through the arrays and compare all element. If the elements are NOT equal print the required message and break the loop.

```
let areEqual = true;
for(let i = 0; i < \underline{arr1}.length; i++) {
    if (arr1[i] !== arr2[i]) {
        console.log(`Arrays are not identical. Found differences at ${i} index.`);
        areEqual = false;
        break;
    }
```

Think about how to solve the other part of the problem.

## 8. Condense Array to Number

Write a program which receives an array of numbers and condense them by summing adjacent couples of elements until a single number is obtained.

## **Examples**

For example, if we have 3 elements [2, 10, 3], we sum the first two and the second two elements and obtain  $\{2+10, 10+3\} = \{12, 13\}$ , then we sum again all adjacent elements and obtain  $\{12+13\} = \{25\}$ .

Input	Output	Comments
[2,10,3]	25	$2\ 10\ 3 \rightarrow 2+10\ 10+3 \rightarrow 12\ 13 \rightarrow 12+13 \rightarrow 25$











[5,0,4,1,2]	35	5 0 4 1 2 → 5+0 0+4 4+1 1+2 → 5 4 5 3 → 5+4 4+5 5+3 → 9 9 8 → 9+9 9+8 → 18 17 → 18+17 → 35
[1]	1	1 is already condensed to number

### **Hints**

While we have more than one element in the array **nums**[], repeat the following:

- Allocate a new array condensed[] of size nums.Length-1.
- Sum the numbers from nums[] to condensed[]:
  - o condensed[i] = nums[i] + nums[i+1]
- nums[] = condensed[]

The process is illustrated below:















