SMPS Module Comparison:

Specification	Easy Power SMPS 5V 1A	Hi-Link HLK-5M05 5V 1A
Brand	Easy Power	Hi-Link
Model	5V 1A AC to DC SMPS Power Supply Module	HLK-5M05 Mini PCB Mounted SMPS Power Supply Module
Input Voltage Range	110V – 260V AC	90V – 265V AC
Output Voltage	5V DC	5V DC
Output Current	800mA continuous, up to 1A for short durations (10 min max)	1A continuous
Output Power	4W (5V × 0.8A)	5W (5V × 1A)
Efficiency	~75%	75-80%
Ripple & Noise	200 - 600 mV (20 MHz bandwidth)	≤50mV (20 MHz bandwidth)
Output Voltage Accuracy	±0.2%	±0.1%
Load Regulation	±0.5%	±0.5%

Line Regulation	±0.5%	±0.2%
Operating Temperature Range	0°C to +50°C	-25°C to +60°C
Protection Features	Short-circuit, Over-voltage	Short-circuit, Over-current, Over-voltage, Self-recovery
Isolation Voltage	1000V AC	3000V AC
Dimensions	37.00mm × 24.00mm × 21.00mm	34mm × 22mm × 18mm
Weight	22g	32g
Cost	Rs. 150-250	Rs. 250-400

Conclusion:

- **Hi-Link HLK-5M05** is a more reliable and robust option, especially for applications requiring higher accuracy, better protection, and compliance with safety standards. It also offers better performance in terms of ripple, noise, and operating temperature range. While it is slightly more expensive, its features make it a good value for the price.