



Python String


#PythonNotes

Python String Methods




Index

- capitalize()
- casefold()
- center()
- count()
- endswith()
- expandtabs()
- find()
- index()
- isalnum()
- isalpha()
- isdigit()
- isidentifier()
- islower()
- isnumeric()
- isspace()
- istitle()
- isupper()
- Join()
- lower()
- partition()
- replace()
- startswith()
- split()
- swapcase()
- title()
- upper()



Python String Methods

- Python has a set of built-in methods that you can use on strings.



capitalize()

- The `capitalize()` method returns a string where the first character is upper case.

```
stringdemo.py > ...
1  mystr = "hello world welcome to akash technolabs"
2
3  myans = mystr.capitalize()
4
5  print(myans)
6
—
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
Hello world welcome to akash technolabs
```

title()

- The title() method returns a string where the first character in every word is upper case. Like a header, or a title.
- If the word contains a number or a symbol, the first letter after that will be converted to upper case.

```
stringdemo.py > ...
1  mystr = "hello how are you ?"
2
3  myans = mystr.title()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
Hello How Are You ?
```

swapcase()

- The swapcase() method returns a string where all the upper case letters are lower case and vice versa.

```
stringdemo.py > ...
1  mystr = "Hello World"
2
3  myans = mystr.swapcase()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
HELLO WORLD
```

casefold()

- The casefold() method returns a string where all the characters are lower case.

```
stringdemo.py > ...
1  mystr = "HELLO World welcome to akash technolabs"
2  ⚡
3  myans = mystr.casefold()
4
5  print(myans)
6
—
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
hello world welcome to akash technolabs
```


center()

- The center() method will center align the string, using a specified character (space is default) as the fill character.

```
stringdemo.py > ...
1  mystr = "Hello World"
2
3  myans = mystr.center(25)
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
Hello World
```

```
stringdemo.py > ...
1  mystr = "Hello World"
2
3  myans = mystr.center(25, '-')
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
-----Hello World-----
```

count()

- The count() method returns the number of times a specified value appears in the string.

```
stringdemo.py > ...  
1  mystr = "Hello World Hello "  
2  
3  myans = mystr.count("Hello")  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
2
```

endswith()

- The endswith() method returns True if the string ends with the specified value, otherwise False.

```
stringdemo.py > ...
1  mystr = "Hello World !"
2
3  myans = mystr.endswith("!")
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```

```
stringdemo.py > ...
1  mystr = "Hello World!"
2
3  myans = mystr.endswith("World!")
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```

expandtabs()

- The `expandtabs()` method sets the tab size to the specified number of whitespaces.

```
stringdemo.py > ...
1  mystr = "H\te\tl\tl\to\t"
2
3  myans = mystr.expandtabs(5)
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
H   e   l   l   o
```

find()

- The find() method finds the first occurrence of the specified value.
- The find() method returns -1 if the value is not found.
- The find() method is almost the same as the index() method, the only difference is that the index() method raises an exception if the value is not found.

Example

 stringdemo.py > ...

```
1 mystr = "Welcome to Akash Technolabs"
2
3 myans = mystr.find("Akash")
4
5 print(myans)
6
```

PROBLEMS

OUTPUT


DEBUG CONSOLE

PORTS

TERMINAL

D:\code\python_code>python stringdemo.py

11



index()

- The index() method finds the first occurrence of the specified value.
- The index() method raises an exception if the value is not found.
- The index() method is almost the same as the find() method, the only difference is that the find() method returns -1 if the value is not found.

Example

```
stringdemo.py > ...  
1  mystr = "Welcome to Akash Technolabs"  
2  
3  myans = mystr.index("Akash")  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
11
```


isalnum()

- The isalnum() method returns True if all the characters are alphanumeric, meaning alphabet letter (a-z) and numbers (0-9).
- Example of characters that are not alphanumeric: (space)!#%&? etc.

Example

```
stringdemo.py > ...  
1  mystr = "WelcomeWorld"  
2  
3  myans = mystr.isalnum()  
4  
5  print(myans)  
6  
PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL  
  
D:\code\python_code>python stringdemo.py  
True
```

```
stringdemo.py > ...  
1  mystr = "Welcome World !"  
2  
3  myans = mystr.isalnum()  
4  
5  print(myans)  
6  
PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL  
  
D:\code\python_code>python stringdemo.py  
False
```

- The `isalpha()` method returns `True` if all the characters are alphabet letters (a-z).
- Example of characters that are not alphabet letters: (space)!#%&? etc.

Example

```
stringdemo.py > ...  
1  mystr = "Welcome World"  
2  
3  myans = mystr.isalpha()  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
False
```

isdigit()

- The isdigit() method returns True if all the characters are digits, otherwise False.

```
stringdemo.py > ...
1  mystr = "999786"
2
3  myans = mystr.isdigit()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```

isidentifier()

- The `isidentifier()` method returns `True` if the string is a valid identifier, otherwise `False`.
- A string is considered a valid identifier if it only contains alphanumeric letters (a-z) and (0-9), or underscores (`_`). A valid identifier cannot start with a number, or contain any spaces.

Example

 stringdemo.py > ...

```
1  mystr = "akash_padhiyar"
2
3  myans = mystr.isidentifier()
4
5  print(myans)
6
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

PORTS

TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```

islower()

- The islower() method returns True if all the characters are in lower case, otherwise False.
- Numbers, symbols and spaces are not checked, only alphabet characters.

Example

```
stringdemo.py > ...  
1  mystr = "akash padhiyar"  
2    
3  myans = mystr.islower()  
4    
5  print(myans)  
6    
PROBLEMS  OUTPUT  DEBUG CONSOLE  PORTS  TERMINAL  
  
D:\code\python_code>python stringdemo.py  
True
```

isupper()

- The isupper() method returns True if all the characters are in upper case, otherwise False.
- Numbers, symbols and spaces are not checked, only alphabet characters.

```
stringdemo.py > ...
1  mystr = "akash padhiyar"
2
3  myans = mystr.isupper()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
False
```

isnumeric()

- The isnumeric() method returns True if all the characters are numeric (0-9), otherwise False.

```
stringdemo.py > ...  
1  mystr = "9898123456"  
2  
3  myans = mystr.isnumeric()  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
True
```

isspace()

- The `isspace()` method returns `True` if all the characters in a string are whitespaces, otherwise `False`.

```
stringdemo.py > ...
1  mystr = " "
2
3  myans = mystr.isspace()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```

istitle()

- The istitle() method returns True if all words in a text start with a upper case letter, AND the rest of the word are lower case letters, otherwise False.
- Symbols and numbers are ignored.

Example

 stringdemo.py > ...

```
1  mystr = "Hello World"
2
3  myans = mystr.istitle()
4
5  print(myans)
6
```

PROBLEMS


OUTPUT

DEBUG CONSOLE

PORTS

TERMINAL

```
D:\code\python_code>python stringdemo.py
True
```



Join()

- The Join() method takes all items in an iterable and joins them into one string.
- A string must be specified as the separator.

Example

 stringdemo.py > ...

```
1  mystr = ("Hello", "World")
2  
3  myans = " ".join(mystr)
4
5  print(myans)
6
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

PORTS

TERMINAL

```
D:\code\python_code>python stringdemo.py
Hello World
```


lower()

- The lower() method returns a string where all characters are lower case.
- Symbols and Numbers are ignored.

```
stringdemo.py > ...
1  mystr = "Hello World"
2
3  myans = mystr.lower()
4
5  print(myans)
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py
hello world
```

upper()

- The upper() method returns a string where all characters are in upper case.
- Symbols and Numbers are ignored.


```
stringdemo.py > ...  
1  mystr = "Hello World"  
2  
3  myans = mystr.upper()  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
HELLO WORLD
```

partition()

- The partition() method searches for a specified string, and splits the string into a tuple containing three elements.
- The first element contains the part before the specified string.
- The second element contains the specified string.
- The third element contains the part after the string.



Example

 stringdemo.py > ...

```
1  mystr = "hello how are you ?"  
2  
3  myans = mystr.partition("how")  
4  
5  print(myans)  
6
```

PROBLEMS


OUTPUT

DEBUG CONSOLE

PORTS

TERMINAL

```
D:\code\python_code>python stringdemo.py  
( 'hello ', 'how', ' are you ?')
```



replace()

- The replace() method replaces a specified phrase with another specified phrase.

```
stringdemo.py > ...  
1  mystr = "Hello World "  
2  
3  myans = mystr.replace("Hello", "Hi")  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
Hi World
```

startswith()

- The startswith() method returns True if the string starts with the specified value, otherwise False.

```
stringdemo.py > ...  
1  mystr = "Hello World "  
2  
3  myans = mystr.startswith("Hello")  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
True
```

split()

- The split() method splits a string into a list.
- You can specify the separator, default separator is any whitespace.

```
stringdemo.py > ...  
1  mystr = "hello how are you ?"  
2  
3  myans = mystr.split()  
4  
5  print(myans)  
6
```

PROBLEMS OUTPUT DEBUG CONSOLE PORTS TERMINAL

```
D:\code\python_code>python stringdemo.py  
['hello', 'how', 'are', 'you', '?']
```

Let's Connect



Akash Padhiyar

Tech Educator • Consultant Tech
Mentor • Founder

On a Mission 🚀 to Bridge the
Gap Between Campus & Corporate

Akashsir.com

SOCIAL MEDIA

#DailyUpdates



@akashsirdotcom

#FreeCode



@akashpadhiyar

#TechUpdates



@akashpadhiyar

#FreeTutorials



@akashtecholabs

#HelpDesk



+91 99786 21654

WEBSITES

> **www.akashtecholabs.com**

> **www.akashsir.com**



akash@akashtecholabs.com

📍 202, Arya Arcade, Mithakhali Six Road, Navrangpura, Ahmedabad, Gujarat 380009