

1. Dynamic Javascript:

```
<html>

<body>

<script type="text/javascript" >

function display()

{

var x=document.getElementById("names").value;

alert(x);

}

function showcommentform() {

var data="Name:<br><input type='text' id='names' name='names'><br>Comment:<br><textarea
rows='5' cols='50'></textarea><br><input type='submit' value='comment' onclick='display()'>";

document.getElementById('mylocation').innerHTML=data;

}

</script>

<form name="myForm">

<input type="button" value="comment" onclick="showcommentform()">

<div id="mylocation"></div>

</form>

</body>

</html>
```

2. Arrays sort

```
<html>

<body>

<p>Click the button to sort the array in ascending order.</p>
```

```
<button onclick="myFunction()">Try it</button>

<p id="demo"></p>

<script>
var points = [40, 100, 1, 5, 25, 10];
document.getElementById("demo").innerHTML = points;
function myFunction() {
    points.sort(function(a, b){return a - b}); //b-a descending
    document.getElementById("demo").innerHTML = points;
}
</script>
</body>
</html>
```

3. Confirm box

```
<!DOCTYPE html>
<html>
<body>

<h2>JavaScript Confirm Box</h2>
```

```
<button onclick="myFunction()">Try it</button>
```

```
<p id="demo"></p>
```

```
<script>
function myFunction() {
    var txt;
    if (confirm("Press a button!")) {
        txt = "You pressed OK!";
```

```
} else {  
    txt = "You pressed Cancel!";  
}  
document.getElementById("demo").innerHTML = txt;  
}  
</script>
```

```
</body>  
</html>
```

4. Compute Cube

```
<script type="text/javascript">  
function getcube(){  
var number=parseInt(document.getElementById("number").value);  
alert(number*number*number);  
}  
</script>  
<form>  
Enter No:<input type="text" id="number" name="number"/><br/>  
<input type="button" value="cube" onclick="getcube()"/>  
</form>
```

5. While loop

```
<!DOCTYPE html>  
<html>  
<body>  
  
<h2>JavaScript While Loop</h2>  
  
<p id="demo"></p>
```

```
<script>
var text = "";
var i = 0;
while (i < 10) {
    text += "<br>The number is " + i;
    i++;
}
document.getElementById("demo").innerHTML = text;
</script>
```

```
</body>
</html>
```

6.For loop

```
<!DOCTYPE html>
<html>
<body>
```

```
<h2>JavaScript For Loop</h2>
```

```
<p id="demo"></p>
```

```
<script>
var cars = ["BMW", "Volvo", "Saab", "Ford", "Fiat", "Audi"];
var text = "";
var i;
for (i = 0; i < cars.length; i++) {
    text += cars[i] + "<br>";
}
document.getElementById("demo").innerHTML = text;
```

```
</script>
```

```
</body>
```

```
</html>
```

7.JS style

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>What Can JavaScript Do?</h2>
```

```
<p id="demo">JavaScript can change the style of an HTML element.</p>
```

```
<button type="button" onclick="document.getElementById('demo').style.fontSize='35px'">Click Me!</button>
```

```
</body>
```

```
</html>
```

8.

Email validate

```
<html>
```

```
<body>
```

```
<script>
```

```
function validateemail()
```

```
{
```

```
var x=document.myform.email.value;
```

```
var atposition=x.indexOf("@");
```

```

var dotposition=x.lastIndexOf(".");
if (atposition<1 || dotposition<atposition+2 || dotposition+2>=x.length){
    alert("Please enter a valid e-mail address \n atpostion:"+atposition+"\n dotposition:"+dotposition);
    return false;
}
}
</script>
<body>
<form name="myform" method="post"
action="http://www.javatpoint.com/javascriptpages/valid.jsp" onsubmit="return validateemail();">
Email: <input type="text" name="email"><br/>

<input type="submit" value="register">
</form>
</body>
</html>

```

9.Simple JS

```

<!DOCTYPE html>
<html>
<body>

<h2>What Can JavaScript Do?</h2>

<p id="demo">JavaScript can change HTML content.</p>

<button type="button" onclick="document.getElementById('demo').innerHTML = 'Hello
JavaScript!'">Click Me!</button>

</body>
</html>

```

10.Validation:

```
<!DOCTYPE html>

<html>

<head>

<script>

function validateForm() {

    var x = document.forms["myForm"]["fname"].value;

    if (x == "") {

        alert("Name must be filled out");

        return false;

    }

}

</script>

</head>

<body>


<form name="myForm" action="/action_page.php" onsubmit="return validateForm()"
method="post">

    Name: <input type="text" name="fname">

    <input type="submit" value="Submit">

</form>


</body>

</html>
```

11.Number validation:

```
<!DOCTYPE html>

<html>

<body>
```

```
<h2>JavaScript Can Validate Input</h2>
```

```
<p>Please input a number between 1 and 10:</p>
```

```
<input id="numb">
```

```
<button type="button" onclick="myFunction()">Submit</button>
```

```
<p id="demo"></p>
```

```
<script>
```

```
function myFunction() {
```

```
    var x, text;
```

```
    // Get the value of the input field with id="numb"
```

```
    x = document.getElementById("numb").value;
```

```
    // If x is Not a Number or less than one or greater than 10
```

```
    if (isNaN(x) || x < 1 || x > 10) {
```

```
        text = "Input not valid";
```

```
    } else {
```

```
        text = "Input OK";
```

```
    }
```

```
    document.getElementById("demo").innerHTML = text;
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

12.Multiply


```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>JavaScript Functions</h2>
```

```
<p>This example calls a function which performs a calculation and returns the result:</p>
```

```
<p id="demo"></p>
```

```
<script>
```

```
var x = myFunction(4, 3);
```

```
document.getElementById("demo").innerHTML = x;
```

```
function myFunction(a, b) {
```

```
    return a * b;
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

13. Select form elements

```
<script type="text/javascript">
```

```
function totalelements()
```

```
{
```

```
var allgenders=document.getElementsByName("gender");
```

```
alert("Total Genders:"+allgenders.length);
```

```
}
```

```
</script>

<form>

Male:<input type="radio" name="gender" value="male">
Female:<input type="radio" name="gender" value="female">


<input type="button" onclick="totalelements()" value="Total Genders">

</form>
```

14.Switch

```
<!DOCTYPE html>

<html>

<body>


<p id="demo"></p>


<script>
var day;
switch (new Date().getDay()) {
    case 0:
        day = "Sunday";
        break;
    case 1:
        day = "Monday";
        break;
    case 2:
        day = "Tuesday";
        break;
    case 3:
        day = "Wednesday";
        break;
```

case 4:

```
    day = "Thursday";
```

```
    break;
```

case 5:

```
    day = "Friday";
```

```
    break;
```

case 6:

```
    day = "Saturday";
```

```
}
```

```
document.getElementById("demo").innerHTML = "Today is " + day;
```

```
</script>
```

```
</body>
```

```
</html>
```

15.Addition

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>The + Operator</h2>
```

```
<p id="demo"></p>
```

```
<script>
```

```
var x = 5;
```

```
var y = 2;
```

```
var z = x + y;
```

```
document.getElementById("demo").innerHTML = z;
```

```
</script>
```

```
</body>
```

```
</html>
```

16.Prompt:

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h2>JavaScript Prompt</h2>
```

```
<button onclick="myFunction()">Try it</button>
```

```
<p id="demo"></p>
```

```
<script>
```

```
function myFunction() {
```

```
    var txt;
```

```
    var person = prompt("Please enter your name:", "Harry Potter");
```

```
    if (person == null || person == "") {
```

```
        txt = "User cancelled the prompt.";
```

```
    } else {
```

```
        txt = "Hello " + person + "! How are you today?";
```

```
    }
```

```
    document.getElementById("demo").innerHTML = txt;
```

```
}
```

```
</script>
```

```
</body>
```

```
</html>
```

Code2:

```
<!DOCTYPE html>

<html>

<head>

<script type="text/javascript">

function matchpass(){

var firstpassword=document.f1.password.value;

var secondpassword=document.f1.password2.value;


if(firstpassword==secondpassword){

return true;

}

else{

alert("password must be same!");

return false;

}

}

</script>

</head>

<body>


<form name="f1" action="http://www.javatpoint.com/javascriptpages/valid.jsp" onsubmit="return matchpass()">

Password:<input type="password" name="password" /><br/>

Re-enter Password:<input type="password" name="password2"/><br/>

<input type="submit">

</form>


</body>

</html>
```

17.External javascript:

```
<html>
<head>
<script type="text/javascript" src="message.js"></script>
</head>
<body>
<p>Welcome to JavaScript</p>
<form>
<input type="button" value="click" onclick="msg()"/>
</form>
</body>
</html>
```

External javascript file: mystyle.js

```
function msg(){
  alert("Hello Javatpoint");
}
```