

Assignment No: 02

Title: Classify the email using the binary classification method. Email Spam detection has two states: a) Normal State – Not Spam, b) Abnormal State – Spam. Use K-Nearest Neighbors and Support Vector Machine for classification. Analyze their performance..

**Name: Aniket Rajani**

**Class :B.E**

**Div:A**

**Batch:A**

**Roll No:405A008**

```
In [2]: # importing required Libraries
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
%matplotlib inline
import warnings
warnings.filterwarnings('ignore')
from sklearn.model_selection import train_test_split
from sklearn.svm import SVC
from sklearn import metrics
```

```
In [3]: df=pd.read_csv('emails.csv')
df.head()
```

```
Out[3]:
```

	Email No.	the	to	ect	and	for	of	a	you	hou	...	connevey	jay	valued	lay	infrastructure	military
0	Email 1	0	0	1	0	0	0	2	0	0	...	0	0	0	0	0	0
1	Email 2	8	13	24	6	6	2	102	1	27	...	0	0	0	0	0	0
2	Email 3	0	0	1	0	0	0	8	0	0	...	0	0	0	0	0	0
3	Email 4	0	5	22	0	5	1	51	2	10	...	0	0	0	0	0	0
4	Email 5	7	6	17	1	5	2	57	0	9	...	0	0	0	0	0	0

5 rows × 3002 columns



```
In [4]: df.columns
```

```
Out[4]: Index(['Email No.', 'the', 'to', 'ect', 'and', 'for', 'of', 'a', 'you', 'hou',
              ...,
              'connevey', 'jay', 'valued', 'lay', 'infrastructure', 'military',
              'allowing', 'ff', 'dry', 'Prediction'],
              dtype='object', length=3002)
```

```
In [5]: # Pre processing dataset
df.isnull().sum()
```

```
Out[5]: Email No.      0
the                0
to                0
ect               0
and               0
...
military          0
allowing          0
```

```
ff          0
dry         0
Prediction  0
Length: 3002, dtype: int64
```

```
In [6]: df.dropna(inplace = True)
```

```
In [7]: df.drop(['Email No.'],axis=1,inplace=True)
```

```
In [8]: X = df.drop(['Prediction'],axis = 1)
y = df['Prediction']
```

```
In [10]: from sklearn.preprocessing import scale
X = scale(X)
```

```
In [11]: # split into train and test
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.3, random_state = 42)
```

```
In [12]: # Apply KNN Classifier
from sklearn.neighbors import KNeighborsClassifier
knn = KNeighborsClassifier(n_neighbors=7)
knn.fit(X_train, y_train)
y_pred = knn.predict(X_test)
print("Prediction",y_pred)
print("KNN accuracy = ",metrics.accuracy_score(y_test,y_pred))
print("Confusion matrix",metrics.confusion_matrix(y_test,y_pred))
```

```
Prediction [0 0 1 ... 1 1 1]
KNN accuracy = 0.8009020618556701
Confusion matrix [[804 293]
 [ 16 439]]
```

```
In [14]: # Apply SVM Classifier
# cost C = 1
model = SVC(C = 1)
# fit
model.fit(X_train, y_train)
# predict
y_pred = model.predict(X_test)
metrics.confusion_matrix(y_true=y_test, y_pred=y_pred)
print("SVM accuracy = ",metrics.accuracy_score(y_test,y_pred))
print("Confusion matrix",metrics.confusion_matrix(y_test,y_pred))
```

```
SVM accuracy = 0.9381443298969072
Confusion matrix [[1091    6]
 [ 90 365]]
```

```
In [ ]:
```